§471.23

SUBPART B-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of magnesium surface treated	
Chromium	0.205 0.681 62.1 27.8	0.084 0.285 27.3 12.3

(g) Surface treatment rinse.

SUBPART B-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of magnesium surface treated	
Chromium Zinc Ammonia Fluoride	0.832 2.76 252 113	0.340 1.16 111 49.9

(h) Sawing or grinding spent emulsions.

SUBPART B-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of magnesium sawed or ground	
ChromiumZincAmmoniaFluoride	0.009 0.029 2.60 1.16	0.004 0.012 1.15 0.515

- (i) Degreasing spent solvents—Subpart B—BAT. There shall be no discharge of process wastewater pollutants.
- (j) Wet air pollution control scrubber blowdown.

SUBPART B-BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of magnesium sanded and repaired or forged	
ChromiumZinc	0.273 0.904	0.112 0.378
Ammonia	82.5	36.3
Fluoride	36.9	16.4

§ 471.23 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards. The mass of pollutants in the magnesium forming process wastewater shall not exceed the following values:

(a) Rolling spent emulsions.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off/kg (pounds per millio off-pounds) of magnesiu rolled with emulsions	
Chromium	0.028	0.011
Zinc	0.076	0.032
Ammonia	9.95	4.37
Fluoride	4.44	1.97
Oil and grease	0.746	0.746
TSS	1.12	0.895
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

- (b) Forging spent lubricants—Subpart B—NSPS. There shall be no discharge of process wastewater pollutants.
 - (c) Forging contact cooling water.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	off-pounds)	nds per million of forged mag- ed with water
Chromium	0.107	0.044
Zinc	0.295	0.122
Ammonia	38.5	17.0
Fluoride	17.2	7.63
Oil and grease	2.89	2.89
TSS	4.34	3.47
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(d) Forging equipment cleaning wastewater.

Environmental Protection Agency

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		inds per million of magnesium
Chromium Zinc Ammonia Fluoride Oil and grease TSS	0.002 0.004 0.532 0.238 0.040 0.060	0.0006 0.002 0.234 0.106 0.040 0.048
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(e) Direct chill casting contact cooling water.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of magnesium cast with direct chill meth- ods	
Chromium	1.46	0.593
Zinc	4.03	1.66
Ammonia	527	232
Fluoride	235	105
Oil and grease	39.5	39.5
TSS	59.3	47.4
pH	(1)	(1)

 $^{^{\}rm 1}\,\mbox{Within}$ the range of 7.5 to 10.0 at all times.

(f) Surface treatment spent baths.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of magnesium surface treated	
0	0.470	0.070
Chromium	0.173	0.070
Zinc	0.476	0.196
Ammonia	62.1	27.3
Fluoride	27.8	12.3
Oil and grease	4.66	4.66
TSS	6.99	5.60
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times

(g) Surface treatment rinse.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pound pers millio off-pounds) of magnesiur surface treated	
Chromium	0.700	0.284
Zinc	1.93	0.794
Ammonia	252	111
Fluoride	113	49
Oil and grease	18.9	18.9
TSS	28.4	22.7
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times

(h) Sawing or grinding spent emulsions.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mill off-pounds) of magnesi sawed or ground	
Chromium	0.007	0.003
Zinc	0.020	0.008
Ammonia	2.60	1.15
Fluoride	1.16	0.515
Oil and grease	0.195	0.195
TSS	0.293	0.234
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

- (i) Degreasing spent Solvents—Subpart B—NSPS. There shall be no discharge of process wastewater pollutants.
- (j) Wet air pollution control scrubber blowdown.

SUBPART B-NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of magnesium sanded and repaired of forged	
Chromium	0.229	0.093
Zinc	0.632	0.260
Ammonia	82.5	36.3
Fluoride	36.9	16.4
Oil and grease	6.19	6.19
TSS	9.29	7.43
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

^{[50} FR 34270, Aug. 23, 1985; 51 FR 2884, Jan. 22, 1986]