Environmental Protection Agency

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals surface treated	
Cadmium	0.033	0.015
Copper	0.183	0.097
Cyanide	0.028	0.012
Silver	0.040	0.017

(o) Surface treatment rinse.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals surface treated	
Cadmium	0.210	0.093
Copper	1.17	0.616
Cyanide	0.179	0.074
Silver	0.253	0.105

(p) Alkaline cleaning spent baths.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals alkaline cleaned	
Cadmium	0.021 0.114 0.018 0.025	0.009 0.060 0.007 0.010

(q) Alkaline cleaning rinse.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals alkaline cleaned	
Cadmium	0.381	0.168
Copper	2.13	1.12
Cyanide	0.325	0.135
Silver	0.459	0.191

(r) Alkaline cleaning prebonding wastewater.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals and base meta cleaned prior to bonding	
Cadmium	0.400 2.210 0.337 0.476	0.174 1.16 0.139 0.197

(s) Tumbling or burnishing wastewater.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals tumbled or but nished	
Cadmium	0.412 2.300 0.351 0.496	0.182 1.21 0.145 0.206

(t) Sawing or grinding spent neat oils—Subpart D—PSES. There shall be no discharge of process wastewater pollutants.

(u) Sawing or grinding spent emulsions.

SUBPART D-PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals sawed or groun with emulsions	
Cadmium Copper Cyanide Silver	0.032 0.178 0.027 0.038	0.014 0.094 0.011 0.016

(v) Degreasing spent solvents—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2886, Jan. 22, 1986]

§471.45 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment

§471.45

standards for new sources (PSNS). The mass of wastewater pollutants in precious metals forming wastewater introduced into a POTW shall not exceed the following values:

- (a) Rolling spent neat oils—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.
 - (b) Rolling spent emulsions.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals rolled with emul sions	
Cadmium	0.026 0.147 0.023 0.032	0.012 0.077 0.010 0.013

- (c) Drawing spent neat oils—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.
 - (d) Drawing spent emulsions.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals drawn with emul- sions	
Cadmium	0.016 0.091 0.014 0.020	0.007 0.048 0.006 0.008

(e) Drawing spent soap solutions.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals drawn with soap so- lutions	
Cadmium	0.001 0.006 0.0009 0.002	0.0005 0.003 0.0004 0.0006

(f) Metal powder production wet atomization wastewater.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals powder wet atom ized	
Cadmium	2.27	1.00
Copper	12.7	6.68
Cyanide	1.94	0.802
Silver	2.74	1.14

(g) Heat treatment contact cooling water.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of extende precious metals heat trea ed	
Cadmium	0.142	0.063
Copper	0.793	0.417
Cyanide	0.121	0.050
Silver	0.171	0.071

(h) Semi-continuous and continuous casting contact cooling water.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precion metals cast by the sen continuous or continuous method	
Cadmium	0.350	0.155
Copper	1.96	1.03
Cyanide	0.299	0.124
Silver	0.423	0.175

- (i) Stationary casting contact cooling water—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.
- (j) Direct chill casting contact cooling water.

Environmental Protection Agency

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals cast by the direct chill method	
Cadmium	0.367	0.162
Copper	2.05	1.08
Cyanide	0.313	0.130
Silver	0.443	0.184

(k) Shot casting contact cooling water.

SUBPART D—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals shot cast	
Cadmium	0.125 0.698 0.107 0.151	0.055 0.367 0.044 0.0631

- (l) Wet air pollution control scrubber blowdown—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.

 (m) Pressure bonding contact cooling
- water.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millio off-pounds) of preciou metals and base meta pressure bonded	
Cadmium	0.029	0.013
Copper	0.159	0.084
Cyanide	0.024	0.010
Silver	0.034	0.014

(n) Surface treatment spent baths.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals surface treated	
Cadmium	0.033 0.183 0.028 0.040	0.015 0.097 0.012 0.017

(o) Surface treatment rinse.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per milli off-pounds) of precio metals surface treated	
Cadmium	0.210 1.17 0.179 0.253	0.093 0.616 0.074 0.105

(p) Alkaline cleaning spent baths.

SUBPART D-PSNS

Maximum for any 1 day	Maximum for monthly average
off-pounds)	of precious
0.021 0.114 0.018 0.025	0.009 0.060 0.007 0.010
	mg/off-kg (pour off-pounds) metals alkalii 0.021 0.114 0.018

(q) Alkaline cleaning rinse.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per milli off-pounds) of precio metals alkaline cleaned	
Cadmium	0.381 2.13 0.325 0.459	0.168 1.12 0.135 0.191

(r) Alkaline cleaning pre-bonding wastewater.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millior off-pounds) of precious metals and base meta cleaned prior to bonding	
Cadmium	0.400	0.174
Copper	2.21	1.16
Cyanide	0.337	0.139
Silver	0.476	0.197

(s) Tumbling or burnishing wastewater.

§471.46

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of precious metals tumbled or bur- nished	
Cadmium	0.412 2.30	0.182 1.21
Cyanide	0.351	0.145
Silver	0.496	0.206

- (t) Sawing or grinding spent neat oils—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.
 - (u) Sawing or grinding spent emulsions.

SUBPART D-PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per mil lion off-pounds) of pre cious metals sawed o ground with emulsions	
Cadmium	0.032	0.014
Copper	0.178	0.094
Cyanide	0.027	0.011
Silver	0.038	0.016

(v) Degreasing spent solvents—Subpart D—PSNS. There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2886, Jan. 22, 1986]

§ 471.46 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

Subpart E—Refractory Metals Forming Subcategory

§ 471.50 Applicability; description of the refractory metals forming subcategory.

This subpart applies to discharges of pollutants to waters of the United States, and introductions of pollutants into publicly owned treatment works from the process operations of the refractory metals forming subcategory.

§ 471.51 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

- (a) Rolling spent neat oils and graphite based lubricants—Subpart E—BPT. There shall be no discharge of process wastewater pollutants.
 - (b) Rolling spent emulsions.

SUBPART E-BPT

005.7		
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per millic off-pounds) of refracto metals rolled with emu sions	
Copper	0.815	0.429
Nickel	0.824	0.545
Fluoride	25.5	11.3
Molybdenum	2.84	1.47
Oil and grease	8.58	5.15
TSS	17.6	8.37
pH	(1)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

- (c) *Drawing spent lubricants—Subpart E—BPT.* There shall be no discharge of process wastewater pollutants.
- (d) Extrusion spent lubricants—Subpart E—BPT. There shall be no discharge of process wastewater pollutants.
- (e) Extrusion press hydraulic fluid leakage.

SUBPART E-BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of refractory metals extruded	
Copper	2.26 2.29 70.8 7.87 23.8 48.8 (1)	1.19 1.51 31.4 4.07 14.3 23.2

¹ Within the range of 7.5 to 10.0 at all times.