

§ 471.76

40 CFR Ch. I (7-1-04 Edition)

SUBPART G—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of sawed or ground uranium rinsed	
Cadmium .....	0.001	0.0004
Chromium .....	0.002	0.0007
Copper .....	0.006	0.003
Lead .....	0.002	0.0006
Nickel .....	0.003	0.002
Fluoride .....	0.277	0.123
Molybdenum .....	0.024	0.011

(k) *Area cleaning rinse.*

SUBPART G—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.016	0.007
Copper .....	0.055	0.026
Lead .....	0.012	0.006
Nickel .....	0.024	0.016
Fluoride .....	2.56	1.14
Molybdenum .....	0.216	0.096

(l) *Drum washwater.*

SUBPART G—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of uranium formed	
Cadmium .....	0.009	0.004
Chromium .....	0.017	0.007
Copper .....	0.057	0.027
Lead .....	0.013	0.006
Nickel .....	0.025	0.017
Fluoride .....	2.64	1.17
Molybdenum .....	0.223	0.099

(m) *Laundry washwater.*

SUBPART G—PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/employee—day	
Cadmium .....	5.24	2.10
Chromium .....	9.70	3.93
Copper .....	33.6	16.0
Lead .....	7.34	3.41
Nickel .....	14.4	9.70
Fluoride .....	1,560	692
Molybdenum .....	132	58.4

(n) *Degreasing spent solvents—Subpart G—PSNS.* There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

**§ 471.76 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]**

**Subpart H—Zinc Forming Subcategory**

**§ 471.80 Applicability; description of the zinc forming subcategory.**

This subpart applies to discharges of pollutants to waters of the United States, and introductions of pollutants into publicly owned treatment works from the process operations of the zinc forming subcategory.

**§ 471.81 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations for the process operations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

(a) *Rolling spent neat oils—Subpart H—BPT.* There shall be no discharge of process wastewater pollutants.

(b) *Rolling spent emulsions.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with emulsions	
Chromium .....	0.0006	0.0003
Copper .....	0.003	0.002
Cyanide .....	0.0004	0.0002
Zinc .....	0.002	0.0009
Oil and grease .....	0.028	0.017
TSS .....	0.057	0.027
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

**Environmental Protection Agency**

**§ 471.81**

*(c) Rolling contact cooling water.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with contact cooling water	
Chromium .....	0.236	0.0097
Copper .....	1.02	0.536
Cyanide .....	0.156	0.065
Zinc .....	0.783	0.327
Oil and grease .....	10.7	6.43
TSS .....	22.0	10.5
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(d) Drawing spent emulsions.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc drawn with emulsions	
Chromium .....	0.003	0.001
Copper .....	0.011	0.006
Cyanide .....	0.002	0.0007
Zinc .....	0.009	0.004
Oil and grease .....	0.116	0.070
TSS .....	0.238	0.113
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(e) Direct chill casting contact cooling water.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc cast by the direct chill method	
Chromium .....	0.222	0.091
Copper .....	0.960	0.505
Cyanide .....	0.147	0.061
Zinc .....	0.738	0.308
Oil and grease .....	10.1	6.06
TSS .....	20.7	9.85
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(f) Stationary casting contact cooling water—Subpart H—BPT.* There shall be no discharge of process wastewater pollutants.

*(g) Heat treatment contact cooling water.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc heat treated	
Chromium .....	0.336	0.138
Copper .....	1.45	0.763
Cyanide .....	0.221	0.092
Zinc .....	1.12	0.466
Oil and grease .....	15.3	9.16
TSS .....	31.3	14.9
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(h) Surface treatment spent baths.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc surface treated	
Chromium .....	0.039	0.016
Copper .....	0.169	0.089
Cyanide .....	0.026	0.011
Zinc .....	0.130	0.054
Oil and grease .....	1.78	1.07
TSS .....	3.64	1.73
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(i) Surface treatment rinse.*

**SUBPART H—BPT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc surface treated	
Chromium .....	1.58	0.645
Copper .....	6.80	3.58
Cyanide .....	1.04	0.430
Zinc .....	5.23	2.19
Oil and grease .....	71.6	43.0
TSS .....	147	69.8
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

*(j) Alkaline cleaning spent baths.*

§ 471.82

40 CFR Ch. I (7-1-04 Edition)

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.002	0.0007
Copper .....	0.007	0.004
Cyanide .....	0.001	0.0004
Zinc .....	0.005	0.002
Oil and grease .....	0.071	0.043
TSS .....	0.146	0.069
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(k) *Alkaline cleaning rinse.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.744	0.304
Copper .....	3.21	1.69
Cyanide .....	0.490	0.203
Zinc .....	2.47	1.03
Oil and grease .....	33.8	20.3
TSS .....	69.3	33.0
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(l) *Sawing or grinding spent emulsions.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc sawed or ground with emulsions	
Chromium .....	0.011	0.005
Copper .....	0.045	0.024
Cyanide .....	0.007	0.003
Zinc .....	0.035	0.015
Oil and grease .....	0.476	0.286
TSS .....	0.976	0.464
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(m) *Electrocoating rinse.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc electrocoated	
Chromium .....	1.01	0.412
Copper .....	4.35	2.29
Cyanide .....	0.664	0.275
Zinc .....	3.35	1.40
Oil and grease .....	45.8	27.5
TSS .....	93.9	44.7
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(n) *Degreasing spent solvents—Subpart H—BPT.* There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

**§ 471.82 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

(a) *Rolling spent neat oils—Subpart H—BAT.* There shall be no discharge of process wastewater pollutants.

(b) *Rolling spent emulsions.*

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with emulsions	
Chromium .....	0.0005	0.0002
Copper .....	0.002	0.0009
Cyanide .....	0.0003	0.0001
Zinc .....	0.002	0.0006

(c) *Rolling contact cooling water.*