

**Environmental Protection Agency**

**§ 445.20**

of analysis in the attachments to Methods 625 and 1625B in Appendix A at 40 CFR Part 136 are as follows:

- (1) Aniline.
- (2) Benzoic acid.
- (3) p-Cresol.
- (4) Pyridine.
- (5) a-Terpineol.

**§ 445.3 General pretreatment standards.**

Any source subject to this part that introduces wastewater pollutants into a publicly owned treatment works (POTW) must comply with 40 CFR part 403.

**Subpart A—RCRA Subtitle C Hazardous Waste Landfill**

**§ 445.10 Applicability.**

Except as provided in § 445.1, this subpart applies to discharges of wastewater from landfills subject to the provisions of 40 CFR Part 264, *Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities, Subpart N—(Landfills)*; and 40 CFR Part 265, *Interim Status Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities, Subpart N—(Landfills)*.

**§ 445.11 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations which represent the application of BPT:

| EFFLUENT LIMITATIONS   |                            |                                   |
|------------------------|----------------------------|-----------------------------------|
| Regulated parameter    | Maximum daily <sup>1</sup> | Maximum monthly avg. <sup>1</sup> |
| BOD <sub>5</sub> ..... | 220                        | 56                                |
| TSS .....              | 88                         | 27                                |
| Ammonia (as N) .....   | 10                         | 4.9                               |
| α-Terpineol .....      | 0.042                      | 0.019                             |
| Aniline .....          | 0.024                      | 0.015                             |
| Benzoic acid .....     | 0.119                      | 0.073                             |
| Naphthalene .....      | 0.059                      | 0.022                             |
| p-Cresol .....         | 0.024                      | 0.015                             |
| Phenol .....           | 0.048                      | 0.029                             |
| Pyridine .....         | 0.072                      | 0.025                             |
| Arsenic .....          | 1.1                        | 0.54                              |
| Chromium .....         | 1.1                        | 0.46                              |
| Zinc .....             | 0.535                      | 0.296                             |

**EFFLUENT LIMITATIONS—Continued**

| Regulated parameter | Maximum daily <sup>1</sup> | Maximum monthly avg. <sup>1</sup> |
|---------------------|----------------------------|-----------------------------------|
| pH .....            | ( <sup>2</sup> )           | ( <sup>2</sup> )                  |

<sup>1</sup> Milligrams per liter (mg/L, ppm).  
<sup>2</sup> Within the range 6 to 9.

[65 FR 3048, Jan. 19, 2000; 65 FR 14344, Mar. 16, 2000]

**§ 445.12 Effluent limitations attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations which represent the application of BCT: Limitations for BOD<sub>5</sub>, TSS and pH are the same as the corresponding limitations specified in § 445.11.

**§ 445.13 Effluent limitations representing the degree of effluent reduction attainable by the application of best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations which represent the application of BAT: Limitations for ammonia (as N), a-terpineol, aniline, benzoic acid, naphthalene, p-cresol, phenol, pyridine, arsenic, chromium and zinc are the same as the corresponding limitations specified in § 445.11.

**§ 445.14 New source performance standards (NSPS).**

Any new source subject to this subpart must achieve the following performance standards: Standards are the same as those specified in § 445.11.

**Subpart B—RCRA Subtitle D Non-Hazardous Waste Landfill**

**§ 445.20 Applicability.**

Except as provided in § 445.1, this subpart applies to discharges of wastewater from landfills subject to the provisions of 40 CFR part 258, *Criteria for Municipal Solid Waste Landfills*; and 40 CFR part 257, *Criteria for Classification of Solid Waste Disposal Facilities and Practices*.