§464.14

 $^2 \, \text{These}$ concentrations must be multiplied by the ratio of (46.3/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) for a specific plant.

[50 FR 45247, Oct. 30, 1985; 51 FR 21760, June 16, 1986]

§464.14 New source performance standards.

Any new source subject to this subpart must achieve the following new source performance standards (NSPS), except that non-continuous dischargers shall not be subject to the maximum day and maximum for monthly average mass (kg/1,000 kkg or lb/million lb of metal poured; kg/62.3 million Sm³ or lb/ billion SCF of air scrubbed) effluent standards for copper, lead, zinc, total phenols, oil and grease, and TSS. For non-continuous dischargers, annual average mass standards and maximum day and maximum for monthly average concentration (mg/l) standards shall apply. Concentration standards and annual average mass standards shall only apply to non-continuous dischargers.

(a) Casting Cleaning Operations.

NSPS

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly aver- age | |
|---|---|---|--|
| | kg/1,000 kkg (pounds per lion pounds) of m poured | | |
| Copper (T) Lead (T) Zinc (T) Oil and grease TSS pH | 0.0771 0.0791 0.114 3.0 3.8 (1) | 0.0421 0.039 0.0431 1.0 1.5 (¹) | |

¹Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | Maximum for monthly average | Annual av- erage ¹ |
|----------------|-----------------------------|-----------------------------------|----------------------------------|
| | (mg/l) ² | (mg/l) ² | |
| Copper (T) | 0.77 | 0.42 | 0.017 |
| Lead (T) | 0.79 | 0.39 | 0.022 |
| Zinc (T) | 1.14 | 0.43 | 0.027 |
| Oil and grease | 30 | 10 | 0.501 |
| TSS | 38 | 15 | 1.0 |
| рН | (3) | (3) | (3) |

¹ kg/1,000 kkg (pounds per million pounds) of metal poured. ² These concentrations must be multiplied by the ratio of (12/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) for a specific plant.

³Within the range of 7.0 to 10.0 at all times.

(b) Casting Quench Operations.

40 CFR Ch. I (7-1-04 Edition)

NSPS

| Dellisteret en reallisteret errorente. | Maximum for | Maximum for monthly aver- age | |
|--|--|-------------------------------------|--|
| | any 1 day | | |
| | kg/1,000 kkg (pounds per n lion pounds) of me poured | | |
| Copper (T) | 0.0093 | 0.0051 | |
| Lead (T) | 0.0096 | 0.0047 | |
| Zinc (T) | 0.0138 | 0.0052 | |
| Oil and grease | 0.363 | 0.121 | |
| TSS | 0.46 | 0.182 | |
| рН | (1) | (1) | |

¹ Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | Maximum for monthly average | Annual aver- age 1 |
|----------------|-----------------------------|-----------------------------------|--------------------------|
| • • | (mg/l) 2 | (mg/l) 2 | |
| Copper (1) | 0.77 | 0.42 | 0.0021 |
| Lead (T) | 0.79 | 0.39 | 0.0027 |
| Zinc (T) | 1.14 | 0.43 | 0.0033 |
| Oil and grease | 30 | 10 | 0.0605 |
| TSS | 38 | 15 | 0.121 |
| рН | (3) | (3) | (3) |

 1 kg/1,000 kkg (pounds per million pounds) of metal poured. ² These concentrations must be multiplied by the ratio of (1.45/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) for a specific plant. ³ Within the range of 7.0 to 10.0 at all times.

(c) *Die Casting Operations.*

NSPS

| Pollutant or pollutant property | Maximum for one 1 day | Maximum for monthly aver age | |
|---------------------------------|--|------------------------------------|--|
| | kg/1,000 kkg (pour lion pounds) poured | | |
| Copper (T) | 0.0066 | 0.0036 | |
| Lead (T) | 0.0068 | 0.0034 | |
| Zinc (T) | 0.0098 | 0.0037 | |
| Total Phenols | 0.0074 | 0.0026 | |
| Oil and grease | 0.259 | | |
| TSS and | 0.33 | | |
| pH | (¹) | | |

¹Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | Maximum for monthly average | Annual aver- age 1 |
|----------------|-----------------------------|-----------------------------------|--------------------------|
| | (mg/l) ² | (mg/l) 2 | |
| Copper (T) | 0.77 | 0.42 | 0.0015 |
| Lead (T) | 0.79 | 0.39 | 0.0019 |
| Zinc (T) | 1.14 | 0.43 | 0.0023 |
| Total phenols | 0.86 | 0.3 | 0.0017 |
| Oil and grease | 30 | 10 | 0.0432 |
| TSS and | 38 | 15 | 0.0864 |
| рН | (3) | (3) | (3) |

¹ kg/1,000 kkg (pounds per million pounds) of metal poured. ² These concentrations must be multiplied by the ratio of (1.04/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) ³ Within the range of 7.0 to 10.0 at all times.

(d) Dust Collection Scrubber Operations.

Environmental Protection Agency

NSPS

| Pollutant of pollutant prop- erty | Maximum for any 1 day | Maximum for monthly aver- age | |
|--|---|--|--|
| | kg/62.3 million Sm ³ (pounds per billion SCF) of air scrubbed | | |
| Cooper (T) Lead (T) Zinc (T) Total phenols Oil and grease TSS | 0.231 0.237 0.343 0.258 9.01 114 | 0.126 0.117 0.129 0.09 3.0 4.51 | |
| рН | (1) | (1) | |

¹ Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | maximum for monthly average | Annual aver- age 1 |
|----------------|-----------------------------|-----------------------------------|--------------------------|
| | (mg/l) ² | (mg/l) 2 | |
| Cooper (T) | 0.77 | 0.42 | 0.0511 |
| Lead (T) | 0.79 | 0.39 | 0.0661 |
| Zinc (T) | 1.14 | 0.43 | 0.0811 |
| Total phenols | 0.86 | 0.3 | 0.0601 |
| Oil and grease | 30 | 10 | 1.5 |
| TSS | 38 | 15 | 3.0 |
| рН | (3) | (3) | (3) |

1 kg/62.3 million Sm3 (pounds per billion SCF) of air

 $^{\rm K}$ (g/oz.3 minute on product product product of the seculated. ² These concentrations must be multiplied by the ratio of (0.036/x) where x is the actual normalized process waste-water flow (in gallons per 1,000 SCF of air scrubbed) for a coeffic plant. specific plant. ³Within the range of 7.0 to 10.0 at all times.

(e) Grinding Scrubber Operations. No discharge of process wastewater pollutants to navigable waters.

(f) Investment Casting.

NSPS

| Pollutant or pollutant prop- erty | Maximum for any 1 day | Maximum for monthly aver- age | |
|--------------------------------------|---|-------------------------------------|--|
| | kg/1,000 kkg (pounds per million pounds) of metal poured | | |
| Copper (T) | 8.48 | 4.63 | |
| Lead (T) | 8.7 | 4.3 | |
| Zinc (T) | 12.6 | 4.74 | |
| Oil and grease | 330 | 110 | |
| TSS | 419 | 165 | |
| рН | (1) | (1) | |

¹ Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | Maximum for monthly average | Annual average ¹ |
|----------------|-----------------------------|-----------------------------------|--------------------------------|
| | (mg/l) ² | (mg/l) ² | |
| Copper (T) | 0.77 | 0.42 | 1.87 |
| Lead (T) | 0.79 | 0.39 | 2.42 |
| Zinc (T) | 1.14 | 0.43 | 2.97 |
| Oil and grease | 30 | 10 | 55.1 |
| TSS | 38 | 15 | 110 |
| рН | (3) | (3) | (3) |

 1 kg/1,000 kkg (pounds per million pounds) of metal poured 2 These concentrations must be multiplied by the ratio of (1,320/x) where x is the actual normalized process waste-water flow (in gallons per 1,000 pounds of metal poured) for a specific plant.

³Within the range of 7.0 to 10.0 at all times.

(g) Melting Furnace Scrubber Operations.

NSPS

| Pollutant or pollutant prop- erty | Maximum for any 1 day | Maximum for monthly aver- age |
|--|--|--|
| | kg/62.3 million per billion SCF) | Sm ³ (pounds of air scrubbed |
| Copper (T) Lead (T) Zinc (T) Total phenols Oil and grease TSS PH | 3.01 3.09 4.45 3.36 117 148 (¹) | 1.64 1.52 1.68 1.17 39.1 58.6 (¹) |
| ¹ Within the range of 7.0 to | 10.0 at all times. | |

| | Maximum for any 1 day | Maximum for monthly average | Annual average ¹ |
|----------------|-----------------------------|-----------------------------------|--------------------------------|
| | (mg/l) ² | (mg/l) ² | |
| Copper (T) | 0.77 | 0.42 | 0.664 |
| Lead (T) | 0.79 | 0.39 | 0.859 |
| Zinc (T) | 1.14 | 0.43 | 1.05 |
| Total phenols | 0.86 | 0.3 | 0.781 |
| Oil and grease | 30 | 10 | 19.5 |
| TSS | 38 | 15 | 39.1 |
| pH | (3) | (3) | (³) |

 $^1\,\mbox{kg/62.3}$ million \mbox{Sm}^3 (pounds per billion SCF) of air scrubbed.

scrubbed. ²These concentrations must be multiplied by the ratio of (0.468/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 SCF of air scrubbed) for a specific plant. ³Within the range of 7.0 to 10.0 at all times.

(h) Mold Cooling Operations.

NSPS

| Pollutant or pollutant prop- erty | Maximum for any 1 day | Maximum for monthly aver- age |
|---|---|---|
| | kg/1,000 kkg (pounds per million pounds) of metal poured | |
| Copper (T) Lead (T) Zinc (T) Oil and grease TSS pH | 0.297 0.305 0.44 11.6 14.7 (¹) | 0.162 0.151 0.166 3.86 5.79 (¹) |

¹ Within the range of 7.0 to 10.0 at all times.

| | Maximum for any 1 day | Maximum for monthly average | Annual average ¹ |
|----------------|-----------------------------|-----------------------------------|--------------------------------|
| | (mg/l) ² | (mg/l) ² | |
| Copper (T) | 0.77 | 0.42 | 0.0656 |
| Lead (T) | 0.79 | 0.39 | 0.0849 |
| Zinc (T) | 1.14 | 0.43 | 0.104 |
| Oil and grease | 30 | 10 | 1.93 |
| TSS | 38 | 15 | 3.86 |
| рН | (3) | (3) | (3) |

1 kg/1,000 kkg (pounds per million pounds of metal poured.

§464.14

§464.15

 2 These concentrations must be multiplied by the ratio of (46.3/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) for a specific plant.

³ Within the range of 7.0 to 10.0 at all times.

[50 FR 45247, Oct. 30, 1985; 51 FR 21760, June 16, 1986]

§464.15 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

(a) Casting Cleaning Operations.

PSES

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly aver- age |
|------------------------------------|--|-------------------------------------|
| | kg/1,000 kkg (pounds per mil- lion pounds) of metal poured | |
| Copper (T) Lead (T) Zinc (T) | 0.0771 0.0791 0.114 | 0.0421 0.039 0.0431 |

(b) Casting Quench Operation.

PSES

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly aver- age |
|--|--|--------------------------------------|
| | kg/1,000 kkg (pounds per mil- lion pounds) of metal poured | |
| Copper (T) Lead (T) Zinc (T) TTO Oil and grease (for alternate | 0.0093 0.0096 0.0138 0.029 | 0.0051 0.0047 0.0052 0.0095 |
| monitoring) | 0.363 | 0.121 |

(c) Die Casting Operations.

40 CFR Ch. I (7-1-04 Edition)

PSES

| Pollutant or pollutant property | Maximum for any 1 day age | |
|---|--|--|
| | kg/1,000 kkg (p lion pound poured | oounds per mil- s) of metal |
| Copper (T) Lead (T) Zinc (T) Total phenols TTO Oil and grease (for alternate | 0.0066 0.0068 0.0098 0.0074 0.0308 | 0.0036 0.0034 0.0037 0.0026 0.01 |
| monitoring) | 0.259 | 0.0864 |

(d) Dust Collection Scrubber Operations.

PSES

| Pollutant or pollutant prop- erty | Maximum for any 1 day | Maximum for monthly aver- age |
|--|---|--|
| | kg/62.3 million per billion SCF) | Sm ³ (pounds of air scrubbed |
| Copper (T) Lead (T) Zinc (T) Total phenols TTO | 0.231 0.237 0.343 0.258 0.613 | 0.126 0.117 0.129 0.09 0.2 |
| nate monitoring) | 9.01 | 3.00 |

(e) *Grinding Scrubber Operations.* No discharge of process wastewater pollutants to a POTW.

(f) Investment Casting.

PSES

| Pollutant or pollutant property | Maximum for any 1 day | Maximum for monthly aver- age | |
|--|---|-------------------------------------|--|
| | kg/1,000 kkg (p lion pound poured | oounds per mil- s) of metal | |
| Copper (T) | 8.48 | 4.63 | |
| Lead (T) | 8.7 | 4.3 | |
| Zinc (T) | 12.6 | 4.74 | |
| TTO | 18.1 | 5.91 | |
| Oil and grease (for alternate monitoring | 330 | 110 | |

(g) Melting Furnace Scrubber Operations.