§ 464.37

PSNS

Pollutant or pollutant property	Maximum for any 1 day Maximum monthly av age	
	kg/1,000 kkg (pounds per mil lion pounds) of meta poured	
Copper (T) Lead (T) Zinc (T) Oil and grease (for alternate	0.0527 0.144 0.267 0.0257	0.0291 0.0709 0.102 0.00838
monitoring)	5.46	1.82

(i) Wet Sand Reclamation Operations. (1) Applicable to plants that are casting primarily ductile iron, to plants that are casting primarily malleable iron where greater than 3,557 tons of metal are poured per year, and to plants that are casting primarily gray iron where greater than 1,784 tons of metal are poured per year.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	kg/1,000 kkg (pounds per m lion pounds) of sand re claimed		
Copper (T)	0.217 0.396 0.732 0.642 1.18	0.12 0.194 0.276 0.224 0.386	
nate monitoring)	22.4	7.47	

(2) Applicable to plants that are casting primarily steel, to plants that are casting primarily malleable iron where equal to or less than 3,557 tons of metal are poured per year, and to plants that are casting primarily gray iron where equal to or less than 1,784 tons of metal are poured per year.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (p lion pounds) claimed	oounds per mil of sand re
Copper (T)	0.217 0.59 1.10 0.642 1.18	0.12 0.291 0.418 0.224 0.386
nate monitoring)	22.4	7.47

§ 464.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

Subpart D—Zinc Casting Subcategory

§ 464.40 Applicability; description of the zinc casting subcategory.

The provisions of this subpart are applicable to discharges to waters of the United States and to the introduction of pollutants into publicly owned treatment works resulting from zinc casting operations as defined in §464.02(d).

§ 464.41 Specialized definitions.

For the purpose of this subpart:

- (a) Total Toxic Organics (TTO). TTO is a regulated parameter under PSES (§464.45) and PSNS (§464.46) for the zinc subcategory and is comprised of a discrete list of toxic organic pollutants for each process segment where it is regulated, as follows:
- (1) Casting Quench (§464.45(a) and §464.46(a)):
- 21. 2,4,6-trichlorophenol
- 22. para-chloro meta-cresol
- 31. 2,4-dichlorophenol
- 34. 2,4-dimethylphenol
- 39. fluoranthene
- 44. methylene chloride (dichloromethane)
- 65. phenol 66. bis(2-ethylhexyl) phthalate
- 68. di-n-butyl phthalate
- 70. diethyl phthalate
- 85. tetrachloroethylene
- Die Casting (§ 465.45(b) and § 464.46(b)):
- 1. acenaphthene
- 21. 2,4,6-trichlorophenol
- 22. para-chloro meta-cresol
- 24. 2-chlorophenol
- 34. 2,4-dimethylphenol
- 44. methylene chloride (dichloromethane)
- 55. naphthalene
- 65. phenol
- 66. bis (2-ethylhexyl) phthalate 68. di-n-butyl phthalate
- 70. diethyl phthalate
- 85. tetrachloroethylene
- 86. toluene
- 87. trichloroethylene
- Melting Furnace Scrubber (§ 464.45(c) and § 464.46(c)):
- 31. 2,4-dichlorophenol
- 34. 2,4-dimethylphenol
- 39. fluoranthene

Environmental Protection Agency

- 44. methylene chloride (dichloromethane)
- 55. naphthalene
- 65. phenol
- 66. bis(2-ethylhexyl) phthalate
- 68. di-n-butyl phthalate
- 85. tetrachloroethylene
- 86. toluene
- 87. trichloroethylene
- (4) Mold Cooling ($\S464.45(d)$ and $\S464.46(d)$):
- 21. 2,4,6-trichlorophenol
- 22. para-chloro meta-cresol
- 31. 2,4-dichlorophenol
- 34. 2,4-dimethylphenol
- 39. fluoranthene
- 44. methylene chloride (dichloromethane)
- 65. phenol
- 66. bis(2-ethylhexyl) phthalate
- 68. di-n-butyl phthalate
- 70. diethyl phthalate
- 85. tetrachloroethylene

[50 FR 45247, Oct. 30, 1985; 51 FR 21762, June 16, 1986]

§ 464.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in $40\ \text{CFR}\ 125.30$ through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available, except that non-continuous dischargers shall not be subject to the maximum day and maximum for monthly average mass (kg/1,000 kkg or lb/million lb of metal poured; kg/62.3 million Sm3 or lb/ billion SCF of air scrubbed) effluent limitations for copper, lead, zinc, total phenols, oil and grease, and TSS. For non-continuous dischargers, annual average mass limitations and maximum day and maximum for monthly average concentration (mg/1) limitations shall apply. Concentration limitations and annual average mass limitations shall only apply to noncontinuous dischargers.

(a) Casting Quench Operations.

BPT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	kg/1,000 kkg (pounds per mil- lion pounds) of metal poured		
Copper (T)	0.0344	0.0187	
Lead (T)	0.0353	0.0174	
Zinc (T)	0.0509	0.0192	
Oil and grease	1.34	0.446	
TSS	1.7	0.67	
pH	(1)	(1)	

¹ Within the range of 7.0 to 10.0 at all times.

Maximum for any 1 day	Maximum for monthly average	Annual aver- age 1
(mg/1) ²	(mg/1) ²	
0.77	0.42	0.0076
0.79	0.39	0.0098
1.14	0.43	0.0121
30	10	0.223
38	15	0.446
(3)	(3)	(3)
	for any 1 day (mg/1) ² 0.77 0.79 1.14 30 38	for any 1 for monthly average (mg/1) ² (mg/1) ² 0.77 0.42 0.79 0.39 1.14 0.43 30 10 38 15

¹ kg/1000 kkg (pound per million pounds) of metal poured. These concentrations must be multiplied by the ratio of (5.35/x) where x is the actual normalized process wastewater flow (in gallons per 1,000 pounds of metal poured) for a specific plane?

BPT EFFLUENT LIMITATIONS

(b) Die Casting Operations.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	kg/1,000 kkg (pounds per mil lion pounds) of meta poured		
Copper (T)	0.0066 0.0068 0.0098 0.0074 0.259 0.328	0.0036 0.0034 0.0037 0.0026 0.0864 0.13	

¹ Within the range of 7.0 to 10.0 at all times.

	Maximum for any 1 day	Maximum for monthly average	Annual average ¹
	(mg/	(mg/	
Copper (T)	0.77	0.42	0.0015
Lead (T)	0.79	0.39	0.0019
Zinc (T)	1.14	0.43	0.0023
Total phenols	0.86	0.3	0.0017
Oil and grease	30	10	0.0432
TSS	38	15	0.0864
pH	(3)	(3)	(3)

¹ kg/1000 kkg (pound per million pounds) of metal poured.

ਗਿੰਦ piant. ³Within the range of 7.0 to 10.0 at all times.