

§ 58.130 Health.

No person afflicted with a communicable disease shall be permitted in any room or compartment where milk and dairy products are prepared, manufactured or otherwise handled. No person who has a discharging or infected wound, sore or lesion on hands, arms or other exposed portion of the body shall work in any dairy processing rooms or in any capacity resulting in contact with milk, or dairy products. Each employee whose work brings him in contact with the processing or handling of dairy products, containers or equipment should have a medical and physical examination by a registered physician or by the local department of health at the time of employment. An employee returning to work following illness from a communicable disease shall have a certificate from the attending physician to establish proof of complete recovery.

PROTECTION AND TRANSPORT OF RAW
MILK AND CREAM

§ 58.131 Equipment and facilities.

(a)(1) *Milk cans.* Cans used in transporting milk from dairy farm to plant shall be of such construction (preferably seamless with umbrella lids) as to be easily cleaned, and shall be inspected, repaired, and replaced as necessary to exclude substantially the use of cans and lids with open seams, cracks, rust, milkstone, or any unsanitary condition. Adequate provisions should be made so that milk in cans will be cooled immediately after milking to 50 °F. or lower unless delivered to the plant within two hours after milking.

(2) *Farm bulk tanks.* Farm bulk tanks shall comply with 3-A Sanitary Standards for Farm Cooling and Holding Tanks or 3-A Sanitary Standards for Farm Milk Storage Tanks, as applicable. They shall be installed in a milk house in accordance with the requirements of the regulatory agency in jurisdiction. The bulk cooling tanks shall be designed and equipped with refrigeration to permit the cooling of the milk to 40 °F. or lower within two hours after milking, and maintain it at 45 °F. or below until picked up.

(b)(1) *Receiving stations.* Receiving stations shall comply with the applicable sections of this subpart covering premises, buildings, facilities, equipment, utensils, personnel, cleanliness and health.

(2) *Transfer stations.* Transfer stations shall comply with the applicable sections of this subpart covering premises, floors, lighting, water supply, hand-washing facilities, disposal of wastes, general construction, repair and installation of equipment, piping and utensils and personnel—cleanliness and health. As climatic and operating conditions require the transfer station shall comply with the applicable sections for walls, ceilings, doors and windows.

(3) *Cream stations.* Cream stations shall provide adequate protection and facilities for the handling, transferring and cooling of farm separated cream. The area shall be large enough to avoid undue crowding with a normal volume of business and shall be separated from other areas and the outside by self closing, tight fitting doors. All openings shall be screened during fly season. The floor, walls and ceiling shall be of satisfactory construction, in good repair and kept clean. Lighting and ventilation shall meet the requirements of § 58.126(d). Cooling facilities shall be provided to cool the cream to 50 °F. or lower unless shipped within 8 hours after receipt. Facilities shall be provided to wash, sanitize and store cans and equipment used in the operation. The cream should not be more than 4 days old when picked up for delivery to the processing plant.

(c)(1) *Transporting milk or cream.* Vehicles used for the transportation of can milk or cream shall be of the enclosed type, constructed and operated to protect the product from extreme temperature, dust, or other adverse conditions and they shall be kept clean. Decking boards or racks shall be provided where more than one tier of cans is carried. Cans or vehicles used for the transportation of milk from the farm to the plant shall not be used for transporting skim milk, buttermilk, or whey to producers.

(2) *Transport tanks.* The exterior shell shall be clean and free from open seams or cracks which would permit liquid to