

## § 58.210

for 15 seconds or its equivalent in bacterial destruction. Dry buttermilk product has a protein content less than 30.0 percent. Dry buttermilk product shall not contain nor be derived from nonfat dry milk, dry whey, or products other than buttermilk, and shall not contain any added preservative, neutralizing agent, or other chemical.

[40 FR 47911, Oct. 10, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 56 FR 33855, July 24, 1991; 61 FR 17548, Apr. 22, 1996; 61 FR 35590, July 8, 1996]

### ROOMS AND COMPARTMENTS

#### § 58.210 Dry storage of product.

Storage rooms for the dry storage of product shall be adequate in size, kept clean, orderly, free from rodents, insects, and mold, and maintained in good repair. They shall be adequately lighted and ventilated. The ceilings, walls, beams and floors should be free from structural defects and inaccessible false areas which may harbor insects.

#### § 58.211 Packaging room for bulk products.

A separate room or area shall be provided for filling bulk containers, and shall be constructed in accordance with § 58.126. The number of control panels and switch boxes in this area should be kept to a minimum. Control panels shall be mounted a sufficient distance from the walls to facilitate cleaning or satisfactorily sealed to the wall, or shall be mounted in the wall and provided with tight fitting removable doors to facilitate cleaning. An adequate exhaust system shall be provided to minimize the accumulation of product dust within the packaging room and where needed, a dust collector shall be provided and properly maintained to keep roofs and outside areas free of dry product. Only packaging materials that are used within a day's operation may be kept in the packaging area. These materials shall be kept on metal racks or tables at least six inches off the floor. Unnecessary fixtures, equipment, or false areas which may collect dust and harbor insects, should not be allowed in the packaging room.

## 7 CFR Ch. I (1-1-05 Edition)

#### § 58.212 Hopper or dump room.

A separate room shall be provided for the transfer of bulk dry dairy products to the hoppers and conveyors which lead to the fillers. This room shall meet the same requirements for construction and facilities as the bulk packaging operation. Areas and facilities provided for the transfer of dry dairy products from portable bulk bins will be accepted if gasketed surfaces or direct connections are used that appreciably eliminate the escape of product into the area.

#### § 58.213 Repackaging room.

A separate room shall be provided for the filling of small packages and shall meet the same requirements for construction and facilities as the bulk packaging operation.

### EQUIPMENT AND UTENSILS

#### § 58.214 General construction, repair and installation.

All equipment and utensils necessary to the manufacture of dry milk products, including pasteurizer, timing-pump or device, flow diversion valve and recorder controller, shall meet the same general requirements as outlined in § 58.128 of this subpart. In addition, for certain other equipment the following requirements shall be met.

#### § 58.215 Pre-heaters.

The pre-heaters shall be of stainless steel or other equally corrosion resistant material, cleanable, accessible for inspection and shall be equipped with suitable automatic temperature controls.

#### § 58.216 Hotwells.

The hotwells shall be enclosed or covered and should be equipped with indicating thermometers either in the hotwell or in the hot milk inlet line to the hotwell. If used for holding high heat products, they should also have recorders.

#### § 58.217 Evaporators and/or vacuum pans.

Evaporators or vacuum pans or both, with open type condensers shall be equipped with an automatic condenser water level control, barometric leg, or