

§ 58.237

7 CFR Ch. I (1-1-05 Edition)

§ 58.237 Condensed surge supply.

Surge tanks or balance tanks if used between the evaporators and dryer shall be used to hold only the minimum amount of condensed product necessary for a uniform flow to the dryers. Such tanks holding product at temperatures below 150 °F. shall be completely emptied and washed after each 4 hours of operation or less. Alternate tanks shall be provided to permit continuous operation during washing of tanks.

§ 58.238 Condensed storage tanks.

(a) Excess production of condensed product over that which the dryer will take continuously from the pans should be bypassed through a cooler into a storage tank at 50 °F. or lower and held at this temperature until used.

(b) Product cut-off points shall be made at least every 24 hours and the tank completely emptied, washed, and sanitized before reuse.

§ 58.239 Drying.

Each dryer should be operated to produce the highest quality dry product consistent with the most efficient operation. The dry products shall be removed from the drying chamber continuously during the drying process.

§ 58.240 Cooling dry products.

Prior to packaging and immediately following removal from the drying chamber the dry product shall be cooled to a temperature not exceeding 110 °F, however, if the product is to be held in a bulk bin the temperature should be reduced to approximately 90 °F but shall be not more than 110 °F.

§ 58.241 Packaging, repackaging and storage.

(a) *Containers.* Packages or containers used for the packaging of non-fat dry milk or other dry milk products shall be any clean, sound commercially accepted container or packaging material which will satisfactorily protect the contents through the regular channels of trade, without significant impairment of quality with respect to flavor, wholesomeness or moisture content under the normal conditions of

handling. In no instance will containers which have previously been used for nonfood items, or food items which would be deleterious to the dairy product be allowed to be used for the bulk handling of dairy products.

(b) *Filling.* Empty containers shall be protected at all times from possible contamination and containers which are to be lined shall not be prepared more than one hour in advance of filling. Every precaution shall be taken during the filling operation to minimize product dust and spillage. When necessary a mechanical shaker shall be provided; the tapping or pounding of containers should be prohibited. The containers shall be closed immediately after filling and the exteriors shall be vacuumed or brushed when necessary to render them practically free of residual product before being transferred from the filling room to the palleting or dry storage areas.

(c) *Repackaging.* The entire repackaging operation shall be conducted in a sanitary manner with all precautions taken to prevent contamination and to minimize dust. All exterior surfaces of individual containers shall be practically free of product before overwrapping or packing in shipping containers. The room shall be kept free of dust accumulation, waste, cartons, liners, or other refuse. Conveyors, packaging and carton making equipment shall be vacuumed frequently during the operating day to prevent the accumulation of dust. No bottles or glass materials of any kind shall be permitted in the repackaging or hopper room. The inlet openings of all hoppers and bins shall be of minimum size, screened and placed well above the floor level. The room and all packaging equipment shall be cleaned as often as necessary to maintain a sanitary operation. Close attention shall be given to cleaning equipment where residues of the dry product may accumulate. A thorough clean-up including windows, doors, walls, light fixtures and ledges, should be performed as frequently as is necessary to maintain a high standard of cleanliness and sanitation. All waste dry dairy products including dribble product at the fillers, shall be properly identified and disposed of as animal feed.