

the amount of curd as it fills. The curd filler shall be constructed so that it can be satisfactorily cleaned.

(e) *Hoop and barrel washer.* The washer shall be constructed so that it can be satisfactorily cleaned. It shall also be equipped with temperature and pressure controls to ensure satisfactory cleaning of the hoops or barrels. It should be adequately vented to the outside.

§ 58.419 Curd mill and miscellaneous equipment.

Knives, hand rakes, shovels, scoops, paddles, strainers, and miscellaneous equipment shall be stainless steel or of material approved in the 3-A Sanitary Standards for Plastic and Rubber-like Material. The product contact surfaces of the curd mill should be of stainless steel. All pieces of equipment shall be so constructed that they can be kept clean and free from rough or sharp edges which might scratch the equipment or remove metal particles. The wires in the curd knives shall be stainless steel, kept tight and replaced when necessary.

§ 58.420 Hoops, forms and followers.

The hoops, forms, and followers shall be constructed of stainless steel, heavy tinned steel or other approved materials. If tinned, they shall be kept tinned and free from rust. All hoops, forms, and followers shall be kept in good repair. Drums or other special forms used to press and store cheese shall be clean and sanitary.

§ 58.421 Press.

The cheese press should be constructed of stainless steel and all joints welded and all surfaces, seams and openings readily cleanable. The pressure device shall be the continuous type. Press cloths shall be maintained in good repair and in a sanitary condition. Single service press cloths shall be used only once.

§ 58.422 Brine tank.

The brine tank shall be constructed of suitable non-toxic material and should be resistant to corrosion, pitting or flaking. The brine tank shall be operated so as to assure the brine is clean, well circulated, and of the prop-

er strength and temperature for the variety of cheese being made.

§ 58.423 Cheese vacuumizing chamber.

The vacuum chamber shall be satisfactorily constructed and maintained so that the product is not contaminated with rust or flaking paint. An inner liner of stainless steel or other corrosion resistant material should be provided.

§ 58.424 Monorail.

The monorail shall be constructed so as to prevent foreign material from falling on the cheese or cheese containers.

§ 58.425 Conveyor for moving and draining block or barrel cheese.

The conveyor shall be constructed so that it will not contaminate the cheese and be easily cleaned. It shall be installed so that the press drippings will not cause an environmental problem.

§ 58.426 Rindless cheese wrapping equipment.

The equipment used to heat seal the wrapper applied to rindless cheese shall have square interior corners, reasonably smooth interior surface and have controls that shall provide uniform pressure and heat equally to all surfaces. The equipment used to apply shrinkable wrapping material to rindless cheese shall operate to maintain the natural intended shape of the cheese in an acceptable manner, reasonably smooth surfaces on the cheese and tightly adhere the wrapper to the surface of the cheese.

§ 58.427 Paraffin tanks.

The metal tank should be adequate in size, have wood rather than metal racks to support the cheese, have heat controls and an indicating thermometer. The cheese wax shall be kept clean.

§ 58.428 Speciality equipment.

All product contact areas of speciality equipment shall be constructed of stainless steel or of material approved in the 3-A Sanitary Standards for Plastic and Rubber and Rubber-