

§ 58.716

§ 58.716 Nonfat dry milk.

Nonfat dry milk used in cheese products should meet the requirements equivalent to U.S. Extra Grade except that the moisture content may be in excess of that specified for the particular grade.

§ 58.717 Whey.

Whey used in cheese products should meet the requirements equivalent to USDA Extra Grade except that the moisture requirement for dry whey may be waived.

§ 58.718 Flavor ingredients.

Flavor ingredients used in process cheese and related products shall be those permitted by the Food and Drug Standards of Identity, and in no way deleterious to the quality or flavor of the finished product. In the case of bulky flavoring ingredients such as pimento, the particles should be, to at least a reasonable degree, uniform in size, shape and consistency. The individual types of flavoring materials should be uniform in color and should impart the characteristic flavor desired in the finished product.

§ 58.719 Coloring.

Coloring shall be Annatto or any other cheese or butter color which is approved by the Food and Drug Administration.

§ 58.720 Acidifying agents.

Acidifying agents if used shall be those permitted by the Food and Drug Administration for the specific pasteurized process cheese product.

§ 58.721 Salt.

Salt shall be free flowing, white refined sodium chloride and shall meet the requirements of The Food Chemical Codex.

§ 58.722 Emulsifying agents.

Emulsifying agents shall be those permitted by the Food and Drug Administration for the specific pasteurized process cheese product, and shall be free from extraneous material.

7 CFR Ch. I (1-1-05 Edition)

OPERATIONS AND OPERATING PROCEDURES

§ 58.723 Basis for selecting cheese for processing.

A representative sample shall have been examined to determine fat and moisture content. One sample unit from each vat of cheese shall have been examined to determine the suitability of the vat for use in process cheese products in accordance with the flavor, body and texture characteristics permitted in §§ 58.711 through 58.714 as applicable, and to determine the characteristics it will contribute to the finished product when blended with other cheese. The cheese included in each blend shall be selected on the basis of the desirable qualities which will result in the desired finished product. Recook from equivalent blends may be used in an amount that will not adversely affect the finished product. Hot cheese from the filler may be added to the cooker in amounts which will not adversely affect the finished product.

§ 58.724 Blending.

To as great an extent as is practical, each vat of cheese should be divided and distributed throughout numerous cooker batches. The purpose being to minimize the preponderance and consequent influence of any one vat on the characteristics of the finished product, and to promote as much uniformity as is practical. In blending also consider the final composition requirements for fat and moisture. Quantities of salt, color, emulsifier and other allowable ingredients to be added shall be calculated and predetermined for each cooker batch.

§ 58.725 Trimming and cleaning.

The natural cheese shall be cleaned free of all non-edible portions. Paraffin and bandages as well as rind surface, mold or unclean areas or any other part which is unwholesome or unappetizing shall be removed.

§ 58.726 Cutting and grinding.

The trimmed and cleaned cheese should be cut into sections of convenient size to be handled by the grinder or shredder. The grinding and mixing of the blended lots of cheese should be

Agricultural Marketing Service, USDA

§ 58.733

done in such a manner as to insure a homogeneous mixture throughout the batch.

§ 58.727 Adding optional ingredients.

As each batch is added to the cooker, the predetermined amounts of salt, emulsifiers, color, or other allowable optional ingredients shall be added. However, a special blending vat may be used to mix the ground cheese and other ingredients before they enter the cooker to provide composition control.

§ 58.728 Cooking the batch.

Each batch of cheese within the cooker, including the optional ingredients, shall be thoroughly commingled and the contents pasteurized at a temperature of at least 158 °F. and held at that temperature for not less than 30 seconds or any other equally effective combination of time and temperature approved by the Administrator. Care shall be taken to prevent the entrance of cheese particles or ingredients after the cooker batch of cheese has reached the final heating temperature. After holding for the required period of time, the hot cheese shall be emptied from the cooker as quickly as possible.

§ 58.729 Forming containers.

Containers either lined or unlined shall be assembled and stored in a sanitary manner to prevent contamination. The handling of containers by filler crews should be done with extreme care and observance of personal cleanliness. Preforming and assembling of pouch liners and containers shall be kept to a minimum and the supply rotated to limit the length of time exposed to possible contamination prior to filling.

§ 58.730 Filling containers.

Hot fluid cheese from the cookers may be held in hotwells or hoppers to assure a constant and even supply of processed cheese to the filler or slice former. Filler valves shall effectively measure the desired amount of product into the pouch or container in a sanitary manner and shall cut off sharply without drip or drag of cheese across the opening. An effective system shall be used to maintain accurate and precise weight control. Damaged or unsatisfactory packages shall be removed

from production, and the cheese may be salvaged into sanitary containers, and added back to cookers.

§ 58.731 Closing and sealing containers.

Pouches, liners, or containers having product contact surfaces, after filling shall be folded or closed and sealed in a sanitary manner, preferably by mechanical means, so as to assure against contamination. Each container in addition to other required labeling shall be coded in such a manner as to be easily identified as to date of manufacture by lot or subplot number.

§ 58.732 Cooling the packaged cheese.

After the containers are filled they shall be stacked, or cased and stacked in such a manner as to prevent breaking of seals due to excessive bulging and to allow immediate progressive cooling of the individual containers of cheese. As a minimum the cheese should be cooled to a temperature of 100 °F. or lower within 24 hours after filling. The temperature of the cheese should be reduced further, before being shipped or if storage is intended.

§ 58.733 Quality control tests.

(a) *Chemical analyses.* The following chemical analyses shall be performed in accordance with the appropriate edition of the Official Methods of Analysis of the AOAC as specified in the appropriate Standards of Identity or in accordance with methods that give equivalent results.

(1) *Cheese.* A representative sample of cheese used in the manufacture of pasteurized process cheese products shall have been tested prior to usage to determine its moisture and fat content.

(2) *Pasteurized process cheese products.* As many samples shall be taken of the finished product direct from the cooker, hopper, filler, or other location as is necessary to assure compliance with composition requirements. Spot checks should be made on samples from the cooker as frequently as is necessary to indicate pasteurization by means of the phosphatase test, as well as any other tests necessary to assure good quality control.

(b) *Examination of physical characteristics.* As many samples shall be taken as