49 CFR Ch. I (10-1-07 Edition)

(b) In addition to complying with §172.407, the background on the RADIO-ACTIVE WHITE-I label must be white. The printing and symbol must be black, except for the "I" which must be red

§ 172.438

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§ 172.438 RADIOACTIVE YELLOW-II label.

(a) Except for size and color, the RA-DIOACTIVE YELLOW-II must be as follows:



(b) In addition to complying with §172.407, the background color on the RADIOACTIVE YELLOW-II label must be yellow in the top half and white in the lower half. The printing and sym-

bol must be black, except for the "II" which must be red.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§ 172.440 RADIOACTIVE YELLOW-III label.

(a) Except for size and color, the RA-DIOACTIVE YELLOW-III label must be as follows:



(b) In addition to complying with §172.407, the background color on the RADIOACTIVE YELLOW-III label must be yellow in the top half and white in the lower half. The printing and symbol must be black, except for the ''III'' which must be red.

[Amdt. 172-123, 56 FR 66259, Dec. 20, 1991]

§172.441 FISSILE label.

(a) Except for size and color, the FISSILE label must be as follows: