## Pipeline and Hazardous Materials Safety Admin., DOT

§172.556

(b) In addition to complying with §172.519, the background on the POI-SON placard must be white. The symbol, text, class number and inner border must be black. The word "TOXIC" may be used in lieu of the word "POI-SON".

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991, as amended by Amdt. 172-139, 59 FR 67490, Dec. 29, 1994]

## §172.555 POISON INHALATION HAZ-ARD placard.

(a) Except for size and color, the POI-SON INHALATION HAZARD placard must be as follows:

INHALATION HAZARD 6 (b) In addition to complying with §172.519, the background on the POI-SON INHALATION HAZARD placard and the symbol must be white. The background of the upper diamond must be black and the lower point of the upper diamond must be 65 mm (25% inches) above the horizontal center line. The text, class number, and inner border must be black.

[62 FR 39409, July 22, 1997]

## §172.556 RADIOACTIVE placard.

(a) Except for size and color, the RA-DIOACTIVE placard must be as follows:

49 CFR Ch. I (10-1-07 Edition)



(b) In addition to complying with \$172.519, the background color on the RADIOACTIVE placard must be white in the lower portion with a yellow triangle in the upper portion. The base of the yellow triangle must be 29 mm  $\pm 5$  mm (1.1 inches  $\pm 0.2$  inches) above the placard horizontal center line. The

§172.558

symbol, text, class number and inner border must be black.

[Amdt. 172-123, 56 FR 66264, Dec. 20, 1991; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993; 65 FR 58627, Sept. 29, 2000]

## §172.558 CORROSIVE placard.

(a) Except for size and color, the CORROSIVE placard must be as follows: