Use Information: This paragraph is informational only and is not exclusively definitive of the end use. For minimum quality face and back offset printing of catalogs, pamphlets, newsletter, newspapers, etc., of a non-permanent nature. Printed matter may include text, line illustrations, and 65-line screen halftones.

Stock : Not less than 40% postconsumer fiber. Any percent over 40 percentage points, is encourage, provided that the requirements of this Standard are met.					Thickness : Average (mils) 2.8 3.0 3.2 3.5 A tolerance of ±0.0005 inch shall be allowed. Paper shall be uniform and shall not vary more than 0.0004 inch from edge to edge.
Basis weight: 24 by 36 inches,					
500 sheets (pounds)	25	28	30	32	General appearance: Paper shall conform to the standard
A tolerance of $\pm 5\%$ shall be allowed.					sample(s) established by the Government.
					Brightness : Shall target 53% or as specified.
Tearing strength: Average each					
direction, not less than (grams)	18	20	22	24	<i>Color</i> : The paper in the order (or publication) shall be
					uniform and the color variation shall not exceed
Opacity : Average not less than					DE(CIELAB) = 1.0.
(percent)	87	89	90	91	<i>Finish and formation</i> : Shall be uniform.
No individual specimen shall average					
less than (percent)	85	87	88	89	<u>Cleanliness</u> : Shall match the Government standard.

Testing: Shall be conducted in accordance with methods in part 2, *Government Paper Specification Standards*. The acceptance criteria Part 4 shall apply.