

**BID LIST NO. 0465**

**SPECIFICATION FOR GLOVES, NEOPRENE COATED, MEDIUM**

**PROPERTY NO. 224995**

**General Requirements**

The gloves shall be puncture and abrasion resistant. They shall have no pinholes or leaks of any sort.

**Specific Requirements**

Construction: Gloves to be neoprene rubber coated and knit lined. The finger and palm areas are to have a slip resistant "sandpaper" textured coating.

Length: 305-mm  $\pm$  12.5 mm (12"  $\pm$  0.5") as measured from the tip of the second finger to the end of the gauntlet.

Thickness: 0.71-mm (0.028") minimum

Size: .....Men's medium

**Sample Requirement**

One pair of gloves is required.

**Qualified Products**

Edmond Scorpio No. 8-352  
Memphis Neomax No. 6912  
Pioneer NL-34

Date of Last Revision: February 21, 1995

**SPECIFICATION FOR GLOVES, NEOPRENE COATED, LARGE**

**PROPERTY NO. 224987**

**General Requirements**

The gloves shall be puncture and abrasion resistant. They shall have no pinholes or leaks of any sort.

**Specific Requirements**

Construction: Gloves to be neoprene rubber coated and knit lined. The finger and palm areas are to have a slip resistant "sandpaper" textured coating.

Length: 305-mm  $\pm$  12.5 mm (12"  $\pm$  0.5") as measured from the tip of the second finger to the end of the gauntlet.

Thickness: 0.71-mm (0.028") minimum

Size: .....Men are large

**Sample Requirement**

One pair of gloves is required.

**Qualified Products**

Edmont Scorpio No. 8-352  
Memphis Neomax No. 6912  
Pioneer NL-34

Date of Last Revision: February 21, 1995

**SPECIFICATION FOR GLOVES, NEOPRENE COATED, EXTRA LARGE**

**PROPERTY NO. 225045**

**General Requirements**

The gloves shall be puncture and abrasion resistant. They shall have no pinholes or leaks of any sort.

**Specific Requirements**

Construction: Gloves to be neoprene rubber coated and knit lined. The finger and palm areas are to have a slip resistant "sandpaper" textured coating.

Length: 305-mm  $\pm$  12.5 mm (12"  $\pm$  0.5") as measured from the tip of the second finger to the end of the gauntlet.

Thickness: 0.71-mm (0.028") minimum

Size: .....Extra Large

**Sample Requirement**

One pair of gloves is required.

**Qualified Products**

Edmont Scorpio No. 8-352  
Memphis Neomax No. 6912  
Pioneer NL-34

Date of Last Revision: February 21, 1995