NASA/TM-2000-209891, Vol. 203



ce Flight Center yland 20771

Nov

#### The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION. English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to: NASA Access Help Desk NASA Center for AeroSpace Information 7121 Standard Drive Hanover, MD 21076-1320



# **Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)**

Forrest G. Hall and Karl Huemmrich, Editors

# Volume 203 BOREAS TF-8 NSA-OJP Tower Flux, Meteorological, and Soil Temperature Data

Kathleen E. Moore and David R. Fitzjarrald State University of New York, Albany

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

Available from:

NASA Center for AeroSpace Information 7121 Standard Drive Hanover, MD 21076-1320 Price Code: A17 National Technical Information Service 5285 Port Royal Road Springfield, VA 22161 Price Code: A10

## BOREAS TF-8 NSA-OJP Tower Flux, Meteorological, and Soil Temperature Data

Kathleen E. Moore, David R. Fitzjarrald

## Summary

The BOREAS TF-8 team collected energy, CO<sub>2</sub>, and water vapor flux data at the BOREAS NSA-OJP site during the growing season of 1994 and most of the year for 1996. The data are available in tabular ASCII files.

## **Table of Contents**

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Åcronyms
- 20) Document Information

## 1. Data Set Overview

### **1.1 Data Set Identification**

BOREAS TF-08 NSA-OJP Tower Flux, Meteorological, and Soil Temperature Data

### **1.2 Data Set Introduction**

This study focused on long-term measurements of radiation, heat, moisture,  $CO_2$ , and momentum budgets from the tower at the BOReal-Ecosystem-Atmosphere Study (BOREAS) Northern Study Area (NSA) Old Jack Pine (OJP) site. Turbulent fluxes were determined using the eddy correlation technique, and radiative fluxes in the short, long, near-infrared, and Photosynthetically Active Radiation (PAR) wavelength bands were acquired as well. Also, soil moisture content data were collected. Through collaboration with other groups, the  $CO_2$  gradients inside and just above the canopy were acquired. In addition, a digital cloud camera was used to obtain a seasonal record of cloud fraction and cloud type.

#### 1.3 Objective/Purpose

The objective was to make measurements of the components of the energy and radiation balances over an old jack pine forest in the Canadian boreal forest ecosystem during a period of time encompassing a large portion of a growing season. These measurements, together with direct measurements of the  $CO_2$  flux, provide a view of ecosystem functioning on a wide range of time scales. In addition, the contribution of jack pine landcover to the regional fluxes of heat, water vapor, momentum, and  $CO_2$  was assessed.

#### **1.4 Summary of Parameters**

Turbulent flux measurements included above- and below-canopy measurements of sensible and latent heat fluxes, CO<sub>2</sub> flux, and friction velocity. Gradient measurements included vertical profiles of wind speed, relative and specific humidity, and air temperature. Radiative measurements included net radiation, upwelling and downwelling PAR, upwelling and downwelling global shortwave radiation, upwelling and downwelling longwave radiation, surface temperature, and undercanopy net radiation. Meteorological measurements included wind speed and direction, air pressure, and rainfall. Soil measurements included soil water potential, soil temperature, and soil heat flux. These measurements were collected at different locations with different ground covers. The soil temperatures were collected at multiple depths.

#### **1.5 Discussion**

The objectives of this study were to obtain the time series of the elements in the surface energy and water balance during the growing season at the BOREAS NSA-OJP in order to provide data to investigate vegetation-atmosphere models; to relate the vertical wind profile to the frequency and type of coherent turbulent eddies in the canopy layer; and to relate components of radiation budget, the observed cloud fraction, type, and height to develop feedback relationships between surface heat and water vapor fluxes and convective cloud cover.

By making redundant measurements of the components of the energy balance, uncertainty is reduced and the possibility of discovering the true balance is increased. Gradient measurements are of interest in their own right, for instance, to obtain estimates of the displacement height. Each measurement has its own footprint. For example, the sonic anemometer at tower top is looking at an area perhaps 200-500 m upwind of the sensor, while the net radiometer is measuring a smaller area closer to the tower.

#### **1.6 Related Data Sets**

BOREAS TF-05 SSA-OJP Tower Flux, Meteorological, and Soil Temperature Data BOREAS TF-03 NSA-OBS Tower Flux, Meteorological, and Soil Temperature Data BOREAS TF-08 NSA-OJP and SSA-OBS Ceilometer Data BOREAS TF-10 NSA-YJP Tower Flux, Meteorological, and Biophysical Data BOREAS TF-10 NSA-Fen Tower Flux and Meteorological Data

## 2. Investigator(s)

#### 2.1 Investigator(s) Name and Title

David R. Fitzjarrald Research Associate Atmospheric Sciences Research Center (ASRC)

Kathleen E. Moore Research Scientist ASRC

#### 2.2 Title of Investigation

Surface Exchange Observations in the Canadian Boreal Forest Region

#### **2.3 Contact Information**

#### Contact 1:

Kathleen E. Moore Research Scientist Atmospheric Sciences Research Center 251 Fuller Rd. Albany, NY 12203 (518) 437-8732 (518) 437-8758 (fax) moore@asrc.cestm.albany.edu

#### Contact 2:

David R. Fitzjarrald Research Associate Atmospheric Sciences Research Center 251 Fuller Rd. Albany, NY 12203 (518) 437-8735 (518) 437-8758 (fax) fitz@asrc.cestm.albany.edu

#### Contact 3:

K. Fred Huemmrich University of Maryland Code 923 NASA GSFC Greenbelt, MD 20771 (301) 286-4862 (301) 286-0239 (fax) Karl.Huemmrich@gsfc.nasa.gov

## 3. Theory of Measurements

The boreal forest is important to the global energy and carbon balance, due partly to the large area covered by this vegetation type. Measurements on a wide variety of time and space scales are required in order to achieve an integrated understanding of these balances and the factors that affect them from day to day and over a growing season. Tower-based measurements provide ground truth for satellite and other remote sensing measurements. Eddy correlation estimates represent the only direct measurements of fluxes. Auxiliary measurements, e.g., soil, gradients, etc., are of fundamental importance. For example, it may be possible to use a similarity argument for water vapor and  $CO_2$  to get the  $CO_2$  storage term at night by examining how humidity builds up in the stable surface layer.

Eddy correlation measurements are accomplished by simply calculating the covariance between the fluctuating vertical velocity and the fluctuating scalar or vector quantity of interest.

## 4. Equipment

#### 4.1 Sensor/Instrument Description

#### **4.1.1** Collection Environment

Measurements were collected from late May through mid-September 1994 and mid-April through mid-November of 1996. Over that time period, temperature conditions from less than -15 °C to over 30 °C were experienced.

#### 4.1.2 Source/Platform

A 30-m Rohn communications tower was used throughout the experiment. Turbulent fluxes were measured at the top of the tower and at 13 m (until 29-Jul-1994, when a separate, 2-m mast was erected for subcanopy fluxes). In 1994, the subcanopy flux measurements were made in an open, lichen-covered area approximately 15 m west of the tall tower. In 1996, the subcanopy array was erected on 09-Jul in a moss-covered area to the north of the tower.

#### 4.1.3 Source/Platform Mission Objectives

The purpose of the tower was to support instruments to measure energy, water, and  $CO_2$  fluxes and related environmental variables above and within an old jack pine forest.

#### 4.1.4 Key Variables

Turbulent flux measurements included above- and below-canopy measurements of sensible and latent heat fluxes, CO<sub>2</sub> flux, and friction velocity.

Gradient measurements included vertical profiles of wind speed, relative and specific humidity, and air temperature.

Radiative measurements included net radiation, upwelling and downwelling PAR, upwelling and downwelling global shortwave radiation, upwelling and downwelling longwave radiation, surface temperature, and undercanopy net radiation.

Meteorological measurements included wind speed and direction, air pressure, and rainfall.

Soil measurements included soil water potential, soil temperature, and soil heat flux. These measurements were collected at different locations with different ground covers. The soil temperatures were collected at multiple depths.

### 4.1.5 Principles of Operation

Eddy correlation variables were acquired at a 10-Hz rate. Serial output from the 3-axis and 1-axis sonic anemometers was collected directly at serial ports in a Sun workstation. In 1994, the 3-axis anemometer was set up to receive a strobe signal from a Harrison datalogger in order to synchronize the sonic measurements with the scalar eddy quantities (e.g., water vapor and CO<sub>2</sub>). The same Harrison datalogger received the analog signals of the scalars and performed the analog to digital conversion. These data were passed to the Sun in a separate serial stream.

A fourth serial stream contained data from the slower response radiation and gradient measurements, converted to digital form by a separate Harrison datalogger. Acquisition for this group of signals was at 0.02 Hz. A custom digital counter board kept count of the cup anemometer rotations; the datalogger read these at a 40-Hz rate and reset the counters every 5 seconds.

In 1994, analog signals from the upper sonic (3-axis) anemometer were also acquired by the Harrison logger.

In 1996, only analog signals from the sonic anemometers were acquired.

Campbell Scientific 21x dataloggers were used as backup acquisition systems for the radiation, gradient, and flux (upper level) systems. A separate Campbell Scientific 21x datalogger was dedicated to the soil measurements. Two Campbell Scientific 21x dataloggers were assigned as backup acquisition systems for the Harrison loggers.

#### 4.1.6 Sensor/Instrument Measurement Geometry

Sonic anemometers were mounted at heights of 30 m and 13 m above ground level. Temperature and humidity gradient measurements were collected at 22.68-m, 15.65-m, 9.32-m, and 4.22-m heights. Wind speed gradient measurements were collected at 18.88-m, 14.65-m, 11.32-m, 9.32-m, 6.35-m, and 1.92-m heights. Radiation measurements, including net radiation, incident and reflected global shortwave radiation, incident and reflected global longwave radiation, incident and reflected PAR, and the temperatures of the upwelling and downwelling longwave radiation were measured at 27-m height. Subcanopy measurements of net radiation were collected at 1-m height in an open lichen covered area, and at 1.5-m in an area under a closed canopy.

In 1994, soil temperature profiles were taken at three locations: a lichen-covered area between two jack pines, a moss-covered area under the jack pine canopy, and an area covered with a mixture of moss and lichen. At the lichen-covered site, soil temperatures were collected at 2.5-cm, 7.5-cm, and 20-cm depths. At the moss-covered site soil temperatures were collected at 2.5-cm, 10-cm, and 22.5-cm depths. At the mixed site, soil temperatures were collected at 2.5-cm, 7.5-cm, and 20-cm depths. At all three sites, soil heat flux was measured at 4-cm depth and soil water potential was measured using gypsum soil moisture blocks at the lichen- and moss-covered areas at a depth of 8-cm. In 1996, there were three sites for soil measurements: a closed site, a semiclosed site, and an open site. At the closed site, soil temperature measurements were collected at 6.4-cm, 14-cm, and 26.7-cm depths. At both the semiclosed and open sites, soil temperature data were collected at 2.5-cm, 10.2-cm, and 22.8-cm depths. Soil heat fluxes were measured at 10.2-cm depth at the closed site, and an open site.

In 1994, three different rainfall measurements were collected. One measurement was made from a 3-m trough (vinyl rain gutter) under the jack pine canopy using an MRI tipping bucket rain gauge. The collecting area for this gauge was expanded 9 times by using the trough. A second rain gauge was located at 0.5-m height in the opening between jack pine trees. A third rainfall measurement was collected from a gauge located at 15 m on the flux tower. These other two rain gauges were both Campbell Scientific model TE525. In 1996, rainfall data were collected from the trough and tower rain gauges.

#### 4.1.7 Manufacturer of Sensor/Instrument

3-axis and 1-axis sonic anemometers: Applied Technologies, Inc. 1120 Delaware Ave. Longmont, CO 80501 (303) 684-8722 (303) 684-8773 (fax) sales@apptech.com

Kipp and Zonen CG-2(net longwave) and CM14 (albedometer): Kipp & Zonen P.O. Box 507 2600AM Delft The Netherlands +31 15 269 8000 +31 15 262 0351 (fax)

LI-COR LI-190SA PAR sensors, LI6262 CO2,H2O instrument: LI-COR, Inc. 4421 Superior Street P.O. Box 4425 Lincoln, NE 68504 (402) 467-3576 Swissteco type S-1 Net Pyradiometer: Swissteco Pty., Ltd. Melbourne, Victoria Australia 31.

Campbell Scientific Krypton hygrometers, soil temperature model 107, soil heat flux model HFT-1: Campbell Scientific, Inc. 815 West 1800 North Logan, UT 84321-1784 (435) 753-2342 (435) 750-9540 (fax) info@campbellsci.com

Vaisala air temperature and relative humidity probes. Temperature measured with AD590 IC temperature transducer, relative humidity probe was humi-cap resistance device: Vaisala, Inc. U.S. Office 100 Commerce Way Woburn, MA 01801-1068 (781) 933-4500

Gill propeller-vane anemometer: Gill Instruments Limited Solent House Cannon Street Lymington, Hampshire SO41 9BR UK +44 (0)1590 679955 +44 (0)1590 676409 (fax)

Met One model 014A cup wind speed sensor and radiation shield (with fan): Met One Instruments, Inc. 1600 Washington Blvd. Grants Pass, OR 97526 (541) 471-7111 (541) 471-7116 (fax)

### 4.2 Calibration

#### 4.2.1 Specifications

Kipp and Zonen albedometer and pyrgeometer used factory calibration. The pyrgeometer was also factory calibrated on 13-Nov-1995.

The upwelling and downwelling longwave temperature represent temperatures for the two thermopiles, measured with PT-100 devices. Following the 1993 Intensive Field Campaign (IFC), a laboratory calibration was done on these instruments, and corrections were determined and applied to the data in postprocessing. Similar tests were run following the 1996 field season. Net Radiometer comparisons with sum of components was done continuously. The two subcanopy net radiometers were compared with the above-canopy instrument in the spring of 1993 at the Atmospheric Sciences Research Center (ASRC).

The air temperature and relative humidity probes were laboratory calibrated after the 1993 IFC. Corrections have been applied to the archived data.

The CO<sub>2</sub> instrument was field calibrated using 1% CO<sub>2</sub> in air. Zero and span calibrations were carried out prior to each field season. The instrument was sent for overhaul and factory recalibration

after the 1994 field season.

Krypton hygrometers were calibrated at the factory in 1993 and 1995. In postprocessing, regressions of the natural log of the voltage on the water vapor density determined from the air temperature and relative humidity probes were done. These daily, "field" regressions were used in place of the factory calibration for the upper Krypton hygrometer in 1994, and for both Krypton hygrometers in 1996.

The LI-COR water vapor instrument was calibrated at the factory before each field season. "Field calibrations" (regression of output against actual field water vapor density measurements) as described above for the Krypton hygrometers were used to convert voltages to water vapor density.

#### 4.2.1.1 Tolerance

Applied Technologies 3-axis and 1-axis sonic anemometers: Sensitivity: u, v, and w wind speeds: 0.01 m/sAccuracy: wind speed  $\pm 1\%$ ; wind direction  $\pm 0.1^{\circ}$ Response time: <0.1 s

Kipp and Zonen CG-2(net longwave) and CM14 (albedometer): Sensitivity: shortwave measurements: approximately 4  $\mu$ V/(W/m<sup>2</sup>); longwave Measurements: approximately 10  $\mu$ V/(W/m<sup>2</sup>) Accuracy: within 1% Response time: 30 s

LI-COR LI-190SA PAR sensors: Sensitivity: 8  $\mu$ A/(1000  $\mu$ mol/s/m<sup>2</sup>) Accuracy:  $\pm$  5% Response time: 10  $\mu$ s

Swissteco type S-1 Net Pyradiometer: Sensitivity: 0.48 mV/(mW cm<sup>2</sup>) Accuracy: ± 2.5% Response time: 30s

LI-COR LI6262 CO<sub>2</sub>, H<sub>2</sub>O instrument (fast response option). Air was drawn down 3/8" Teflon tubing by a 30-liters per minute (lpm) pump. The sensor was placed in a side stream drawn off with a 10-lpm pump. A flow controller was placed in the stream going to the sensor to limit the flow through the sensor to 1 lpm, in 1994, or 2 lpm in 1996. Sensitivity: 0.1-0.5 ppm/mv Response time: < 0.5 s

Campbell Scientific Krypton hygrometers: Sensitivity: 105 mV/gm<sup>3</sup> Response time: 0.1 s

Vaisala air temperature and relative humidity probes were installed in Met One radiation shields (with fans). Temperature was measured with AD590 IC temperature transducers, fed into a custom circuit, and calibrated in the lab in mineral oil in a precision temperature bath. Relative humidity probes were humi-cap resistance devices. Sensitivity: Temperature - 0.01 °C /mV; Relative humidity (RH) 0.1% RH/mV Accuracy: Temperature  $\pm$  0.01 °C; Relative humidity 3%

Response time: Temperature (AD590) 10 s; Relative humidity 15 s

Soil thermistors: Campbell Scientific 107 temperature probes. Accuracy: 0.2  $^{\circ}\mathrm{C}$  Response time: 10 s

A Gill propeller-vane anemometer was mounted on the tower at 25.7. At the six remaining lower heights, Met-one model 014A cup wind speed sensors were used: Threshold: cups: 0.5 m/s; Gill: 0.1-0.2 m/sAccuracy: cups:  $\pm 1.5\%$ ; Gill: unknown Distance constant: cups: 4.6 m; Gill: 1 m (speed), 1.2 m (direction)

Rain gauge: Campbell Scientific model TE525 Precision: 0.1 mm

Rain gauge: MRI tipping bucket: Precision: 0.256 mm Total area collected: 0.290 m<sup>2</sup>

## 4.2.2 Frequency of Calibration

See Section 4.2.1.

#### 4.2.3 Other Calibration Information

Webb corrections were applied to vapor density fluxes, to account for effect of density fluctuations on flux estimates (Webb et al., 1980). The effect of water vapor flux on the heat capacity of air was also accounted for in the conversion from kinematic heat flux to W/m<sup>2</sup>. The effect of oxygen absorption in the ultraviolet (UV) was corrected for in calculating water vapor flux from the krypton hygrometer (Campbell and Tanner, 1985).

The air temperature and relative humidity probes were laboratory calibrated after the 1993 IFC. The laboratory calibration yielded these corrections:

T_22.7m	=	0.01013*(mv)	+	0.00075
T_15.7m	=	0.0103*(mv)	+	0.00257
T_9.3m	=	0.0101*(mv)	+	0.00278
T_4.2m	=	0.01001*(mv)	+	0.00125

The air temperature variables are represented in the form where T\_22.7m is the air temperature at 22.7 m height, and mv is the instrument output in millivolts.

## 5. Data Acquisition Methods

Eddy correlation variables were acquired at a 10-Hz rate. Serial output from the 3-axis and 1-axis sonic anemometers was collected directly at serial ports in a Sun workstation. In 1994, the 3-axis anemometer was set up to receive a strobe signal from a Harrison datalogger in order to synchronize the sonic measurements with the scalar eddy quantities (e.g., water vapor and  $CO_2$ ). The same Harrison datalogger received the analog signals of the scalars and performed the analog to digital conversion. These data were passed to the Sun in a separate serial stream.

A fourth serial stream contained data from the slower response radiation and gradient measurements, converted to digital form by a separate Harrison datalogger. Acquisition for this group of signals was at 0.02 Hz. A custom digital counter board kept count of the cup anemometer rotations; the datalogger read these at a 40-Hz rate and reset the counters every 5 seconds.

In 1994, analog signals from the upper sonic (3-axis) anemometer were also acquired by the Harrison logger.

In 1996, only analog signals from the sonic anemometers were acquired.

Campbell Scientific 21x dataloggers were used as backup acquisition systems for the radiation, gradient, and flux (upper level) systems. A separate Campbell Scientific 21x datalogger was dedicated to the soil measurements. Two Campbell Scientific 21x dataloggers were assigned as backup acquisition systems for the Harrison loggers.

A sky imaging system was located on the roof of the hut. In 1993 and 1994, the imaging system consisted of one charged coupled device (CCD) with image acquisition hardware and software. This system used fish-eye and 28-mm lenses and produced digitized images with 256 by 244 pixels and 64 gray scales. In 1996, video images were digitized in 24-bit color using joint photographic experts group (jpg) format, with 751 by 484 pixels and 256 levels each of red, green, and blue.

### 6. Observations

#### 6.1 Data Notes

Gaps in the data in all years occur due to instrument failure or computer failure.

#### **6.2 Field Notes**

Field notes are contained in four notebooks located at ASRC in Albany.

## 7. Data Description

#### 7.1 Spatial Characteristics

#### 7.1.1 Spatial Coverage

All data were collected at the BOREAS NSA-OJP site. The North American Datum of 1983 (NAD83) coordinates for the NSA-OJP tower were latitude 55.92842° N, longitude 98.62396° W, and elevation of 255.1 m.

Turbulent fluxes were measured at the top of the flux tower, and at 13 m high on the flux tower, until 29-Jul-1994, when a separate 2-m-tall mast was erected for subcanopy fluxes. In 1994, the subcanopy flux measurements were made in an open, lichen-covered area approximately 15 m west of the main tower. In 1996, the subcanopy array was erected on 09-Jul in a moss-covered area to the north of the tower.

Soil temperature and heat flux measurements were made at three sites chosen for their microsite variation (mossy cover, lichen cover, and intermediate). These sites were all 30-40 m from the flux tower in the northwest direction.

The sky camera was placed on the roof of the shack at the site. The ceilometer was located on the tent platform to the south of the shack.

Subcanopy net radiation measurements in 1994 were made in an open area and an area of denser canopy, to the north of the flux tower. One rain gauge was located on the flux tower at 15 m, one was in the subcanopy layer in an opening, and a third collected rain from a trough 10 feet long under closed canopy.

#### 7.1.2 Spatial Coverage Map

Not applicable.

#### 7.1.3 Spatial Resolution

Data collected from flux towers are often thought of as point data. However, particularly in terms of the eddy flux data, they actually represent an integrated upwind source region. The size of the region being sampled is related to factors such as the height of the tower, the roughness of the canopy, and the wind speed.

#### 7.1.4 Projection

None.

#### 7.1.5 Grid Description

None.

### 7.2 Temporal Characteristics

#### 7.2.1 Temporal Coverage

Data collection in 1993 covered the following dates:

- Turbulent fluxes: 11-Aug to 29-Aug-1993
- Soil measurements: 11-Aug to 29-Aug-1993
- Water vapor flux: 20-Aug to 29-Aug-1993
- CO<sub>2</sub> flux : 23-Aug to 29-Aug-1993
- Radiative fluxes: 14-Aug to 29-Aug-1993
- Gradient measurements: 14-Aug to 29-Aug-1993
- Sky camera images: 17-Aug to 29-Aug-1993

Data collection in 1994 covered the following dates:

- Turbulent fluxes: 24-May to 19-Sep-1994
- Second level fluxes moved from  $1\frac{1}{3}$  m to 2 m on 29-Jul-1994
- Soil measurements: 28-May to 19-Sep-1994
- Radiative fluxes: 24-May to 19-Sep-1994
- Gradient measurements: 24-May to 19-Sep-1994
- Sky camera images: 01-Jun to 19-Sep-1994
- Ceilometer measurements: 28-May 28 to 17-Sep-1994

Data collection in 1996 covered the following dates:

- Turbulent fluxes: 15-Apr to 09-Nov-1996
- Second level fluxes: 19-Jul to 09-Nov-1996
- Second level CO<sub>2</sub> flux: 26-Sep to 09-Nov-1996
- Soil measurements: 25-May to 09-Nov-1996
- Radiative fluxes: 15-Apr to 09-Nov-1996
- IR thermometers: 20-Jul to 09-Nov-1996
- Gradient measurements: 15-Apr to 09-Nov-1996
- Sky camera images: 06-May to 09-Nov-1996
- Ceilometer measurements: 29-May to 09-Nov-1996

#### 7.2.2 Temporal Coverage Map

None.

#### 7.2.3 Temporal Resolution

The 1996 data were averaged over 30-minute periods. The 1993 and 1994 data were averaged over 20-minute periods. These data were then interpolated to 30-minute time periods.

#### 7.3 Data Characteristics

#### 7.3.1 Parameter/Variable

The parameters contained in the data files on the CD-ROM are:

Column Name SITE\_NAME SUB\_SITE DATE\_OBS TIME\_OBS SENSIBLE\_HEAT\_FLUX\_ABV\_CNPY LIC\_LATENT\_HEAT\_FLUX\_ABV\_CNPY LATENT\_HEAT\_FLUX\_ABV\_CNPY NET\_RAD\_ABV\_CNPY

CO2 FLUX ABV CNPY DOWN PPFD ABV CNPY UP PPFD ABV CNPY WIND SPEED 192CM WIND SPEED 635CM WIND SPEED 932CM WIND SPEED 1132CM WIND SPEED 1465CM WIND SPEED ABV CNPY GILL WIND SPEED ABV CNPY WIND DIR ABV CNPY FRICTION VEL ABV CNPY AIR TEMP ABV CNPY SOIL HEAT FLUX CLOSED 102MM SOIL HEAT FLUX SEMI CLOSE 64MM SOIL HEAT FLUX OPEN 64MM SOIL HEAT FLUX MOSS 40MM SOIL HEAT FLUX LICH MOSS 40MM SOIL HEAT FLUX LICHEN 40MM SOIL TEMP LICH MOSS 25MM SOIL TEMP LICH MOSS 75MM SOIL TEMP LICH MOSS 200MM SOIL TEMP MOSS 25MM SOIL TEMP MOSS 100MM SOIL TEMP MOSS 225MM SOIL TEMP LICHEN 25MM SOIL TEMP LICHEN 75MM SOIL TEMP LICHEN 200MM SOIL TEMP CLOSED 64MM SOIL TEMP CLOSED 140MM SOIL TEMP CLOSED 267MM SOIL TEMP SEMI CLOSED 25MM SOIL TEMP SEMI CLOSED 102MM SOIL TEMP SEMI CLOSED 229MM SOIL TEMP OPEN 25MM SOIL TEMP OPEN 102MM SOIL TEMP OPEN 229MM SOIL WATER POT LICHEN 8CM SOIL WATER POT MOSS 8CM RAINFALL ABV CNPY RAINFALL BELOW CNPY TROUGH RAINFALL DOWN SOLAR RAD ABV CNPY UP SOLAR RAD ABV CNPY AIR TEMP 422CM AIR TEMP 932CM AIR TEMP 1565CM SURF PRESS DOWN LONGWAVE RAD ABV CNPY UP LONGWAVE RAD ABV CNPY UP LONGWAVE RAD SENSOR TEMP DOWN LONGWAVE RAD SENSOR TEMP LONG PLUS SHORT RAD ABV CNPY SURF TEMP ABV CNPY

SPECIFIC\_HUM\_422CM SPECIFIC\_HUM\_932CM SPECIFIC\_HUM\_1565CM SPECIFIC\_HUM\_ABV\_CNPY REL\_HUM\_422CM REL\_HUM\_932CM REL\_HUM\_1565CM REL\_HUM\_ABV\_CNPY SENSIBLE\_HEAT\_FLUX\_BELOW\_CNPY LATENT\_HEAT\_FLUX\_BELOW\_CNPY CO2\_FLUX\_BELOW\_CNPY NET\_RAD\_OPEN\_100CM NET\_RAD\_BELOW\_CNPY CRTFCN\_CODE REVISION DATE

#### 7.3.2 Variable Description/Definition

The descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description			
SITE_NAME	The identifier assigned to the site by BOREAS, in the format SSS-TTT-CCCCC, where SSS identifies the portion of the study area: NSA, SSA, REG, TRN, and TTT identifies the cover type for the site, 999 if unknown, and CCCCC is the identifier for site, exactly what it means will vary with site type.			
SUB_SITE	The identifier assigned to the sub-site by BOREAS in the format GGGGG-IIIII, where GGGGG is the group associated with the sub-site instrument, e.g. HYD06 or STAFF, and IIIII is the identifier for sub-site, often this will refer to an instrument.			
DATE OBS	The date on which the data were collected.			
TIME_OBS	The Greenwich Mean Time (GMT) of the start of the data collection.			
SENSIBLE HEAT FLUX ABV CNPY	The sensible heat flux measured above the canopy.			
LIC_LATENT_HEAT_FLUX_ABV_CNPY	The latent heat flux measured above the canopy using a LI-COR instrument.			
LATENT HEAT FLUX ABV CNPY	The latent heat flux measured above the canopy.			
NET RAD ABV CNPY	The net radiation measured above the canopy.			
CO2_FLUX_ABV_CNPY	The carbon dioxide flux measured above the canopy.			
DOWN_PPFD_ABV_CNPY	The downward (incoming) photosynthetic photon flux density measured above the canopy.			
UP_PPFD_ABV_CNPY	The reflected photosynthetic photon flux density measured above the canopy.			
WIND SPEED 192CM	The wind speed measured 1.92 m above the ground.			
WIND SPEED 635CM	The wind speed measured 6.35 m above the ground.			
WIND SPEED 932CM	The wind speed measured 9.32 m above the ground.			
WIND SPEED 1132CM	The wind speed measured 11.32 m above the ground.			
WIND_SPEED_1465CM	The wind speed measured 14.65 m above the ground.			
WIND_SPEED_ABV_CNPY	The wind speed measured above the canopy. In			

this case at 18.88 m above the ground. The wind speed measured above the canopy with the GILL WIND SPEED ABV CNPY Gill anemometer at 25.7 m above the ground. WIND DIR ABV CNPY The direction from which the wind is blowing (in creasing in a clockwise direction from the North) and measured above the canopy at 25.7 m above the ground. FRICTION VEL ABV CNPY The friction velocity above the canopy. AIR TEMP ABV CNPY The air temperature measured above the canopy. SOIL HEAT FLUX\_CLOSED\_102MM The soil heat flux measured at 10.16 cm depth at a site under closed canopy. SOIL HEAT FLUX SEMI CLOSE 64MM The soil heat flux measured at 6.35 cm depth at a site under a semi-closed canopy. SOIL HEAT FLUX OPEN 64MM The soil heat flux measured at 6.35 cm depth at an open site. SOIL HEAT FLUX MOSS 40MM The soil heat flux measured at 4 cm depth at a moss covered site. SOIL HEAT FLUX LICH MOSS 40MM The soil heat flux measured at 4 cm depth at a lichen and moss covered site. SOIL HEAT FLUX LICHEN 40MM The soil heat flux measured at 4 cm depth at a lichen covered site. SOIL TEMP LICH MOSS 25MM Soil temperature at 2.5 cm depth at a lichen and moss covered site. SOIL TEMP LICH MOSS 75MM Soil temperature at 7.5 cm depth at a lichen and moss covered site. SOIL TEMP LICH MOSS 200MM Soil temperature at 20 cm depth at a lichen and moss covered site. Soil temperature at 2.5 cm depth at a moss SOIL TEMP MOSS 25MM Covered site. SOIL TEMP MOSS 100MM Soil temperature at 10 cm depth at a moss covered site. SOIL TEMP MOSS 225MM Soil temperature at 22.5 cm depth at a moss covered site. SOIL TEMP LICHEN 25MM Soil temperature at 2.5 cm depth at a lichen covered site. SOIL TEMP LICHEN 75MM Soil temperature at 7.5 cm depth at a lichen covered site. SOIL TEMP LICHEN 200MM Soil temperature at 20 cm depth at a lichen covered site. SOIL TEMP CLOSED 64MM Soil temperature at 6.4 cm depth at a site under closed canopy. SOIL TEMP CLOSED 140MM Soil temperature at 13.97 cm depth at a site under closed canopy. SOIL TEMP CLOSED 267MM Soil temperature at 26.67 cm depth at a site under closed canopy. SOIL TEMP SEMI CLOSED 25MM Soil temperature at 2.54 cm depth at a site under a semi-closed canopy. SOIL TEMP SEMI CLOSED 102MM Soil temperature at 10.16 cm depth at a site under a semi-closed canopy. SOIL TEMP SEMI CLOSED 229MM Soil temperature at 22.86 cm depth at a site under a semi-closed canopy. SOIL TEMP OPEN 25MM Soil temperature at 2.54 cm depth at an open site. SOIL TEMP OPEN 102MM Soil temperature at 10.16 cm depth at an open

site. SOIL TEMP OPEN 229MM Soil temperature at 22.86 cm depth at an open site. The soil water potential at 8 cm depth at a SOIL WATER POT LICHEN 8CM lichen covered site. SOIL WATER POT MOSS 8CM The soil water potential at 8 cm depth at a moss covered site. RAINFALL ABV CNPY The amount of rainfall measured above the canopy. In 1994 the measurement is over a 30 minute period, in 1996 over an hour. RAINFALL BELOW CNPY The amount of rainfall measured below the canopy in a clearing. In 1994 the measurement is over a 30 minute period, in 1996 over an hour. TROUGH RAINFALL The amount of rainfall measured in a trough below the canopy, the trough area is 9 times the collection area of the other rain gauges. In 1994 the measurement is over a 30 minute period, in 1996 over an hour. DOWN SOLAR RAD ABV CNPY The downward (incoming) solar radiation measured above the canopy. UP SOLAR RAD ABV CNPY The reflected (outgoing) solar radiation measured above the canopy. AIR TEMP 422CM The air temperature measured at 4.22 meters above the ground. AIR TEMP 932CM The air temperature measured at 9.32 meters above the ground. AIR TEMP 1565CM The air temperature measured at 15.65 meters Above the ground. SURF PRESS The atmospheric pressure measured at the station. DOWN LONGWAVE RAD ABV CNPY The downward (incoming) longwave radiation measured above the canopy. UP LONGWAVE RAD ABV CNPY The upward (outgoing) longwave radiation measured above the canopy. UP LONGWAVE RAD SENSOR TEMP The temperature of the sensor measuring the upward longwave radiation. DOWN LONGWAVE RAD SENSOR TEMP The temperature of the sensor measuring the downward longwave radiation. LONG PLUS SHORT RAD ABV CNPY The sum of the longwave and shortwave radiation measurements. SURF TEMP ABV CNPY The surface radiation temperature measured from above the canopy. SPECIFIC HUM 422CM The specific humidity measured at 4.22 meters above the ground. SPECIFIC HUM 932CM The specific humidity measured at 9.32 meters above the ground. SPECIFIC HUM 1565CM The specific humidity measured at 15.65 meters above the ground. SPECIFIC HUM ABV CNPY The specific humidity measured above the canopy. REL HUM 422CM The relative humidity measured at 4.22 meters above the ground. REL HUM 932CM The relative humidity measured at 9.32 meters above the ground. The relative humidity measured at 15.65 meters REL HUM 1565CM above the ground.

REL_HUM_ABV_CNPY	The relative humidity measured above the canopy.
SENSIBLE_HEAT_FLUX_BELOW_CNPY	The sensible heat flux measured below the canopy.
LATENT_HEAT_FLUX_BELOW_CNPY	The latent heat flux measured below the canopy.
CO2_FLUX_BELOW_CNPY	The carbon dioxide flux measured below the
	canopy.
NET_RAD_OPEN_100CM	The net radiation measured at 1 meter in canopy
	opening.
NET_RAD_BELOW_CNPY	The net radiation measured below the canopy.
CRTFCN_CODE	The BOREAS certification level of the data.
	Examples are CPI (Checked by PI), CGR (Certified
	by Group), PRE (Preliminary), and CPI-??? (CPI
	but questionable).
REVISION_DATE	The most recent date when the information in the
	referenced data base table record was revised.

**7.3.3 Unit of Measurement** The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SITE NAME	[none]
SUB SITE	[none]
DATE OBS	[DD-MON-YY]
TIME OBS	[HHMM GMT]
SENSIBLE_HEAT_FLUX_ABV_CNPY	[Watts][meter^-2]
LIC LATENT HEAT FLUX ABV CNPY	[Watts][meter^-2]
LATENT_HEAT_FLUX_ABV_CNPY	[Watts][meter^-2]
NET_RAD_ABV_CNPY	[Watts][meter^-2]
CO2_FLUX_ABV_CNPY	[micromoles][meter^-2][second^-1]
DOWN_PPFD_ABV_CNPY	[micromoles][meter^-2][second^-1]
UP_PPFD_ABV_CNPY	[micromoles][meter^-2][second^-1]
WIND_SPEED_192CM	[meters][second^-1]
WIND_SPEED_635CM	[meters][second^-1]
WIND_SPEED_932CM	[meters][second^-1]
WIND_SPEED_1132CM	[meters][second^-1]
WIND_SPEED_1465CM	[meters][second^-1]
WIND_SPEED_ABV_CNPY	[meters][second^-1]
GILL_WIND_SPEED_ABV_CNPY	[meters][second^-1]
WIND_DIR_ABV_CNPY	[degrees]
FRICTION_VEL_ABV_CNPY	[meters][second^-1]
AIR_TEMP_ABV_CNPY	[degrees Celsius]
SOIL_HEAT_FLUX_CLOSED_102MM	[Watts][meter^-2]
SOIL_HEAT_FLUX_SEMI_CLOSE_64MM	[Watts][meter^-2]
SOIL_HEAT_FLUX_OPEN_64MM	[Watts][meter^-2]
SOIL_HEAT_FLUX_MOSS_40MM	[Watts][meter^-2]
SOIL_HEAT_FLUX_LICH_MOSS_40MM	[Watts][meter^-2]
SOIL_HEAT_FLUX_LICHEN_40MM	[Watts][meter^-2]
SOIL_TEMP_LICH_MOSS_25MM	[degrees Celsius]
SOIL_TEMP_LICH_MOSS_75MM	[degrees Celsius]
SOIL_TEMP_LICH_MOSS_200MM	[degrees Celsius]
SOIL_TEMP_MOSS_25MM	[degrees Celsius]
SOIL_TEMP_MOSS_100MM	[degrees Celsius]
SOIL_TEMP_MOSS_225MM	[degrees Celsius]
SOIL_TEMP_LICHEN_25MM	[degrees Celsius]

SOIL TEMP LICHEN 75MM [degrees Celsius] SOIL TEMP LICHEN 200MM [degrees Celsius] SOIL TEMP CLOSED 64MM [degrees Celsius] SOIL TEMP CLOSED 140MM [degrees Celsius] SOIL TEMP CLOSED 267MM [degrees Celsius] SOIL TEMP SEMI CLOSED 25MM [degrees Celsius] SOIL TEMP SEMI CLOSED 102MM [degrees Celsius] SOIL TEMP SEMI CLOSED 229MM [degrees Celsius] SOIL TEMP OPEN 25MM [degrees Celsius] SOIL TEMP OPEN 102MM [degrees Celsius] SOIL TEMP OPEN 229MM [degrees Celsius] SOIL WATER POT LICHEN 8CM [megaPascals] SOIL WATER POT MOSS 8CM [megaPascals] RAINFALL ABV CNPY [millimeters] RAINFALL BELOW CNPY [millimeters] TROUGH RAINFALL [millimeters] DOWN SOLAR RAD ABV CNPY [Watts] [meter^-2] UP SOLAR RAD ABV CNPY [Watts] [meter^-2] AIR TEMP 422CM [degrees Celsius] AIR TEMP 932CM [degrees Celsius] AIR TEMP 1565CM [degrees Celsius] SURF PRESS [kiloPascals] DOWN LONGWAVE RAD ABV CNPY [Watts] [meter^-2] UP LONGWAVE RAD ABV CNPY [Watts][meter^-2] UP LONGWAVE RAD SENSOR TEMP [degrees Celsius] DOWN LONGWAVE RAD SENSOR TEMP [degrees Celsius] LONG PLUS SHORT RAD ABV CNPY [Watts] [meter^-2] SURF TEMP ABV CNPY [degrees Celsius] SPECIFIC HUM 422CM [grams][kilogram^-1] SPECIFIC HUM 932CM [grams][kilogram^-1] SPECIFIC HUM 1565CM [grams][kilogram^-1] [grams][kilogram^-1] SPECIFIC HUM ABV CNPY REL HUM 422CM [percent] REL HUM 932CM [percent] REL HUM 1565CM [percent] REL HUM ABV CNPY [percent] SENSIBLE HEAT FLUX BELOW CNPY [Watts][meter^-2] [Watts][meter^-2] LATENT HEAT FLUX BELOW CNPY CO2 FLUX BELOW CNPY [micromoles] [meters^-2] [second^-1] NET RAD OPEN 100CM [Watts][meter^-2] NET RAD BELOW CNPY [Watts] [meter^-2] CRTFCN CODE [none] REVISION DATE [DD-MON-YY]

**7.3.4 Data Source** The sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SITE_NAME	[Assigned by BORIS.]
SUB_SITE	[Assigned by BORIS.]
DATE_OBS	[Supplied by Investigator.]
TIME_OBS	[Supplied by Investigator.]
SENSIBLE_HEAT_FLUX_ABV_CNPY	[Sonic anemometer]
LIC_LATENT_HEAT_FLUX_ABV_CNPY	[LI-COR Infrared Gas Analyzer]
LATENT_HEAT_FLUX_ABV_CNPY	[Campbell Scientific Krypton hygrometer]
NET_RAD_ABV_CNPY	[Net radiometer]
CO2_FLUX_ABV_CNPY	[Infrared Gas Analyzer]
DOWN_PPFD_ABV_CNPY	[quantum sensor]
UP_PPFD_ABV_CNPY	[quantum sensor]
WIND_SPEED_192CM	[Met-One cup anemometer]
WIND_SPEED_635CM	[Met-One cup anemometer]
WIND_SPEED_932CM	[Met-One cup anemometer]
WIND_SPEED_1132CM	[Met-One cup anemometer]
WIND_SPEED_1465CM	[Met-One cup anemometer]
WIND_SPEED_ABV_CNPY	[Met-One cup anemometer]
GILL_WIND_SPEED_ABV_CNPY	[Gill propeller-vane anemometer]
WIND_DIR_ABV_CNPY	[Gill propeller-vane anemometer]
FRICTION_VEL_ABV_CNPY	[Sonic anemometer]
AIR_TEMP_ABV_CNPY	[air temperature probe]
SOIL_HEAT_FLUX_CLOSED_102MM	[soil heat flux plate]
SOIL_HEAT_FLUX_SEMI_CLOSE_64MM	[soil heat flux plate]
SOIL_HEAT_FLUX_OPEN_64MM	[soil heat flux plate]
SOIL_HEAT_FLUX_MOSS_40MM	[soil heat flux plate]
SOIL_HEAT_FLUX_LICH_MOSS_40MM	[soil heat flux plate]
SOIL_HEAT_FLUX_LICHEN_40MM	[soil heat flux plate]
SOIL_TEMP_LICH_MOSS_25MM	[soil temperature probe]
SOIL_TEMP_LICH_MOSS_75MM	[soil temperature probe]
SOIL_TEMP_LICH_MOSS_200MM	[soil temperature probe]
SOIL_TEMP_MOSS_25MM	[soil temperature probe]
SOIL_TEMP_MOSS_100MM	[soil temperature probe]
SOIL_TEMP_MOSS_225MM	[soil temperature probe]
SOIL_TEMP_LICHEN_25MM	[soil temperature probe]
SOIL_TEMP_LICHEN_75MM	[soil temperature probe]
SOIL_TEMP_LICHEN_200MM	[soil temperature probe]
SOIL_TEMP_CLOSED_64MM	[soil temperature probe]
SOIL TEMP CLOSED 140MM	[soil temperature probe]
SOIL TEMP CLOSED 267MM	[soil temperature probe]
SOIL TEMP SEMI CLOSED 25MM	[soil temperature probe]
SOIL TEMP SEMI CLOSED 102MM	[soil temperature probe]
SOIL TEMP SEMI CLOSED 229MM	[soil temperature probe]
SOIL TEMP OPEN 25MM	[soil temperature probe]
SOIL TEMP OPEN 102MM	[soil temperature probe]
SOIL TEMP OPEN 229MM	[soil temperature probe]
SOIL WATER POT LICHEN 8CM	[gypsum soil moisture block]
SOIL WATER POT MOSS 8CM	[gypsum soil moisture block]
RAINFALL ABV CNPY	[Campbell Scientific rain gauge]
RAINFALL_BELOW_CNPY	[Campbell Scientific rain gauge]

TROUGH_RAINFALL	[MRI tipping bucket rain gauge]
DOWN_SOLAR_RAD_ABV_CNPY	[albedometer]
UP_SOLAR_RAD_ABV_CNPY	[albedometer]
AIR_TEMP_422CM	[air temperature probe]
AIR_TEMP_932CM	[air temperature probe]
AIR_TEMP_1565CM	[air temperature probe]
SURF_PRESS	[barometer]
DOWN_LONGWAVE_RAD_ABV_CNPY	[pyrgeometer]
UP_LONGWAVE_RAD_ABV_CNPY	[pyrgeometer]
UP_LONGWAVE_RAD_SENSOR_TEMP	[thermopile]
DOWN_LONGWAVE_RAD_SENSOR_TEMP	[thermopile]
LONG_PLUS_SHORT_RAD_ABV_CNPY	[albedometer and pyrgeometer]
SURF_TEMP_ABV_CNPY	[IR thermometer]
SPECIFIC_HUM_422CM	[hygrometer]
SPECIFIC_HUM_932CM	[hygrometer]
SPECIFIC_HUM_1565CM	[hygrometer]
SPECIFIC_HUM_ABV_CNPY	[hygrometer]
REL_HUM_422CM	[psychrometer]
REL_HUM_932CM	[psychrometer]
REL_HUM_1565CM	[psychrometer]
REL_HUM_ABV_CNPY	[psychrometer]
SENSIBLE_HEAT_FLUX_BELOW_CNPY	[Sonic anemometer]
LATENT_HEAT_FLUX_BELOW_CNPY	[Campbell Scientific Krypton hygrometer]
CO2_FLUX_BELOW_CNPY	[Sonic anemometer]
NET_RAD_OPEN_100CM	[Net radiometer]
NET_RAD_BELOW_CNPY	[Net radiometer]
CRTFCN_CODE	[Assigned by BORIS.]
REVISION_DATE	[Assigned by BORIS.]

**7.3.5 Data Range** The following table gives information about the parameter values found in the data files on the CD-ROM.

	Minimum Data	Maximum Data	Missng Data	Unrel Data	Below Detect	Data Not
Column Name	Value	Value	Value	Value	Limit 	Cllctd
SITE_NAME	NSA-OJP-FLXTR	NSA-OJP-FLXTR	None	None	None	None
SUB_SITE	9TF08-FLX01	9TF08-FLX01	None	None	None	None
DATE_OBS	24-MAY-94	12-NOV-96	None	None	None	None
TIME_OBS	0	2330	None	None	None	None
SENSIBLE_HEAT_FLUX_	-124.74	997.44	-999	None	None	Blank
ABV_CNPY						
LIC_LATENT_HEAT_FLUX	39.49	701.34	-999	None	None	Blank
ABV_CNPY						
LATENT_HEAT_FLUX_ABV	117.83	544.18	-999	None	None	Blank
CNPY						
NET_RAD_ABV_CNPY	-703.8	326.69	-999	None	None	Blank
CO2_FLUX_ABV_CNPY	-15	8.409	-999	None	None	Blank
DOWN_PPFD_ABV_CNPY	-1980	2360	None	None	None	Blank
UP_PPFD_ABV_CNPY	-1080	2410	None	None	None	Blank
WIND_SPEED_192CM	-15.07	155.73	-999	None	None	Blank
WIND_SPEED_635CM	-114.69	175.63	-999	None	None	Blank
WIND_SPEED_932CM	-92.58	191.22	-999	None	None	Blank
WIND_SPEED_1132CM	-14.86	184.76	-999	None	None	Blank

WIND_SPEED_1465CM	-115.91	44.97	-999	None	None	Blank
WIND SPEED ABV CNPY	-122.6	24.04	-999	None	None	Blank
GILL_WIND_SPEED_ABV_	.03	7.19	-999	None	None	Blank
WIND DIR ABV CNPY	1 14	359 18	-999	None	None	Blank
FRICTION VEL ABV	0	2 626	-999	None	None	Blank
CNPY	0	2.020	-999	none	None	DIAIIK
AIR_TEMP_ABV_CNPY	-18.02	40.8	-999	None	None	Blank
SOIL_HEAT_FLUX_ CLOSED 102MM	-35.99	13.5	None	None	None	Blank
SOIL_HEAT_FLUX_SEMI_ CLOSE 64MM	-70.7	19.8	None	None	None	Blank
SOIL_HEAT_FLUX_OPEN_ 64MM	-95.45	19.98	None	None	None	Blank
SOIL_HEAT_FLUX_MOSS_	-4.723	40.637	-999	None	None	Blank
SOTI, HEAT FLUX LICH	-516.282	108.18	-999	None	None	Blank
MOSS 40MM						
SOIL_HEAT_FLUX_	-288.485	171.79	-999	None	None	Blank
SOLI TEMP LICH MOSS	8 205	21 307	- 9 9 9	Nono	None	Blank
25MM	0.200	24.397		None	None	DIGHK
SOIL_TEMP_LICH_MOSS_ 75MM	4.955	16.135	-999	None	None	Blank
SOIL_TEMP_LICH_MOSS_ 200MM	4.019	59.389	-999	None	None	Blank
SOIL TEMP MOSS 25MM	3.723	59.051	-999	None	None	Blank
SOIL TEMP MOSS 100MM	4.962	59.678	-999	None	None	Blank
SOTE TEMP MOSS 225MM	4 962	59 678	-999	None	None	Blank
SOIL TEMP LICHEN	6 191	46 177	-999	None	None	Blank
25MM		10.1,7				
SOIL_TEMP_LICHEN_ 75MM	6.642	44./03	-999	None	None	Blank
SOIL_TEMP_LICHEN_	7.133	42.94	-999	None	None	Blank
SOTI, TEMP CLOSED	-1.25	20.06	-999	None	None	Blank
64MM	1120	20100	555			Diam
SOIL_TEMP_CLOSED_ 140MM	03	15.96	-999	None	None	Blank
SOIL_TEMP_CLOSED_ 267MM	.08	14.62	-999	None	None	Blank
SOIL_TEMP_SEMI_	-3.5	24.18	-999	None	None	Blank
CLOSED_25MM						
SOIL_TEMP_SEMI_	77	16.97	-999	None	None	Blank
SOLI TEMD SEMI	-15 50	17 35	-000	Nono	Nono	Plank
CLOSED_229MM	-13.39	17.33	-999	none	None	DIAIIK
SOIL_TEMP_OPEN_25MM	74	20.8	-999	None	None	Blank
SOIL_TEMP_OPEN_102MM	54	19	-999	None	None	Blank
SOIL_TEMP_OPEN 229MM	.21	18.12	-999	None	None	Blank
SOIL_WATER_POT_	-2.4807	032	None	None	None	Blank
SOTI WATER POT MOSS	-2.3104	0301	None	None	None	Blank
8CM						

RAINFALL_ABV_CNPY	0	4.5	None	None	None	Blank
RAINFALL_BELOW_CNPY	0	8.2	None	None	None	Blank
TROUGH_RAINFALL	0	43.44	None	None	None	Blank
DOWN_SOLAR_RAD_ABV_ CNPY	-944.88	235.38	-999	None	None	Blank
UP_SOLAR_RAD_ABV_ CNPY	-471.38	804.16	-999	None	None	Blank
AIR TEMP 422CM	-18.06	40.8	-999	None	None	Blank
AIR TEMP 932CM	-18.21	38.49	-999	None	None	Blank
AIR TEMP 1565CM	-18.42	41.13	-999	None	None	Blank
SURF PRESS	95.65	997	-999	None	None	Blank
DOWN LONGWAVE RAD	-530.27	-15.87	-999	None	None	Blank
ABV CNPY						
UP_LONGWAVE_RAD_ABV_ CNPY	-69.45	1158.79	None	None	None	Blank
DOWN_LONGWAVE_RAD_ SENSOR_TEMP	-1.94	35.31	None	None	None	Blank
UP LONGWAVE RAD	-1.81	35.62	None	None	None	Blank
SENSOR TEMP						
LONG_PLUS_SHORT_RAD_ ABV CNPY	-750.83	545.71	None	None	None	Blank
SURF TEMP ABV CNPY	-109.58	104.94	-999	None	None	Blank
SPECIFIC HUM 422CM	-530.6	3528.7	-999	None	None	Blank
SPECIFIC HUM 932CM	-511.74	51.16	-999	None	None	Blank
SPECIFIC HUM 1565CM	-831.9	156.11	-999	None	None	Blank
SPECIFIC HUM ABV	-482.14	49.54	-999	None	None	Blank
CNPY						
REL_HUM_422CM	16	203	-999	None	None	Blank
REL HUM 932CM	10.63	175	-999	None	None	Blank
REL_HUM_1565CM	-72	156	-999	None	None	Blank
REL_HUM_ABV_CNPY	13.88	156	-999	None	None	Blank
SENSIBLE_HEAT_FLUX_	-149.6	593.58	-999	None	None	Blank
BETOM CUBJ	04.00	F00 06				<b>D</b> 1 1
BELOW CNPY	-84.39	509.86	-999	None	None	Blank
CO2 FLUX BELOW CNPY	227	1.591	-999	None	None	Blank
NET RAD OPEN 100CM	-996.95	1903.82	-999	None	None	Blank
NET RAD BELOW CNPY	-998.65	1600.33	-999	None	None	Blank
CRTFCN CODE	CPI	CPI	None	None	None	None
REVISION_DATE	14-JUL-99	17-AUG-99	None	None	None	None
Minimum Data Value	- The minimum va	alue found in th	he colum	 n.		
Maximum Data Value	- The maximum va	ilue found in th	ne columi	n. 	. ,	
Missng Data Value	- The value that indicate that	an attempt was	sing data made to	a. This determ:	ine the	to
	parameter valu	e, but the atte	empt was	unsucce	essful.	
Unrel Data Value	- The value that	: indicates unre	eliable d	data. 1	This is u	ised
	to indicate ar	n attempt was ma	ade to de	etermine	e the	
	parameter valu	e, but the valu	ue was de	eemed to	o be	
	unreliable by	the analysis pe	ersonnel			
Below Detect Limit	- The value that	indicates para	ameter va	alues be	elow the	
	instruments de	etection limits	. This :	is used	to	
	indicate that	an attempt was	made to	determ	ine the	
	parameter valu	e, but the ana	lysis pe	rsonnel	determir	ned

Data Not Cllctd	<pre>that the parameter value was below the detection limit of the instrumentation. - This value indicates that no attempt was made to determine the parameter value. This usually indicates that BORIS combined several similar but not identical data sets into the same data base table but this particular science team did not measure that parameter. that blank spaces are used to denote that type of value. that the value is not applicable to the respective column.</pre>	
Blank Indicates tha N/A Indicates tha None Indicates tha	t blank spaces are used to denote that type of value. t the value is not applicable to the respective column. t no values of that sort were found in the column.	

#### 7.4 Sample Data Record

The following are wrapped versions of data records from a sample data file on the CD-ROM.

```
SITE NAME, SUB SITE, DATE OBS, TIME OBS, SENSIBLE HEAT FLUX ABV CNPY,
LIC LATENT HEAT FLUX ABV CNPY, LATENT HEAT FLUX ABV CNPY, NET RAD ABV CNPY,
CO2 FLUX ABV CNPY, DOWN PPFD ABV CNPY, UP PPFD ABV CNPY, WIND SPEED 192CM,
WIND SPEED 635CM, WIND SPEED 932CM, WIND SPEED 1132CM, WIND SPEED 1465CM,
WIND SPEED ABV CNPY,GILL WIND SPEED ABV CNPY,WIND DIR ABV CNPY,
FRICTION VEL ABV CNPY, AIR TEMP ABV CNPY, SOIL HEAT FLUX CLOSED 102MM,
SOIL HEAT FLUX SEMI CLOSE 64MM, SOIL HEAT FLUX OPEN 64MM,
SOIL HEAT FLUX MOSS 40MM, SOIL HEAT FLUX LICH MOSS 40MM,
SOIL HEAT FLUX LICHEN 40MM, SOIL TEMP LICH MOSS 25MM, SOIL TEMP LICH MOSS 75MM,
SOIL TEMP LICH MOSS 200MM, SOIL TEMP MOSS 25MM, SOIL TEMP MOSS 100MM,
SOIL TEMP MOSS 225MM, SOIL TEMP LICHEN 25MM, SOIL TEMP LICHEN 75MM,
SOIL TEMP LICHEN 200MM, SOIL TEMP CLOSED 64MM, SOIL TEMP CLOSED 140MM,
SOIL TEMP CLOSED 267MM, SOIL TEMP SEMI CLOSED 25MM, SOIL TEMP SEMI CLOSED 102MM,
SOIL TEMP SEMI CLOSED 229MM, SOIL TEMP OPEN 25MM, SOIL TEMP OPEN 102MM,
SOIL_TEMP_OPEN_229MM, SOIL_WATER_POT_LICHEN_8CM, SOIL_WATER_POT_MOSS_8CM,
RAINFALL ABV CNPY, RAINFALL BELOW CNPY, TROUGH RAINFALL, DOWN SOLAR RAD ABV CNPY,
UP SOLAR RAD ABV CNPY, AIR TEMP 422CM, AIR TEMP 932CM, AIR TEMP 1565CM, SURF PRESS,
DOWN LONGWAVE RAD ABV CNPY, UP LONGWAVE RAD ABV CNPY,
DOWN LONGWAVE RAD SENSOR TEMP, UP LONGWAVE RAD SENSOR TEMP,
LONG PLUS SHORT RAD ABV CNPY, SURF TEMP ABV CNPY, SPECIFIC HUM 422CM,
SPECIFIC HUM 932CM, SPECIFIC HUM 1565CM, SPECIFIC HUM ABV CNPY, REL HUM 422CM,
REL HUM 932CM, REL HUM 1565CM, REL HUM ABV CNPY, SENSIBLE HEAT FLUX BELOW CNPY,
LATENT HEAT FLUX BELOW CNPY, CO2 FLUX BELOW CNPY, NET RAD OPEN 100CM,
NET RAD BELOW CNPY, CRTFCN CODE, REVISION DATE
'NSA-OJP-FLXTR', '9TF08-FLX01',01-JUL-94,0,35.84,-1.29,43.73,-139.48,.227,
-490.0, -60.0, .57, .83, 1.33, 1.7, 2.18, 2.51, , , .004, 19.68, , , , 4.371, 1.72, -14.666, \\
-.152, -.2857, 0.0, 0.0, 0.0, -254.58, 40.5, 20.34, 20.09, 19.92, 97.47, -287.0,
402.39,21.58,21.72,-98.68,17.09,4.75,4.53,4.51,4.35,31.0,30.0,30.0,29.0,
54.84,45.12,,-58.08,-66.91,'CPI',14-JUL-99
'NSA-OJP-FLXTR', '9TF08-FLX01', 01-JUL-94, 30, 15.84, -.28, 20.99, -56.15, .227,
-310.0, -50.0, .55, .75, 1.25, 1.9, 2.39, 2.91, ,, .004, 19.1, ,, ,3.54, .801, -14.674,
-999.0,10.833,10.545,10.676,11.089,11.089,13.885,13.93,13.722,,,,,,,,,,
-.1528, -.2879, 0.0, 0.0, 0.0, -166.46, 32.56, 19.61, 19.37, 19.31, 97.49, -271.98,
396.46,20.04,20.22,-9.42,16.01,5.28,5.1,5.02,4.86,36.0,35.0,35.0,34.0,
42.69,25.82,,-4.65,-25.11,'CPI',14-JUL-99
```

## 8. Data Organization

#### 8.1 Data Granularity

The smallest unit of data tracked by the BOREAS Information System (BORIS) was data collected at a given site on a given date.

#### 8.2 Data Format

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML) code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

## 9. Data Manipulations

### 9.1 Formulae

#### 9.1.1 Derivation Techniques and Algorithms

Eddy correlation measurements are accomplished by simply calculating the covariance between the fluctuating vertical velocity and the fluctuating scalar or vector quantity of interest.

#### 9.2 Data Processing Sequence

#### 9.2.1 Processing Steps

Averages were calculated over 20-minute periods in 1993 and 1994, and over 30-minute periods in 1996. Eddy variables had a 4-minute running mean removed from them. The Sun workstation received the serial data and put a time stamp on each "chunk" of data representing 10 seconds. The four serial streams were synchronized using these time stamps. To make eddy correlation estimates of scalars, a more precise synchronization was provided by the lagged cross-correlation. This procedure was also used to provide the appropriate lag for the LI-COR CO<sub>2</sub> and H<sub>2</sub>O signals, as there was a separate delay introduced by the time it took air to travel down the tubing to the sensor. Data submitted to the archive were interpolated to half-hour intervals.

Power spectra, co- and quad-spectra, and moments (up to the 4th) were calculated in real time, in the normal acquisition routine. Post-IFC calculations were redone after the 1993 field campaign. The coordinate rotation of McMillen et al. (1986) was done for the 3-axis sonic.

 $CO_2$  fluxes were calibrated to ppm-m/s. The conversion from  $CO_2$  flux in ppm-m/s to mg/(m<sup>2</sup> s) is: (1e-3\*44\*Pa)/(R\*Tk), where Pa is the surface atmospheric pressure (kPa), R is gas constant, and Tk is the ambient air temperature (K).

In the processing of the flux data, a program read in the daily calibration data for latent heat and for  $CO_2$  fluxes, and also made the following corrections:

- Specific heat capacity of air was corrected for effects of vapor.
- The water vapor flux from the Krypton hygrometer was corrected for oxygen absorption.
- The Webb (Webb et al., 1980) correction was applied.

Outliers were then removed from the data set. Finally, these data, which were still on the original 20-minute time base, were interpolated to the half-hour.

BORIS staff processed these data by:

- Reviewing the initial data files and loading them online for BOREAS team access.
- Designing relational data base tables to inventory and store the data.
- Loading the data into the relational data base tables.
- Working with the team to document the data set.
- Extracting the data into logical files.

#### 9.2.2 Processing Changes

The 1996 data were averaged over 30-minute periods. The 1993 and 1994 data were averaged over 20-minute periods. These data were then interpolated to 30-minute time periods.

#### 9.3 Calculations

#### 9.3.1 Special Corrections/Adjustments

The trough rain gauge values represent a direct measurement from that gauge. No correction was made to compensate for the increase of the collection area. The collecting area for this gauge was expanded 9 times by using the trough.

Theten's equation was used to calculate the mixing ratio. Pressure corrections due to different height locations on the tower were considered using hydrostatic equation. The air density was held constant at 1.212 g/m<sup>3</sup>.

#### 9.3.2 Calculated Variables

All of the turbulent flux values were calculated, including sensible and latent heat fluxes, CO<sub>2</sub> flux, and friction velocity.

#### 9.4 Graphs and Plots

None.

## **10.** Errors

#### **10.1 Sources of Error**

Webb corrections were applied to vapor density fluxes, to account for the effect of density fluctuations on flux estimates (Webb et al., 1980). The effect of water vapor flux on the heat capacity of air was also accounted for in the conversion from kinematic heat flux to W/m<sup>2</sup>. The effect of oxygen absorption in the UV was corrected for in calculating water vapor flux from the krypton hygrometer (Campbell and Tanner, 1985).

#### **10.2** Quality Assessment

None given.

#### **10.2.1 Data Validation by Source**

Net radiometer comparisons with the sum of components was done continuously.

## 10.2.2 Confidence Level/Accuracy Judgment

See Section 4.2.1.1.

- **10.2.3 Measurement Error for Parameters** See Section 4.2.1.1.
- **10.2.4 Additional Quality Assessments** None.

#### 10.2.5 Data Verification by Data Center

Data were examined to check for spikes, values that are four standard deviations from the mean, long periods of constant values, and missing data.

## 11. Notes

#### 11.1 Limitations of the Data

None given.

#### 11.2 Known Problems with the Data

In 1994, the PAR sensors had offsets in them that can be readily identified by looking at the nighttime data. Problems with lags in the analog versus the serial-stream data in 1994 caused us to recalculate fluxes using only the analog sonic signals velocity.

#### **11.3 Usage Guidance**

All investigators are urged to contact D. Fitzjarrald or K. Moore concerning questions about data handling or instrument capability.

#### **11.4 Other Relevant Information**

None.

## **12.** Application of the Data Set

These data are useful for the study of water, energy, and carbon exchange in a mature jack pine forest.

## **13. Future Modifications and Plans**

None.

## 14. Software

#### **14.1 Software Description** None given.

14.2 Software Access None given.

## 15. Data Access

The NSA-OJP tower flux, meteorological, and soil temperature data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

#### **15.1** Contact Information

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407 Phone: (423) 241-3952 Fax: (423) 574-4665 E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

#### 15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/.

#### **15.3 Procedures for Obtaining Data**

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

#### 15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

## **16. Output Products and Availability**

#### **16.1 Tape Products**

None.

### **16.2 Film Products**

None.

#### **16.3 Other Products**

These data are available on the BOREAS CD-ROM series.

## **17. References**

#### **17.1 Platform/Sensor/Instrument/Data Processing Documentation** None.

### **17.2 Journal Articles and Study Reports**

Campbell, G.S. and B.D. Tanner. 1985. A Krypton hygrometer for measurement of atmospheric water vapor concentration. Proc. Int. Symposium on Humidity and Moisture. Instrument Society of America. pp. 609-614.

Funk, J.P. 1959. Improved polythene-shielded net radiometer. J. Sci. Inst. 36: 267-270.

McMillen, R.T. 1986. A BASIC program for eddy correlation in non-simple terrain. NOAA Tech. Memo. ERL-ARL-147.

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.

Webb, E.K., G.I. Pearman, and R. Leuning. 1980. Correction of flux measurements density effects due to heat and water vapour transfer. Quart. J. R. Met. Soc. 106:85-100.

#### **17.3 Archive/DBMS Usage Documentation** None.

## **18.** Glossary of Terms

None.

## 19. List of Acronyms

ASCII	-	American Standard Code for Information Interchange				
ASRC	-	Atmospheric Sciences Research Center				
ATD	-	Atmospheric Technology Division				
ATI	-	Applied Technologies, Inc.				
BOREAS	-	BOReal Ecosystem-Atmosphere Study				
BORIS	-	BOREAS Information System				
CCD	-	Charged Coupled Device				
CD-ROM	-	Compact Disk-Read-Only Memory				
DAAC	-	Distributed Active Archive Center				
EOS	-	Earth Observing System				
EOSDIS	-	EOS Data and Information System				
GIS	-	Geographic Information System				
GMT	-	Greenwich Mean Time				
GSFC	-	Goddard Space Flight Center				
HTML	-	Hyper-Text Markup Language				
IFC	-	Intensive Field Campaign				
jpg	-	Joint Photographic experts Group				
lpm	-	Liters Per Minute				
NAD83	-	North American Datum of 1983				
NASA	-	National Aeronautics and Space Administration				
NCAR	-	National Center for Atmospheric Research				
NEP	-	Net Ecosystem Productivity				
NSA	-	Northern Study Area				
OBS	-	Old Black Spruce				
OJP	-	Old Jack Pine				
ORNL	-	Oak Ridge National Laboratory				
PAR	-	Photosynthetically Active Radiation				
ppm	-	Parts Per Million				
SSA	-	Southern Study Area				
TF	-	Tower Flux				
URL	-	Uniform Resource Locator				
UV	-	Ultraviolet				
YJP	-	Young Jack Pine				

## 20. Document Information

#### **20.1 Document Revision Date** Written: 21-May-1999

Written: 21-May-1999 Revised: 10-Nov-1999

#### **20.2 Document Review Date(s)** BORIS Review: 07-Jun-1999 Science Review:

Science Keview.

## 20.3 Document ID

#### **20.4** Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

These data were provided by Drs. David R. Fitzjarrald and Kathleen E. Moore.

If using data from the BOREAS CD-ROM series, also reference the data as:

Fitzjarrald, D.R. and K.E. Moore, "Surface Exchange Observations in the Canadian Boreal Forest Region." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

#### 20.5 Document Curator

20.6 Document URL

REPOR	T DOCUMENTATIO	N PAGE	Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.					
1. AGENCY USE ONLY (Leave blan	(k) 2. REPORT DATE November 2000	3. REPORT TYPE AN Techni	D DATES COVERED ical Memorandum		
<ul> <li>4. TITLE AND SUBTITLE Technical Report Series on th BOREAS TF-8 NSA-OJP Te Data</li> <li>6. AUTHOR(S) Kathleen E. Moore and D Forrest G. Hall and Karl H</li> </ul>	e Boreal Ecosystem-Atmosph ower Flux, Meteorological, a avid R. Fitzjarrald Iuemmrich, Editors	ere Study (BOREAS) nd Soil Temperature	<b>5. FUNDING NUMBERS</b> 923 RTOP: 923-462-33-01		
7. PERFORMING ORGANIZATION N	IAME(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION		
Goddard Space Flight Cento Greenbelt, Maryland 20771	er		2000-03136-0		
9. SPONSORING / MONITORING National Aeronautics and Sp Washington, DC 20546-000	AGENCY NAME(S) AND ADDRE pace Administration	SS (ES)	10. SPONSORING / MONITORING AGENCY REPORT NUMBER TM—2000–209891 Vol. 203		
11. SUPPLEMENTARY NOTES K.E. Moore and D.R. Fitz K. Huemmrich: Universit	jarrald: State University of y of Maryland, NASA God	New York, Albany; Idard Space Flight C	enter, Greenbelt, Maryland		
12a. DISTRIBUTION / AVAILABILITY Unclassified–Unlimited Subject Category: 43 Report available from the N 7121 Standard Drive, Hanoy	ASA Center for AeroSpace I ver, MD 21076-1320. (301)	nformation, 521-0390.	12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words	3)				
The BOREAS TF-8 team site during the growing se ASCII files.	collected energy, CO <sub>2</sub> , and ason of 1994 and most of t	l water vapor flux da he year for 1996. Th	ta at the BOREAS NSA-OJP ne data are available in tabular		
14. SUBJECT TERMS BOREAS, tower flux, me	teorological data, soil temp	perature data.	15. NUMBER OF PAGES 28		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	BE. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIF OF ABSTRACT Unclassified	ICATION 20. LIMITATION OF ABSTRACT		
NSN 7540-01-280-5500			Standard Form 298 (Rev. 2-89)		

Prescribed by ANSI Std. Z39.18 298-102