



**Technical Report Series on the  
Biosystem-Aerosphere Study (BOREAS)**

*William J. Shuttleworth and Karl Huemmrich, Editors*

**205**

**NASA TF-9 SSA-OBS  
Data**

*William J. Shuttleworth and P.G. Jarvis*

Aeronautics and  
Administration

Space Flight Center  
Greenland 20771

## The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov/STI-homepage.html>
- E-mail your question via the Internet to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:  
NASA Access Help Desk  
NASA Center for AeroSpace Information  
7121 Standard Drive  
Hanover, MD 21076-1320

NASA/TM—2000–209891, Vol. 205



**Technical Report Series on the  
Boreal Ecosystem-Atmosphere Study (BOREAS)**

*Forrest G. Hall and Karl Huemmrich, Editors*

**Volume 205**

**BOREAS TF-9 SSA-OBS  
Branch Level Flux Data**

*Mark. B. Rayment and Paul G. Jarvis  
University of Edinburgh, UK*

National Aeronautics and  
Space Administration

**Goddard Space Flight Center**  
Greenbelt, Maryland 20771

---

---

November 2000

Available from:

NASA Center for AeroSpace Information  
7121 Standard Drive  
Hanover, MD 21076-1320  
Price Code: A17

National Technical Information Service  
5285 Port Royal Road  
Springfield, VA 22161  
Price Code: A10

# BOREAS TF-9 SSA-OBS Branch Level Flux Data

Mark B. Rayment, Paul G. Jarvis

## Summary

The BOREAS TF-9 team collected data that describe carbon dioxide and water vapor fluxes from foliage at the BOREAS SSA-OBS site from 07-April through 23-November-1996. The data are available in tabular ASCII files.

## Table of Contents

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

## 1. Data Set Overview

### 1.1 Data Set Identification

BOREAS TF-09 SSA-OBS Branch Level Flux Data

### 1.2 Data Set Introduction

A system of large cuvettes was used to measure whole branch CO<sub>2</sub> and H<sub>2</sub>O vapor exchange of four black spruce (*Picea mariana* [Mill] BSP) branches at the BOREal Ecosystem-Atmosphere Study (BOREAS) Southern Study Area (SSA) Old Black Spruce (OBS) site.

### 1.3 Objective/Purpose

The objective of this study was to measure and model the CO<sub>2</sub> exchanges of boreal black spruce forest branches over the course of an entire growing season. These measurements will be used to parameterize models and to assist scaling up procedures from leaf level to stand level (eddy covariance) measurements.

### 1.4 Summary of Parameters and Variables

Measurements include CO<sub>2</sub> and H<sub>2</sub>O fluxes, photosynthetic photon flux density (PPFD), air and leaf temperatures, relative humidity, air humidity deficit, and CO<sub>2</sub> concentration.

## 1.5 Discussion

The branch bags consisted of two 5-mm-thick acrylic end pieces, oval in shape (600-mm major axis, 300-mm minor axis, 0.14-m<sup>2</sup> area), separated by five thin (5-mm diameter) stainless steel rods. One end was made such that it could slide up or down the rods in order to adjust the bag length to suit the individual branch. An ovaloid shape was chosen to minimize dead volume within the bag, to minimize the bag's surface area to volume ratio (minimizing any adsorption/desorption effects), to minimize attenuation of incoming light, and for aesthetic reasons. The bag itself was effected by covering the structure with polypropylene film (ICI Propafilm, 34-mm thickness, ICI PLC, London) and sealing along the edge of the end piece with silicone sealant. The bottom of the bag was left unsealed to allow placement of the bag upon the branch; afterward, it and the branch entry point were sealed in a similar fashion. A 12-volt electric fan (RS 583-050, RS Components Ltd., Northants) was mounted at the trunk end of each bag, and blew air at a high flow rate (40 dm<sup>3</sup>/s, approximately 18 to 26 air changes min<sup>-1</sup>) through the bag via large shrouded inlet and outlet ports. When a gas exchange measurement was to be made, the ventilation fan was switched off, thin flap valves dropped over the inlet and outlet and were shut tight with small electromagnets, and an internal circulating fan was switched on. Air was circulated (5 dm<sup>3</sup>/min) at all times between all bags and the box containing the infrared gas analyzer (IRGA) and control system through loops of tubing (5-mm i.d. Dekabon, Furon, Gembioux, Belgium), and at measurement time a small amount of air (0.2 dm<sup>3</sup>/min) was diverted from the appropriate loop to the IRGA (LI-6262, LI-COR, Inc., Lincoln, NE) operating in absolute mode. Within each bag, relative humidity and air temperature were measured (Vaisala HMB 30A, Vaisala (UK) Ltd., Cambridge), as was leaf temperature (thin Cu-Con thermocouple referenced to the air temperature sensor) and, for a period, bag internal vs. external temperature (Cu-Con thermocouple). Light incident upon each branch was measured with a Macam light sensor (Macam SD101QV, Macam, Livingstone) mounted directly onto the branch, midway along its length. Sensor outputs were recorded through a Campbell AM416 multiplexer to a Campbell CR21X data logger (Campbell Scientific, Ltd., Shepshed, Leics.), which also initiated the measurement sequence.

Each bag was closed for 5 minutes in turn, during which time the sensors were read every 20 seconds; thus, each bag was measured every 20 minutes. Gas exchange was calculated from the slope of the regression of gas concentration upon time (excluding the readings from the initial 40 s for CO<sub>2</sub> and the initial 80 s for H<sub>2</sub>O vapor in order to ensure that the IRGA was entirely flushed of the previous sample) and the volume of the system (106.3, 134.3, 91.9, and 106.3 dm<sup>3</sup> for bags 1 to 4, respectively). The air sample bleed to the IRGA during the measurement period was negligible (~1 dm<sup>3</sup>) compared to the bag volume and was ignored in calculations. All bags were leak tested by shading the branch to its light compensation point, blowing into the bag to create a high internal/external concentration differential, closing the inlet and outlet ports, and monitoring bag concentration over a period of time.

## 1.6 Related Data Sets

BOREAS TF-09 SSA-OBS Tower Flux, Meteorological, and Soil Temperature Data

BOREAS TE-10 Leaf Gas Exchange Data

BOREAS TE-11 Leaf Gas Exchange Measurements

BOREAS TE-12 Leaf Gas Exchange Data

## 2. Investigator(s)

### 2.1 Investigator(s) Name and Title

Mr. Mark B. Rayment and Prof. Paul G. Jarvis  
Institute of Ecology and Resource Management  
University of Edinburgh UK

### 2.2 Title of Investigation

The CO<sub>2</sub> Exchanges of Boreal Black Spruce Forest

## **2.3 Contact Information**

### **Contact 1:**

Mr. Mark B. Rayment  
Institute of Ecology and Resource Management  
University of Edinburgh  
Darwin Building  
King's Buildings  
Edinburgh EH9 3JU  
UK  
+131 650 5423  
+131 662 0478 (fax)  
M.Rayment@ed.ac.uk

### **Contact 2:**

K. Fred Huemmrich  
University of Maryland  
Code 923  
NASA GSFC  
Greenbelt, MD 20771  
(301) 286-4862  
(301) 286-0239 (fax)  
Karl.Huemmrich@gsfc.nasa.gov

## **3. Theory of Measurements**

The net carbon uptake of a tree depends on the assimilation of carbon dioxide by photosynthesis in the leaves and the carbon dioxide emissions resulting from respiratory processes in the leaves and woody tissues of the tree. Transpiration of water occurs mainly from the foliage. Enclosures surrounding branches remain open for the majority of the time and are periodically closed, at which time the rate of change of gas concentration allows calculation of an integrated measure of the net exchange of gases between the branch and the atmosphere.

## **4. Equipment**

### **4.1 Sensor/Instrument Description**

#### **4.1.1 Collection Environment**

Measurements were collected from early April through late November; temperatures ranged from below freezing to over 30 °C during that period.

#### **4.1.2 Source/Platform**

The branch bags surrounded individual spruce branches. The bags were supported in position by elastic ropes attached to the trunk above the bag and, where necessary, to a support projecting from the canopy access tower. This arrangement allowed the bags to move freely as the trees and branches moved with the wind. Each of the bags was positioned on a south-facing branch to minimize shading by the tower. The bags could be reached from the canopy access tower, made of 5- by 9-foot scaffolding.

#### Instruments:

- Gas concentration: IRGA LI-6262 (LI-COR, Inc., Lincoln, NE) operating in absolute mode.
- Relative humidity and air temperature: Vaisala HMB 30A (Vaisala (UK) Ltd., Cambridge).
- Leaf temperature: thin Cu-Con thermocouple referenced to the air temperature sensor.
- Incident PPFD: Macam SD101QV light sensor mounted directly onto the branch, midway along its length.
- Logger: Campbell AM416 multiplexer and Campbell CR21X data logger.
- Tubing: 5-mm i.d. Dekabon.

#### **4.1.3 Source/Platform Mission Objectives**

The objective was to measure branch-scale CO<sub>2</sub> and water vapor fluxes and related environmental variables in black spruce at the southern edge of the boreal forest.

#### **4.1.4 Key Variables**

CO<sub>2</sub> and water vapor fluxes. Supporting meteorological variables: PPFD, air temperature, leaf temperature, CO<sub>2</sub>, and water vapor concentration.

#### **4.1.5 Principles of Operation**

The LI-COR LI-6262 IRGA is a closed-path instrument with reference and sample cells with an infrared source at one end and a detector at the other. Different gases absorb infrared of different frequencies, and filters are used to select a narrow band that corresponds to an absorption band of the gas of interest. The LI-6262 measures CO<sub>2</sub> and H<sub>2</sub>O concentrations. A gas of known concentration is passed through a reference cell, and the gas whose concentration is to be measured is passed through the sample cell. The amount of infrared reaching the detector in each cell is a function of the gas concentration in the cell. The difference in voltage produced by the detectors of the reference and sample cells is then a function of the difference in concentration of the gas in the cells. Other sensors were common meteorological sensors used in a standard fashion. For principles of operations of these sensors, please see a relevant textbook; e.g., Percy et al. (1991).

#### **4.1.6 Sensor/Instrument Measurement Geometry**

Two branch bags were installed on each of two trees at the SSA-OBS site in early April 1996. Two bags were positioned in the upper canopy (at 7.85 m above the ground for branch number 1 and 8.25 m for branch number 3) and two in the lower canopy (at 5.22 m for branch number 2 and 5.48 m for branch number 4); the trees' diameters at breast height (DBH) were 10 cm and 9 cm. The bags were supported in position by elastic ropes attached to the trunk above the bag and, where necessary, to a support projecting from the canopy access tower. This arrangement allowed the bags to move freely as the trees and branches moved with the wind. Each of the bags was positioned on a south-facing branch to minimize shading by the tower. Humidity, air and leaf temperatures, and PPFD were measured within the bag, close to or in contact with the leaves. Gas concentration was measured on a sample of air circulated between the bag and the IRGA. The IRGA was positioned in an insulated box mounted on the canopy access tower.

#### **4.1.7 Manufacturer of Instrument**

LI-COR LI-6262  
P.O. Box 4425/4421  
Superior Street  
Lincoln, NE 68504  
USA

Vaisala HMB 30A  
Vaisala (UK) Ltd.  
Cambridge  
UK



Macam SD101QV light sensor  
Macam  
Livingstone  
UK

Campbell AM416 multiplexer and Campbell CR21X data logger  
Campbell Scientific  
P.O. Box 551  
Logan, UT 84321  
USA

Dekabon tubing  
J.P. Deane & Co. Ltd.  
91, Ormonde Crescent  
Glasgow G44 3SW  
UK

## **4.2 Calibration**

### **4.2.1 Specifications**

The LI-6262: The output linearization of this instrument was calibrated by the manufacturer and was last performed in July 1993. The field calibration fixes the lower and upper ends of the linearization function and is carried out by passing CO<sub>2</sub> and water vapor free air through the reference cell (the instrument is used in the absolute mode) and setting the CO<sub>2</sub> and water vapor channels to zero. The upper point is set by passing dry air of known CO<sub>2</sub> or of known water vapor concentration through the sample cell and adjusting the appropriate channel to read the correct value. CO<sub>2</sub> standard gases were cross-referenced to the BOREAS primary standards, and a LI-COR LI-610 dewpoint generator was used to produce air of known water vapor density.

The Vaisala temperature and humidity probes either were bought new or were returned to the manufacturer for calibration immediately prior to installation.

The Macam PPFD sensors were purchased new immediately prior to installation, and the manufacturer's calibration factors were used.

All bags were leak tested by shading the branch to its light compensation point, blowing into the bag to create a high internal/external concentration differential, closing the inlet and outlet ports, and monitoring bag concentration over a period of time.

The LI-6262 was usually calibrated every 4 to 7 days. Typical CO<sub>2</sub> drift was 1-ppm drift in span and offset. Typical drift for the water vapor was 0.1 kPa in span and offset.

#### **4.2.1.1 Tolerance**

None.

#### **4.2.2 Frequency of Calibrations**

The LI-6262 was usually calibrated every 4 to 7 days.

#### **4.2.3 Other Calibration Information**

None.

## 5. Data Acquisition Methods

When a gas exchange measurement was to be made, the ventilation fan was switched off, thin flap valves dropped over the inlet and outlet and were shut tight with small electromagnets, and an internal circulating fan was switched on. Air was circulated (5 dm<sup>3</sup>/min) at all times between all bags and the box containing the IRGA and control system through loops of tubing, and at measurement time a small amount of air (0.2 dm<sup>3</sup>/min) was diverted from the appropriate loop to the IRGA operating in absolute mode. Within each bag, relative humidity and air temperature were measured, as was leaf temperature and, for a period, bag internal vs. external temperature. Light incident upon each branch was measured with a Macam light sensor mounted directly onto the branch, midway along its length.

Each bag was closed for 5 minutes in turn, during which time the sensors were read every 20 seconds; thus, each bag was measured every 20 minutes. Gas exchange was calculated from the slope of the regression of gas concentration upon time (excluding the readings from the initial 40 s for CO<sub>2</sub> and the initial 80 s for H<sub>2</sub>O vapor in order to ensure that the IRGA was entirely flushed of the previous sample) and the volume of the system (106.3, 134.3, 91.9, and 106.3 dm<sup>3</sup> for bags 1 to 4, respectively). The air sample bleed to the IRGA during the measurement period was negligible (~1 dm<sup>3</sup>) compared to the bag volume and was ignored in calculations.

A Campbell Scientific 21x data logger was used to log the data together with a Campbell AM416 multiplexer. The raw signal from each sensor was converted into the appropriate units in the data logger program. The data logger also initiated the measurement sequence.

## 6. Observations

### 6.1 Data Notes

Values given are on a PROJECTED leaf area basis; that is, values should be adjusted by a shape factor to express rates on a total surface or hemisurface area basis. For black spruce, hemisurface area was last reported to be 1.27 x projected area; i.e., these rates would be divided by 1.27 to given rates on a hemisurface area basis.

### 6.2 Field Notes

None given.

## 7. Data Description

### 7.1 Spatial Characteristics

#### 7.1.1 Spatial Coverage

All data were collected at the BOREAS SSA-OBS site. North American Datum of 1983 (NAD83) coordinates for this site are latitude 53.98717° N, longitude 105.11779° W, and elevation of 628.94 m.

Branches had total projected needle areas of 3115, 2014, 1657, and 2342 cm<sup>2</sup>, for chambers one through 4, respectively.

#### 7.1.2 Spatial Coverage Map

None.

#### 7.1.3 Spatial Resolution

The values are point measurements from trees near the locations given in Section 7.1.1.

#### 7.1.4 Projection

None.

### 7.1.5 Grid Description

None.

## 7.2 Temporal Characteristics

### 7.2.1 Temporal Coverage

The data were collected from 06-April to 22-November-1996. Data were collected continuously with gaps between 18- and 26-June and 03- and 07-July.

### 7.2.2 Temporal Coverage Map

All data were collected at the BOREAS SSA-OBS site.

### 7.2.3 Temporal Resolution

Each observation took 5 minutes to complete data collection cycled through each of the four bags so that observations of any given bag occur every 20 minutes.

## 7.3 Data Characteristics

### 7.3.1 Parameter/Variable

The parameters contained in the data files on the CD-ROM are:

Column Name
SITE_NAME
SUB_SITE
DATE_OBS
TIME_OBS
CHAMBER_NUM
CO2_FLUX_CHAMBER
H2O_FLUX_CHAMBER
DOWN_PPFD_CHAMBER
AIR_TEMP_CHAMBER
LEAF_TEMP_CHAMBER
AIR_HUM_DEFICIT_CHAMBER
REL_HUM_CHAMBER
CO2_CONC_CHAMBER
CRTFCN_CODE
REVISION_DATE

### 7.3.2 Variable Description/Definition

The descriptions of the parameters contained in the data files on the CD-ROM are:

Column Name	Description
SITE_NAME	The identifier assigned to the site by BOREAS, in the format SSS-TTT-CCCCC, where SSS identifies the portion of the study area: NSA, SSA, REG, TRN, and TTT identifies the cover type for the site, 999 if unknown, and CCCCC is the identifier for site, exactly what it means will vary with site type.
SUB_SITE	The identifier assigned to the sub-site by BOREAS, in the format GGGGG-IIIII, where GGGGG is the group associated with the sub-site

DATE_OBS	instrument, e.g. HYD06 or STAFF, and IIIII is the identifier for sub-site, often this will refer to an instrument.
TIME_OBS	The date on which the data were collected.
CHAMBER_NUM	The Greenwich Mean Time (GMT) of the start of the data collection.
CO2_FLUX_CHAMBER	Identification number of chamber.
H2O_FLUX_CHAMBER	The chamber CO2 flux.
DOWN_PPFD_CHAMBER	The water vapor flux measured in the chamber.
AIR_TEMP_CHAMBER	The incoming photosynthetic photon flux density measured in the chamber.
LEAF_TEMP_CHAMBER	The temperature of the air in the chamber.
AIR_HUM_DEFICIT_CHAMBER	The temperature of leaves in the chamber.
REL_HUM_CHAMBER	The air humidity deficit measured in the chamber.
CO2_CONC_CHAMBER	The relative humidity of the air in the chamber.
CRTFCN_CODE	The CO2 concentration in the chamber.
REVISION_DATE	The BOREAS certification level of the data. Examples are CPI (Checked by PI), CGR (Certified by Group), PRE (Preliminary), and CPI-??? (CPI but questionable).
	The most recent date when the information in the referenced data base table record was revised.

### 7.3.3 Unit of Measurement

The measurement units for the parameters contained in the data files on the CD-ROM are:

Column Name	Units
SITE_NAME	[none]
SUB_SITE	[none]
DATE_OBS	[DD-MON-YY]
TIME_OBS	[HHMM GMT]
CHAMBER_NUM	[unitless]
CO2_FLUX_CHAMBER	[micromoles][meter <sup>-2</sup> ][second <sup>-1</sup> ]
H2O_FLUX_CHAMBER	[millimoles][meters <sup>-2</sup> ][second <sup>-1</sup> ]
DOWN_PPFD_CHAMBER	[micromoles][meters <sup>-2</sup> ][second <sup>-1</sup> ]
AIR_TEMP_CHAMBER	[degrees Celsius]
LEAF_TEMP_CHAMBER	[degrees Celsius]
AIR_HUM_DEFICIT_CHAMBER	[parts per thousand]
REL_HUM_CHAMBER	[percent]
CO2_CONC_CHAMBER	[parts per million]
CRTFCN_CODE	[none]
REVISION_DATE	[DD-MON-YY]

### 7.3.4 Data Source

The sources of the parameter values contained in the data files on the CD-ROM are:

Column Name	Data Source
SITE_NAME	[Assigned by BORIS.]
SUB_SITE	[Assigned by BORIS.]
DATE_OBS	[Supplied by Investigator.]
TIME_OBS	[Supplied by Investigator.]
CHAMBER_NUM	[Supplied by Investigator.]

CO2_FLUX_CHAMBER	[LI-COR LI-6262 IRGA]
H2O_FLUX_CHAMBER	[LI-COR LI-6262 IRGA]
DOWN_PPFD_CHAMBER	[Macam SD101QV light sensor]
AIR_TEMP_CHAMBER	[Vaisala temperature and humidity probes]
LEAF_TEMP_CHAMBER	[Cu-Con thermocouple]
AIR_HUM_DEFICIT_CHAMBER	[Vaisala temperature and humidity probes]
REL_HUM_CHAMBER	[Vaisala temperature and humidity probes]
CO2_CONC_CHAMBER	[LI-COR LI-6262 IRGA]
CRTFCN_CODE	[Assigned by BORIS.]
REVISION_DATE	[Assigned by BORIS.]

### 7.3.5 Data Range

The following table gives information about the parameter values found in the data files on the CD-ROM.

Column Name	Minimum Data Value	Maximum Data Value	Missng Data Value	Unrel Data Value	Below Detect Limit	Data Not Cllctd
SITE_NAME	SSA-OBS-FLXTR	SSA-OBS-FLXTR	None	None	None	None
SUB_SITE	9TF09-FLX02	9TF09-FLX02	None	None	None	None
DATE_OBS	07-APR-96	23-NOV-96	None	None	None	None
TIME_OBS	0	2355	None	None	None	None
CHAMBER_NUM	1	4	None	None	None	None
CO2_FLUX_CHAMBER	-5.95	1.57	None	None	None	None
H2O_FLUX_CHAMBER	-.16	2	None	None	None	None
DOWN_PPFD_CHAMBER	0	1838	None	None	None	Blank
AIR_TEMP_CHAMBER	-33.8	47.8	None	None	None	None
LEAF_TEMP_CHAMBER	-34.5	48.7	None	None	None	None
AIR_HUM_DEFICIT_CHAMBER	-1.33	77.41	None	None	None	Blank
REL_HUM_CHAMBER	0	111.5	None	None	None	None
CO2_CONC_CHAMBER	133	661	None	None	None	None
CRTFCN_CODE	CPI	CPI	None	None	None	None
REVISION_DATE	02-SEP-98	02-SEP-98	None	None	None	None

- Minimum Data Value -- The minimum value found in the column.
- Maximum Data Value -- The maximum value found in the column.
- Missng Data Value -- The value that indicates missing data. This is used to indicate that an attempt was made to determine the parameter value, but the attempt was unsuccessful.
- Unrel Data Value -- The value that indicates unreliable data. This is used to indicate an attempt was made to determine the parameter value, but the value was deemed to be unreliable by the analysis personnel.
- Below Detect Limit -- The value that indicates parameter values below the instruments detection limits. This is used to indicate that an attempt was made to determine the parameter value, but the analysis personnel determined that the parameter value was below the detection limit of the instrumentation.
- Data Not Cllctd -- This value indicates that no attempt was made to determine the parameter value. This usually indicates that BORIS combined several similar but not identical data sets into the same data base table

but this particular science team did not measure that parameter.

Blank -- Indicates that blank spaces are used to denote that type of value.  
N/A -- Indicates that the value is not applicable to the respective column.  
None -- Indicates that no values of that sort were found in the column.

---

## 7.4 Sample Data Record

The following are wrapped versions of data record from a sample data file on the CD-ROM.

```
SITE_NAME, SUB_SITE, DATE_OBS, TIME_OBS, CHAMBER_NUM, CO2_FLUX_CHAMBER,  
H2O_FLUX_CHAMBER, DOWN_PPFD_CHAMBER, AIR_TEMP_CHAMBER, LEAF_TEMP_CHAMBER,  
AIR_HUM_DEFICIT_CHAMBER, REL_HUM_CHAMBER, CO2_CONC_CHAMBER, CRTFCN_CODE,  
REVISION_DATE  
'SSA-OBS-FLXTR', '9TF09-FLX02', 01-JUN-96, 0, 1, -3.13, .001, 902.0, 27.5, 28.3, 15.34,  
63.41, 352.0, 'CPI', 02-SEP-98  
'SSA-OBS-FLXTR', '9TF09-FLX02', 01-JUN-96, 5, 2, -3.94, -.001, 1299.0, 26.4, 26.4, 9.44,  
78.93, 314.0, 'CPI', 02-SEP-98
```

## 8. Data Organization

### 8.1 Data Granularity

The smallest unit of data tracked by the BOREAS Information System (BORIS) was data collected at a given site on a given date.

### 8.2 Data Format

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. The character fields are enclosed with single apostrophe marks. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML) code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

## 9. Data Manipulations

### 9.1 Formulae

None.

#### 9.1.1 Derivation Techniques and Algorithms

None.

### 9.2 Data Processing Sequence

A linear fit was made between the gas concentrations and time; data were rejected if the sum of the squares of the residuals was less than 0.9 and the calculated flux was nonzero.

### **9.2.1 Processing Steps**

BORIS staff processed these data by:

- Reviewing the initial data files and loading them online for BOREAS team access.
- Designing relational data base tables to inventory and store the data.
- Loading the data into the relational data base tables.
- Working with the team to document the data set.
- Extracting the data into logical files.

### **9.2.2 Processing Changes**

None.

### **9.3 Calculations**

Flux calculations:  $\text{flux} = (\text{concentration change} * \text{molar volume}) / (\text{time interval} * \text{leaf area})$

#### **9.3.1 Special Corrections/Adjustments**

None.

#### **9.3.2 Calculated Variables**

None.

### **9.4 Graphs and Plots**

None.

## **10. Errors**

### **10.1 Sources of Error**

Major sources of error include sensor drift, measurement of branch bag volume, and measurement of leaf area.

### **10.2 Quality Assessment**

#### **10.2.1 Data Validation by Source**

None given.

#### **10.2.2 Confidence Level/Accuracy Judgment**

None given.

#### **10.2.3 Measurement Error for Parameters**

None given.

#### **10.2.4 Additional Quality Assessments**

None given.

#### **10.2.5 Data Verification by Data Center**

Data were examined to check for spikes, values that are four standard deviations from the mean, long periods of constant values, and missing data.

## **11. Notes**

### **11.1 Limitations of the Data**

Potential users of these data should be aware of the limitations of gas exchange as a means of investigating photosynthesis and of the implications of these measurements having been made on entire, enclosed branches.

### **11.2 Known Problems with the Data**

All known bad data have been removed from the files.

### **11.3 Usage Guidance**

Potential users of these data should be aware of the limitations of gas exchange as a means of investigating photosynthesis and of the implications of these measurements having been made on entire, enclosed branches. They should also be aware that these data have been submitted to BORIS out of courtesy rather than contractual obligation and should therefore seek the permission of the investigators before publishing analyses derived from them. These data remain the property of the University of Edinburgh and of the UK Natural Environment Research Council.

### **11.4 Other Relevant Information**

None.

## **12. Application of the Data Set**

This data set is useful for the examination of effects of environmental variables on photosynthesis and transpiration at the scale of individual branches.

## **13. Future Modifications and Plans**

Although these data represent the most recent data set, believed to be error free, some data might, in the future, be found to be in error.

## **14. Software**

### **14.1 Software Description**

The logger program was written with Campbell PC208. Flux and humidity-based calculations and initial screening of the data were carried out with a program written in Microsoft Visual Basic. Final data screening was carried out in Statistical Analysis System (SAS).

### **14.2 Software Access**

None given.



## **15. Data Access**

The SSA-OBS branch-level flux data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

### **15.1 Contact Information**

For BOREAS data and documentation please contact:

ORNL DAAC User Services  
Oak Ridge National Laboratory  
P.O. Box 2008 MS-6407  
Oak Ridge, TN 37831-6407  
Phone: (423) 241-3952  
Fax: (423) 574-4665  
E-mail: ornl daac@ornl.gov or ornl@eos.nasa.gov

### **15.2 Data Center Identification**

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics  
<http://www-eosdis.ornl.gov/>.

### **15.3 Procedures for Obtaining Data**

Users may obtain data directly through the ORNL DAAC online search and order system [<http://www-eosdis.ornl.gov/>] and the anonymous FTP site [<ftp://www-eosdis.ornl.gov/data/>] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

### **15.4 Data Center Status/Plans**

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

## **16. Output Products and Availability**

### **16.1 Tape Products**

None.

### **16.2 Film Products**

None.

### **16.3 Other Products**

These data are available on the BOREAS CD-ROM series.

## 17. References

### 17.1 Platform/Sensor/Instrument/Data Processing Documentation

None.

### 17.2 Journal Articles and Study Reports

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Pearcy, R.W., J. Ehleringer, H.A. Mooney, and P.W. Rundel. 1991. Plant Physiological Ecology: Field methods and instrumentation. Chapman and Hall, London and New York.

Rayment, M.B. 1998. Ph.D. Thesis. University of Edinburgh.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. *Bulletin of the American Meteorological Society*. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. *Journal of Geophysical Research* 102(D24): 28,731-28,770.

### 17.3 Archive/DBMS Usage Documentation

None.

## 18. Glossary of Terms

None.

## 19. List of Acronyms

ASCII	- American Standard Code for Information Interchange
BOREAS	- BOReal Ecosystem-Atmosphere Study
BORIS	- BOREAS Information System
CD-ROM	- Compact Disk-Read-Only Memory
DAAC	- Distributed Active Archive Center
DBH	- Diameter at Breast Height
EOS	- Earth Observing System
EOSDIS	- EOS Data and Information System
GIS	- Geographic Information System
GMT	- Greenwich Mean Time
GSFC	- Goddard Space Flight Center
HTML	- HyperText Markup Language
IRGA	- Infra-Red Gas Analyzer
NASA	- National Aeronautics and Space Administration
NSA	- Northern Study Area
OBS	- Old Black Spruce
ORNL	- Oak Ridge National Laboratory
PANP	- Prince Albert National Park
PPFD	- Photosynthetic Photon Flux Density
SAS	- Statistical Analysis System
SSA	- Southern Study Area
TE	- Terrestrial Ecology
TF	- Tower Flux
URL	- Uniform Resource Locator

## 20. Document Information

### 20.1 Document Revision Date

Written: 25-Jun-1997

Revised: 10-Aug-1999

### 20.2 Document Review Date(s)

BORIS Review: 23-Jul-1998

Science Review:

### 20.3 Document ID

### 20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

M.B. Rayment and P.G. Jarvis, Institute of Ecology and Resource Management, Edinburgh University.

Users of these data should be aware that these data have been submitted to BORIS out of courtesy rather than contractual obligation and should therefore seek the permission of the investigators before publishing analyses derived from them. These data remain the property of the University of Edinburgh and of the UK Natural Environment Research Council.

If using data from the BOREAS CD-ROM series, also reference the data as:

Rayment, M.B and P.G. Jarvis, "The CO<sub>2</sub> Exchanges of Boreal Black Spruce Forest." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

## **20.5 Document Curator**

## **20.6 Document URL**

**REPORT DOCUMENTATION PAGE**Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> November 2000	<b>3. REPORT TYPE AND DATES COVERED</b> Technical Memorandum	
<b>4. TITLE AND SUBTITLE</b> Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS) BOREAS TF-9 SSA-OBS Branch Level Flux			<b>5. FUNDING NUMBERS</b> 923 RTOP: 923-462-33-01	
<b>6. AUTHOR(S)</b> Mark B. Rayment and Paul G. Jarvis Forrest G. Hall and Karl Huemmrich, Editors				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS (ES)</b> Goddard Space Flight Center Greenbelt, Maryland 20771			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b> 2000-03136-0	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS (ES)</b> National Aeronautics and Space Administration Washington, DC 20546-0001			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b> TM—2000—209891 Vol. 205	
<b>11. SUPPLEMENTARY NOTES</b> M.B. Rayment and P.G. Jarvis: University of Edinburgh, UK; K. Huemmrich: University of Maryland, NASA Goddard Space Flight Center, Greenbelt, Maryland				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Unclassified—Unlimited Subject Category: 43 Report available from the NASA Center for AeroSpace Information, 7121 Standard Drive, Hanover, MD 21076-1320. (301) 621-0390.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b>  The BOREAS TF-9 team collected data that describe carbon dioxide and water vapor fluxes from foliage at the BOREAS SSA-OBS site from 07-April through 23-November-1996. The data are available in tabular ASCII files.				
<b>14. SUBJECT TERMS</b> BOREAS, tower flux.			<b>15. NUMBER OF PAGES</b> 16	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> Unclassified	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> Unclassified	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> Unclassified	<b>20. LIMITATION OF ABSTRACT</b> UL	

