

CHARACTERISTICS OF LIGHTS

Left Descending Bank

F. W.	Fixed White
F. R.	Fixed Red
2 F. R.	Two Fixed Red
FL (2) W5s	Group Flashing White every 5 Sec. (2 flashes)
FL (2) W6s	Group Flashing White every 6 sec. (2 flashes)
FL (2) R5s	Group Flashing Red every 5 sec. (2 flashes)
FL (2) R6s	Group Flashing Red every 6 sec. (2 flashes)
Iso W 2s	Equal Interval White 2 sec.
Iso R 2s	Equal Interval Red 2 sec.
Q R	Quick Flashing Red
IQ R	Interrupted Quick Flashing Red

Right Descending Bank

F. W.	Fixed White
F. G.	Fixed Green
2 F. G.	Two Fixed Green
FL W4s	Flashing White every 4 Sec.
FL G4s	Flashing Green every 4 sec.
Iso W 2s	Equal Interval White 2 sec.
Iso G 2s	Equal Interval Green 2 sec.
Q G	Quick Flashing Green
IQ G	Interrupted Quick Flashing Green

CHARACTERISTICS OF BEACONS

All beacons have reflective material which matches the color indicated below:

SG	Square shaped Green PASSING beacon.
CG	Diamond shaped Green CROSSING beacon.
TR	Triangle shaped Red PASSING beacon.
CR	Diamond shaped Red CROSSING beacon.
JR	Triangle shaped Red and Green JUNCTION beacon.

POSITION OF AIDS TO NAVIGATION

Buoys are set to mark project depths taking into consideration the prevailing river stage and obstructions. Buoy positions as shown on the obstructions. Buoy position as shown on the chart are approximate and should always be given as wide a berth in passing as possible consistent with the length and width of the bend or crossing.

Buoys should always be used with caution. They may be carried off position by high water accumulation of drift, ice, or sunk by collision or other causes. When carried off position destroyed, or removed to prevent loss, buoys are replaced at the earliest opportunity.

LIGHTS AND BEACONS ARE ALSO SHOWN IN APPROXIMATE LOCATIONS.

NOTE

NAVIGATIONAL SYMBOLS AS SHOWN IN THE LEGEND ARE ONLY REPRESENTATIVE. THE ACTUAL LOCATION OF THE ITEMS WHICH THEY REPRESENT MAY VARY FROM WHAT IS SHOWN ON THE NAVIGATION CHART.

MARINE RADIO CHANNELS

CHANNEL	FREQUENCY	PURPOSE
13	156.650mhz	Bridge to Bridge
14	156.700mhz	Port Operations
16	156.800mhz	Hailing & Distress

NOTES:

1. Locks monitor Channels 13 & 16.
2. Coast Guard monitors Channel 16 for Distress Calls.

CHARACTERISTICS OF LIGHTS AND NOTES NAVIGATION CHARTS OHIO RIVER

U.S. ARMY ENGINEER DISTRICT, PITTSBURGH
Revised: 1 January 2000