

U. S. DEPARTMENT OF COMMERCE
NATIONAL BUREAU OF STANDARDS
WASHINGTON 25, D. C.
PROVISIONAL CERTIFICATE
STANDARD SAMPLE 1056
CUPRIC CYCLOHEXANEBUTYRATE

(Standard for Determination of Copper in Petroleum Products)

This compound was prepared to insure material that is essentially free from other metals and has suitable solubility, compatibility, and uniformity for use in the preparation of a standard of copper in lubricating oils. The compound is being certified provisionally to one part per hundred of copper, pending further studies of analytical procedures, of loss of weight on drying, and of changes in weight when exposed to air. Every effort should be made to maintain a uniform procedure by following the directions in this certificate.

CHEMICAL AND SPECTROGRAPHIC ANALYSES

Procedure and Results of Chemical Analysis

Copper, percent - - - - - 16.0

Copper was determined by wet-ashing a 1-g sample (dried for 2 hours over phosphorus pentoxide) with sulfuric and nitric acids, depositing the copper by electrolysis, and weighing as metallic copper. Determinations were also made by direct ignition of a dried 1-g sample, wrapped in filter paper and covered with oxalic acid. The oxide was ignited under hydrogen, and weighed as the metal. Analysts, B. B. Bendigo and L. A. Machlan.

Procedure and Results of Spectrographic Analysis

The compound was examined spectrographically for metallic impurities. A 5-mg sample of the compound was excited in a direct-current arc and the photographed spectrum was examined for the characteristic lines of 51 elements. Several impurities were found, but none is considered to be present in sufficient concentration to interfere with the intended use. The principal impurities were aluminum and silicon, each estimated to be less than 0.01 percent. Analyst, Elizabeth K. Hubbard.

STABILITY. - Tests show that standard lubricating-oil solutions of this compound with concentrations of copper up to 500 ppm are stable for several weeks when prepared by the directions given below.

COMPATIBILITY. - Lubricating-oil solutions of this compound have been found to be compatible with lubricating-oil solutions of the other compounds in this series. Blends of several different compounds have been prepared by the procedures given in the provisional certificates for the other compounds. (Tests have not been carried out to insure compatibility with the various additives that may be in the oils to be analyzed.)

DIRECTIONS FOR PREPARING LUBRICATING-OIL SOLUTIONS OF COPPER CYCLOHEXANEBUTYRATE

Transfer approximately 0.5 g of this compound from the bottle to a small beaker and dry over phosphorus pentoxide in a desiccator for two hours. (Tightly close the bottle containing the remainder of the compound.) Quickly and accurately transfer 0.313 g of this dried salt to a weighed 200-ml flask. (This weight of salt is equivalent to 50 mg of copper.) Add 2 ml of xylene and 4 ml of 2-ethylhexylamine and heat the flask on a hot plate, with swirling and without charring, until a clear solution forms. Add to the hot solution 2 ml of 2-ethylhexanoic acid and 80 to 90 ml of lubricating oil and gently shake the flask to mix the contents. Allow the flask to cool to room temperature and add enough lubricating oil to bring the total weight of the contents of the flask to 100 ± 0.5 g. Stopper the flask and shake gently to insure a homogeneous solution. The concentration of copper in this solution is 500 ppm.



MERRILL B. WALLENSTEIN, Chief
Division of Chemistry II

October 31, 1960
Washington, D. C.

USCOMM-NBS-DC