




Durability and Reliability of Materials and Components for Solid-Oxide Fuel Cells (SOFC)






ORNL is participating in the Solid State Energy Conversion Alliance (SECA) Core Technology Program to support the SECA industrial teams in the identification of the mechanisms responsible for the failure of SOFC materials and components. ORNL is also formulating models to predict the reliability and durability of SOFC materials and components. The implementation of such models, which account for the stochastic nature of the mechanical properties of these materials, will lead to the development of more reliable and durable SOFCs

ORNL has characterized SOFC materials (e.g., Ni-based materials for anodes, YSZ electrolytes) to determine the effect of microstructure and geometry on their physical and mechanical properties

Fracture Toughness of Ni-Based Electrodes



Strength of Ni-Based Electrodes



- The porosity of NiO-YSZ samples increases after reduction
- The biaxial strength and fracture toughness of NiO-YSZ and Ni-YSZ decrease with increasing porosity
- The biaxial strength of NiO-YSZ decreases after reduction into Ni-YSZ
- Ni-YSZ materials are tougher than their NiO-YSZ precursors

ORNL 2004-02180502



Funded by the U.S. Department of Energy, National Energy Technology Laboratory, and the Fossil Energy Solid State Energy Conversion Alliance (SECA) Program

OAK RIDGE NATIONAL LABORATORY

