§ 39.13 [Amended]

2. The Federal Aviation Administration (FAA) amends § 39.13 by adding the following new airworthiness directive (AD):

Directorate Identifier 2007-NM-088-AD.

Boeing: Docket No. FAA–2007–28380;

Comments Due Date

(a) The FAA must receive comments on this AD action by August 17, 2007.

Affected ADs

(b) None.

TABLE 1.—APPLICABILITY OF THIS AD

Applicability

(c) This AD applies to the Boeing airplane models, certificated in any category, identified in the service bulletins specified Table 1 of this AD.

Boeing model—	As identified in Boeing Special Attention Service Bulletin-
747–400, 747–400D, and 747–400F series airplanes 757–200 series airplanes 767–200, –300, and –300F series airplanes	757–26–0051, dated July 28, 2006.

Unsafe Condition

(d) This AD results from a report indicating that failure of a time delay relay on a Boeing Model 777 ELMS (electrical load management system) panel led to testing of other time delay relays at Boeing and at the supplier. Similar relays are used in the cargo fire suppression system. We are issuing this AD to ensure there is sufficient fire suppressant to control a cargo fire if the airplane is more than the relay delay time from a suitable airport, which could result in uncontrollable fire in the cargo compartment.

Compliance

(e) You are responsible for having the actions required by this AD performed within the compliance times specified, unless the actions have already been done.

Service Bulletin Reference

(f) The term "service bulletin," as used in this AD, means the Accomplishment Instructions of the following service bulletins, as applicable:

(1) For Model 747–400, 747–400D, and 747–400F series airplanes: Boeing Special Attention Service Bulletin 747–26–2281, dated July 24, 2006;

(2) For Model 757–200 series airplanes: Boeing Special Attention Service Bulletin 757–26–0051, dated July 28, 2006; and

(3) For Model 767–200, –300, and –300F series airplanes: Boeing Special Attention Service Bulletin 767–26–0131, dated July 24, 2006.

Inspection

(g) Within 24 months after the effective date of this AD: Do a general visual inspection of the part number (P/N) TDH6103–1204, -1804, and -6003 time delay relay, as applicable, in the Main Equipment Center to determine if the relay was manufactured during a certain date range, in accordance with the applicable service bulletin.

Replacement

(h) Within 30 days after finding a relay manufactured during the date range specified in the service bulletin, as required by paragraph (g) of this AD: Replace the relay with a relay that was not manufactured during the specified date range, or with a relay that has been tested by the supplier and found to be unaffected by thermal expansion, in accordance with the applicable service bulletin.

Parts Installation

(i) As of the effective date of this AD, no person may install a time delay relay, P/N TDH6103–1204, -1804, or -6003, on any airplane if the relay has a date code between 0000 and 0343 and does not have an additional date code with the letter "T."

Alternative Methods of Compliance (AMOCs)

(j)(1) The Manager, Seattle Aircraft Certification Office (ACO), FAA, has the authority to approve AMOCs for this AD, if requested in accordance with the procedures found in 14 CFR 39.19.

(2) To request a different method of compliance or a different compliance time for this AD, follow the procedures in 14 CFR 39.19. Before using any approved AMOC on any airplane to which the AMOC applies, notify your appropriate principal inspector (PI) in the FAA Flight Standards District Office (FSDO), or lacking a PI, your local FSDO.

Issued in Renton, Washington, on June 22, 2007.

Ali Bahrami,

Manager, Transport Airplane Directorate, Aircraft Certification Service. [FR Doc. E7–12836 Filed 7–2–07; 8:45 am]

BILLING CODE 4910-13-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2007-28385; Directorate Identifier 2006-NM-181-AD]

RIN 2120-AA64

Airworthiness Directives; Boeing Model 747–100, 747–100B, 747–100B SUD, 747–200B, 747–200C, 747–200F, 747–300, 747SR, and 747SP Series Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT). **ACTION:** Notice of proposed rulemaking (NPRM).

SUMMARY: The FAA proposes to adopt a new airworthiness directive (AD) for all Boeing Model 747-100, 747-100B, 747-100B SUD, 747-200B, 747-200C, 747-200F, 747-300, 747SR, and 747SP series airplanes. This proposed AD would require revising the FAA-approved maintenance program by incorporating new airworthiness limitations (AWLs) for fuel tank systems to satisfy Special Federal Aviation Regulation No. 88 requirements. This proposed AD would also require the initial inspection of certain repetitive AWL inspections to phase in those inspections, and repair if necessary. This proposed AD results from a design review of the fuel tank systems. We are proposing this AD to prevent the potential for ignition sources inside fuel tanks caused by latent failures, alterations, repairs, or maintenance actions. which, in combination with flammable fuel vapors, could result in a fuel tank explosion and consequent loss of the airplane.

DATES: We must receive comments on this proposed AD by August 17, 2007. **ADDRESSES:** Use one of the following addresses to submit comments on this proposed AD.

• DOT Docket Web site: Go to http://dms.dot.gov and follow the instructions for sending your comments electronically.

• Government-wide rulemaking Web site: Go to http://www.regulations.gov and follow the instructions for sending your comments electronically.

• *Mail:* U.S. Department of Transportation, Docket Operations, M– 30, West Building Ground Floor, Room W12–140, 1200 New Jersey Avenue SE., Washington, DC 20590.

• Fax: (202) 493-2251.

• *Hand Delivery:* Room W12–140 on the ground floor of the West Building, 1200 New Jersey Avenue SE., Washington, DC, between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays.

Contact Boeing Commercial Airplanes, P.O. Box 3707, Seattle, Washington 98124–2207, for the service information identified in this proposed AD.

FOR FURTHER INFORMATION CONTACT:

Kathrine Rask, Aerospace Engineer, Propulsion Branch, ANM–140S, FAA, Seattle Aircraft Certification Office, 1601 Lind Ave, SW., Renton, Washington 98057–3356; telephone (425) 917–6505; fax (425) 917–6590.

SUPPLEMENTARY INFORMATION:

Comments Invited

We invite you to submit any relevant written data, views, or arguments regarding this proposed AD. Send your comments to an address listed in the **ADDRESSES** section. Include the docket number "FAA–2007–28385; Directorate Identifier 2006–NM–181–AD" at the beginning of your comments. We specifically invite comments on the overall regulatory, economic, environmental, and energy aspects of the proposed AD. We will consider all comments received by the closing date and may amend the proposed AD in light of those comments.

We will post all comments we receive, without change, to http:// dms.dot.gov, including any personal information you provide. We will also post a report summarizing each substantive verbal contact with FAA personnel concerning this proposed AD. Using the search function of that Web site, anyone can find and read the comments in any of our dockets, including the name of the individual who sent the comment (or signed the comment on behalf of an association, business, labor union, etc.). You may review DOT's complete Privacy Act Statement in the Federal Register published on April 11, 2000 (65 FR 19477–78), or you may visit http:// dms.dot.gov.

Examining the Docket

You may examine the AD docket on the Internet at *http://dms.dot.gov*, or in person at the Docket Operations office between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The Docket Operations office (telephone (800) 647–5527) is located on the ground floor of the West Building at the DOT street address stated in the **ADDRESSES** section. Comments will be available in the AD docket shortly after the Docket Management System receives them.

Discussion

The FAA has examined the underlying safety issues involved in fuel tank explosions on several large transport airplanes, including the adequacy of existing regulations, the service history of airplanes subject to those regulations, and existing maintenance practices for fuel tank systems. As a result of those findings, we issued a regulation titled "Transport Airplane Fuel Tank System Design Review, Flammability Reduction and Maintenance and Inspection Requirements" (67 FR 23086, May 7, 2001). In addition to new airworthiness standards for transport airplanes and new maintenance requirements, this rule included Special Federal Aviation Regulation No. 88 ("SFAR 88," Amendment 21-78, and subsequent Amendments 21-82 and 21-83).

Among other actions, SFAR 88 requires certain type design (i.e., type certificate (TC) and supplemental type certificate (STC)) holders to substantiate that their fuel tank systems can prevent ignition sources in the fuel tanks. This requirement applies to type design holders for large turbine-powered transport airplanes and for subsequent modifications to those airplanes. It requires them to perform design reviews and to develop design changes and maintenance procedures if their designs do not meet the new fuel tank safety standards. As explained in the preamble to the rule, we intended to adopt airworthiness directives to mandate any changes found necessary to address unsafe conditions identified as a result of these reviews.

In evaluating these design reviews, we have established four criteria intended to define the unsafe conditions associated with fuel tank systems that require corrective actions. The percentage of operating time during which fuel tanks are exposed to flammable conditions is one of these criteria. The other three criteria address the failure types under evaluation: single failures, single failures in combination with another latent condition(s), and in-service failure experience. For all four criteria, the evaluations included consideration of previous actions taken that may mitigate the need for further action.

We have determined that the actions identified in this proposed AD are necessary to reduce the potential of ignition sources inside fuel tanks, which, in combination with flammable fuel vapors, could result in a fuel tank explosion and consequent loss of the airplane.

Relevant Service Information

We have reviewed Boeing 747–100/ 200/300/SP Airworthiness Limitations (AWLs) and Certification Maintenance Requirements (CMRs), D6-13747-CMR, Revision March 2006 (hereafter referred to as "Revision March 2006 of Document D6-13747-CMR"). (For the purposes of Revision March 2006 of Document D6–13747-CMR, the Model 747SR series airplane is basically a Model 747-100 series airplane with certain modifications to improve fatigue life.) Section D of Revision March 2006 of Document D6-13747-CMR describes new AWLs for fuel tank systems. The new AWLs include:

• AWL inspections, which are periodic inspections of certain features for latent failures that could contribute to an ignition source; and

• Critical design configuration control limitations (CDCCLs), which are limitation requirements to preserve a critical ignition source prevention feature of the fuel tank system design that is necessary to prevent the occurrence of an unsafe condition. The purpose of a CDCCL is to provide instruction to retain the critical ignition source prevention feature during configuration change that may be caused by alterations, repairs, or maintenance actions. A CDCCL is not a periodic inspection.

Accomplishing the actions specified in the service information is intended to adequately address the unsafe condition.

FAA's Determination and Requirements of the Proposed AD

We have evaluated all pertinent information and identified an unsafe condition that is likely to exist or develop on other airplanes of this same type design. For this reason, we are proposing this AD, which would require revising the FAA-approved maintenance program by incorporating the information in Section D of Revision March 2006 of Document D6–13747– CMR. This proposed AD would also require the initial inspection of certain repetitive AWL inspections to phase in those inspections, and repair if necessary.

Explanation of Compliance Time

In most ADs, we adopt a compliance time allowing a specified amount of time after the AD's effective date. In this case, however, the FAA has already issued regulations that require operators to revise their maintenance/inspection programs to address fuel tank safety issues. The compliance date for these regulations is December 16, 2008. To provide for efficient and coordinated implementation of these regulations and this proposed AD, we are using this same compliance date in this proposed AD, instead of the 18-month compliance time recommended by Boeing.

Rework Required When Implementing AWLs Into an Existing Fleet

The maintenance program revision for the fuel tank systems specified in paragraph (g) of this proposed AD, which involves incorporating the information specified in Revision March 2006 of Document D6-13747-CMR, would affect how operators maintain their airplanes. After doing that maintenance program revision, operators would need to do any maintenance on the fuel tank system as specified in the CDCCLs. Maintenance done before the maintenance program revision specified in paragraph (g) would not need to be redone in order to comply with paragraph (g). For example, the AWL that requires fuel pumps to be repaired and overhauled per an FAA-approved component maintenance manual (CMM) applies to fuel pumps repaired after the maintenance programs are revised; spare or on-wing fuel pumps do not need to be reworked. For AWLs that require repetitive inspections, the initial inspection interval (threshold) starts from the date the maintenance program revision specified in paragraph (g) is done, except as provided by paragraph (h) of this proposed AD. This proposed AD would require only the maintenance program revision specified in paragraph (g), and initial inspections specified in paragraph (h). No other fleet-wide inspections need to be done.

Changes to Fuel Tank System AWLs

Paragraph (g) of this proposed AD would require revising the FAAapproved maintenance program by incorporating certain information specified in Section D of Revision March 2006 of Document D6–13747– CMR. Paragraph (g) allows accomplishing the maintenance program revision in accordance with later revisions of Document D6-13747-CMR as an acceptable method of compliance if they are approved by the Manager, Seattle Aircraft Certification Office (ACO), FAA. Paragraph (h) allows accomplishing the initial inspections and repair in accordance with later revisions of Document D6-13747-CMR as an acceptable method of compliance if they are approved by the Manager, Seattle ACO. In addition, Section D specifies that any deviations from the published AWL instructions, including AWL intervals, must be approved by the Manager, Seattle ACO. Therefore, after the maintenance program revision, any further revision to an AWL or AWL interval should be done as an AWL change, not as an alternative method of compliance (AMOC). For U.S.-registered airplanes, operators must make requests through an appropriate FAA Principal Maintenance Inspector (PMI) or Principal Avionics Inspector (PAI) for approval by the Manager, Seattle ACO. A non-U.S. operator should coordinate changes with its governing regulatory agency.

Exceptional Short-Term Extensions

Section D of Revision March 2006 of Document D6-13747-CMR has provisions for an exceptional short-term extension of 30 days. An exceptional short-term extension is an increase in an AWL interval that may be needed to cover an uncontrollable or unexpected situation. For U.S.-registered airplanes, the FAA PMI or PAI must concur with any exceptional short-term extension before it is used, unless the operator has identified another appropriate procedure with the local regulatory authority. The FAA PMI or PAI may grant the exceptional short-term extensions described in Section D without consultation with the Manager, Seattle ACO. A non-U.S. operator should coordinate changes with its governing regulatory agency. As explained in Revision March 2006 of Document D6-13747-CMR, exceptional short-term extensions must not be used for fleet AWL extensions. An exceptional short-term extension should not be confused with an operator's short-term escalation authorization approved in accordance with the Operations Specifications or the operator's reliability program.

Ensuring Compliance With Fuel Tank System AWLs

Boeing has revised applicable maintenance manuals and task cards to address AWLs and to include notes about CDCCLs. Operators that do not use Boeing's revision service should revise their maintenance manuals and task cards to highlight actions tied to CDCCLs to ensure that maintenance personnel are complying with the CDCCLs. Appendix 1 of this proposed AD contains a list of Air Transport Association (ATA) sections for the revised maintenance manuals. Operators might wish to use the appendix as an aid to implement the AWLs.

Recording Compliance With Fuel Tank System AWLs

The applicable operating rules of the Federal Aviation Regulations (14 CFR parts 91, 121, 125, and 129) require operators to maintain records with the identification of the current inspection status of an airplane. Some of the AWLs contained in Section D of Revision March 2006 of Document D6-13747-CMR are inspections for which the applicable sections of the operating rules apply. Other AWLs are CDCCLs, which are tied to conditional maintenance actions. An entry into an operator's existing maintenance record system for corrective action is sufficient for recording compliance with CDCCLs, as long as the applicable maintenance manual and task cards identify actions that are CDCCLs.

Changes to CMMs Cited in Fuel Tank System AWLs

Some of the AWLs in Section D of Revision March 2006 of Document D6-13747-CMR refer to specific revision levels of the CMMs as additional sources of service information for doing the AWLs. Boeing is referring to the CMMs by revision level in the applicable AWL for certain components rather than including information directly in Document D6-13747-CMR because of the volume of that information. As a result, the Manager, Seattle ACO, must approve the CMMs. Any later revision of those CMMs will be handled like a change to the AWL itself. Any use of parts (including the use of parts manufacturer approval (PMA) approved parts), methods, techniques, and practices not contained in the CMMs need to be approved by the Manager, Seattle ACO, or governing regulatory authority. For example, pump repair/overhaul manuals must be approved by the Manager, Seattle ACO.

Changes to AMMs Referenced in Fuel Tank System AWLs

In other AWLs in Section D of Revision March 2006 of Document D6-13747–CMR, the AWLs contain all the necessary data. The applicable section of the maintenance manual is usually included in the AWLs. Boeing intended this information to assist operators in maintaining the maintenance manuals. A maintenance manual change to these tasks may be made without approval by the Manager, Seattle ACO, through an appropriate FAA PMI or PAI, by the governing regulatory authority, or by using the operator's standard process for revising maintenance manuals. An acceptable change would have to maintain the information specified in

the AWL such as the pass/fail criteria or special test equipment.

Costs of Compliance

There are about 308 airplanes of the affected design in the worldwide fleet.

ESTIMATED COSTS

The following table provides the estimated costs, at an average labor rate of \$80 per hour, for U.S. operators to comply with this proposed AD.

Action	Work hours	Parts	Cost per airplane	Number of U.S registered airplanes	Fleet cost
Maintenance program revision		None	\$640	93	\$59,520
Inspections			640	93	59,520

Authority for This Rulemaking

Title 49 of the United States Code specifies the FAA's authority to issue rules on aviation safety. Subtitle I, Section 106, describes the authority of the FAA Administrator. Subtitle VII, Aviation Programs, describes in more detail the scope of the Agency's authority.

We are issuing this rulemaking under the authority described in Subtitle VII, Part A, Subpart III, Section 44701, "General requirements." Under that section, Congress charges the FAA with promoting safe flight of civil aircraft in air commerce by prescribing regulations for practices, methods, and procedures the Administrator finds necessary for safety in air commerce. This regulation is within the scope of that authority because it addresses an unsafe condition that is likely to exist or develop on products identified in this rulemaking action.

Regulatory Findings

We have determined that this proposed AD would not have federalism implications under Executive Order 13132. This proposed AD would not have a substantial direct effect on the States, on the relationship between the national Government and the States, or on the distribution of power and responsibilities among the various levels of government.

For the reasons discussed above, I certify that the proposed regulation:

1. Is not a "significant regulatory action" under Executive Order 12866;

2. Is not a "significant rule" under the DOT Regulatory Policies and Procedures (44 FR 11034, February 26, 1979); and

3. Will not have a significant economic impact, positive or negative, on a substantial number of small entities under the criteria of the Regulatory Flexibility Act.

We prepared a regulatory evaluation of the estimated costs to comply with this proposed AD and placed it in the AD docket. See the **ADDRESSES** section for a location to examine the regulatory evaluation.

List of Subjects in 14 CFR Part 39

Air transportation, Aircraft, Aviation safety, Safety.

The Proposed Amendment

Accordingly, under the authority delegated to me by the Administrator, the FAA proposes to amend 14 CFR part 39 as follows:

PART 39—AIRWORTHINESS DIRECTIVES

1. The authority citation for part 39 continues to read as follows:

Authority: 49 U.S.C. 106(g), 40113, 44701.

§39.13 [Amended]

2. The Federal Aviation Administration (FAA) amends § 39.13 by adding the following new airworthiness directive (AD):

Boeing: Docket No. FAA–2007–28385; Directorate Identifier 2006–NM–181–AD.

Comments Due Date

(a) The FAA must receive comments on this AD action by August 17, 2007.

Affected ADs

(b) None.

Applicability

(c) This AD applies to all Boeing Model 747–100, 747–100B, 747–100B SUD, 747– 200B, 747–200C, 747–200F, 747–300, 747SR, and 747SP series airplanes, certificated in any category.

Note 1: This AD requires revisions to certain operator maintenance documents to include new inspections and maintenance actions. Compliance with these limitations is required by 14 CFR 43.16 and 91.403(c). For airplanes that have been previously modified, altered, or repaired in the areas addressed by these limitations, the operator may not be able to accomplish the actions described in the revisions. In this situation, to comply with 14 CFR 43.16 and 91.403(c), the operator must request approval for revision to the airworthiness limitations in the Boeing 747-100/200/300/SP Airworthiness Limitations (AWLs) and **Certification Maintenance Requirements**

(CMRs), D6–13747–CMR, according to paragraph (g) or (i) of this AD, as applicable.

Unsafe Condition

(d) This AD results from a design review of the fuel tank systems. We are issuing this AD to prevent the potential for ignition sources inside fuel tanks caused by latent failures, alterations, repairs, or maintenance actions, which, in combination with flammable fuel vapors, could result in a fuel tank explosion and consequent loss of the airplane.

Compliance

(e) You are responsible for having the actions required by this AD performed within the compliance times specified, unless the actions have already been done.

Service Information Reference

(f) The term "Revision March 2006 of Document D6–13747–CMR" as used in this AD, means Boeing 747–100/200/300/SP AWLs and CMRs, D6–13747–CMR, Revision March 2006. (For the purposes of Revision March 2006 of Document D6–13747–CMR, the Model 747SR series airplane is basically a Model 747–100 series airplane with certain modifications to improve fatigue life.)

Maintenance Program Revision

(g) Before December 16, 2008, revise the FAA-approved maintenance program to incorporate the information in Section D of Revision March 2006 of Document D6–13747–CMR; except that the initial inspections required by paragraph (h) of this AD must be done at the applicable compliance time specified in that paragraph. Accomplishing the revision in accordance with a later revision of Document D6–13747–CMR is an acceptable method of compliance if the revision is approved by the Manager, Seattle Aircraft Certification Office (ACO), FAA.

Initial Inspections and Repair if Necessary

(h) Do the inspections specified in Table 1 of this AD and repair any discrepancy, in accordance with Section D, "AIRWORTHINESS LIMITATIONS— SYSTEMS," of Revision March 2006 of Document D6–13747–CMR. The repair must be done before further flight. Accomplishing the actions required by this paragraph in accordance with a later revision of Document D6–13747–CMR is an acceptable method of compliance if the revision is approved by the Manager, Seattle ACO. **Note 2:** For the purposes of this AD, a detailed inspection is: "An intensive examination of a specific item, installation, or assembly to detect damage, failure, or irregularity. Available lighting is normally supplemented with a direct source of good lighting at an intensity deemed appropriate.

Inspection aids such as mirror, magnifying lenses, etc., may be necessary. Surface cleaning and elaborate procedures may be required."

Note 3: For the purposes of this AD, a special detailed inspection is: "An intensive

examination of a specific item, installation, or assembly to detect damage, failure, or irregularity. The examination is likely to make extensive use of specialized inspection techniques and/or equipment. Intricate cleaning and substantial access or disassembly procedure may be required."

TABLE 1.—INITIAL INSPECTIONS

AWL No.	Description	Compliance time (whichever occurs later)			
		Threshold	Grace period		
28–AWL–01	A detailed inspection of external wires over the center fuel tank for damaged clamps, wire chafing, and wire bun- dles in contact with the surface of the center fuel tank.	Before the accumulation of 36,000 total flight cycles, or within 144 months since the date of issuance of the original standard airworthiness certifi- cate or the date of issuance of the original export certificate of airworthi- ness, whichever occurs first.	Within 72 months after the effective date of this AD.		
28–AWL–03	A special detailed inspection of the lightning shield to ground termination on the out-of-tank fuel quantity indicating system to verify functional integrity.	Before the accumulation of 36,000 total flight cycles, or within 144 months since the date of issuance of the original standard airworthiness certifi- cate or the date of issuance of the original export certificate of airworthi- ness, whichever occurs first.	Within 24 months after the effective date of this AD.		
28-AWL-13	A special detailed inspection of the fault current bond of the fueling shutoff valve actuator of the center wing tank to verify electrical bond.		Within 60 months after the effective date of this AD.		

Alternative Methods of Compliance (AMOCs)

(i)(1) The Manager, Seattle ACO, has the

authority to approve AMOCs for this AD, if

requested in accordance with the procedures found in 14 CFR 39.19. (2) To request a different method of

(2) To request a different method of compliance or a different compliance time for this AD, follow the procedures in 14 CFR 39.19. Before using any approved AMOC on any airplane to which the AMOC applies, notify your appropriate principal inspector (PI) in the FAA Flight Standards District Office (FSDO), or lacking a PI, your local FSDO.

APPENDIX 1.—IMPLEMENTING FUEL TANK SYSTEM AIRWORTHINESS LIMITATIONS ON MODEL 747–100, 747–100B, 747– 100B SUD, 747–200B, 747–200C, 747–200F, 747–300, 747SR, and 747SP Series Airplanes

AWL No.	ALI/CDCCL	ATA section or CMM document	Task title
28–AWL–01	ALI	AMM 28–11–00/601	External Wires Over the Center Tank Inspection.
28-AWL-02	CDCCL	SWPM 20-10-11	Wiring Assembly and Installation Configuration.
28-AWL-03	ALI	AMM 05–55–54/601.	
28-AWL-04	CDCCL	SWPM 20–10–15	Assembly of Shield Ground Wires.
28–AWL–05	CDCCL	AMM 28–22–07/401	Install the Bulkhead Fitting for the Engine Fuel Feed Tube.
28-AWL-06	CDCCL	AMM 29-11-22/401	Install the Heat Exchanger.
28–AWL–07	CDCCL	CMM 28–22–07, Revision 1; CMM 28–31–03, Revision 3; CMM 28–22–06, Revision 6; CMM 28– 31–05, Revision 1; CMM 28–20–02, Revision 4 or Revision 9; or subsequent revisions.	
28–AWL–08	CDCCL	AMM 28–22–03/401	Install Boost Pump Housing.
		AMM 28–31–01/401	Jettison Pump Motor/Impeller Unit Installation.
28-AWL-09	ALI	AMM 28–31–00/501	Operational Test—Fault Current Detector.
28-AWL-10	CDCCL.		
28–AWL–11	CDCCL	SWPM 20–10–11	Wiring Assembly and Installation Configuration.
28–AWL–12	CDCCL	AMM 28–21–02/401	Install the Refuel Valve Control Unit.
		AMM 28–21–13/401	Install Center Wing Tank Refuel Valve Unit.
28–AWL–13	ALI	AMM 28–21–13/601	Center Wing Tank Refuel Valve—Fault Current Bond Inspection.
28–AWL–14	CDCCL	AMM 28–11–02/401	Install the Reserve and Main Tank Access Door.
		AMM 28–11–03/401	Install the Surge Tank Access Door.

APPENDIX 1.—IMPLEMENTING FUEL TANK SYSTEM AIRWORTHINESS LIMITATIONS ON MODEL 747–100, 747–100B, 747– 100B SUD, 747–200B, 747–200C, 747–200F, 747–300, 747SR, AND 747SP SERIES AIRPLANES—Continued

AWL No.	ALI/CDCCL	ATA section or CMM document	Task title
28-AWL-15	CDCCL	CMM 28–40–10, Revision 13; CMM 28–40–12, Re- vision 9; CMM 28–40–16, Revision 1; CMM 28– 40–14, Revision 8; CMM 28–40–15, Revision 0; or subsequent revisions.	
28-AWL-16	CDCCL	SWPM 20–14–12	Repair of Fuel Quantity Indicator System (FQIS) Wire Harness.
		AMM 28–41–09/401	Replace the Fuel Tank Wire Bundle.
28-AWL-17	CDCCL	CMM 28–31–22, Revision 4; or subsequent revisions.	
28–AWL–18 28–AWL–19		AMM 28–22–00/101	Engine Fuel Feed System—Trouble Shooting.

Issued in Renton, Washington, on June 22, 2007.

Ali Bahrami,

Manager, Transport Airplane Directorate, Aircraft Certification Service.

[FR Doc. E7–12815 Filed 7–2–07; 8:45 am] BILLING CODE 4910–13–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 39

[Docket No. FAA-2007-28386; Directorate Identifier 2006-NM-162-AD]

RIN 2120-AA64

Airworthiness Directives; Boeing Model 747–400, –400D, and –400F Series Airplanes

AGENCY: Federal Aviation Administration (FAA), Department of Transportation (DOT). **ACTION:** Notice of proposed rulemaking (NPRM).

SUMMARY: The FAA proposes to adopt a new airworthiness directive (AD) for certain Boeing Model 747-400, -400D, and –400F series airplanes. This proposed AD would require revising the FAA-approved maintenance program by incorporating new airworthiness limitations (AWLs) for fuel tank systems to satisfy Special Federal Aviation Regulation No. 88 requirements. This proposed AD would also require the initial inspection of certain repetitive AWL inspections to phase in those inspections, and repair if necessary. This proposed AD results from a design review of the fuel tank systems. We are proposing this AD to prevent the potential for ignition sources inside fuel tanks caused by latent failures, alterations, repairs, or maintenance actions, which, in combination with flammable fuel vapors, could result in a

fuel tank explosion and consequent loss of the airplane.

DATES: We must receive comments on this proposed AD by August 17, 2007. **ADDRESSES:** Use one of the following addresses to submit comments on this proposed AD.

• DOT Docket Web site: Go to http://dms.dot.gov and follow the instructions for sending your comments electronically.

• Government-wide rulemaking Web site: Go to http://www.regulations.gov and follow the instructions for sending your comments electronically.

• *Mail*: U.S. Department of Transportation, Docket Operations, M– 30, West Building Ground Floor, Room W12–140, 1200 New Jersey Avenue, SE., Washington, DC 20590.

• Fax: (202) 493-2251.

• *Hand Delivery:* Room W12–140 on the ground floor of the West Building, 1200 New Jersey Avenue, SE., Washington, DC, between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays.

Contact Boeing Commercial Airplanes, P.O. Box 3707, Seattle, Washington 98124–2207, for the service information identified in this proposed AD.

FOR FURTHER INFORMATION CONTACT:

Kathrine Rask, Aerospace Engineer, Propulsion Branch, ANM–140S, FAA, Seattle Aircraft Certification Office, 1601 Lind Ave, SW., Renton, Washington 98057–3356; telephone (425) 917–6505; fax (425) 917–6590. SUPPLEMENTARY INFORMATION:

Comments Invited

We invite you to submit any relevant written data, views, or arguments regarding this proposed AD. Send your comments to an address listed in the **ADDRESSES** section. Include the docket number "FAA–2007–28386; Directorate Identifier 2006–NM–162–AD" at the beginning of your comments. We specifically invite comments on the overall regulatory, economic, environmental, and energy aspects of the proposed AD. We will consider all comments received by the closing date and may amend the proposed AD in light of those comments.

We will post all comments we receive, without change, to http:// dms.dot.gov, including any personal information you provide. We will also post a report summarizing each substantive verbal contact with FAA personnel concerning this proposed AD. Using the search function of that Web site, anyone can find and read the comments in any of our dockets, including the name of the individual who sent the comment (or signed the comment on behalf of an association, business, labor union, etc.). You may review DOT's complete Privacy Act Statement in the Federal Register published on April 11, 2000 (65 FR 19477–78), or you may visit http:// dms.dot.gov.

Examining the Docket

You may examine the AD docket on the Internet at *http://dms.dot.gov*, or in person at the Docket Operations office between 9 a.m. and 5 p.m., Monday through Friday, except Federal holidays. The Docket Operations office (telephone (800) 647–5527) is located on the ground floor of the West Building at the DOT street address stated in the **ADDRESSES** section. Comments will be available in the AD docket shortly after the Docket Management System receives them.

Discussion

The FAA has examined the underlying safety issues involved in fuel tank explosions on several large transport airplanes, including the adequacy of existing regulations, the service history of airplanes subject to those regulations, and existing maintenance practices for fuel tank systems. As a result of those findings, we issued a regulation titled "Transport