landing weight limitations in the Approved Airplane Flight Manual or equivalent for operations under this part.

(b) No person may operate an airplane that is certificated under §135.169(b)(6) unless that person complies with the landing limitations prescribed in §§135.385 and 135.387 of this part. For purposes of this paragraph, §§135.385 and 135.387 are applicable to reciprocating and turbopropeller-powered small airplanes notwithstanding their stated applicability to turbine engine powered large transport category airplanes.

[44 FR 53731, Sept. 17, 1979]

## Subpart J—Maintenance, Preventive Maintenance, and Alterations

### §135.411 Applicability.

- (a) This subpart prescribes rules in addition to those in other parts of this chapter for the maintenance, preventive maintenance, and alterations for each certificate holder as follows:
- (1) Aircraft that are type certificated for a passenger seating configuration, excluding any pilot seat, of nine seats or less, shall be maintained under parts 91 and 43 of this chapter and §§ 135.415, 135.417, 135.421 and 135.422. An approved aircraft inspection program may be used under § 135.419.
- (2) Aircraft that are type certificated for a passenger seating configuration, excluding any pilot seat, of ten seats or more, shall be maintained under a maintenance program in §§ 135.415, 135.417, 135.423 through 135.443.
- (b) A certificate holder who is not otherwise required, may elect to maintain its aircraft under paragraph (a)(2) of this section.
- (c) Single engine aircraft used in passenger-carrying IFR operations shall also be maintained in accordance with §135.421 (c), (d), and (e).
- (d) A certificate holder who elects to operate in accordance with \$135.364 must maintain its aircraft under paragraph (a)(2) of this section and the ad-

ditional requirements of Appendix G of this part.

[Doc. No. 16097, 43 FR 46783, Oct. 10, 1978, as amended by Amdt. 135–70, 62 FR 42374, Aug. 6, 1997; Amdt. 135–78, 65 FR 60556, Oct. 11, 2000; Amdt. 135–92, 68 FR 69308, Dec. 12, 2003; Amdt. 135–81, 70 FR 5533, Feb. 2, 2005; Amdt. 135–108, 72 FR 1885, Jan. 16, 2007; 72 FR 53114, Sept. 18, 2007]

# § 135.413 Responsibility for airworthiness.

- (a) Each certificate holder is primarily responsible for the airworthiness of its aircraft, including airframes, aircraft engines, propellers, rotors, appliances, and parts, and shall have its aircraft maintained under this chapter, and shall have defects repaired between required maintenance under part 43 of this chapter.
- (b) Each certificate holder who maintains its aircraft under §135.411(a)(2) shall—
- (1) Perform the maintenance, preventive maintenance, and alteration of its aircraft, including airframe, aircraft engines, propellers, rotors, appliances, emergency equipment and parts, under its manual and this chapter: or
- (2) Make arrangements with another person for the performance of maintenance, preventive maintenance, or alteration. However, the certificate holder shall ensure that any maintenance, preventive maintenance, or alteration that is performed by another person is performed under the certificate holder's manual and this chapter.

# § 135.415 Service difficulty reports.

- (a) Each certificate holder shall report the occurrence or detection of each failure, malfunction, or defect in an aircraft concerning—
- (1) Fires during flight and whether the related fire-warning system functioned properly;
- (2) Fires during flight not protected by related fire-warning system;
- (3) False fire-warning during flight;
- (4) An exhaust system that causes damage during flight to the engine, adjacent structure, equipment, or components:
- (5) An aircraft component that causes accumulation or circulation of smoke, vapor, or toxic or noxious

#### § 135.415

fumes in the crew compartment or passenger cabin during flight;

- (6) Engine shutdown during flight because of flameout;
- (7) Engine shutdown during flight when external damage to the engine or aircraft structure occurs;
- (8) Engine shutdown during flight due to foreign object ingestion or icing;
- (9) Shutdown of more than one engine during flight:
- (10) A propeller feathering system or ability of the system to control overspeed during flight;
- (11) A fuel or fuel-dumping system that affects fuel flow or causes hazardous leakage during flight:
- (12) An unwanted landing gear extension or retraction or opening or closing of landing gear doors during flight;
- (13) Brake system components that result in loss of brake actuating force when the aircraft is in motion on the ground:
- (14) Aircraft structure that requires major repair;
- (15) Cracks, permanent deformation, or corrosion of aircraft structures, if more than the maximum acceptable to the manufacturer or the FAA; and
- (16) Aircraft components or systems that result in taking emergency actions during flight (except action to shut-down an engine).
- (b) For the purpose of this section, during flight means the period from the moment the aircraft leaves the surface of the earth on takeoff until it touches down on landing.
- (c) In addition to the reports required by paragraph (a) of this section, each certificate holder shall report any other failure, malfunction, or defect in an aircraft that occurs or is detected at any time if, in its opinion, the failure, malfunction, or defect has endangered or may endanger the safe operation of the aircraft
- (d) Each certificate holder shall submit each report required by this section, covering each 24-hour period beginning at 0900 local time of each day and ending at 0900 local time on the next day, to the FAA offices in Oklahoma City, Oklahoma. Each report of occurrences during a 24-hour period shall be submitted to the collection point within the next 96 hours. However, a report due on Saturday or Sun-

day may be submitted on the following Monday, and a report due on a holiday may be submitted on the next work-

- (e) The certificate holder shall transmit the reports required by this section on a form and in a manner prescribed by the Administrator, and shall include as much of the following as is available:
- (1) The type and identification number of the aircraft.
  - (2) The name of the operator.
  - (3) The date.
- (4) The nature of the failure, malfunction, or defect.
- (5) Identification of the part and system involved, including available information pertaining to type designation of the major component and time since last overhaul, if known.
- (6) Apparent cause of the failure, malfunction or defect (e.g., wear, crack, design deficiency, or personnel error).
- (7) Other pertinent information necessary for more complete identification, determination of seriousness, or corrective action.
- (f) A certificate holder that is also the holder of a type certificate (including a supplemental type certificate), a Parts Manufacturer Approval, or a Technical Standard Order Authorization, or that is the licensee of a type certificate need not report a failure, malfunction, or defect under this section if the failure, malfunction, or defect has been reported by it under §21.3 or §37.17 of this chapter or under the accident reporting provisions of part 830 of the regulations of the National Transportation Safety Board.
- (g) No person may withhold a report required by this section even though all information required by this section is not available.
- (h) When the certificate holder gets additional information, including information from the manufacturer or other agency, concerning a report required by this section, it shall expeditiously submit it as a supplement to the first report and reference the date and place of submission of the first report.

[Doc. No. 16097, 43 FR 46783, Oct. 10, 1978, as amended by Amdt. 135–102, 70 FR 76979, Dec. 29, 2005]