

APPENDIX B TO PART 135—AIRPLANE FLIGHT RECORDER SPECIFICATIONS

Parameters	Range	Installed system <sup>1</sup> minimum accuracy (to recovered data)	Sampling interval (per second)	Resolution <sup>4</sup> read out
Relative time (from recorded on prior to takeoff).	25 hr minimum .....	±0.125% per hour .....	1 .....	1 sec.
Indicated airspeed .....	V <sub>SO</sub> to V <sub>D</sub> (KIAS) .....	±5% or ±10 kts., whichever is greater. Resolution 2 kts. below 175 KIAS.	1 .....	1% <sup>3</sup> .
Altitude .....	− 1,000 ft. to max cert. alt. of A/C.	±100 to ±700 ft. (see Table 1, TSO C51-a).	1 .....	25 to 150
Magnetic heading .....	360° .....	±5° .....	1 .....	1°
Vertical acceleration .....	− 3g to +6g .....	±0.2g in addition to ±0.3g maximum datum.	4 (or 1 per second where peaks, ref. to 1g are re-corded).	0.03g.
Longitudinal acceleration .....	±1.0g .....	±1.5% max. range excluding datum error of ±5%.	2 .....	0.01g.
Pitch attitude .....	100% of usable .....	±2° .....	1 .....	0.8°
Roll attitude .....	±60° or 100% of usable range, whichever is greater.	±2° .....	1 .....	0.8°
Stabilizer trim position .....	Full range .....	±3% unless higher uniquely required.	1 .....	1% <sup>3</sup> .
Or Pitch control position .....	Full range .....	±3% unless higher uniquely required.	1 .....	1% <sup>3</sup> .
<i>Engine Power, Each Engine</i>				
Fan or N <sub>1</sub> speed or EPR or cockpit indications used for aircraft certification.	Maximum range .....	±5% .....	1 .....	1% <sup>3</sup> .
Or Prop. speed and torque (sample once/sec as close together as practicable).	.....	.....	1 (prop speed), 1 (torque).	
Altitude rate <sup>2</sup> (need depends on altitude resolution).	±8,000 fpm .....	±10%. Resolution 250 fpm below 12,000 ft. indicated.	1 .....	250 fpm Below 12,000
Angle of attack <sup>2</sup> (need depends on altitude resolution).	− 20° to 40° or of usable range.	±2° .....	1 .....	0.8% <sup>3</sup>
Radio transmitter keying (discrete).	On/off .....	.....	1.	
TE flaps (discrete or analog) ..	Each discrete position (U, D, T/O, AAP). Or Analog 0–100% range ....	.....	1.	
LE flaps (discrete or analog) ..	Each discrete position (U, D, T/O, AAP). Or Analog 0–100% range ....	±3° .....	1 .....	1% <sup>3</sup>
Thrust reverser, each engine (Discrete).	Stowed or full reverse ....	.....	1.	
Spoiler/speedbrake (discrete)	Stowed or out .....	.....	1.	
Autopilot engaged (discrete) ..	Engaged or disengaged .....	.....	1.	

<sup>1</sup> When data sources are aircraft instruments (except altimeters) of acceptable quality to fly the aircraft the recording system excluding these sensors (but including all other characteristics of the recording system) shall contribute no more than half of the values in this column.

<sup>2</sup> If data from the altitude encoding altimeter (100 ft. resolution) is used, then either one of these parameters should also be recorded. If however, altitude is recorded at a minimum resolution of 25 feet, then these two parameters can be omitted.

<sup>3</sup> Per cent of full range.

<sup>4</sup> This column applies to aircraft manufacturing after October 11, 1991.

[Doc. No. 25530, 53 FR 26152, July 11, 1988; 53 FR 30906, Aug. 16, 1988, as amended by Amdt. 135-69, 62 FR 38397, July 17, 1997]

APPENDIX C TO PART 135—HELICOPTER FLIGHT RECORDER SPECIFICATIONS

Parameters	Range	Installed system <sup>1</sup> minimum accuracy (to recovered data)	Sampling interval (per second)	Resolution <sup>3</sup> read out
Relative time (from recorded on prior to takeoff).	25 hr minimum .....	±0.125% per hour .....	1 .....	1 sec.

Parameters	Range	Installed system <sup>1</sup> minimum accuracy (to recovered data)	Sampling interval (per second)	Resolution <sup>3</sup> read out
Indicated airspeed .....	V <sub>m</sub> in to V <sub>D</sub> (KIAS) (minimum airspeed signal attainable with installed pilot-static system).	±5% or ±10 kts., whichever is greater.	1 .....	1 kt.
Altitude .....	-1,000 ft. to 20,000 ft. pressure altitude.	±100 to ±700 ft. (see Table 1, TSO C51-a).	1 .....	25 to 150 ft.
Magnetic heading .....	360° .....	±5° .....	1 .....	1°.
Vertical acceleration .....	-3g to +6g .....	±0.2g in addition to ±0.3g maximum datum.	4 (or 1 per second where peaks, ref. to 1g are recorded).	0.05g.
Longitudinal acceleration .....	±1.0g .....	±1.5% max. range excluding datum error of ±5%.	2 .....	0.03g.
Pitch attitude .....	100% of usable range ....	±2° .....	1 .....	0.8°.
Roll attitude .....	±60° or 100% of usable range, whichever is greater.	±2° .....	1 .....	0.8°.
Altitude rate .....	±8,000 fpm .....	±10% Resolution 250 fpm below 12,000 ft. indicated.	1 .....	250 fpm below 12,000.
<i>Engine Power, Each Engine</i>				
Main rotor speed .....	Maximum range .....	±5% .....	1 .....	1% <sup>2</sup>
Free or power turbine .....	Maximum range .....	+5% .....	1 .....	1% <sup>2</sup>
Engine torque .....	Maximum range .....	±5% .....	1 .....	1% <sup>2</sup>
<i>Flight Control—Hydraulic Pressure</i>				
Primary (discrete) .....	High/low .....	.....	1.	
Secondary—if applicable (discrete).	High/low .....	.....	1.	
Radio transmitter keying (discrete).	On/off .....	.....	1.	
Autopilot engaged (discrete) ..	Engaged or disengaged .....	.....	1.	
SAS status—engaged (discrete).	Engaged/disengaged .....	.....	1.	
SAS fault status (discrete) ....	Fault/OK .....	.....	1.	
<i>Flight Controls</i>				
Collective .....	Full range .....	±3% .....	2 .....	1% <sup>2</sup>
Pedal position .....	Full range .....	±3% .....	2 .....	1% <sup>2</sup>
Lat. cyclic .....	Full range .....	±3% .....	2 .....	1% <sup>2</sup>
Long. cyclic .....	Full range .....	±3% .....	2 .....	1% <sup>2</sup>
Controllable stabilator position	Full range .....	±3% .....	2 .....	1% <sup>2</sup>

<sup>1</sup> When data sources are aircraft instruments (except altimeters) of acceptable quality to fly the aircraft the recording system excluding these sensors (but including all other characteristics of the recording system) shall contribute no more than half of the values in this column.

<sup>2</sup> Per cent of full range.

<sup>3</sup> This column applies to aircraft manufactured after October 11, 1991.

[Doc. No. 25530, 53 FR 26152, July 11, 1988; 53 FR 30906, Aug. 16, 1988, as amended by Amdt. 135-69, 62 FR 38397, July 17, 1997]

APPENDIX D TO PART 135—AIRPLANE FLIGHT RECORDER SPECIFICATION

Parameters	Range	Accuracy sensor input to DFDR readout	Sampling interval (per second)	resolution <sup>4</sup> read out
Time (GMT or Frame Counter) (range 0 to 4095, sampled 1 per frame).	24 Hrs .....	±0.125% Per Hour .....	0.25 (1 per 4 seconds).	1 sec.
Altitude .....	-1,000 ft to max certified altitude of aircraft.	±100 to ±700 ft (See Table 1, TSO-C51a).	1 .....	5' to 35' <sup>1</sup> .
Airspeed .....	50 KIAS to V <sub>so</sub> , and V <sub>so</sub> to 1.2 V <sub>D</sub> .	±5%, ±3% .....	1 .....	1kt
Heading .....	360° .....	±2° .....	1 .....	0.5°
Normal Acceleration (Vertical)	-3g to +6g .....	±1% of max range excluding datum error of ±5%.	8 .....	0.01g
Pitch Attitude .....	±75° .....	±2° .....	1 .....	0.5°
Roll Attitude .....	±180° .....	±2° .....	1 .....	0.5°.
Radio Transmitter Keying .....	On-Off (Discrete) .....	.....	1 .....	
Thrust/Power on Each Engine	Full range forward .....	±2% .....	1 (per engine) ...	0.2% <sup>2</sup> .