§ 121.645 Fuel supply: Turbine-engine powered airplanes, other than turbo propeller: Flag and supplemental operations.

- (a) Any flag operation within the 48 contiguous United States and the District of Columbia may use the fuel requirements of § 121.639.
- (b) For any certificate holder conducting flag or supplemental operations outside the 48 contiguous United States and the District of Columbia, unless authorized by the Administrator in the operations specifications, no person may release for flight or takeoff a turbine-engine powered airplane (other than a turbo-propeller powered airplane) unless, considering wind and other weather conditions expected, it has enough fuel—
- (1) To fly to and land at the airport to which it is released;
- (2) After that, to fly for a period of 10 percent of the total time required to fly from the airport of departure to, and land at, the airport to which it was released;
- (3) After that, to fly to and land at the most distant alternate airport specified in the flight release, if an alternate is required; and
- (4) After that, to fly for 30 minutes at holding speed at 1,500 feet above the alternate airport (or the destination airport if no alternate is required) under standard temperature conditions.
- (c) No person may release a turbineengine powered airplane (other than a turbo-propeller airplane) to an airport for which an alternate is not specified under §121.621(a)(2) or §121.623(b) unless it has enough fuel, considering wind and other weather conditions expected, to fly to that airport and thereafter to fly for at least two hours at normal cruising fuel consumption.
- (d) The Administrator may amend the operations specifications of a certificate holder conducting flag or supplemental operations to require more fuel than any of the minimums stated in paragraph (a) or (b) of this section if he finds that additional fuel is necessary on a particular route in the interest of safety.
- (e) For a supplemental operation within the 48 contiguous States and the District of Columbia with a turbine

engine powered airplane the fuel requirements of §121.643 apply.

[Doc. No. 6258, 29 FR 19222, Dec. 31, 1964, as amended by Amdt. 121–10, 30 FR 10025, Aug. 12, 1965; Amdt. 121–144, 43 FR 22649, May 25, 1978; Amdt. 121–253, 61 FR 2615, Jan. 26, 1996]

§ 121.646 En-route fuel supply: flag and supplemental operations.

- (a) No person may dispatch or release for flight a turbine-engine powered airplane with more than two engines for a flight more than 90 minutes (with all engines operating at cruise power) from an Adequate Airport unless the following fuel supply requirements are met:
- (1) The airplane has enough fuel to meet the requirements of §121.645(b);
- (2) The airplane has enough fuel to fly to the Adequate Airport—
- (i) Assuming a rapid decompression at the most critical point;
- (ii) Assuming a descent to a safe altitude in compliance with the oxygen supply requirements of §121.333; and
- (iii) Considering expected wind and other weather conditions.
- (3) The airplane has enough fuel to hold for 15 minutes at 1500 feet above field elevation and conduct a normal approach and landing.
- (b) No person may dispatch or release for flight an ETOPS flight unless, considering wind and other weather conditions expected, it has the fuel otherwise required by this part and enough fuel to satisfy each of the following requirements:
- (1) Fuel to fly to an ETOPS Alternate Airport.
- (i) Fuel to account for rapid decompression and engine failure. The airplane must carry the greater of the following amounts of fuel:
- (A) Fuel sufficient to fly to an ETOPS Alternate Airport assuming a rapid decompression at the most critical point followed by descent to a safe altitude in compliance with the oxygen supply requirements of §121.333 of this chapter;
- (B) Fuel sufficient to fly to an ETOPS Alternate Airport (at the one-engine-inoperative cruise speed) assuming a rapid decompression and a simultaneous engine failure at the most critical point followed by descent to a safe altitude in compliance with the