§ 173.201

conditions normally incident to transportation. The secondary container must be marked with a BIOHAZARD marking conforming to 29 CFR 1910.1030(g)(1)(i).

- (3) The secondary container must be placed inside an outer packaging with sufficient cushioning material to prevent movement between the secondary container and the outer packaging. An itemized list of the contents of the primary container and information concerning possible contamination with a Division 6.2 material, including its possible location on the product, must be placed between the secondary container and the outside packaging.
- (e) Training. Each person who offers or transports a diagnostic specimen or used health care product under the provisions of this section must know about the requirements of this section.

[67 FR 53240, Aug. 14, 2002]

EFFECTIVE DATE NOTE: At 67 FR 53140, Aug. 14, 2002, §173.199 was added, effective Oct. 1, 2002. At 67 FR 54967, Aug. 27, 2002, the effective date was corrected to Feb. 14, 2003.

§173.201 Non-bulk packagings for liquid hazardous materials in Packing Group I.

- (a) When §172.101 of this subchapter specifies that a liquid hazardous material be packaged under this section, only non-bulk packagings prescribed in this section may be used for its transportation. Each packaging must conform to the general packaging requirements of subpart B of part 173, to the requirements of part 178 of this subchapter at the Packing Group I performance level, and to the requirements of the special provisions of column 7 of the §172.101 table.
- (b) The following combination packagings are authorized:

Outer packagings:

Steel drum: 1A1 or 1A2 Aluminum drum: 1B1 or 1B2 Metal drum other than steel or aluminum: 1N1 or 1N2 Plywood drum: 1D Fiber drum: 1G Plastic drum: 1H1 or 1H2 Steel jerrican: 3A1 or 3A2 Plastic jerrican: 3H1 or 3B2

Steel box: 4A Aluminum box: 4B

Natural wood box: 4C1 or 4C2

Plywood box: 4D Reconstituted wood box: 4F Fiberboard box: 4G Expanded plastic box: 4H1 Solid plastic box: 4H2

Inner packagings: Glass or earthenware receptacles Plastic receptacles Metal receptacles Glass ampoules

(c) Except for transportation by passenger aircraft, the following single packagings are authorized:

Steel drum: 1A1 or 1A2 Aluminum drum: 1B1 or 1B2

Metal drum other than steel, or aluminum:

1N1 or 1N2

Plastic drum: 1H1 or 1H2 Steel jerrican: 3A1 or 3A2 Plastic jerrican: 3H1 or 3H2 Aluminum jerrican: 3B1 or 3B2

Plastic receptacle in steel, aluminum, fiber or plastic drum: 6HA1, 6HB1, 6HG1, 6HH1

Plastic receptacle in steel, aluminum, wooden, plywood or fiberboard box: 6HA2, 6HB2, 6HC, 6HD2 or 6HG2

Glass, porcelain or stoneware in steel, aluminum or fiber drum: 6PA1, 6PB1 or 6PG1 Glass, porcelain or stoneware in steel, aluminum, wooden or fiberboard box: 6PA2, 6PB2, 6PC or 6PG2

Glass, porcelain or stoneware in solid or expanded plastic packaging: 6PH1 or 6PH2 Cylinders, specification, as prescribed for any compressed gas, except for Specifications 8 and 3HT

[Amdt. 173–224, 55 FR 52634, Dec. 21, 1990, as amended by Amdt. 173–241, 59 FR 67518, Dec. 29, 1994; Amdt. 173–261, 62 FR 24734, May 6, 1997]

§ 173.202 Non-bulk packagings for liquid hazardous materials in Packing Group II.

- (a) When \$172.101 of this subchapter specifies that a liquid hazardous material be packaged under this section, only non-bulk packagings prescribed in this section may be used for its transportation. Each packaging must conform to the general packaging requirements of subpart B of part 173, to the requirements of part 178 of this subchapter at the Packing Group I or II performance level (unless otherwise excepted), and to the particular requirements of the special provisions of column 7 of the \$172.101 table.
- (b) The following combination packagings are authorized:

Outer packagings: