

**§ 108.499 Fire axes.**

Each unit must have at least two fire axes.

**Subpart E—Lifesaving Equipment**

SOURCE: CGD 84-069, 61 FR 25291, May 20, 1996, unless otherwise noted.

**§ 108.500 General.**

(a) Each unit, other than a drillship, must meet the requirements in this subpart.

(b) Each drillship must meet the lifesaving system requirements in subchapter W of this chapter for a tank vessel certificated to carry cargoes that have a flash point less than 60° C as determined under ASTM D 93 (incorporated by reference, see § 108.101).

(c) The OCMI may require a unit to carry specialized or additional lifesaving equipment other than as required by this part, if the OCMI determines the conditions of the unit's service present uniquely hazardous circumstances which are not adequately addressed by existing requirements.

[CGD 84-069, 61 FR 25291, May 20, 1996, as amended at 63 FR 52814, Oct. 1, 1998; USCG 1999-5151, 64 FR 67182, Dec. 1, 1999]

**§ 108.503 Relationship to international standards.**

For the purposes of this part, any unit carrying a valid IMO MODU Safety Certificate, including a listing of lifesaving equipment as required by the 1989 IMO MODU Code, is considered to have met the requirements of this subpart if, in addition to the requirements of the 1989 IMO MODU Code, it meets the following requirements:

(a) Each new lifeboat and launching appliance may be of aluminum construction only if its stowage location is protected with a water spray system in accordance with § 108.550(d) of this chapter.

(b) Each lifejacket, immersion suit, and emergency position indicating radiobeacon (EPIRB) must be marked with the unit's name in accordance with §§ 108.649 and 108.650.

(c) Inflatable lifejackets, if carried, must be of the same or similar design as required by § 108.580(b).

(d) Containers for lifejackets, immersions suits, and anti-exposure suits must be marked as specified in § 108.649(g).

(e) Each liferaft must be arranged to permit it to drop into the water from the deck on which it is stowed as required in § 108.530(c)(3).

(f) Survival craft must be arranged to allow safe disembarkation onto the unit after a drill in accordance with § 108.540(f).

(g) The requirements for guarding of falls in §§ 108.553 (d) and (f) must be met.

(h) The winch drum requirements described in § 108.553(e) must be met for all survival craft winches, not just multiple drum winches.

(i) The maximum lowering speed requirements from §§ 108.553 (h) and (i) must be met.

(j) An auxiliary line must be kept with each line-throwing appliance in accordance with § 108.597(c)(2).

(k) Immersion suits are required on all units, except those operating between the 32 degrees north and 32 degrees south latitude in accordance with § 108.580(c).

(l) All abandonment drills conducted on units carrying immersion suits must include immersion suits.

**§ 108.510 Application.**

(a) For the purposes of this subpart—  
(1) *Similar stage of construction* means the stage at which—

(i) Construction identifiable with a specific unit begins; and

(ii) Assembly of that unit comprising at least 50 metric tons (55.1 U.S. tons) or 1 percent of the estimated mass of all structural material, whichever is less, has been achieved.

(2) *Unit constructed* means a unit, the keel of which is laid or which is at a similar stage of construction.

(b) Subject to § 108.515, each unit constructed before October 1, 1996, must meet the requirements of this subpart, except for the number, type, and arrangement of lifeboats (including survival capsules), lifeboat davits, winches, inflatable liferafts, liferaft launching equipment, and rescue boats.

(c)(1) If a District Commander determines that the overall safety of the