

posted next to a fire apparatus described in paragraph (a) of this section.

§ 108.633 Fire stations.

Each fire station must be identified by marking: "FIRE STATION NO. ___;" next to the station in letters and numbers at least 5 centimeters (2 inches) high.

§ 108.635 Self-contained breathing apparatus.

Each locker or space containing self-contained breathing apparatus must be marked: "SELF CONTAINED BREATHING APPARATUS".

§ 108.636 Work vests.

Each space containing a work vest must be marked: "WORK VEST".

§ 108.637 Hand portable fire extinguishers.

(a) Each hand portable fire extinguisher must be marked with a number that identifies it in relation to all other hand portable fire extinguishers.

(b) The location of each hand portable fire extinguisher must be marked with the same number that is marked on the extinguisher.

§ 108.639 Emergency lights.

Each emergency light must be marked: "E".

§ 108.641 Instructions for changing steering gear.

Instructions stating, in order, the different steps to be taken for changing to emergency and secondary steering gear must be posted in the steering gear room and at each secondary steering station in 1.3 centimeters (½ inch) letters and numerals of contrasting color to the background.

§ 108.643 Rudder orders.

At each steering station, the direction which the wheel or steering device must be moved for right rudder or left rudder must be marked in letters of contrasting color to the background on the wheel or steering device or in a place that is directly in the helmsman's line of vision to indicate "RIGHT RUDDER" and "LEFT RUDDER".

§ 108.645 Markings on lifesaving appliances.

(a) *Lifeboats and rescue boats.* Each lifeboat and rescue boat must be plainly marked as follows:

(1) Each side of each lifeboat and rescue boat bow must be marked in block capital letters and numbers with—

(i) The name of the unit; and

(ii) The name of the port required to be marked on the unit to meet the requirements of subpart 67.123 of this chapter.

(2) The number of persons the boat is equipped for, which may not exceed the number shown on its nameplate, must be clearly marked in permanent characters.

(3) The number of the boat and the unit's name, must be plainly marked or painted so that the markings are visible from above the boat.

(4) Type II retro-reflective material approved under approval series 164.018 must be placed on the boat and meet the arrangement requirements in IMO Resolution A.658(16).

(b) *Rigid liferafts.* Each rigid liferaft must be marked as follows:

(1) The name of the unit must be marked on each rigid liferaft.

(2) The name of the port required to be marked on the unit to meet the requirements of subpart 67.123 of this chapter.

(3) The length of the painter must be marked on each rigid liferaft.

(4) At each entrance of each rigid liferaft, the number of persons the rigid liferaft is equipped for, not exceeding the number shown on its nameplate, must be marked in letters and numbers at least 100 millimeters (4 inches) high, in a color contrasting to that of the liferaft.

[CGD 84-069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

§ 108.646 Marking of stowage locations.

(a) Containers, brackets, racks, and other similar stowage locations for lifesaving equipment, must be marked with symbols in accordance with IMO Resolution A.760(18), indicating the devices stowed in that location for that purpose.

§ 108.647

46 CFR Ch. I (10-1-06 Edition)

(b) If more than one device is stowed in that location, the number of devices must also be indicated.

(c) Survival craft should be numbered.

[CGD 84-069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

§ 108.647 Inflatable liferafts.

The number of the liferaft and the number of persons it is permitted to accommodate must be marked or painted in a conspicuous place in the immediate vicinity of each inflatable liferaft in block capital letters and numbers. The word "liferaft" or the appropriate symbol from IMO Resolution A.760(18) shall be used to identify the stowage location. Liferafts stowed on the sides of the unit should be numbered in the same manner as the lifeboats. This marking must not be on the inflatable liferaft container.

[CGD 84-069, 61 FR 25298, May 20, 1996]

§ 108.649 Lifejackets, immersion suits, and lifebuoys.

(a) Each lifejacket must be marked—
(1) In block capital letters with the name of the unit; and

(2) With type I retro-reflective material approved under approval series 164.018. The arrangement of the retro-reflective material must meet IMO Resolution A.658(16).

(b) The stowage positions for lifejackets, other than lifejackets stowed in staterooms, must be marked with either the word "LIFEJACKET" or with the appropriate symbol from IMO Resolution A.760(18).

(c) Each immersion suit or anti-exposure suit must be marked to identify the person or unit to which it belongs.

(d) Immersion suits or anti-exposure suits must be stowed so they are readily accessible, and the stowage positions must be marked with either the words "IMMERSION SUITS" or "ANTI-EXPOSURE SUITS", or with the appropriate symbol from IMO Resolution A.760(18).

(e) Each lifebuoy must be marked—
(1) In block capital letters with the unit's name and with the name of the port required to be marked on the unit under subpart 67.123 of this chapter; and

(2) With type II retro-reflective material approved under part 164, subpart 164.018 of this chapter. The arrangement of the retro-reflective material must meet IMO Resolution A.658(16).

(f) Each lifebuoy stowage position must be marked with either the words "LIFEBUOY" or "LIFE BUOY", or with the appropriate symbol from IMO Resolution A.760(18).

(g) Each lifejacket, immersion suit, and anti-exposure suit container must be marked in block capital letters and numbers with the minimum quantity, identity, and if sizes other than adult or universal sizes are used on the unit, the size of the equipment stowed inside the container. The equipment may be identified in words or with the appropriate symbol from IMO Resolution A.760(18).

[CGD 84-069, 61 FR 25298, May 20, 1996, as amended at 63 FR 52815, Oct. 1, 1998]

§ 108.650 EPIRBs and SARTs.

Emergency position indicating radiobeacons and search and rescue transponders. Each EPIRB and SART should have the name of the unit plainly marked or painted on its label, except for EPIRBs or SARTs in an inflatable liferaft or permanently installed in a survival craft.

[CGD 84-069, 61 FR 25299, May 20, 1996]

§ 108.651 Portable magazine chests.

Each portable magazine chest must be marked: "PORTABLE MAGAZINE CHEST—FLAMMABLE—KEEP LIGHTS AND FIRE AWAY" in letters at least 7.5 centimeters (3 inches) high.

§ 108.653 Helicopter facilities.

(a) Each helicopter fueling facility must be marked adjacent to the fueling hose storage: "WARNING—HELICOPTER FUELING STATION—KEEP LIGHTS AND FIRE AWAY".

(b) Each storage tank for helicopter fuel must be marked: "DANGER—FLAMMABLE LIQUID".

(c) Each access to a helicopter landing area must be marked: "BEWARE OF TAIL ROTOR".

(d) Each marking required by this section must be in letters at least 7.5 centimeters (3 inches) high.