

(b) Steering Gear, Whistle, and Means of Communication. Prior to departure. See § 97.15-3.

(c) Drafts and Load Line Markings. Prior to leaving port, ocean, coastwise, and Great Lakes services only. See § 97.15-5.

(d) Verification of vessel compliance with applicable stability requirements. After loading and prior to departure and at all other times necessary to assure the safety of the vessel. See § 97.15-7.

(e) Loading doors. Where applicable, every closing and any opening when not docked. See § 97.15-17.

(f) Hatches and other openings. All openings and closings, or leaving port without closing. Except vessels on protected waters. See § 97.15-20.

(g) Emergency Lighting and Power Systems. Weekly and semi-annually. See § 97.15-30.

(h) Fuel oil data: Upon receipt of fuel oil on board. See § 97.15-55.

(i) Cargo gear inspections: At least once a month. See § 91.37-70 of this subchapter.

(j) Inflatable hopper gate seals. Where installed to comply with subpart G of part 172 of this chapter after each carriage of cargo. See § 97.15-75.

[CGFR 65-50, 30 FR 17011, Dec. 30, 1965, as amended by CGD 80-159, 51 FR 33059, Sept. 18, 1986; CGD 89-037, 57 FR 41823, Sept. 11, 1992; CGD 84-069, 61 FR 25289, May 20, 1996]

### Subpart 97.36—Display of Plans

#### § 97.36-1 When required.

Barges with sleeping accommodations for more than six persons and all self-propelled vessels shall have permanently exhibited for the guidance of the officer in charge of the vessel the following plans:

(a) General arrangement plans showing for each deck the fire control stations, the various sections enclosed by fire-resisting bulkheads, together with particulars of the fire alarms, detecting systems, the sprinkler installation (if any), the fire extinguishing appliances, means of access to different compartments, decks, etc., and the ventilating systems including particulars of the master fan controls, the positions of dampers, the location of the remote means of stopping fans, and

identification numbers of the ventilating fans serving each section. If cargo compartments are "specially suitable for vehicles," they shall be so indicated on the plan. Alternatively, at the discretion of the Commandant, the aforementioned details may be set out in any other medium, such as a booklet or on computer software, provided that the aforementioned details are available to each officer and a copy is retained on board at all times and is accessible during emergencies. For vessels constructed on or after September 30, 1997 or for existing vessels which have their plans redrawn, the symbols used to identify the aforementioned details shall be in accordance with IMO Assembly resolution A.654(16). These identical symbols can also be found in ASTM Adjunct F 1626 (incorporated by reference, see § 97.01-2).

(b) Plans showing clearly for each deck and hold the boundaries of the watertight compartments, the openings therein with the means of closure and position of any controls thereof, and the arrangements for the correction of any list due to flooding.

(c) The aforementioned information shall be kept up-to-date, any alteration being recorded in the applicable medium as soon as practicable.

[CGD 95-028, 62 FR 51207, Sept. 30, 1997, as amended by USCG-2000-7790, 65 FR 58461, Sept. 29, 2000]

### Subpart 97.37—Markings for Fire and Emergency Equipment, Etc.

#### § 97.37-1 Application.

(a) The provisions of this subpart, with the exception of § 97.37-90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952, shall meet the requirements of § 97.37-90.

#### § 97.37-3 General.

(a) It is the intent of this subpart to provide such markings as are necessary for the guidance of the person on board in case of an emergency. In any specific case, and particularly on small vessels, where it can be shown to the satisfaction of the Officer in Charge, Marine