

§ 131.880

identity, or IMO symbol specified by IMO Resolution A.760(18), and size of the items stowed inside.

(c) Each ring buoy on a vessel in ocean service must be marked in block capital letters with the name of the port whose marking on the stern of the vessel is required by §67.123 of this chapter.

(d) Each stowage site for a ring buoy must be marked "LIFE BUOY" or marked with the IMO symbol.

(e) Each lifejacket must be marked with Type I retro-reflective material approved under subpart 164.018 of this chapter. The arrangement of the retro-reflective material must comply with IMO Resolution A.658(16).

(f) Each ring life buoy must be marked with Type I or II retro-reflective material approved under subpart 164.018 of this chapter. The arrangement of the retro-reflective material must comply with IMO Resolution A.658(16).

§ 131.880 Fire hoses and axes.

Each fire hose and axe must be marked with the vessel's name.

§ 131.890 EPIRBs and SARTs.

The name of the vessel must be plainly marked or painted on each Emergency Position Indicating Radio Beacon (EPIRB) and on each Search and Rescue Transponder (SART), except on an EPIRB or SART—

(a) In an inflatable liferaft; or

(b) Permanently installed in a survival craft.

§ 131.893 Watertight doors and watertight hatches.

Each watertight door in a bulkhead that must be watertight in compliance with the requirements in part 174 of this chapter, and each watertight hatch, must be marked on both sides in letters at least 50 millimeters (2 inches) high that state the following: "WATERTIGHT DOOR—KEEP CLOSED EXCEPT FOR PASSAGE" or "WATERTIGHT HATCH—KEEP CLOSED WHEN NOT IN USE".

§ 131.896 Remote stopping-systems.

The remote stopping-systems required by §129.540 of this subchapter

46 CFR Ch. I (10–1–06 Edition)

must be clearly marked to show what system each controls.

§ 131.899 Fire dampers.

Each fire damper installed within the boundary of a space protected by a fixed fire extinguishing system must be fitted with an indicator showing whether the damper is open or closed and must be marked with red letters at least 13 millimeters (½-inch) high stating "FIRE DAMPER" and, as otherwise appropriate, identifying the space served by the fire damper.

Subpart I—Miscellaneous

§ 131.905 Statutory penalties.

(a) The marine-safety statutes and other statutes impose criminal and civil penalties for violating the applicable provisions of this subchapter. Possible sanctions include:

(1) Assessment and collection of civil monetary penalty.

(2) Criminal prosecution, where no loss of life results.

(3) Criminal prosecution for manslaughter, where loss of life results from violating marine-safety statutes or regulations or from misconduct, negligence, or inattention to duty.

(4) Libel against vessel.

(b) 46 U.S.C. Chapter 77 allows, in addition to the foregoing, the suspension or revocation of licenses, certificates, or documents issued by the Coast Guard, for incompetence, misconduct, or negligence or for violating marine-safety statutes or regulations.

§ 131.910 Notices to mariners and aids to navigation.

Each master and mate shall acquaint himself or herself with the latest information published by the Coast Guard and the National Imagery and Mapping Agency regarding aids to navigation in the area in which the vessel operates.

[CGD 82-004 and CGD 86-074, 62 FR 49340, Sept. 19, 1997, as amended by USCG-2001-10224, 66 FR 48620, Sept. 21, 2001]

§ 131.915 Persons allowed in pilot-house and on navigational bridge.

No person may be in the pilothouse while the vessel is under way, unless connected with the navigation of the