

specifically required by law is unreasonable or impracticable, the Commandant may permit the use of alternate equipment apparatus, or arrangement to such an extent and upon such conditions as will insure, to his satisfaction, a degree of safety consistent with the minimum standards set forth in this part.

**§ 151.02–5 Design of unmanned barges.**

(a) In order not to inhibit design and application, the Commandant may approve vessels of novel design, both new and for conversion, after it is shown to his satisfaction that such a vessel is at least as safe as any vessel which meets the standards required by this part.

(b) [Reserved]

**Subpart 151.03—Definitions**

**§ 151.03–1 Definitions of terms.**

Certain terms used in the regulations in this subchapter are defined in this subpart.

**§ 151.03–3 Angle of downflooding.**

The angle of heel of the vessel at which any opening in the hull not provided with a water tight closure would be immersed.

**§ 151.03–5 Approved.**

This term means approved by the Commandant unless otherwise stated.

**§ 151.03–7 Barge.**

This term means any non-self-propelled vessel designed to carry cargo.

**§ 151.03–9 Cargo.**

This term means any liquid, gas or solid having one or more of the dangerous properties defined in this subchapter.

**§ 151.03–11 Coastwise.**

This designation refers to all vessels normally navigating the waters of any ocean or the Gulf of Mexico 20 nautical miles or less offshore.

**§ 151.03–13 Cofferdam.**

This term means a void or empty space separating two or more compartments for the purpose of isolation or to prevent the contents of one compart-

ment from entering another in the event of the failure of the walls of one to retain their tightness.

**§ 151.03–15 Commandant.**

This term means Commandant of the U.S. Coast Guard.

**§ 151.03–17 Compatible.**

Compatible means that a cargo will not react in an unsafe manner with other cargo or materials used in construction of the barge. The prime considerations are the chemical, physical, or thermal properties of the reaction including heat, pressure, toxicity, stability, and explosive nature of the reaction and its end products.

**§ 151.03–19 Environment.**

This term refers to the atmosphere within a cargo tank and the spaces adjacent to the tank or spaces in which cargo is handled.

**§ 151.03–21 Filling density.**

The ratio, expressed as a percentage, of the weight of cargo that may be loaded into a tank compared to the weight of water that the tank will hold at 60 °F. The weight of a gallon of water at 60 °F in air shall be 8.32828 pounds.

**§ 151.03–23 Flame arrestor.**

Any device or assembly of cellular, tubular, pressure or other type used for preventing the passage of flames into enclosed spaces.

**§ 151.03–25 Flame screen.**

A fitted single screen of corrosion-resistant wire of at least 30 by 30 mesh or two fitted screens, both of corrosion-resistant wire, of at least 20 by 20 mesh spaced not less than one-half inch or more than 1½ inches apart.

**§ 151.03–27 Gas free.**

Free from dangerous concentrations of flammable or toxic gases.

**§ 151.03–29 Great Lakes.**

A designation for all vessels in Great Lakes service.