

## § 151.50–86

## 46 CFR Ch. I (10–1–06 Edition)

cargo transfer piping must be disconnected at the cargo tanks. After the cargo piping is disconnected, both ends of the line must be plugged or fitted with blind flanges.

[CGD 80–001, 46 FR 63280, Dec. 31, 1981, as amended by CGD 82–063b, 48 FR 4781, Feb. 3, 1983; CGD 88–100, 54 FR 40041, Sept. 29, 1989; 55 FR 17276, Apr. 24, 1990]

### § 151.50–86 Alkyl (C7–C9) nitrates.

(a) The carriage temperature of octyl nitrates must be maintained below 100 °C (212 °F) in order to prevent the occurrence of a self-sustaining exothermic decomposition reaction.

(b) Octyl nitrates may not be carried in a deck tank unless the tank has a combination of insulation and a water deluge system sufficient to maintain the tank's cargo temperature below 100 °C (212 °F) and the cargo temperature rise at or below 1.5 °C(2.7 °F)/hour, for a fire of 650 °C (1200 °F).

[CGD 88–100, 54 FR 40040, Sept. 29, 1989; CGD 92–100, 59 FR 17028, Apr. 11, 1994]

## Subpart 151.55—Special Requirements for Materials of Construction

### § 151.55–1 General.

(a) This section provides special requirements for the materials of construction of equipment that may come into contact with various cargoes. Table 151.05 contains specific requirements for various cargoes.

(b) Copper, copper alloys, zinc, and aluminum shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor. (Equivalent to §151.56–1(a),(b), and (c).)

(c) Copper, copper alloys, zinc, galvanized steel, and mercury shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor. (Equivalent to §151.56–1(b),(c), and (g).)

(d) Aluminum, magnesium, zinc, and lithium shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact

with the cargo liquid or vapor. (Equivalent to §151.56–1(a),(c), and (d).)

(e) Copper and copper bearing alloys shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo liquid or vapor. (Equivalent to §151.56–1(b).)

(f) Aluminum or copper or alloys of either shall not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with the cargo vapor or liquid. (Equivalent to §151.56–1(a) and (b).)

(g) Aluminum, stainless steel, or steel covered with a suitable protective lining or coating shall be used as materials of construction for tanks, pipelines, valves fittings, and other items of equipment that may come in contact with the cargo liquid or vapor. (Equivalent to §151.58–1(a).)

(h) Alkaline or acidic materials, such as caustic soda or sulfuric acid, should not be allowed to contaminate this cargo.

(i) For concentrations of 98 percent or greater, aluminum or stainless steel shall be used as materials of construction. For concentrations of less than 98 percent, 304L or 316 stainless steel shall be used as materials of construction.

(j) Zinc, alloys that have more than 10 percent zinc by weight, and aluminum may not be used as materials of construction for tanks, pipelines, valves, fittings, and other items of equipment that may come in contact with cargo liquid or vapor. (Equivalent to §151.56–1(a) and (c).)

[CGFR 70–10, 35 FR 3714, Feb. 25, 1970, as amended by CGD 73–275R, 41 FR 3087, Jan. 21, 1976; CGD 75–223, 42 FR 8378, Feb. 10, 1977; CGD 88–100, 54 FR 40041, Sept. 29, 1989]

## Subpart 151.56—Prohibited Materials of Construction

### § 151.56–1 Prohibited materials.

When one of the following paragraphs of this section is referenced in table 151.05, the materials listed in that paragraph may not be used in components that contact the cargo or its vapor:

- (a) Aluminum or aluminum alloys.
- (b) Copper or copper alloys.

(c) Zinc, galvanized steel, or alloys having more than 10 percent zinc by weight.

(d) Magnesium.

(e) Lead.

(f) Silver or silver alloys.

(g) Mercury.

[CGD 88-100, 54 FR 40041, Sept. 29, 1989]

### Subpart 151.58—Required Materials of Construction

#### § 151.58-1 Required materials.

When one of the following paragraphs of this section is referenced in table 151.05, only those materials listed in that paragraph may be used in components that contact the cargo or its vapor:

(a) Aluminum, stainless steel, or steel covered with a protective lining or coating. (See § 151.15-3(f)(2).)

(b)-(c) [Reserved]

(d) Solid austenitic stainless steel.

(e) Stainless steel or steel covered with a suitable protective lining or coating. (See § 151.15-3(f)(2).)

[CGD 88-100, 54 FR 40041, Sept. 29, 1989]

## PART 152 [RESERVED]

## PART 153—SHIPS CARRYING BULK LIQUID, LIQUEFIED GAS, OR COMPRESSED GAS HAZARDOUS MATERIALS

### Subpart A—General

Sec.

- 153.0 Availability of materials.
- 153.1 Applicability.
- 153.2 Definitions and acronyms.
- 153.3 Right of appeal.
- 153.4 Incorporation by reference.
- 153.7 Ships built before December 27, 1977 and non-self-propelled ships built before July 1, 1983: Application.
- 153.8 Procedures for requesting an endorsed Certificate of Inspection.
- 153.9 Foreign flag vessel endorsement application.
- 153.10 Procedures for requesting alternatives and waivers; termination of waivers.
- 153.12 IMO Certificates for United States Ships.
- 153.15 Conditions under which the Coast Guard issues a Certificate of Inspection or Certificate of Compliance.

153.16 Requirements for foreign flag vessel permits.

153.30 Special area endorsement.

153.40 Determination of materials that are hazardous.

### Subpart B—Design and Equipment

#### GENERAL VESSEL REQUIREMENTS

- 153.190 Stability requirements.
- 153.201 Openings to accommodation, service or control spaces.
- 153.208 Ballast equipment.
- 153.209 Bilge pumping systems.
- 153.214 Personnel emergency and safety equipment.
- 153.215 Safety equipment lockers.
- 153.216 Shower and eyewash fountains.
- 153.217 Access to enclosed spaces and dedicated ballast tanks.
- 153.219 Access to double bottom tanks serving as dedicated ballast tanks.

#### CARGO CONTAINMENT SYSTEMS

- 153.230 Type I system.
- 153.231 Type II system.
- 153.232 Type III system.
- 153.233 Separation of tanks from machinery, service and other spaces.
- 153.234 Fore and aft location.
- 153.235 Exceptions to cargo piping location restrictions.
- 153.236 Prohibited materials.
- 153.238 Required materials.
- 153.239 Use of cast iron.
- 153.240 Insulation.

#### CARGO TANKS

- 153.250 Double-bottom and deep tanks as cargo tanks.
- 153.251 Independent cargo tanks.
- 153.252 Special requirement for an independent cargo tank.
- 153.254 Cargo tank access.
- 153.256 Trunks, domes, and openings of cargo tanks.
- 153.266 Tank linings.

#### PIPING SYSTEMS AND CARGO HANDLING EQUIPMENT

- 153.280 Piping system design.
- 153.281 Piping to independent tanks.
- 153.282 Cargo filling lines.
- 153.283 Valving for cargo piping.
- 153.284 Characteristics of required quick closing valves.
- 153.285 Valving for cargo pump manifolds.
- 153.292 Separation of piping systems.
- 153.294 Marking of piping systems.
- 153.296 Emergency shutdown stations.
- 153.297 Emergency actuators at the point of cargo control.

#### CARGO HANDLING SPACE VENTILATION

- 153.310 Ventilation system type.
- 153.312 Ventilation system standards.