

IX. APPENDIX C

MATERIAL SAFETY DATA SHEET

The following items of information which are applicable to a specific product or material shall be provided in the appropriate block of the Material Safety Data Sheet (MSDS).

The product designation is inserted in the block in the upper left corner of the first page to facilitate filing and retrieval. Print in upper case letters as large as possible. It should be printed to read upright with the sheet turned sideways. The product designation is that name or code designation which appears on the label or by which the product is sold or known by workers. The relative numerical hazard ratings and key statements are those determined by the rules in Chapter V, Part B, of the NIOSH publication, A Recommended Standard...An Identification System for Occupationally Hazardous Materials [49]. The company identification may be printed in the upper right corner if desired.

Section I. Production Identification

The manufacturer's name, address, and regular and emergency telephone numbers (including area code) are inserted in the appropriate blocks of Section I. The company listed should be a source of detailed backup information on the hazards of the material(s) covered by the MSDS. The listing of suppliers or wholesale distributors is discouraged. The trade name should be the product designation or common name associated with the material. The synonyms are those commonly used for the product, especially formal chemical nomenclature. Not every known chemical designation or competitor's trade name needs to be listed.

Section II. Hazardous Ingredients

The "materials" listed in Section II shall be those substances which are part of the hazardous product covered by the MSDS and which individually meet any of the criteria defining a hazardous material. Thus, one component of a multicomponent product might be listed because of its toxicity, another component because of its flammability, while a third component could be included both for its toxicity and its reactivity. Note that a MSDS for a single component product must have the name of the material repeated in this section to avoid giving the impression that there are no hazardous ingredients.

Chemical substances should be listed according to their complete name derived from a recognized system of nomenclature. Where possible, avoid using common names and general class names such as "aromatic amine," "safety solvent," or "aliphatic hydrocarbon" when the specific name is known.

The "%" may be the approximate percentage by weight or volume (indicate basis) which each hazardous ingredient of the mixture bears to the whole mixture. This may be indicated as a range or maximum amount, i.e., "10-40% vol." or "10% max. wt." to avoid disclosure of trade secrets.

Toxic hazard data shall be stated in terms of concentration, mode of exposure or test, and animal used, e.g., "100 ppm LC50-rat," "25 mg/kg LD50-skin-rabbit," "75 ppm LC man," "permissible exposure from 29 CFR 1910.1000," or, if not available, from other sources such as publications of the American Conference of Governmental Industrial Hygienists (ACGIH) or the American National Standards Institute, Inc. (ANSI). Flashpoint, shock sensitivity, or similar descriptive data may be used to indicate flammability, reactivity, or similar hazardous properties of the material.

Section III. Physical Data

The data in Section III should be for the total mixture and should include the boiling point and melting point in degrees Fahrenheit (Celsius in parentheses); vapor pressure, in conventional millimeters of mercury (mmHg); vapor density of gas or vapor (air=1); solubility in water, in parts/hundred parts of water by weight; specific gravity (water=1); percent volatiles (indicated if by weight or volume) at 70°F (21.1°C); evaporation rate for liquids or sublimable solids, relative to butyl acetate; and appearance and odor. These data are useful for the control of toxic substances. Boiling point, vapor density, percent volatiles, vapor pressure, and evaporation are useful for designing proper ventilation equipment. This information is also useful for design and deployment of adequate fire and spill containment equipment. The appearance and odor may facilitate identification of substances stored in improperly marked containers or when spilled.

Section IV. Fire and Explosion Data

Section IV should contain complete fire and explosion data for the product, including flash point and autoignition temperature in degrees Fahrenheit (Celsius in parentheses); flammable limits, in percent by volume in air; suitable extinguishing media or materials; special firefighting procedures; and unusual fire and explosion hazard information. If the product presents no fire hazard, insert "NO FIRE HAZARD" on the line labeled "Extinguishing Media."

Section V. Health Hazard Information

The "Health Hazard Data" should be a combined estimate of the hazard of the total product. This can be expressed as a TWA concentration, as a permissible exposure, or by some other indication of an acceptable standard. Other data are acceptable, such as lowest LD50 if multiple components are involved.

Under "Routes of Exposure," comments in each category should reflect the potential hazard from absorption by the route in question. Comments should indicate the severity of the effect and the basis for the statement if possible. The basis might be animal studies, analogy with similar products, or human experiences. Comments such as "yes" or "possible" are not helpful. Typical comments might be:

Skin Contact--single short contact, no adverse effects likely; prolonged or repeated contact, possibly mild irritation.

Eye Contact--some pain and mild transient irritation; no corneal scarring.

"Emergency and First Aid Procedures" should be written in lay language and should primarily represent first-aid treatment that could be provided by paramedical personnel or individuals trained in first aid.

Information in the "Notes to Physician" section should include any special medical information which would be of assistance to an attending physician including required or recommended preplacement and periodic medical examinations, diagnostic procedures, and medical management of overexposed workers.

Section VI. Reactivity Data

The comments in Section VI relate to safe storage and handling of hazardous, unstable substances. It is particularly important to highlight instability or incompatibility to common substances or circumstances, such as water, direct sunlight, steel or copper piping, acids, alkalies, etc. "Hazardous Decomposition Products" shall include those products released under fire conditions. It must also include dangerous products produced by aging, such as peroxides in the case of some ethers. Where applicable, shelf life should also be indicated.

Section VII. Spill or Leak Procedures

Detailed procedures for cleanup and disposal should be listed with emphasis on precautions to be taken to protect workers assigned to cleanup detail. Specific neutralizing chemicals or procedures should be described in detail. Disposal methods should be explicit including proper labeling of containers holding residues and ultimate disposal methods such as "sanitary landfill" or "incineration." Warnings such as "comply with local, state, and Federal antipollution ordinances" are proper but not sufficient. Specific procedures shall be identified.

Section VIII. Special Protection Information

Section VIII requires specific information. Statements such as "Yes," "No," or "If necessary" are not informative. Ventilation requirements should be specific as to type and preferred methods. Respirators shall be specified

as to type and NIOSH or Mine Safety and Health Administration approval class, i.e., "Supplied air," "Organic vapor canister," etc. Protective equipment must be specified as to type and materials of construction.

Section IX. Special Precautions

"Precautionary Statements" shall consist of the label statements selected for use on the container or placard. Additional information on any aspect of safety or health not covered in other sections should be inserted in Section IX. The lower block can contain references to published guides or in-house procedures for handling and storage. Department of Transportation markings and classifications and other freight, handling, or storage requirements and environmental controls can be noted.

Signature and Filing

Finally, the name and address of the responsible person who completed the MSDS and the date of completion are entered. This will facilitate correction of errors and identify a source of additional information.

The MSDS shall be filed in a location readily accessible to workers exposed to the hazardous substance. The MSDS can be used as a training aid and basis for discussion during safety meetings and training of new workers. It should assist management by directing attention to the need for specific control engineering, work practices, and protective measures to ensure safe handling and use of the material. It will aid the safety and health staff in planning a safe and healthful work environment and in suggesting appropriate emergency procedures and sources of help in the event of harmful exposure of workers.

--

MATERIAL SAFETY DATA SHEET

I PRODUCT IDENTIFICATION		
MANUFACTURER'S NAME	REGULAR TELEPHONE NO. EMERGENCY TELEPHONE NO.	
ADDRESS		
TRADE NAME		
SYNONYMS		
II HAZARDOUS INGREDIENTS		
MATERIAL OR COMPONENT	%	HAZARD DATA
III PHYSICAL DATA		
BOILING POINT, 760 MM HG		MELTING POINT
SPECIFIC GRAVITY (H ₂ O=1)		VAPOR PRESSURE
VAPOR DENSITY (AIR=1)		SOLUBILITY IN H ₂ O, % BY WT
% VOLATILES BY VOL		EVAPORATION RATE (BUTYL ACETATE=1)
APPEARANCE AND ODOR		

IV FIRE AND EXPLOSION DATA				
FLASH POINT (TEST METHOD)			AUTOIGNITION TEMPERATURE	
FLAMMABLE LIMITS IN AIR, % BY VOL.		LOWER		UPPER
EXTINGUISHING MEDIA				
SPECIAL FIRE FIGHTING PROCEDURES				
UNUSUAL FIRE AND EXPLOSION HAZARD				
V HEALTH HAZARD INFORMATION				
HEALTH HAZARD DATA				
ROUTES OF EXPOSURE				
INHALATION				
SKIN CONTACT				
SKIN ABSORPTION				
EYE CONTACT				
INGESTION				
EFFECTS OF OVEREXPOSURE				
ACUTE OVEREXPOSURE				
CHRONIC OVEREXPOSURE				
EMERGENCY AND FIRST AID PROCEDURES				
EYES				
SKIN				
INHALATION				
INGESTION				
NOTES TO PHYSICIAN				

VI REACTIVITY DATA	
CONDITIONS CONTRIBUTING TO INSTABILITY	
INCOMPATIBILITY	
HAZARDOUS DECOMPOSITION PRODUCTS	
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION	
VII SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	
NEUTRALIZING CHEMICALS	
WASTE DISPOSAL METHOD	
VIII SPECIAL PROTECTION INFORMATION	
VENTILATION REQUIREMENTS	
SPECIFIC PERSONAL PROTECTIVE EQUIPMENT	
RESPIRATORY (SPECIFY IN DETAIL)	
EYE	
GLOVES	
OTHER CLOTHING AND EQUIPMENT	

IX SPECIAL PRECAUTIONS

PRECAUTIONARY
STATEMENTS

OTHER HANDLING AND
STORAGE REQUIREMENTS

PREPARED BY _____

ADDRESS: _____

DATE _____

X. APPENDIX D

PERTINENT OSHA STANDARDS FOR
THE PAINT AND ALLIED COATING PRODUCTS INDUSTRY*

<u>Section</u> (29 CFR)	<u>Title</u>
1910.23	Guarding floor and wall openings and holes.
1910.24	Fixed industrial stairs.
1910.25	Portable wood ladders.
1910.26	Portable metal ladders.
1910.27	Fixed ladders.
1910.36	General requirements for Subpart E - Means of Egress.
1910.37	Means of egress, general.
1910.94	Ventilation.
1910.95	Occupational noise exposure.
1910.97	Nonionizing radiation.
1910.101	Compressed gases (general requirements).
1910.106	Flammable and combustible liquids.
1910.132	General requirements for Subpart I - Personal Protective Equipment.
1910.133	Eye and face protection.
1910.134	Respiratory protection.
1910.135	Occupational head protection.
1910.136	Occupational foot protection.
1910.141	Sanitation.
1910.144	Safety color code for marking physical hazards.
1910.145	Specifications for accident prevention signs and tags.
1910.151	Medical services and first aid.
1910.156	Fire brigades.
1910.157	Portable fire extinguishers.
1910.158	Standpipe and hose systems.
1910.159	Automatic sprinkler systems.
1910.160	Fixed extinguishing systems, general.
1910.161	Fixed extinguishing systems, dry chemical.
1910.162	Fixed extinguishing systems, gaseous agent.
1910.163	Fixed extinguishing systems, water spray and foam.
1910.164	Fire detection systems.
1910.166	Inspection of compressed gas cylinders.
1910.167	Safety relief devices for compressed gas cylinders.
1910.176	Handling materials-general.
1910.178	Powered industrial trucks.
1910.212	General requirements for all machines (part of Subpart O - Machinery and Machine Guarding).

(Continued)

APPENDIX D

PERTINENT OSHA STANDARDS FOR
THE PAINT AND ALLIED COATING PRODUCTS INDUSTRY*

<u>Section (29 CFR)</u>	<u>Title</u>
1910.219	Mechanical power-transmission apparatus.
1910.242	Hand and portable powered tools and equipment, general.
1910.243	Guarding of portable powered tools.
1910.244	Other portable tools and equipment.
1910.303	General requirements for Subpart S - Electrical.
1910.304	Wiring design and protection.
1910.305	Wiring methods, components, and equipment for general use.
1910.307	Hazardous (classified) locations.
1910.1000	Air contaminants.
1910.1001	Asbestos.
1910.1002	Coal tar pitch volatiles.
1910.1017	Vinyl chloride.
1910.1025	Lead.
1910.1045	Acrylonitrile.

*Does not include all OSHA regulations that are applicable to the paint and allied coating products industry

KEY WORD INDEX

A

acetate(s) 10, 19, 60, 61, 62, 99, 100, 101, 111
 acetic acid 106
 acetone 10, 19, 60, 101
 acetonitrile 103
 acid(s) 13, 27, 42, 60, 62, 91, 106, 108, 109, 112
 acrolein 42, 106
 acrylate(s) 44, 73, 103
 acrylic acids 91
 acrylic resins 8, 91
 acrylics 9, 10, 16, 17
 acrylonitrile 104, 119
 additive(s) 7, 8, 11, 12, 13, 14, 16, 40, 41, 43, 46, 59, 105
 agitators 16, 29
 alcohol(s) 8, 10, 19, 41, 60, 61, 91, 96, 97, 102
 aldehydes 42
 aliphatic hydrocarbons 8, 97
 aliphatic naphthas 10
 alkalis 112
 alkyd resins 17, 91
 alkyd(s) 7, 8, 9, 17
 allyl glycidyl ether 105
 aluminum pigments 66
 aluminum silicate (china clay) 9
 amines 106
 amino-formaldehydes 10
 amino resins 8, 9
 ammonia 107
 antifoam agents 8, 11
 antifoulants 12
 antifouling paints 69
 anti-livering agents 12, 91
 anti-skinning agents 8, 11, 12
 antimony 60, 94
 antioxidants 12
 aromatic hydrocarbons 8, 10, 94, 98
 arsenic 60, 69, 105
 asbestos 9, 60, 94, 96, 119

B

bacteria 12

ball mill(s) 41, 52, 53, 57, 73, 91
 barite 8
 barium 60, 94
 benzene 60, 61, 69, 98, 107
 p-benzoquinone 103
 benzoyl peroxide 60, 107
 beryllium 60, 107
 binder(s) 9, 91
 biocides 11, 12
 butanol 10
 2-butanone 60, 101
 2-butoxy ethanol 60, 96
 butyl acetate 60, 99
 sec-butyl acetate 99
 butyl alcohol 60, 96
 butyl Cellosolve® 60, 96
 n-butyl glycidyl ether 60, 105

C

cadmium 60, 94
 calcium carbonate 8
 calcium silicate 9
 calcium sulfate 17
 camphor 107
 cancer 45, 94, 95, 105, 107
 canister 77, 113
 carbon black 8, 17, 60, 94
 carbon monoxide 40, 60, 98, 107
 carbon tetrachloride 60, 107
 carcinogen(s) 44, 64, 99, 103, 104, 105
 carcinogenic 94
 catalyst(s) 13, 44
 caustic(s) 14, 23, 43, 66, 75
 Cellosolve® 60, 61, 62, 96, 100
 Cellosolve® acetate 99
 cellulose esters 10, 13
 cellulotics 8, 9
 china clay (aluminum silicate) 9
 chlorinated hydrocarbons 98
 chlorinated solvents 8, 9, 10
 chromate(s) 60, 61, 68, 69, 107
 chromic acid 60, 107
 chromium 60, 61, 94

KEY WORD INDEX (CONTINUED)

coal tar pitch volatiles 61, 107,
119
cobalt 61, 95
cold cutting 15, 91
colloidal dispersions 4
combustible materials 40, 59
confined spaces 43, 68
cooking 2, 14, 15, 16, 42, 43,
73, 74, 91
copper 61, 95, 107
copper naphthenate 12
creosote 12
cresols 8, 69
crystalline silica 93, 96, 109
cuprous oxide 12, 69
cyclohexane 10, 61, 97
cyclohexanone 101
cycloparaffins 10
cyclopentane 10

D

depalletizer(s) 42, 91
diacetone alcohol 96, 102
diatomaceous earth 9, 43
diethylene dioxide (dioxane) 99
diisobutyl ketone 102
diisocyanates 104
dimethylaniline 108
dioxane (diethylene dioxide) 99
dipentene 10
dispersion(s) 1, 4, 6, 9, 11, 13,
14, 15, 17, 41, 51, 66, 69, 72,
91, 92
dough-type mixers 14, 17
driers 6, 8, 11, 16
drums 9, 25, 32, 33, 34, 35, 36,
37, 54, 56
drying oils 8, 9, 91
dust(s) 1, 40, 41, 43, 45, 60,
61, 66, 67, 68, 69, 71, 94, 95, 96

E

enamels 1, 2, 3, 5, 20
engineering controls 1, 4, 47,
48, 51, 60, 63, 69, 74, 75, 76,
114
epichlorohydrin 104

epoxy resins 7, 8, 9, 10, 16
ethanol 10, 60, 61, 96, 101
ethanolamine 107
2-ethoxy ethanol 61, 100
2-ethoxyethyl acetate 61, 99
ethyl acetate 61, 99
ethyl acrylate 44, 61, 73, 103
ethyl alcohol (ethanol) 10, 60,
61, 96, 101
ethyl sec-amyl ketone 61, 102
ethyl benzene 61, 98
ethylene 100, 101
explosion(s) 1, 40, 43, 44, 46,
54, 59, 66, 111
extender(s) 8, 9, 12, 67, 91, 94

F

fatty acids 42, 91
filler(s) 6, 7, 9, 63
film-former(s) 7, 8, 9, 10, 12,
14, 15, 17, 46, 59, 91, 93, 103
fire(s) 1, 2, 15, 30, 40, 43, 44,
46, 54, 59, 66, 68, 92, 111, 112,
118
flammable 1, 39, 40, 41, 44, 46,
54, 59, 73, 111, 118
flash point 91, 111
flush colors 92
formaldehyde 104
freeze-thaw stablizers 12
fumaric anhydride 42
fungi 12
fungicides 8, 12
furans 9, 10, 100
furfural 61, 100
furfuryl alcohol 96

G

glycerin 42, 91
glycidyl ethers 105
glycols 8, 10, 42, 100
grounding 54, 55, 56, 57, 58

H

heptane (n-heptane) 97
2-heptanone 103

KEY WORD INDEX (CONTINUED)

hexamethylene diisocyanate (HDI)
104
hexane (n-hexane) 97
2-hexanone 61, 102
hexone 61, 102
hiding power 7, 9, 92
high-solids coatings 4, 5, 92
hydrocarbon mixtures 101
hydrocarbon solvents 8, 9, 10
hydrogen chloride 61, 108
hydrogen gas 66
4-hydroxy-4-methyl-2-pentanone 96,
102

I

illumination 47, 50
inorganic 8, 9, 20, 21, 60, 61,
92, 95, 105
iron oxide 8, 17, 61, 95
isobutyl acetate 61, 99
isobutyl alcohol 61, 97
isophorone 61, 102
isopropanol 10
isopropyl acetate 99
isopropyl alcohol 61, 97
isopropyl glycidyl ether 105

K

Kady® mills 14, 41
ketones 8, 10, 42, 101
kettle(s) 2, 14, 15, 16, 42, 43,
73, 74, 92

L

laboratory 1, 6, 7, 12, 15, 19,
41, 44, 73
lacquer(s) 1, 2, 5, 13, 15, 19,
20, 41, 42, 45, 92
latex(es) 4, 7, 11, 12, 92
lead 8, 52, 61, 68, 69, 95, 119
lead arsenate 61
lead chromate 61
leukemia 45, 107
linseed oil(s) 8, 9, 17
livering 91, 92
low-solids coatings 4, 17

M

magnesium carbonate 9
maleic anhydride 42, 61, 108
manganese 61, 95
marine (paints) 3, 12
materials handling aids 48, 49, 50
mercury 61, 68, 69, 95, 111
mesityl oxide 103
methanol (methyl alcohol) 10, 97
2-methoxy ethanol 101
methyl acetate 100
methyl acrylate 104
methyl alcohol (methanol) 10, 97
methyl (n-amyl) ketone 103
methyl butyl ketone 61, 102
methyl Cellosolve® 101
methyl Cellosolve® acetate 62,
100, 101
methyl chloroform 62, 108
methylcyclohexane 97
methylene bisphenyl isocyanate (MDI)
104
methylene chloride 10, 19, 62, 98
methyl ethyl ketone 10, 19, 60,
101
5-methyl-3-heptanone 102
methyl isobutyl ketone 10, 61
methyl methacrylate 104
mica 9
microorganisms 12
mildew 9, 12
mildewcides 12
mill(s) 6, 14, 41, 73, 92
mineral spirits 10, 101
molybdates 69
molybdenum 105

N

naphtha (coal tar) 62, 101
naphthalene 62, 98
nickel 62, 95
nitrocellulose 41
nitrogen dioxide 108
nitroparaffins 8, 9, 10, 103
2-nitropropane 10, 103
noise 1, 39, 41, 42, 51, 52, 118
nuisance (inert) dust 61, 95

KEY WORD INDEX (CONTINUED)

O

octane 97
 oil(s) 2, 7, 8, 9, 10, 11, 13,
 14, 15, 16, 17, 42, 75, 91, 92
 organosol 92
 organotin 62, 69
 oxygenated solvents 8, 9, 10

P

paint removers 1, 2, 19, 69
 paraffins 10
 pebble mills 14, 16, 41, 73, 92
 pentachlorophenol 12, 105
 pentane 97
 2-pentanone 103
 perchloroethylene 62, 99
 petroleum distillates (naphtha)
 62, 101
 phenol 42, 69
 phenolic(s) 8, 9
 phenyl glycidyl ether 105
 phenylmercury salts 12
 phosphates 69
 photoinitiators 44
 phthalic acid 91
 phthalic anhydride 42, 62, 108
 phthalocyanine 8
 pigment(s) 1, 2, 7, 8, 9, 11, 12,
 13, 14, 16, 17, 18, 40, 41, 43,
 45, 46, 59, 66, 67, 69, 70, 91,
 92, 93, 94
 pine oil 10
 plasticizer(s) 8, 11, 92
 plastisol 92
 polybasic acids 91
 polyester(s) 8, 9, 16
 polyhydric alcohols 91
 polyurethanes 10
 powder coatings 4, 5, 16, 17,
 18, 43, 77, 92
 preservatives 6, 8, 12
 primer(s) 2, 3
 n-propyl acetate 62, 100
 propyl alcohol 97
 putties 1, 2, 17
 pyridine 108

Q

quartz 62, 95
 quinone 103

R

radiation-curable coatings 4, 17,
 44, 68, 73, 77, 92
 raw material(s) 1, 2, 6, 7, 8,
 14, 17, 19, 39, 40, 42, 54, 59,
 63, 66, 68, 69, 92
 Raynaud's phenomenon 51
 reactor(s) 2, 7, 14, 15, 16, 42,
 43, 73
 reproductive effects 100
 resin(s) 1, 2, 7, 8, 9, 14, 15,
 16, 17, 18, 41, 43, 45, 59, 75,
 91, 92, 93
 rosins 8, 9

S

semidrying oils 9
 shellac 8, 9, 10, 14, 19
 silica 8, 9, 62, 95, 109
 silicones 10
 silver 105
 sodium hydroxide 108
 solvent(s) 1, 2, 4, 5, 6, 7, 8,
 9, 10, 14, 15, 16, 17, 19, 40,
 41, 42, 43, 44, 45, 54, 59, 62,
 66, 68, 73, 75, 77, 91, 92, 93,
 96, 101, 110
 stain(s) 1, 2, 3, 12, 17
 static electricity 40, 54
 stoddard solvent 62, 101
 styrene 62, 105
 styrene-butadiene resins 8, 9
 sulfuric acid 62, 109
 surfactants 11

T

talc 8, 9, 62, 96
 terpenes 9, 10, 103
 tetrachloroethylene 62, 99
 tetrahydrofuran 10, 100
 tetrahydrofurfural alcohol 10
 thickeners 8, 19
 thickening agents 11

KEY WORD INDEX (CONTINUED)

thinner(s) 2, 6, 15, 16
 tin 62, 105
 titanium dioxide 8, 9, 17, 62, 96
 toluene 10, 19, 62, 98
 toluene-2,4-diisocyanate (TDI)
 62, 104
 tributyl phosphate 62, 106
 tributyltin oxide 12
 trichloroethylene 99
 n-(trichloromethylthio)phthalimide
 12
 triethylamine 62, 106
 trimellitic anhydride 62, 106
 triorthocresyl phosphate 106
 turpentine 8, 10, 103
 two-part catalyzed coatings 4, 5,
 93

U

ultraviolet-curable coatings 44
 urethane(s) 8, 9, 93

V

varnish(es) 1, 2, 3, 5, 6, 7, 10,
 13, 14, 15, 16, 19, 20, 42, 43,
 45, 69, 73, 74, 91, 92, 93
 vinyl chloride 62, 105, 119
 vinyls 9, 10
 VM&P naphtha 10

W

worker/container coupling 49
 worker/floor coupling 49, 50

X

xylene (xylol) 10, 19, 62, 98

Z

zinc chloride fume 8, 109
 zinc metal 8, 69
 zinc naphthenate 12
 zinc oxide 8, 12, 62, 69, 96, 106
 zirconium compounds 106

REFERENCE INDEX

<u>Reference</u>	<u>Page</u>	<u>Reference</u>	<u>Page</u>
1	2, 4, 5, 8, 9, 10, 11, 12	36	44
2	2, 4, 9, 10, 11, 12, 13, 17, 41, 54, 59, 66	37	44, 73
3	2	38	45
4	2	39	46, 47
5	2	40	47, 48
6	2, 3, 4, 5, 7, 9, 10, 77	41	48, 49, 50
7	4	42	51
8	4	43	51, 59, 66, 73
9	5, 12	44	51, 66, 68, 73
10	5	45	51
11	5, 20, 46	46	51
12	6, 7, 13, 15	47	54
13	7, 12, 69	48	60, 61, 62
14	9	49	64, 110
15	10	50	64
16	11, 12	51	65
17	11	52	66, 67
18	13, 15, 16, 43, 73	53	66
19	13, 14, 15, 16, 42, 69, 72, 73, 74	54	66
20	16	55	68
21	17	56	68, 101
22	18, 43	57	68
23	19, 66, 69	58	68
24	19	59	69
25	20, 21	60	69, 70
26	20	61	69
27	20	62	69, 75
28	20, 21, 22, 23, 24, 31, 37, 38, 40, 46, 75	63	73
29	38	64	75
30	40, 59	65	75
31	40, 54	66	75
32	40, 54, 55, 56, 57, 58	67	75
33	41, 51	68	75
34	41, 51, 52, 53	69	77
35	42	70	77
		71	77
		72	94
		73	94
		74	94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109
		75	94
		76	94

REFERENCE INDEX (CONTINUED)

<u>Reference</u>	<u>Page</u>	<u>Reference</u>	<u>Page</u>
77	94	101	104
78	95	102	104
79	95	103	104
80	95	104	104
81	95	105	104
82	95	106	104
83	96, 106	107	105
84	96, 101, 102, 103	108	105
85	96	109	105
86	96	110	105
87	97	111	105
88	97	112	106
89	97	113	107
90	98	114	107
91	98	115	107
92	99	116	107
93	99	117	107
94	99	118	107
95	99	119	107
96	99	120	107
97	100, 101	121	107
98	103	122	108
99	104	123	108
100	104	124	108
		125	109

DEPARTMENT OF HEALTH AND HUMAN SERVICES
PUBLIC HEALTH SERVICE
CENTERS FOR DISEASE CONTROL
NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH
ROBERT A. TAFT LABORATORIES
4676 COLUMBIA PARKWAY, CINCINNATI, OHIO 45226

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE. \$300

Special Fourth Class - Book



POSTAGE AND FEES PAID
U.S. DEPARTMENT OF HHS
HHS 396