

ANNEX N

GLOBAL POSITIONING SYSTEM DATA TRANSFER FORMAT
(G-FILE)

This annex contains information about the Global Positioning System (GPS) Data Transfer Format (G-File) records. The G-File consists of eight 80-column record types that are used to document the results of the computation of relative vectors, expressed as components, from simultaneously observed GPS phase measurements. There may be only one G-file for a project. Each G-file must contain one Project Record (A) and one or more Session Header Records (B). A Session Header Record (B) is required for each individually processed vector or each simultaneously processed group of vectors (session) at three or more survey points. Each Session Header Record is followed by one or more Vector (C) and/or Long Vector (F) Records, Correlation (D) or Covariance (E) Records, optional Coordinate (G) Records, and optional and/or required Station Information (H) Records. Vector and Long Vector Records contain relative vector components between two survey points. Correlation Records contain the off-diagonal elements only of the correlation matrix for the vector components in a session. Covariance Records contain the off-diagonal elements only of the covariance matrix for the vector components in a session. The records for a simultaneously processed vector set may only contain correlation or covariance records but not a mix of the two. A Long Vector Record may only be used when a vector component is larger than +/- 999,999.9999 meters. The Coordinate (G) Records may be used to record, for informational purposes within the G-file, the coordinates of survey points held fixed during the vector computations or to provide location information regarding the G-file. Relative vectors are required even if coordinates are included. Station Information Records are used to document differing conditions or solution types for vectors within a session. The Station Information Record (H) is required only when an external time standard is used with a receiver, when a comment needs to be made about a station occupation, or when information about a station occupation or vector solution is not the same as for all other stations or vectors in a session. Multiple H records are allowed.

This annex documents the record formats, provides an explanation of the fields within each record, and gives G-file examples using the various record types.

<u>CC-1 CODE</u>	<u>RECORD TYPE</u>	
A	Project Record	(required)
B	Session Header Record	(required)
C	Vector Record	(required)
D	Correlation Record	(Either the D record or the
E	Covariance Record	(E record is required)
F	Long Vector Record	
G	Coordinate/Absolute Position Record	(optional)
H	Station Information Record	
I	Session Models Record	(optional; follows the B record if used)

Project Record

01-01	A		
02-03	Job Code (Chapter 1)		Alpha
04-07	Year, Start of Project (local) (CCYY)		Integer
08-09	Month, Start of Project (local) (MM)		Integer
10-11	Day, Start of Project (local) (DD)		Integer
12-15	Year, End of Project (local) (CCYY)		Integer
16-17	Month, End of Project (local) (MM)		Integer
18-19	Day, End of Project (local) (DD)		Integer
20-78	Title of project		Alpha
79-80	Reserved		

Session Header Record

01-01	B		
02-05	Year, First Actual Measurement (UTC) (CCYY)		Integer
06-07	Month, First Actual Measurement (UTC) (MM)		Integer
08-09	Day, First Actual Measurement (UTC) (DD)		Integer
10-13	Time, First Actual Measurement (UTC) (HHMM)		Integer
14-17	Year, Last Actual Measurement (UTC) (CCYY)		Integer
18-19	Month, Last Actual Measurement (UTC) (MM)		Integer
20-21	Day, Last Actual Measurement (UTC) (DD)		Integer
22-25	Time, Last Actual Measurement (UTC) (HHMM)		Integer
26-27	Number of Vectors in the Session		Integer
28-42	Software Name & Version		Alpha
43-47	Orbit Source (agency that computes orbit)		Alpha
48-51	Orbit accuracy estimate (XX.xx meters)	Implied	Decimal
52-53	Solution coordinate system code (table, N-6)		Integer
54-55	Solution meteorological use code (table, N-6)		Integer
56-57	Solution ionosphere use code (table, N-6)		Integer
58-59	Solution time parameter use code (table, N-6)		Integer
60-60	Nominal accuracy code (table, N-8)		Integer
61-66	Processing agency code (Annex C)		Alpha
67-70	Year of Processing (CCYY)		Integer
71-72	Month of processing (MM)		Integer
73-74	Day of processing (DD)		Integer
75-80	Solution Type (table, N-7)		Alpha

Note: Columns 43 through 47 of Record B contain the symbol of the agency which computes and provides GPS satellite orbit information. Columns 61 through 66 contain the symbol of the agency that does the observation reduction processing. Columns 52 through 80 of Record B assume all stations use identical observing and computation procedures. If this is not the case, use Record H to record the differences for each station which varies from those conditions noted on the B record.

Note: If the number of vectors in a session exceeds 99, leave columns 26 through 27 blank. In such cases, the number of vectors can be determined by counting the "C" records or the "F" records.

Vector Record

01-01	C		
02-05	Origin Station Serial Number (ssn)	(vector tail)	Integer
06-09	Differential Station Serial Number	(vector head)	Integer
10-20	Delta X	(XXXXXXXX.xxxx meters)	Implied Decimal
21-25	Standard Deviation	(X.xxxx meters)	Implied Decimal
26-36	Delta Y	(XXXXXXXX.xxxx meters)	Implied Decimal
37-41	Standard Deviation	(X.xxxx meters)	Implied Decimal
42-52	Delta Z	(XXXXXXXX.xxxx meters)	Implied Decimal
53-57	Standard Deviation	(X.xxxx meters)	Implied Decimal
58-58	Rejection Code (use upper case R to reject)		Alpha
59-68	Origin Station Data Media Identifier		(See page N-6)
69-78	Differential Station Data Media Identifier		(See page N-6)
79-80	Reserved		

Note: Standard deviation values must be positive, non-zero numbers.

Correlation Record

01-01	D		
02-04	Row Index Number		Integer
05-07	Column Index Number		Integer
08-16	Correlation	(XX.xxxxxxxx)	Implied Decimal
17-19	Row Index Number		Integer
20-22	Column Index Number		Integer
23-31	Correlation	(XX.xxxxxxxx)	Implied Decimal
32-34	Row Index Number		Integer
35-37	Column Index Number		Integer
38-46	Correlation	(XX.xxxxxxxx)	Implied Decimal
47-49	Row Index Number		Integer
50-52	Column Index Number		Integer
53-61	Correlation	(XX.xxxxxxxx)	Implied Decimal
62-64	Row Index Number		Integer
65-67	Column Index Number		Integer
68-76	Correlation	(XX.xxxxxxxx)	Implied Decimal
77-80	Reserved		

Note: This record is to record the off-diagonal correlates only from the session (or vector) correlation matrix. Since the correlation matrix is symmetric about the diagonal, only the upper or the lower half should be recorded.

Covariance Record

01-01	E		
02-04	Row Index Number		Integer
05-07	Column Index Number		Integer
08-19	Covariance (XXXX.xxxxxxxx meters ²)	Implied	Decimal
20-22	Row Index Number		Integer
23-25	Column Index Number		Integer
26-37	Covariance (XXXX.xxxxxxxx meters ²)	Implied	Decimal
38-40	Row Index Number		Integer
41-43	Column Index Number		Integer
44-55	Covariance (XXXX.xxxxxxxx meters ²)	Implied	Decimal
56-58	Row Index Number		Integer
59-61	Column Index Number		Integer
62-73	Covariance (XXXX.xxxxxxxx meters ²)	Implied	Decimal
74-80	Reserved		

Note: This record is to record the off-diagonal covariances only from the vector variance-covariance matrix. The square root of the diagonal elements, the component standard deviations, are recorded on records C and F. Since the variance-covariance matrix is symmetric about the diagonal, only the upper or the lower half should be recorded.

Long Vector Record

01-01	F		
02-05	Origin Station Serial Number (ssn) (vector tail)		Integer
06-09	Differential Station Serial Number (vector head)		Integer
10-22	Delta X (XXXXXXXXXX.xxxx meters)	Implied	Decimal
23-27	Standard Deviation (X.xxxx meters)	Implied	Decimal
28-40	Delta Y (XXXXXXXXXX.xxxx meters)	Implied	Decimal
41-45	Standard Deviation (X.xxxx meters)	Implied	Decimal
46-58	Delta Z (XXXXXXXXXX.xxxx meters)	Implied	Decimal
59-63	Standard Deviation (X.xxxx meters)	Implied	Decimal
64-64	Rejection Code (use upper case R to reject)		Alpha
65-65	Origin station manufacturer code		(N-6)
66-68	Origin station UTC day of year of occupation (DDD)		Integer
69-69	Origin station year of occupation (Y) UTC		Integer
70-70	Origin station session indicator		Alpha
71-71	Differential station manufacturer code		(N-6)
72-74	Differential station day of year (DDD) UTC		Integer
75-75	Differential station year of occupation (Y) UTC		Integer
76-76	Differential station session indicator		Alpha
77-80	Reserved		

Note: Standard deviation values must be positive, non-zero numbers.

Coordinate Record

01-01 G
02-02 Blank
03-03 Record usage code K - see below
04-05 Blank
06-09 Station Serial Number
10-10 Blank
11-14 Optional 4-character ID or "short" station name - see below
15-15 Blank
16-20 Coordinate frame designator (e.g. NAD 83, WGS 84, NAD 27, WGS 72, ITR 90, etc.; inquire for additions)
21-21 Blank
22-33 X coordinate (XXXXXXXX.xxxx meters) Implied Decimal
34-34 Blank
35-46 Y coordinate (YYYYYYYY.yyyy meters) Implied Decimal
47-47 Blank
48-59 Z coordinate (ZZZZZZZZ.zzzz meters) Implied Decimal
60-60 Blank
61-64 Sigma X (SS.ss m) blank if unknown or greater than 99.99 m
65-65 Blank
66-69 Sigma Y (SS.ss m) blank if unknown or greater than 99.99 m
70-70 Blank
71-74 Sigma Z (SS.ss m) blank if unknown or greater than 99.99 m
75-80 Reserved

K = 0 or blank indicates that the position is approximate and has no particular interpretation.

K = 1 indicates that these are exact coordinates (to 0.1 mm) used during the processing of the G-file vectors.

The 4-character ID or "short" name, if used in cc 11-14, should be the same abbreviation used elsewhere in the G-file (Data Media Identifier) and in other related data files (for example, the *25* records of the B file).

Station Information Record

01-01 H
02-05 Station Serial Number (ssn) Integer
06-09 Four Character Identifier Alpha
10-11 External frequency standard code (table, N-8)
12-13 Vector meteorological use code (table, N-6)
14-15 Vector time parameter use code (table, N-6)
16-17 Vector ionosphere use code (table, N-6)
18-23 Vector Solution type (table, N-7)
24-78 Comments Alpha
79-80 Reserved

Use comment field to record clarifying information or instrument type if noted as "other" in Data Media Identifier.

Session Model Record

01-01 I
02-13 Name of Antenna Pattern File
14-21 Reserved
22-27 Agency/Source of Antenna Pattern File (From Annex C)
28-35 Version/Date for Antenna Pattern File (YYYYMMDD)
36-80 Blank

CODE TABLES

Solution Coordinate Reference System Codes

01 -- WGS 72 Precise Ephemeris [DMA] Used from GPS beginning through 1/3/87
02 -- WGS 84 Precise Ephemeris [DMA] from 1/4/87 through 1/1/94
03 -- WGS 72 Broadcast Ephemeris [DOD] from GPS beginning through 1/22/87
04 -- WGS 84 Broadcast Ephemeris [DOD] from 1/23/87 through 6/28/94
05 -- ITRF 89 Epoch 1988.0 (International Earth Rotation Service
NOT USED AS A GPS REFERENCE FRAME
06 -- NEOS 91.25 Epoch 1988 [NGS] from Spring 1991 through 10/19/91
SPECIAL VLBI COORDINATE SOLUTION written by Mike Abell
07 -- NEOS 90 Epoch 1988.0 [NGS] from 10/20/91 through 8/15/92
08 -- ITRF 91 Epoch 1988.0 [NGS] from 8/16/92 through 12/19/92
09 -- SIO/MIT 1992.57 Epoch 1992.57 [NGS] from 12/20/92 through 11/30/93
10 -- ITRF 91 Epoch 1992.6 [NGS] from 12/1/93 through 1/8/94
11 -- ITRF 92 Epoch 1994.0 [NGS] from 1/9/94 through 12/31/95
12 -- ITRF 93 Epoch 1995.0 [NGS] from 1/1/95 through 6/29/96
13 -- WGS 84 (G730) Epoch 1994.0 [DMA] from 1/2/94 through 9/28/96
14 -- WGS 84 (G730) Epoch 1994.0 Broadcast [DOD USAF] from 6/29/94 through 1/28/97
15 -- ITRF 94 Epoch 1996.0 [NGS] from 6/30/96 through 2/28/98
16 -- WGS 84 (G873) Epoch 1997.0 [NIMA] (formerly DMA) from 9/29/96 to the present
17 -- WGS 84 (G873) Epoch 1997.0 Broadcast [DOD USAF] from 1/29/97 to the present
18 -- ITRF 96 Epoch 1997.0 [NGS] from 3/1/98 through 7/31/99
19 -- ITRF 97 Epoch 1997.0 [NGS] from 8/1/1999 through 6/3/2000
20 -- IGS 97 Epoch 1997.0 [NGS] from 6/4/2000 through 12/1/2001
21 -- ITRF 00 Epoch 1997.0
22 -- IGS 00 Epoch 1998.0 [NGS] from 12/2/2001 through January 10, 2004
23 -- WGS 84 (G1150) Epoch 2001.0 [NIMA] from January 20, 2002 to the present
24 -- IGB 00 Epoch 1998.0 [NGS] from 0000 UTC January 11, 2004 to the present

Solution Meteorological Use Codes

01 -- Default values used (model used)
02 -- Observed meteorological data used
03 -- Water vapor radiometer used

Solution Ionosphere Use Code

01 -- None
02 -- Dual frequency ionospheric correction used
03 -- Ionospheric model used

Solution Time Parameter Use Codes

01 -- Observed time synchronization data used
02 -- Time parameters solved for in data reduction

Data Media Identifier

Required format: ADDDYSCCCC where

A is one of the following characters which indicates the manufacturer of the receiver used for the observation:

A = Ashtech, Inc; C = Topcon Corp; D = Del Norte Technology, Inc;
E = Magellan; G = Allen Osborne; I = Istac; J = Javad Position Systems;
K = Sokkia; L = MINI-MAC^R; M = MACROMETER^R; N = Norstar Instruments;
O = Motorola, Inc; P = Spectra Precision; Q = 3S Navigation;
R = Trimble Navigation Ltd.; S = SERCEL, Inc; T = Texas Instruments;
V = NovAtel Communications Ltd; W = Wild, Leica, Magnavox; X = other

DDD is the day of the year of the first data epoch (UTC)

Y is the last digit of the year of the first data epoch (UTC)

S is an alphanumeric designation of the session

CCCC is the project-unique, four-character ID or abbreviation of a station designation used to cross-reference station occupations between the B and G files

CODE TABLES (continued)

Solution Type Use Codes

+ L1TD--	L1SDFL	L1DDFL	IFDDFL	OTDDFL	K1DDFX
+ L2TD--	L1SDFX	L1DDFX	IFDDFX	OTDDFX	K2DDFX
+ IFTD--	L1SDPF	L1DDPF	IFDDPF	OTDDPF	K1DDFX
+ WLTD--					KWDDFX
		L2DDFL	WLDDFL		P1DDFX
		L2DDFX	WLDDFX		P2DDFX
		L2DDPF	WLDDPF		P1DDFX
					PWDDFX

Where: L1 = Frequency 1
 L2 = Frequency 2
 IF = Ionosphere Free Combination (Static) *
 WL = Wide Lane Combination (Static or Rapid Static)**
 OT = Other (Explain in Station Information Record)

K1 = L1 Kinematic Observation (Single visit, continuous lock - also known as Continuous Kinematic, Stop and Go Kinematic, or On-the-Fly Kinematic)

K2 = L2 Kinematic

KI = Ionosphere Free Combination Kinematic *

KW = Wide Lane Combination Kinematic **

P1 = L1 Pseudo-kinematic (Two or more visits, intermittent lock - also known as Pseudo-static, Intermittent Static or Reoccupation techniques)

P2 = L2 Pseudo-kinematic

PI = Ionosphere Free Combination Pseudo-kinematic *

PW = Wide Lane Combination Pseudo-kinematic **

TD = Triple Difference Solution

DD = Double Difference Solution

SD = Single Difference Solution

FL = Float (real number) estimate of biases

FX = Fixed integer estimate of biases

PF = Partial, fixed integer estimate of biases
 (Not all integer biases determinable).

+ Triple Difference Solutions have no integer ambiguities, leave trailing columns blank.

* IF = ionosphere free = $\{f_1^2/(f_1^2 - f_2^2)\}L_1 - \{f_1f_2/(f_1^2 - f_2^2)\}L_2$

** WL = wide lane = $L_1 - L_2$

Where, $f_1 = 1575.42$ MHz, $f_2 = 1227.60$ MHz, and L_1 and L_2 are phase measurements in units of cycles.

CODE TABLES (continued)

External Frequency Standard

- 01 -- No external frequency standard used
- 02 -- Rubidium frequency standard used
- 03 -- Cesium frequency standard used
- 04 -- Hydrogen Maser frequency standard used
- 05 -- External crystal frequency standard used
- 06 -- Other (Comment in Station Information Record)

Vector Nominal Accuracy Codes

		Order/Class
4	-- Intended accuracy 100 ppm plus 5.0 cm	3
3	-- Intended accuracy 50 ppm plus 3.0 cm	2-II
2	-- Intended accuracy 20 ppm plus 2.0 cm	2-I
5	-- Intended accuracy 10 ppm plus 1.0 cm	1
6	-- Intended accuracy 1 ppm plus 0.8 cm	B
7	-- Intended accuracy 0.1 ppm plus 0.5 cm	A
8	-- Intended accuracy 0.01 ppm plus 0.3 cm	AA

G-FILE EXAMPLES

Below are fragments from six independent, simulated GPS Data Transfer Format files (G-FILES). There is one Project record (A) per G-file. Each session vector set, or individually computed vector in a multi-receiver session, requires a Session Record (B). Each vector requires at least one Vector Record (C) or Long Vector Record (F). Vector Records with Coordinate Records must follow the same Session Record. Station Information (H) Records are required as circumstances dictate and may be optionally added where not required. These records must be followed by sufficient Correlation (D) or Covariance Records (E) to express all off-diagonal correlation or covariance terms in the matrix half provided from the session computation. Correlation and Covariance Records may not be intermixed.

1. Project (A), Session (B), Vector (C), and Correlation (D) records for a single vector between two stations in a two receiver session or individually computed vector in a multi-receiver session.

```
AKS1989061619890810
B19890622210419890623003201OMNI21JUL89      BDCST200040101025NGS      19890919L1DDFX
C02860255  22818804  691  517712752 1665  621497962 1259 M1739APACIM1739AK60A
D 1 2 -1507832 1 3 -1653265 2 3 -9400487
```

2. Project (A), Session (B), Vector (C), and Correlation (D) records for a three-receiver (two vector) session computed simultaneously in session mode.

```
AA21989061619890810
B198907191920198907192022020MNI21JUL89      NSWC 200020202026NGS      19891010IFDDFL
C02520251  2090836  21  3595939  80  5412122  45 T1735BTOLPT1735BIO35
C02520250 -42878920  42 -19024426  93 -28455946  69 T1735BTOLP71735BIO17
D 1 2 -3449463 1 3 -169254 1 4 -7443040 1 5 -3452654 1 6 1753975
D 2 3 -7698120 2 4 -6329835 2 5 1258498 2 6 8573493 3 4 -6485385
D 3 5 -6084380 3 6 -477478 4 5 -6124087 4 6 -3864367 5 6 8630812
```

Note: If a multi-receiver session is computed as if all possible vectors are independent, then there would be Session, Vector, and Correlation records for each vector in the session. Thus, the record sequence would be A, B, C, D, B, C, D, B, C, D, etc. The Session records would be nearly identical to the multi-receiver example except that start and stop times could vary with each vector. The number of vectors indicated on each Session Record would be one, i.e., there would be a Session Record for each vector and the cross correlation terms between vectors would not exist.

3. Project (A), Session (B), Vector (C), and Correlation (D) Records for a five-receiver (four vector) session computed simultaneously in session mode.

AW11989061619890810

B19890718192419890718225204OMNI21JUL89 BDCST 200020202025NGS 19891003L1DDFL
 C03000287 5764741 77 1459095 44 2345097 54 R1765ASMILR1765ANEOP
 C03000223 -52521873 47 -229406 101 -1142670 75 R1765ASMILR1765ACESZ
 C03000305 -42878920 42 -19024426 93 -28455945 69 R1765ASMILR1765AX042
 C03000240 7097171 69 -1171456 40 -1443438 46 R1765ASMILR1765AG042
 D 1 2 -7621157 1 3 -6268111 1 4 1032188 1 5 -7397468 1 6 2749723
 D 1 7 -7716473 1 8 -6339150 1 9 1294594 1 10 -2396473 1 11 -2753742
 D 1 12 -5804898 2 3 -791184 2 4 -6108347 2 5 -1739462 2 6 9010327
 D 2 7 -7729301 2 8 -6463718 2 9 1526641 2 10 -3826492 2 11 3610736
 D 2 12 -6449538 3 4 170894 3 5 -6299216 3 6 -1003847 3 7 -5307149
 D 3 8 -7680811 3 9 -6477668 3 10 1506536 3 11 -9537262 3 12 -1836426
 D 4 5 -6154878 4 6 -248020 4 7 -6087715 4 8 -1633847 4 9 6354725
 D 4 10 -7804602 4 11 -6047825 4 12 1262026 5 6 3746287 5 7 -7243634
 D 5 8 -6110139 5 9 -321344 5 10 -6165227 5 11 8362528 5 12 9162533
 D 6 7 -5971690 6 8 -516393 6 9 -6136978 6 10 -9354622 6 11 1535474
 D 6 12 -5920223 7 8 -559594 7 9 -6153794 7 10 2645373 7 11 -5373742
 D 7 12 -5527744 8 9 -7793107 8 10 1043462 8 11 5378213 8 12 -2564522
 D 9 10 -5371777 9 11 -7908942 9 12 1046883 10 11 8354256 10 12 -3372634
 D 11 12 7153372

4. Project (A), Session (B), Vector (C), and Covariance (E) Records for a three-receiver (two vector) session computed simultaneously in session mode.

AC51989061619890810

B198907191920198907192022020MNI21JUL89 NSWC 200020202026NGS 19891010WLDDPF
 C02520251 2090836 21 3595939 80 5412122 45 T1735BTOLPT1735BIO35
 C02520250 -42878920 42 -19024426 93 -28455946 69 T1735BTOLPT1735BIO17
 E 1 2 -3449231 1 3 169013 1 4 -7443219 1 5 -3452017
 E 1 6 -1753648 2 3 7698884 2 4 -6329438 2 5 1258689
 E 2 6 8573027 3 4 -6485903 3 5 -6084227 3 6 -477369
 E 4 5 6124824 4 6 -3864711 5 6 8630682

5. Project (A), Session (B), Long Vector (F), and Correlation (D) Records for a three-receiver (two vector) session computed simultaneously in session mode.

AM31989061619890810

B199003121920199003122022030MNI21JUL89 NSWC 200050202027NGS 19900605IFDDPF
 F02520251 -7398138095 62 -611028070 140 -759539795 81 R0710AR0710A
 F02520210 -28097365450 2 6537703840 2 1612488880 2 R0710AR0710A
 D 1 2 -3449463 1 3 -169254 1 4 -7443040 1 5 -3452654 1 6 1753975
 D 2 3 -7698120 2 4 -6329835 2 5 1258498 2 6 8573493 3 4 -6485385
 D 3 5 -6084380 3 6 -477478 4 5 -6124087 4 6 -3864367 5 6 8630812

6. Project (A), Session (B), Vector (C), Coordinate (G), Station Information (H), and Correlation (D) Records for a five-receiver session computed simultaneously.

```

AG41989061619890810
B19921019162019921019202204OMNI06JAN93      NGS      50090202027NGS      19930115IFDDFX
C02520251 -121666909   30  157350726   56  117976050   41  R2932ANORDR2932ASECO
C02520250 -418472429   32  247232117   60   8372071   44  R2932ANORDR2932ABURR
C02520253 -553950607   35  500052515   64  221106176   48  R2932ANORDR2932AFIGU
C02520254 -289152973   31  300310186   55  183697838   42  R2932ANORDR2932APINE
G 1  0252  NORD  SIO92 -25711011350 -45925184360 35928923390 010 010 010
H0252NORD01020202IFDDFXREFERENCE STATION
D 1  2 -7621157   1  3 -6268111   1  4  1032188   1  5 -7397468   1  6  2749723
D 1  7 -7716473   1  8 -6339150   1  9  1294594   1 10 -2396473   1 11 -2753742
D 1 12 -5804898   2  3  -791184   2  4 -6108347   2  5 -1739462   2  6  9010327
D 2  7 -7729301   2  8 -6463718   2  9  1526641   2 10 -3826492   2 11  3610736
D 2 12 -6449538   3  4   170894   3  5 -6299216   3  6 -1003847   3  7 -5307149
D 3  8 -7680811   3  9 -6477668   3 10  1506536   3 11 -9537262   3 12 -1836426
D 4  5 -6154878   4  6  -248020   4  7 -6087715   4  8 -1633847   4  9  6354725
D 4 10 -7804602   4 11 -6047825   4 12  1262026   5  6  3746287   5  7 -7243634
D 5  8 -6110139   5  9  -321344   5 10 -6165227   5 11  8362528   5 12  9162533
D 6  7 -5971690   6  8  -516393   6  9 -6136978   6 10 -9354622   6 11  1535474
D 6 12 -5920223   7  8  -559594   7  9 -6153794   7 10  2645373   7 11 -5373742
D 7 12 -5527744   8  9 -7793107   8 10  1043462   8 11  5378213   8 12 -2564522
D 9 10 -5371777   9 11 -7908942   9 12  1046883  10 11  8354256  10 12 -3372634
D 11 12  7153372

```