

2/5/07

LONG-TERM RETARDANT

Qualified by USDA Forest Service In Accordance with Forest Service Specification 5100-304b, As Amended

The listed products are qualified and approved for use, only at the specified mix ratio, and only with the indicated application equipment.

Consult individual agencies for specific policies relating to long-term retardant use.

<u>Chemical</u>	Mix Ratio	Qualified/Approved Applications ¹				
	(Pounds concentrate Per gallon water)	Fixed-Wing Airtanker	SEATS	Fixed-Tank Helicopter	Helicopter Bucket	Ground Engine
Phos-Chek D75-R	1.20 lb/gal	•	•		•	
Phos-Chek D75-F	1.20 lb/gal	•	•		•	
Dry Concentrate - Gum-thick	ened; Temporary Base					
Phos-Chek 259-R	1.14 – 1.60 lb/gal	•	•	•	•	•
Phos-Chek 259-F	1.14 – 1.60 lb/gal	•	•	•	•	•
Phos-Chek G75-F	1.12 lb/gal	•	•		•	•
Phos-Chek G75-W	1.12 lb/gal				•	•
Wet Concentrate - Gum-thick	ened; Permanent or Tempor	rary Base				
Phos-Chek LV-R	3.6:1	•	•		•	•
Phos-Chek LC-95A-R	5.5:1	•	•		•	•
	complies with all requirements roduct complies with all require			aluation; a field evaluation	on is required for full qu	alification.