



Sample abbreviated label below shows the structure of a tight fitting CBRN PAPR canister label.

Color of the label must be olive.

This label must be attached to the canister. If the label does not fit on the canister, the portion of the label below the dashed line may be provided in a form that is removable, as long as the Cautions and Limitations in the boxed area are added. Dashed lines are added here for illustration only and should not appear on production labels.

	XYZ Safety Company ANYWHERE USA 1-800-XXX-XXXX	
Approval Number TC-14G-XXXX	Canister P/N 12345XYZ Protections CBRN PAPR Cap 1	CAUTIONS AND LIMITATIONS AFHJLMNORYZ.BB.CC.GG.UU.VV

REFER TO THE APPROVED USER'S INSTRUCTIONS FOR THE COMPLETE LIST OF COMPONENT PARTS MAKING UP THE APPROVED ASSEMBLY.

2. CAUTIONS AND LIMITATIONS
A-Not for use in atmospheres containing less than 19.5 percent oxygen.
F-Do not use powered air-purifying respirators if airflow is less than four cfm (115 lpm) for tight fitting facepieces and six cfm (170 lpm) for hoods and/or helmets.
H-Follow established cartridge and canister change schedules or observe ESLI to ensure that cartridges and canisters are replaced before breakthrough occurs.
J-Failure to properly use and maintain this product could result in injury or death.
L-Follow the manufacturer's User's Instructions for changing canister(s).
M-All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
N-Never substitute, modify, add or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
O-Refer to User's Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
(If applicable)S-Special or critical User's Instructions and/or specific use limitations apply. Refer to User's Instructions before donning.

3. CBRN CAUTIONS AND LIMITATIONS
R-Some CBRN agents may not present immediate effects from exposure, but can result in delayed impairment, illness, or death.
Decontamination and disposal procedures must be followed. If contaminated with liquid chemical warfare agents, dispose of the respirator after decontamination.
Y-The respirator provides respiratory protection against inhalation of radiological and nuclear dust particles. Procedures for monitoring radiation exposure and full radiation protection must be followed.
Z-If during use, an unexpected hazard is encountered such as a secondary CBRN device, pockets of entrapped hazard or any unforeseen hazard, immediately leave the area for clean air.
BB-Not for use for entry into atmospheres immediately dangerous to life or health.
CC-For entry, do not exceed maximum use concentrations established by regulatory standards.
GG-Direct contact with CBRN agents requires proper handling of the respirator after use. Correct disposal procedures must be followed.
UU-The respirator should not be used beyond eight (8) hours after initial exposure to chemical warfare agents to avoid possibility of agent permeation. If liquid exposure is encountered, the respirator should not be used for more than two (2) hours.
VV-PAPRS with TC-23C approvals may not be used for escape from IDLH atmospheres.