



Management and Control Measures

(Tab K)

Norman R. Francingues, MSEE

frasang@canufly.net

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Training Objectives

- To become familiar with a variety of management and control measures.
- Identify differences between engineered and operational controls for environmental dredging projects.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Control Measures

- Engineered Containment for
 - Resuspension
 - Residuals
 - Volatiles
 - Noise
- Operational Controls



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Resuspension Principles

- 3 R's – Resuspension, Release, Residual
- All dredges resuspend some sediment
- Operations must be properly managed
- Resuspension generally not a problem for navigation
- Resuspension is a serious concern for remedial dredging


4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Resuspension Concerns

- Navigation
 - Seasonal restrictions (windows)
 - Physical effects of turbidity and burial
- Remedial
 - Chemical releases
 - Residual contamination



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)

Resuspension Concerns

- The actual dredging process may result in a limited impact on the water column.
- Support activities around the project may have a greater impact on the water quality.
- Ambient and local disturbances may have a similar or greater impact than the dredging operation.



(Completed)



Process & Potential Effects



- Resuspension Processes
 - Equipment specific
 - Sediment specific
 - Operator specific
 - Site specific (hydrodynamics, etc)
- Resuspension Effects
 - Physical (turbidity, contaminant migration, residual)
 - Chemical (WQS)
 - Biological (toxicity)

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Engineered Containment



- Structural Barriers
 - Cofferdams
 - Removable Dams (Portadam, Geotubes)
 - Sheet piles
- Nonstructural Barriers
 - Silt Curtains
 - Silt Screens
 - Oil booms
 - Pneumatic (Bubble) Curtains

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Coffer Dam



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Temporary Dam/Rerouting



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Portable Water Filled Dam



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Sheetpiles



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Sub-division of the Dredging Site by Contaminant Concentration



3,081 Feet of Sheetpile
Enclosed the Dredge Area




4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Primary/Secondary Containment




4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Pneumatic Barrier St. Lawrence River



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Silt Curtains



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Terminology

- What are silt or turbidity curtains/screens/barriers/gunderbooms?
 - Term used to describe devices deployed in water to control suspended solids or turbidity resulting from dredging and construction operations.
 - Used to protect water quality and sensitive aquatic habitat from dredging and construction operations.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



USACE Technical Note

- TN covers the following items:
 - Reviews the basic types of silt and turbidity curtains
 - Emphasizes the state of the practice and circumstances under which silt curtains function best
 - Presents a checklist to aid the designer or reviewer of silt curtains
 - Updates and supplements earlier corps guidance (JBF scientific corporation (1977 and 1978) on use of silt curtains.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Early Curtains

- **Florida’s “Pervious Diaper”** – 12 oz. untreated canvas supported by Styrofoam lobster trap floats and driven poles
 - Plugged quickly by marine growth, sank, and rapidly disintegrated
- **Later models** – 16-mil vinyl plastic and 10-mil Visqueen
 - Torn and penetrated by sharks and turtles

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Industry’s Response

- Replace skirt material with various thicknesses of polymeric films and reinforced with embedded woven fabric
- Flotation and ballast were “heat-sealed” into material to become integral member of commercial silt curtains
- Pole and timber supports yielded to conventional anchor-buoy systems
- Spin-offs from oil boom technology but better construction


4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Types of Curtains

- Floating and hanging
- Solid diversion baffle
- Permeable or filter
- Standing frame sinkable hanging, combinations
- Based on water or current (e.g., slack, medium, fast, rough, tidal, etc.)




4/21/2005

Environmental Dredging Workshop
Seattle, Washington 2005



Typical Floating



4/21/2005

Environmental Dredging Workshop
Seattle, Washington 2005



Mechanical Grab & Barge Operating Inside Hanging Curtin




4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Typical Standing



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Delivery/Assembly



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Deploy From Barge



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Assemble/Deploy From Land




4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Completed)



Processes Affecting Curtains



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Effectiveness Depends on:

- Nature of the operation (i.e., navigation or environmental dredging)
- Quantity and type of material in suspension within or upstream of the curtain (including debris, oils and chemicals)
- Characteristics, construction, and condition of the curtain as well as the area and configuration of the barrier enclosure (e.g., partial or full depth containment either solid or permeable)

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Effectiveness Depends on:

- Method of deployment
- Hydrodynamic conditions
 - strong currents [>1 knot or 1.5 fps]
 - high winds [especially with long fetch areas]
 - fluctuating water levels [i.e., tidal events]
 - excessive wave height, including ship wakes
 - drifting debris and ice
- Site Conditions
 - water depth, slopes, debris

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Completed)



Specialty Booms



□ Particulate Control System™ Curtains used in:


- Harbor Development
- Dredging
- Sediments and
- Construction Debris

4/21/2005

Environmental Dredging Workshop
Seattle, Washington 2005



Specialty Booms



4/21/2005

Environmental Dredging Workshop
Seattle, Washington 2005



Lessons Learned

- Very few silt curtains applications are alike.
- Each one has unique features that require a site-specific application and adaptation.
- For all practical purposes the cost-effective, limiting deployment value of 1 to 1-1/2 knot current velocity appears to be an industry standard with exceptions on a case-by-case basis.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Lessons Learned

- Effectiveness is influenced by
 - Quantity and type of suspended solids
 - Mooring method
 - Characteristics of the curtain
- Deployment should
 - Remain in place until the dredging is completed
 - Allow for traffic in and out
 - Allow relocation as dredge moves to new site

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Lessons Learned

- BMP's should cover the following topics:
 - planning considerations (site specific project conditions)
 - design or performance criteria
 - construction specifications (curtains and other materials)
 - installation or deployment, removal, decontamination, and maintenance
 - monitoring of silt curtain performance

4/21/2005

Environmental Dredging Workshop
Seattle, Washington 2005

(Completed)



Silt Curtain Bottom Line

- Silt curtains are not a one solution fits all type of best management practice.
- Highly specialized, temporary-use device.
- Selected only after careful evaluation of the intended function.
- Designed based on a detailed knowledge of the site where it will be used.

4/21/2005


Environmental Dredging Workshop
Seattle, Washington 2005



Residuals



Grasse River



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Control Measures for Residuals



- Additional cleanup passes
- Placement of a Residual Cap, a thin layer cap of clean material (few inches) to mix with and partially isolate the residual sediment
- Placement of an Isolation Cap. Thick layer same as that for in situ capping.



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Volatiles

- At the dredging site
 - Operational measures are based on
 - Nature of the site conditions
 - Very contaminant and site specific.
 - Oil sheen collection booms
- During transport
 - In barge or pipeline
- During offloading
 - Mechanically or hydraulically



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



VOC Controls During Dredging

- Operational measures may include:
 - Reducing dredging production rates to minimize resuspension and releases.
 - Overlapping dredge passes to minimize resuspension at edge of cut where sloughing may occur.
 - Modifying dredgehead to retain oils.
 - Decreasing the sweep speed of the cutterhead.
 - Modifying the dredging sequence so most of contaminated sediments dredged in winter.
 - Using night time dredging during summer months to minimize the influence of temperature and solar radiation on valorization.

4/21/2005


*Environmental Dredging Workshop
Seattle, Washington 2005*



Floating Sheen Containment



| | | | |
|----------|-------------------|------------------|-----------------|
| Results: | Sheen: | Present | No Sheen |
| | Turbidity: | 96 NTU | 1.5 NTU |
| | TSS: | 350 mg/l | 13 mg/l |
| | Chrysene | 0.36 ug/l | ND |



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



VOC Control During Transport



- Physical measures may include:
 - Covering the dredged material with physical barriers such as (foam), plastic liner, or absorbent mats or materials.
 - Degassing pipeline before discharging into onshore facility.



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



VOC Control During Offloading

- Physical measures may include:
 - Covering the dredged material with physical barriers such as (foam), plastic liner, or absorbent material.



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Noise Control

- Monitoring of noise from dredging activities to establish operating levels.
- Provide adequate muffler systems or sound dampening methods or enclosures.
- Procedural modifications to the work schedule.



Acoustical Control Measure

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Project Managers Should:

- Recognize unique project features that require a site-specific application and adaptation of control measures.
- Be aware of the increased potential for scour to occur around the outside of structural controls.
- Recognize that resuspension will occur during placement and removal of structural controls.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Continued)



Project Managers Should:

- Be aware that sheet piling can change the carrying capacity of a stream or river making it temporarily more susceptible to flooding.
- Select silt curtains only after careful evaluation of their intended function.
- Recognize that all dredging will result in some residuals requiring control measures.
- Should consider impacts of dredging volatiles and noise on project production rates and schedules.

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*

(Completed)



QUESTIONS?



4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*



Thank You

Norman R. Francingues, MSEE

frasang@canufly.net

4/21/2005

*Environmental Dredging Workshop
Seattle, Washington 2005*