

**USE INSTRUCTIONS**

1. Failure to follow all instructions and limitations concerning the use of the respirator and/or failure to wear the respirator for the whole duration of exposure to contaminants can seriously reduce the performance characteristics of the respirator and lead to illness, injury or death.
2. Before occupational use, the wearer must first be trained by the employer in the correct use of the respirator in accordance with applicable safety and health standards.
3. OSHA standards including 29CFR1910.134 (e) (5) and CSA standard Z94.4-93 require that the wearer be fit-tested.
4. Discard the respirator and replace with a new one if:
  - excessive clogging of the respirator causes breathing difficulty
  - the respirator becomes damaged.
5. Leave the contaminated area if dizziness, irritation or other distress occurs.

**Discard the respirator and replace with a new one after every use.**

**USE LIMITATIONS**

1. Do **NOT** use the respirator or enter or stay in a contaminated area under the following circumstances:
  - atmosphere contains less than 19.5% oxygen
  - if you smell or taste a contaminant
  - for protection against gases or vapors
  - contaminants or their concentrations are unknown or immediately dangerous to life or health
  - concentrations of contaminants exceed maximum use concentrations in applicable OSHA standards or applicable government regulations or 10 times the PEL (Permissible Exposure Limit), whichever is lower
  - for sandblasting, paint-spray operations, asbestos.
2. Do **NOT** modify or misuse the respirator.
3. Do **NOT** use the respirator with beards or other facial hair that interferes with direct contact between the face and the edge of the respirator, or any other conditions that may prevent a good face-seal.

*"N" Series respirators should be replaced when the wearer senses an increase in breathing resistance due to the filters collecting particulate matter. Replace masks frequently.*

**PROTECTION**

- N-series filters: effective against particulate aerosols free of oil.

**Do NOT use:**

- for protection against hazardous concentrations of gases or vapors
- for sandblasting, paint-spray operations, asbestos.

**DONNING and FITTING INSTRUCTIONS:**

Follow these instructions each time respirator is worn.

1. Remove respirator from package and "pre-form" the aluminum nose bridge adjustor.
2. Hold the respirator in the hand, allowing the head-straps to hang loosely in front of the mask.
3. Position the lower head strap around the neck below the ears. Hold the respirator against the face and place the top head-strap around the crown of the head.
4. Adjust head straps by grasping the locking slide and pull adjuster ring until respirator fits comfortably.
5. Fit the nose area to the shape of the face by forming the nose piece with the fingertips. Start from the top of the nose piece working downward while pressing against the nose. Always use both hands.

**FIT-CHECK THE FACE-SEAL AS FOLLOWS:**

- Place both hands over the respirator(covering exhalation valve if mask is so equipped) - do not disturb the position of the respirator
- Exhale sharply to detect leakage.
- If the respirator contains an exhalation valve, inhale sharply (a negative pressure should be detected inside the respirator). If you sense air leakage, re-adjust the respirator and re-check the fit.



**WARNING:**

- If you cannot achieve satisfactory fit, do NOT enter the contaminated area. See your Supervisor.
- This respirator helps protect against certain contaminants. It may not eliminate the risk of contracting disease or infection. **Misuse may result in sickness or death.**

FOR MORE INFORMATION or assistance on this product, contact **ECI** (1-xxx-xxx-xxxx)

ECI-CN95UIc.doc

*(approval label on reverse side of UI)*



Emany Consulting  
 2966 Linda Lane  
 Sinking Spring, PA 19608  
 (610)670-8571



**THESE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS:**

RESPIRATOR COMPONENTS					
TC-	Protection <sup>1</sup>	Alternate Respirators			Cautions and Limitations <sup>2</sup>
		CN95	CVN95	CN95-OV	
84A-4177	N95	X			ABCJMNOP
84A-4191	N95		X		ABCJMNOP
84A-4239	N95			X	ABCJMNOP

**1. Protection:**

N95 - Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil.

**2. Cautions and Limitations:**

- A - Not for use in atmospheres containing less than 19.5 percent oxygen.
- B - Not for use in atmospheres immediately dangerous to life or health.
- C - Do not exceed maximum use concentrations established by regulatory standards.
- J - Failure to properly use and maintain this product could result in injury or death.
- M - All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
- N - Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configuration as specified by the manufacturer.
- O - Refer to User's Instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
- P - NIOSH does not evaluate respirators for use as surgical masks.