

REPORT OF NAVIGATION CHANNELS

ER 1130-2-306

YAQUINA BAY AND HARBOR YAQUINA RIVER - OREGON

Minimum depths channel entering from seaward

Authorized Project NAME OF CHART Name of Channel (Mileage)	Date of Survey	Feet Width	Miles Length	Project Depth	Left Outside Quarter Feet	Mid-Channel for half project width Feet	Right Outside Quarter Feet
YAQUINA BAY AND HARBOR Entrance	15-Jul-08	400	1.0	40	33	33	28
		300	0.5	30	27	34	33
South Beach Marina	15-Jul-08	100	0.4	10	9	10	6
HARBOR Entrance To Turning Basin	14-Jul-08	300	1.5	30	25	25	16
		1200	0.3	30	12	18	23
THE MUD FLATS	29-Aug-01	200	2.0	18	13	12	13
YAQUINA RIVER Weiser Point to 1 Johnson Slough	Jul-00						
		150	3.1	10	10	9	9
Fleisher Slough 2 to Nutes Slough	Jul-00						
		150	2.7	10	9	9	9
Amundson Slough 3 to Toledo	Jul-00	150	3.2	10	6	7	3
Toledo to Mi. 14.5 4	Mar-85	150	1.0	10	8	6	8
Depoe Slough	12-Mar-08	200	0.4	10	0	1	0

ENG Form 4021-R (Nov 1990)
Reference is Navigation Chart No. 18581.
NOTE All Depths refer to Mean Lower Low Water.

The information shown on this channel statement represents the results of the surveys made on the dates indicated and can only be considered as indicating the general conditions existing at that time.