NW	Summary
Number	Ails to Naviousian The placement of dileter and the second of the second
NW-01	<i>Aids to Navigation.</i> The placement of aids to navigation and regulatory markers which are approved by and installed in accordance with the requirements of the U.S. Coast Guard (see
	33 CFR, chapter 1, subchapter C, part 66). (Section 10)
<u>NW-02</u>	Structures in Artificial Canals. Structures constructed in artificial canals within principally
	residential developments where the connection of the canal to a navigable water of the United
	States has been previously authorized (see 33 CFR 322.5(g)). (Section 10)
<u>NW-03</u>	<i>Maintenance</i> . (a) The repair, rehabilitation, or replacement of any previously authorized,
	currently serviceable, structure, or fill, or of any current serviceable structure or fill authorized
	by 33 CFR 330.3, provided that the structure or fill is not to be put to uses differing from those
	uses specified or contemplated for it in the original permit or the most recently authorized
	modification. Minor deviations in the structure's configuration or filled area, including those
	due to changes in materials, construction techniques, or current construction codes or safety
	standards that are necessary to make the repair, rehabilitation, or replacement are authorized.
	This NWP authorizes the repair, rehabilitation, or replacement of those structures or fills
	destroyed or damaged by storms, floods, fire or other discrete events, provided the repair,
	rehabilitation, or replacement is commenced, or is under contract to commence, within two
	years of the date of their destruction or damage. In cases of catastrophic events, such as
	hurricanes or tornadoes, this two-year limit may be waived by the district engineer, provided the permittee can demonstrate funding, contract, or other similar delays.
	(b) This NWP also authorizes the removal of accumulated sediments and debris in the
	vicinity of and within existing structures (e.g. bridges, culverted road crossings, water intake
	structures, etc.) and the placement of new or additional riprap to protect the structure. The
	removal of sediment is limited to the minimum necessary to restore the waterway in the
	immediate vicinity of the structure to the approximate dimensions that existed when the
	structure was built, but cannot extend further than 200 feet in any direction from the structure.
	This 200 foot limit does not apply to maintenance dredging to remove accumulated sediments
	blocking or restricting outfall and intake structures or to maintenance dredging to remove
	accumulated sediments from canals associated with outfall and intake structures. All dredged
	or excavated materials must be deposited and retained in an upland area unless otherwise
	specifically approved by the district engineer under separate authorization. The placement of
	riprap must be the minimum necessary to protect the structure or to ensure the safety of the
	structure. Any bank stabilization measures not directly associated with the structure will
	require a separate authorization from the district engineer.
	(c) This NWP also authorizes temporary structures, fills, and work necessary to
	conduct the maintenance activity. Appropriate measures must be taken to maintain normal
	downstream flows and minimize flooding to the maximum extent practicable, when temporary structures, work, and discharges, including cofferdams, are necessary for construction
	activities, access fills, or dewatering of construction sites. Temporary fills must consist of
	materials, and be placed in a manner, that will not be eroded by expected high flows.
	Temporary fills must be removed in their entirety and the affected areas returned to pre-
	construction elevations. The areas affected by temporary fills must be revegetated, as
	appropriate.
	(d) This NWP does not authorize maintenance for dredging for the primary purpose of
	navigation or beach restoration. This NWP does not authorize new stream channelization or
	stream relocation projects.
	Notification: For activities authorized by paragraph (b) of this NWP, the permittee
	must submit a pre-construction notification to the district engineer prior to commencing the
	activity (see General Condition 27). Where maintenance dredging is proposed, the pre-
	construction notification must include information regarding the original design capacities and

	configurations of the outfalls, intakes, small impoundments, and canals. (See Section 10 and 404)
	Note: This NWP authorizes the repair, rehabilitation, or replacement of any
	previously authorized structure or fill that does not qualify for the Clean Water Act
	Section 404(f) exemption maintenance.
<u>NW-04</u>	Fish and Wildlife Harvesting, Enhancement, and Attraction Devices and Activities. Fish
	and wildlife harvesting devices and activities such as pound nets, crab traps, duck blinds, and
	clam and oyster digging, and small fish attraction devices such as open water fish
	concentrators (sea kites etc.). This NWP does not authorize artificial reefs or impoundment
	and semi-impoundments of waters of the United States for the culture or holding of motile
	species such as lobster, or the use of covered oyster trays or clam racks. (Sections 10 and 404)
<u>NW-05</u>	Scientific Measurement Devices. Devices, whose purpose is to measure and record scientific
	data, such as staff gages, tide gages, water recording devices, water quality testing and
	improvement devices, and similar structures. Small weirs and flumes constructed primarily to
	record water quantity and velocity are also authorized provided the discharge is limited to 25
	cubic yards. (Sections 10 and 404).
<u>NW-06</u>	Survey Activities. Survey activities, such as core sampling, seismic exploratory operations,
	plugging of seismic shot holes and other exploratory-type bore holes, exploratory trenching,
	soil surveys, sampling, and historic resources surveys. For the purposes of this NWP, the term
	"exploratory trenching" means mechanical land clearing of the upper soil profile to expose
	bedrock or substrate, for the purpose of mapping or sampling the exposed material. The area
	in which the exploratory trench is dug must be restored to its pre-construction elevation upon
	completion of the work. In wetlands, the top 6 to 12 inches of the trench should normally be
	backfilled with topsoil from the trench. This NWP authorizes the construction of temporary
	pads, provided the discharge does not exceed 25 cubic yards. Discharges and structures
	associated with the recovery of historic resources are not authorized by this NWP. Drilling
	and the discharge of excavated material from test wells for oil and gas exploration are not
	authorized by this NWP; the plugging of such wells is authorized. Fill placed for roads and
	other similar activities is not authorized by this NWP. The NWP does not authorize any
	permanent structures. The discharge of drilling mud and cuttings may require a permit under Section 402 of the Clean Water Act. (Sections 10 and 404)
NW-07	7. Outfall Structures and Associated Intake Structures. Activities related to the construction
<u>14 44 -07</u>	or modification of outfall structures and associated intake structures, where the effluent from
	the outfall is authorized, conditionally authorized, or specifically exempted by, or that are
	otherwise in compliance with regulations issued under the National Pollutant Discharge
	Elimination System Program (Section 402 of the Clean Water Act). The construction of
	intake structures is not authorized by this NWP, unless they are directly associated with an
	authorized outfall structure.
	Notification: The permittee must submit a pre-construction notification to the district
	engineer prior to commencing the activity. (See General Condition 27) (Sections 10 and 404)
NW-08	Oil and Gas Structures on the Outer Continental Shelf. Structures for the exploration,
	production, and transportation of oil, gas, and minerals on the outer continental shelf within
	areas leased for such purposes by the Department of the Interior, Minerals Management
	Service. Such structures shall not be placed within the limits of any designated shipping
	safety fairway or traffic separation scheme, except temporary anchors that comply with the
	fairway regulations in 33 CFR 322.5(1). The district engineer will review such proposals to
	ensure compliance with the provisions of the fairway regulations in 33 CFR 322.5(1). Any
	Corps review under this NWP will be limited to the effects on navigation and national security
	in accordance with 33 CFR 322.5(f). Such structures will not be placed in established danger
	zones or restricted areas as designated in 33 CFR part 334, nor will such structures be
	•

	permitted in EPA or Corps designated dredged material disposal areas.
	<i>Notification:</i> The permittee must submit a pre-construction notification to the district
	engineer prior to commencing the activity. (See General Condition 27.) (Section 10)
NW-09	Structures in Fleeting and Anchorage Areas. Structures, buoys, floats and other devices
	placed within anchorage or fleeting areas to facilitate moorage of vessels where the U.S. Coast
	Guard has established such areas for that purpose. (Section 10)
<u>NW-10</u>	Mooring Buoys. Non-commercial single-boat, mooring buoys. (Section 10)
<u>NW-11</u>	Temporary Recreational Structures. Temporary buoys, markers, small floating docks, and
	similar structures placed for recreational use during specific events such as water skiing
	competitions and boat races or seasonal use, provided that such structures are removed within
	30 days after use has been discontinued. At Corps of Engineers reservoirs, the reservoir
	manager must approve each buoy or marker individually. (Section 10)
<u>NW-12</u>	Utility Line Activities. Activities required for the construction, maintenance, repair, and
	removal of utility lines and associated facilities in waters of the United States, provided the
	activity does not result in the loss of greater than 1/2 acre of waters of the United States.
	Utility lines: This NWP authorizes the construction, maintenance, or repair of utility
	lines, including outfall and intake structures, and the associated excavation, backfill, or
	bedding for the utility lines, in all waters of the United States, provided there is no change in
	pre-construction contours. A "utility line" is defined as any pipe or pipeline for the
	transportation of any gaseous, liquid, liquescent, or slurry substance, for any purpose, and any
	cable line, or wire for the transmission for any purpose of electrical energy, telephone, and
	telegraph messages, and radio and television communication. The term "utility line" does not
	include activities that drain a water of the United States, such as drainage tile or French drains,
	but it does apply to pipes conveying drainage from another area.

Material resulting from trench excavation may be temporarily sidecast into waters of the United States for no more than three months, provided the material is not placed in such a manner that it is dispersed by currents or other forces. The district engineer may extend the period of temporary side casting for no more than a total of 180 days, where appropriate. In wetlands, the top 6 to 12 inches of the trench should normally be backfilled with topsoil from the trench. The trench cannot be constructed or backfilled in such a manner as to drain waters of the United States (e.g., backfilling with extensive gravel layers, creating a French drain effect). Any exposed slopes and stream banks must be stabilized immediately upon completion of the utility line crossing of each waterbody.

Utility line substations: This NWP authorizes the construction, maintenance, or expansion of substation facilities associated with a power line or utility line in non-tidal waters of the United States, provided the activity, in combination with all other activities included in one single and complete project, does not result in the loss of greater than 1/2 acre of waters of the United States. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters of the United States to construct, maintain, or expand substation facilities.

Foundations for overhead utility line towers, poles, and anchors: This NWP authorizes the construction or maintenance of foundations for overhead utility line towers, poles, and anchors in all waters of the United States, provided the foundations are the minimum size necessary and separate footings for each tower leg (rather than a larger single pad) are used where feasible.

Access roads: This NWP authorizes the construction of access roads for the construction and maintenance of utility lines, including overhead power lines and utility line substations, in non-tidal waters of the United States, provided the total discharge from a single and complete project does not cause the loss of greater than 1/2-acre of non-tidal waters of the

United States. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters for access roads. Access roads must be the minimum width necessary (see Note 2, below). Access roads must be constructed so that the length of the road minimizes any adverse effects on waters of the United States and must be as near as possible to preconstruction contours and elevations (e.g., at grade corduroy roads or geotextile/gravel roads.) Access roads constructed above pre-construction contours and elevations in waters of the United States must be properly bridged or culverted to maintain surface flows.

This NWP may authorize utility lines in or affecting navigable waters of the United States even if there is no associated discharge of dredged or fill material (see CFR part 322). Overhead utility lines constructed over Section 10 waters and utility lines that are routed in or under Section 10 waters without a discharge of dredged or fill material require a Section 10 permit.

This NWP also authorizes temporary structures, fills, and work necessary to conduct the utility line activity. Appropriate measures must be taken to maintain normal downstream flows and minimize flooding to the maximum extent practicable, when temporary structures, work, and discharges, including cofferdams, are necessary for construction activities, access fills, or dewatering of construction sites. Temporary fills must consist of materials, and be placed in a manner, that will not be eroded by expected high flows. Temporary fills must be removed in their entirety and the affected areas returned to pre-construction elevations. The areas affected by temporary fills must be revegetated, as appropriate.

Notification: The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if any of the following criteria are met: (1) The activity involves mechanized land clearing in a forested wetland for the utility line right-of-way; (2) a Section 10 permit is required; (3) the utility line in waters of the United States, excluding overhead lines, exceeds 500 feet; (4) the utility line is placed within a jurisdictional area (i.e., water of the United States), and it runs parallel to a stream bed that is within that jurisdictional area: (5) discharges that result in the loss of greater than 1/10-acre of waters of the United States; (6) permanent access roads are constructed above grade in waters of the United States for a distance of more than 500 feet; or (7) permanent access roads are constructed in waters of the United States with impervious materials. (See General Condition 27.) (Sections 10 and 404)

**Note 1:** Where the proposed utility line is constructed or installed in navigable waters of the United States (i.e. Section 10 waters), copies of the pre-construction notification and NWP verification will be sent by the Corps to the National Oceanic and Atmospheric Administration (NOAA), National Ocean Service (NOS), for charting the utility line to protect navigation.

**Note 2:** Access roads used for both construction and maintenance may be authorized provided they meet the terms and conditions of this NWP. Access roads used solely for construction of the utility line must be removed upon completion of the work, in accordance with the requirements for temporary fills.

**Note 3:** Pipes or pipelines used to transport gaseous, liquid, liquescent, or slurry substances over navigable waters of the United States are considered to be bridges, not utility lines, and may require permit from the U.S. Coast Guard pursuant to Section 9 of the Rivers and Harbors Act of 1899. However, any discharges of dredged of fill material into waters of the United States associated with such pipelines will require a Section 404 permit (see NWP 15).

- NW-13 **Bank Stabilization**. Bank stabilization activities necessary for erosion prevention, provided the activity meets all of the following criteria:
  - (a) No material is placed in excess of the minimum needed for erosion protection;
  - (b) The activity is no more than 500 feet in length along the bank, unless this criterion is waived in writing by the district engineer;

- (c) The activity will not exceed an average of one cubic yard per running foot placed along the bank below the plane of the ordinary high water mark or the high tide line, unless this criterion is waived in writing by the district engineer;
- (d) The activity does not involve discharges of dredged or fill material into special aquatic sites, unless this criterion is waived in writing by the district engineer;
- (e) No material is of the type, or is placed in any location, or in any manner, to impair surface water flow into or out of any water of the United States;
- (f) No material is placed in a manner that will be eroded by normal or expected high flows (properly anchored trees and treetops may be used in low energy areas); and,
  - (g) The activity is not a stream channelization activity.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if the bank stabilization activity: (1) involves discharges into special aquatic sites; (2) is in excess of 500 feet in length; or (3) will involve the discharge of greater than an average of one cubic yard per running foot along the bank below the plane of the ordinary high water mark or the high tide line. (See General Condition 27). (Sections 10 and 404)

NW-14

*Linear Transportation Projects*: Activities required for the construction, expansion, modification, or improvement of linear transportation projects (e.g., roads, highways, railways, trails, airport runways, and taxiways) in waters of the United States. For linear transportation projects in non-tidal waters, the discharge cannot cause the loss of greater than 1/2-acre of waters of the United States. For linear transportation projects in tidal waters, the discharge cannot cause the loss of greater than 1/3-acre of waters of the United States. Any stream channel modification, including bank stabilization, is limited to the minimum necessary to construct or protect the linear transportation project; such modifications must be in the immediate vicinity of the project.

This NWP also authorizes temporary structures, fills, and work necessary to construct the linear transportation project. Appropriate measures must be taken to maintain normal downstream flows and minimize flooding to the maximum extent practicable, when temporary structures, work, and discharges, including cofferdams, are necessary for construction activities, access fills, or dewatering of construction sites. Temporary fills must consist of materials, and be placed in a manner, that will not be eroded by expected high flows. Temporary fills must be removed in their entirety and the affected areas returned to preconstruction elevations. The areas affected by temporary fills must be revegetated, as appropriate.

This NWP cannot be used to authorize non-linear features commonly associated with transportation projects, such as vehicle maintenance or storage buildings, parking lots, train stations, or aircraft hangars.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if: (1) The loss of waters of the United States exceeds 1/10 acre; or (2) there is a discharge in a special aquatic site; including wetlands. (See General Condition 27.) (Sections 10 and 404)

**Note:** Some discharges for the construction of farm roads or forest roads, or temporary roads for moving mining equipment, may qualify for an exemption under Section 404(f) of the Clean Water Act (see 33 CFR 323.4)

<u>NW-15</u>

*U.S. Coast Guard Approved Bridges*. Discharges of dredged or fill material incidental to the construction of bridges across navigable waters of the United States, including cofferdams, abutments, foundation seals, piers, and temporary construction and access fills, provided such discharges have been authorized by the U.S. Coast Guard as part of the bridge permit.

	Causeways and approach fills are not included in this NWP and will require a separate Section
	404 permit. (Section 404).
NW-16	Return Water From Upland Contained Disposal Areas. Return water from an upland contained dredged material disposal area. The return water from a contained disposal area is administratively defined as a discharge of dredged material by 33 CFR 323.2(d), even though the disposal itself occurs on the upland an does not require a Section 404 permit. This NWP satisfies the technical requirement for a Section 404 permit for the return water where the quality of the return water is controlled by the state through the Section 401 certification procedures. The dredging activity may require a Section 404 permit (33 CFR 323.2(d)), and will require a Section 10 permit if located in navigable waters of the United States. (Section 404)
<u>NW-17</u>	Hydropower Projects. Discharges of dredged or fill material associated with hydropower
	projects having: (a) Less than 5000 kW of total generating capacity at existing reservoirs, where the project, including the fill, is licensed by the Federal Energy Regulatory Commission (FERC) under the Federal Power Act of 1920, as amended; or (b) a licensing exemption granted by the FERC pursuant to Section 408 of the Energy Security Act of 1980 (16 U.S.C. 2705 and 2708) and Section 30 of the Federal Power Act, as amended.  *Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Section 404)
<u>NW-18</u>	Minor Discharges. Minor discharges of dredged or fill material into all waters of the United
	States, provided the activity meets all of the following criteria:
	(a) The quantity of discharged material and the volume of area excavated do not
	exceed 25 cubic yards below the plane of the ordinary high water mark or the high tide line;
	(b) The discharge will not cause the loss of more than 1/10 acre of waters of the
	Untied States; and (c) The discharge is not placed for the purpose of a stream diversion.
	Notification: The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if: (1) The discharge or the volume of area excavated exceeds 10 cubic yards below the plane of the ordinary high water mark or the high tide line, or (2) the discharge is in a special aquatic site, including wetlands. (See General Condition 27.) (Sections 10 and 404)
<u>NW-19</u>	<i>Minor Dredging</i> . Dredging of no more than 25 cubic yards below the plane of the ordinary
	high water mark or the mean high water mark from navigable waters of the United States (i.e.,
	Section 10 waters). This NWP does not authorize the dredging or degradation through
	siltation of coral reefs, sites that support submerged aquatic vegetation (including sites where
	submerged aquatic vegetation is documented to exist but may not be present in a given year), anadromous fish spawning areas, or wetlands, or the connection of canals or other artificial
	waterways to navigable waters of the Untied States (see CFR 322.5(g)). (Sections 10 and 404)
NW-20	Oil Spill Cleanup. Activities required for the containment and cleanup of oil and hazardous
1111 20	substances that are subject to the National Oil and Hazardous Substances Pollution
	Contingency Plan (40 CFR part 300) provided that the work is done in accordance with the
	Spill Control and Countermeasure Plan required by 40 CFR 112.3 and any existing state
	contingency plan and provided that the Regional Response Team (if one exists in the area)
	concurs with the proposed containment and cleanup action. This NWP also authorizes
	activities required for the cleanup of oil releases in waters of the United States from electrical
	equipment that are governed by EPA's polychlorinated biphenyl spill response regulations at
NITT 24	40 CFR part 761. (Sections 10 and 404)
<u>NW-21</u>	Surface Coal Mining Operations. Discharges of dredged or fill material into waters of the
	United States associated with surface coal mining and reclamation operations provided the
	activities are already authorized, or are currently being processed as part of an integrated

processing procedure, by the Department of Interior (DOI), Office of Surface Mining (OSM), or by states with approved programs under Title V of the Surface Mining Control and Reclamation Act of 1977.

*Notification:* The permittee must submit a pre-construction notification to the district engineer and receive written authorization prior to commencing the activity. (See General Condition 27) (Sections 10 and 404)

NW-22

**Removal of Vessels.** Temporary structures or minor discharges of dredged or fill material required for the removal of wrecked, abandoned, or disabled vessels, or the removal of manmade obstructions to navigation. This NWP does not authorize maintenance dredging, shoal removal, or riverbank snagging.

Notification: The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if: (1) The vessel is listed or eligible for listing in the National Register of Historic Places; or (2) the activity is conducted in a special aquatic site, including coral reefs and wetlands. (See General Condition 27.) If condition (1) above is triggered, the permittee cannot commence the activity until informed by the district engineer that compliance with the "Historic Properties" general condition is completed. (Sections 10 and 404).

**Note 1:** If a removed vessel is disposed of in waters of the United States, a permit from the U.S. EPA may be required (see 40 CFR 229.3). If a Department of the Army permit is required for vessel disposal in waters of the United States, separate authorization will be required.

**Note 2:** Compliance with General Condition 17, Endangered Species, and General Condition 18, Historic Properties, is required for all NWPs. The concern with historic properties is emphasized in the notification requirements for this NWP because of the likelihood that submerged vessels may be historic properties.

NW-23

**Approved Categorical Exclusions.** Activities undertaken, assisted, authorized, regulated, funded, or financed, in whole or in part, by another Federal agency or department where:

- (a) That agency or department has determined, pursuant to the Council on Environmental Quality's implementing regulations for the National Environmental Policy Act (40 CFR part 1500 et seq.), that the activity is categorically excluded from environmental documentation, because it is included within a category of actions which neither individually nor cumulatively have a significant effect on the human environment; and
- (b) The Office of the Chief of Engineers (Attn: CECW-CO) has concurred with the agency's or department's determination that the activity is categorically excluded and approved the activity for authorization under NWP 23.

The Office of the Chief of Engineers may require additional conditions, including preconstruction notification, for authorization of an agency's categorical exclusions under this NWP.

*Notification:* Certain categorical exclusions approved for authorization under this NWP require the permittee to submit a pre-construction notification to the district engineer prior to commencing the activity (See General Condition 27). The activities that require pre-construction notification are listed in the appropriate Regulatory Guidance Letters. (Sections 10 and 404)

**Note:** The agency or department may submit an application for an activity believed to be categorically excluded to the Office of the Chief of Engineers (Attn: CECW-CO). Prior to approval for authorization under this NWP of any agency's activity, the Office of the Chief of Engineers will solicit public comment. As of the date of issuance of this NWP, agencies with approved categorical exclusions are the: Bureau of Reclamation, Federal Highway Administration, and U.S. Coast Guard. Activities

approved for authorization under this NWP as of the date of this notice are found in Corps Regulatory Guidance Letter 05-07, which is available at: http://www.usace.army.mil/inet/functions/cw/cecwo/reg/rglsindx.htm. Any future approved categorical exclusions will be announced in Regulatory Guidance Letters and posted on this same Web site.

## NW-24

Indian Tribe or State Administered Section 404 Programs. Any activity permitted by a state or Indian Tribe administering its own Section 404 permit program pursuant to 33 U.S.C. 1344(g)-(1) is permitted pursuant to Section 10 of the Rivers and Harbors Act of 1899. (Section 10)

**Note:** As of the date of the promulgation of this NWP, only New Jersey and Michigan administer their own Section 404 permit programs.

Note 2: Those activities that do not involve an Indian Tribe or State Section 404 permit are not included in this NWP, but certain structures will be exempted by Section 154 of Pub. L. 94-587, 90 Stat. 2917 (33 U.S.C. 591) (see 33 CFR 322.3(a)

# NW-25

Structural Discharges: Discharges of material such as concrete, sand, rock, etc., into tightly sealed forms or cells where the material will be used as a structural member for standard pile supported structures, such as bridges, transmission line footings, and walkways, or for general navigation, such as mooring cells, including the excavation of bottom material from within the form prior to the discharge of concrete, sand, rock, etc. This NWP does not authorize filled structural members that would support buildings, building pads, homes, house pads, parking areas, storage areas and other such structures. The structure itself may require a Section 10 permit if located in navigable waters of the United States. (Section 404)

#### NW-26

## [Reserved] NW-27

Aquatic Habitat Restoration, Establishment, and Enhancement Activities. Activities in waters of the United States associated with the restoration, enhancement, and establishment of tidal and non-tidal wetlands and riparian areas and the restoration and enhancement of nontidal streams and other non-tidal open waters, provided those activities result in net increases in aquatic resource functions and services.

To the extent that a Corps permit is required, activities authorized by this NWP include, but are not limited to: the removal of accumulated sediments; the installation, removal, and maintenance of small water control structures, dikes, and berms; the installation of current deflectors; the enhancement, restoration, or establishment of riffle and pool stream structure; the placement of in-stream habitat structures; modifications of the stream bed and/or banks to restore or establish stream meanders; the backfilling of artificial channels and drainage ditches; the removal of existing drainage structures; the construction of small nesting islands; the construction of open water areas; the construction of oyster habitat over unvegetated bottom in tidal waters; shellfish seeding; activities needed to reestablish vegetation, including plowing or disking for seed bed preparation and the planting of appropriate wetland species; mechanized land clearing to remove non-native invasive, exotic, or nuisance vegetation; and other related activities. Only native plant species should be planted at the site.

This NWP authorizes the relocation of non-tidal waters, including non-tidal wetlands and streams, on the project site provided there are net increases in aquatic resource functions and services. Except for the relocation of non-tidal waters on the project site, this NWP does not authorize the conversion of a stream or natural wetlands to another aquatic habitat type (e.g. stream to wetland and vice versa) or uplands. This NWP does not authorize stream channelization. This NWP does not authorize the relocation of tidal waters or the conversion of tidal waters, including tidal wetlands, to other aquatic uses, such as the conversion of tidal wetlands into open water impoundments.

Reversion. For enhancement, restoration, and establishment activities conducted:

- (1) In accordance with the terms and conditions of a binding wetland enhancement, restoration, or establishment agreement between the landowner and the U.S. Fish and Wildlife Service (FWS), the National Conservation Service (NRCS), the Farm Service Agency (FSA), the National Marine Fisheries Service (NMFS), the National Ocean Service (NOS), or their designated state cooperating agencies;
- (2) as voluntary wetland restoration, enhancement, and establishment actions documented by the NRCS or USDA Technical Service Provider pursuant to NRCS Field Office Technical Guide standards; or
- (3) on reclaimed surface coal mine lands, in accordance with a Surface Mining Control and Reclamation Act permit issued by the OSM or the applicable state agency, this NWP also authorizes any future discharge of dredged or fill material associated with the reversion of the area to its documented prior condition and use (i.e. prior to the restoration, enhancement, or establishment activities). The reversion must occur within five years after expiration of a limited term wetland restoration or establishment agreement or permit, and is authorized in these circumstances even if the discharge occurs after this NWP expires. The five-year reversion limit does not apply to agreements without time limits reached between the landowner and the FWS, NRCS, FSA, NMFS, NOS, or an appropriate state cooperating agency. This NWP also authorizes discharges of dredged or fill material in waters of the United States for reversion of wetlands that were restored, enhanced, or established on priorconverted cropland that has not been abandoned or on uplands, in accordance with a binding agreement between the landowner and NRCS, FSA, FWS, or their designated state cooperating agencies (even though the restoration, enhancement, or establishment activity did not require a Section 404 permit). The prior condition will be documented in the original agreement or permit, and the determination of return to prior conditions will be made by the Federal agency or appropriate state agency executing the agreement or permit. Before conducting reversion activity the permittee or the appropriate Federal or state agency must notify the district engineer and include the documentation of the prior condition. Once an area has reverted to its prior physical condition, it will be subject to whatever the Corps Regulatory requirements are applicable to that type of land at the time. The requirement that the activity result in a net increases in aquatic resource functions and services does not apply to reversion activities meeting the above conditions. Except for the activities described above, this NWP does not authorize any future discharge of dredged or fill material associated with the reversion of the area to its prior condition. In such cases a separate permit would be required for any reversion.

*Reporting:* For those activities that do not require a pre-construction notification, the permittee must submit to the district engineer a copy of :

- (1) The binding wetland enhancement, restoration, or establishment agreement, or a project description, including project plans and location map;
- (2) the NRCS or USDA Technical Service Provider documentation for the voluntary wetland restoration, enhancement, or establishment action; or
- (3) the SMCRA permit issued by OSM or the applicable state agency. These documents must be submitted to the district engineer at least 30 days prior to commencing activities in waters of the United States authorized by this NWP.

*Notification*: The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity (see General Condition 27), except for the following activities:

- (1) Activities conducted on non-Federal public and private lands, in accordance with the terms and conditions of a binding wetland enhancement, restoration, or establishment agreement between the landowner and the U.S. FWS, NRCS, FSA, NMFS, NOS, or their designated state cooperating agencies:
  - (2) Voluntary wetland restoration, enhancement, and establishment actions

documented by the NRCS or USDA Technical Service Provider pursuant to NRCS Field Office Technical Guide standards; or

(3) The reclamation of surface coal mine lands, in accordance with an SMCRA permit issued by the OSM or the applicable state agency.

However, the permittee must submit a copy of the appropriate documentation. (Sections 10 and 404)

**Note:** This NWP can be used to authorize compensatory mitigation projects, including mitigation banks and in-lieu fee programs. However, this NWP does not authorize the reversion of an area used for a compensatory mitigation project to its prior condition Since compensatory mitigation is generally intended to be permanent.

NW-28

*Modifications of Existing Marinas.* Reconfiguration of existing docking facilities within an unauthorized marina area. No dredging, additional slips, dock spaces, or expansion of any kind within waters of the United States is authorized by this NWP. (Section 10)

NW-29

**Residential Developments.** Discharges of dredged or fill material into non-tidal waters of the United States for the construction or expansion of a single residence, a multiple unit residential development, or a residential subdivision. This NWP authorizes the construction of building foundations and building pads and attendant features that are necessary for the use of the residence or residential development. Attendant features may include but are not limited to roads, parking lots, garages, yards, utility lines, stormwater management facilities, septic fields, and recreation facilities such as playgrounds, playing fields, and golf courses (provided the golf course is an integral part of the residential development).

The discharge must not cause the loss of greater than ½-acre of non-tidal waters of the United States, including the loss of no more than 300 linear feet of stream bed, unless for intermittent and ephemeral stream beds this 300 linear foot limit is waived in writing by the district engineer. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters.

Subdivisions: For residential subdivisions, the aggregate total loss of waters of the United States authorized by this NWP cannot exceed ½ acre. This includes any loss of waters of the United States associated with development of individual subdivision lots.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Sections 10 and 404)

NW-30

Moist Soil Management for Wildlife. Discharges of dredged or fill material into non-tidal waters of the United States and maintenance activities that are associated with moist soil management for wildlife for the purpose of continuing ongoing, site-specific, wildlife management activities where soil manipulation is used to manage habitat and feeding areas for wildlife. Such activities include, but are not limited to, plowing or disking to impede succession, preparing seed beds, or establishing fire breaks. Sufficient riparian areas must be maintained adjacent to all open water bodies, including streams to preclude water quality degradation due to erosion and sedimentation. This NWP does not authorize the construction of new dikes, roads, water control structures, or similar features associated with the management areas. The activity must not result in a net loss of aquatic resource functions and services. This NWP does not authorize the conversion of wetlands, impoundments, or other open water bodies. (Section 404)

**Note:** The repair, maintenance, or replacement of existing water control structures or the repair or maintenance of dikes may be authorized by NWP 3. Some such activities may qualify for an exemption under Section 404(f) of the Clean Water Act. (See CFR 323.4)

NW-31 | Maintenance of Existing Flood Control Facilities. Discharges of dredged or fill material

resulting from activities associated with the maintenance of existing flood control facilities, including debris basins, retention/detention basins, levees, and channels that:

- (i) were previously authorized by the Corps by individual permit, general permit, by 33 CFR 330.3, or did not require a permit at the time they were constructed, or
- (ii) were constructed by the Corps and transferred to a non-Federal sponsor for operation and maintenance. Activities authorized by this NWP are limited to those resulting from maintenance activities that are conducted within the "maintenance baseline," as described in the definition below. Discharges of dredged or fill materials associated with maintenance activities in flood control facilities in any watercourse that have previously been determined to be within the maintenance baseline are authorized under this NWP. This NWP does not authorize the removal of sediment and associated vegetation from natural water courses except when these activities have been included in the maintenance baseline. All dredged material must be placed in an upland site or an authorized disposal site in waters of the United States, and proper siltation controls must be used.

Maintenance Baseline: The maintenance is a description of the physical characteristics (e.g., depth, width, length, location, configuration, or design flood capacity, etc.) of a flood control project within which maintenance activities are normally authorized by NWP 31, subject to any case-specific conditions required by the district engineer. The district engineer will approve the maintenance baseline based on the approved or constructed capacity of the flood control facility, whichever is smaller, including any areas where there are no constructed channels, but which are part of the facility. The prospective permittee will provide documentation of the physical characteristics of the flood control facility (which will normally consist of as-built or approved drawings) and documentation of the approved and constructed design capacities of the flood control facility. If no evidence of the constructed capacity exists, the approved capacity will be used. The documentation will also include best management practices to ensure that the impacts to the aquatic environment are minimal, especially in maintenance areas where there are no constructed channels. (The Corps may request maintenance records in areas where there has not been recent maintenance.) Revocation or modification of the final determination of the maintenance baseline can only be done in accordance with 33 CFR 330.5. Except in emergencies as described below, this NWP cannot be used until the district engineer approves the maintenance baseline and determines the need for mitigation and any regional or activity-specific conditions. Once determined, the maintenance baseline will remain valid for any subsequent reissuance of this NWP. This NWP does not authorize maintenance of a flood control facility that has been abandoned. A flood control facility will be considered abandoned if it has operated at a significantly reduced capacity without needed maintenance being accomplished in a timely manner.

Mitigation: The district engineer will determine any required mitigation one-time only for impacts associated with maintenance work at the same time that the maintenance baseline is approved. Such one-time mitigation will be required when necessary to ensure that adverse environmental impacts are no more than minimal, both individually and cumulatively. Such mitigation will only be required once for any specific reach of a flood control project. However, if one-time mitigation is required for impacts associated with maintenance activities, the district engineer will not delay needed maintenance, provided the district engineer and the permittee establish a schedule for identification, approval, development, construction and completion of any such required mitigation. Once the one-time mitigation described above has been completed, or a determination made that mitigation is not required, no further mitigation will be required for maintenance activities within the maintenance baseline. In determining appropriate mitigation, the district engineer will give special consideration to natural water courses that have been included in the maintenance baseline and require compensatory mitigation and/or best management practices as appropriate.

Emergency Situations: In emergency situations, this NWP may be used to authorize

maintenance activities in flood control facilities for which no maintenance baseline has been approved. Emergency situations are those which would result in an unacceptable hazard to life, a significant loss of property, or an immediate, unforeseen, and significant economic hardship if action is not taken before a maintenance baseline can be approved. In such situations, the determination of mitigation requirements, if any, may be deferred until the emergency has been resolved. Once the emergency has ended, a maintenance baseline must be established expeditiously, and mitigation, including mitigation for maintenance conducted during the emergency, must be required as appropriate.

*Notification:* The permittee must submit a pre-construction notification to the district engineer before any maintenance work is conducted (see General Condition 27). The pre-construction notification may be for activity-specific maintenance or for maintenance of the entire flood control facility by submitting a five-year (or less) maintenance plan. The pre-construction notification must include a description of the maintenance baseline and the dredged material disposal site. (Sections 10 and 404).

## NW-32

*Completed Enforcement Actions.* Any structure, work, or discharge of dredged or fill material remaining in place or undertaken for mitigation, restoration, or environmental benefit in compliance with either:

- (i) The terms of a final written Corps non-judicial settlement agreement resolving a violation of Section 404 of the Clean Water Act and/or Section 10 of the Rivers and Harbors Act of 1899; or the terms of an EPA 309(a) order on consent resolving a violation of Section 404 of the Clean Water Act, provided that:
- (a) The unauthorized activity affected no more than 5 acres of non-tidal waters or 1 acre of tidal waters;
- (b) The settlement agreement provides for environmental benefits, to an equal or greater degree, than the environmental detriments caused by the unauthorized activity that is authorized by this NWP; and
- (c) The district engineer issues a verification letter authorizing the activity subject to the terms and conditions of this NWP and the settlement agreement, including a specified completion date; or
- (ii) The terms of a final Federal court decision, consent decree, or settlement agreement resulting from an enforcement action brought by the United States under Section 404 of the Clean Water Act and/or Section 10 of the Rivers and Harbors Act of 1899; or
- (iii) The terms of a final court decision, consent decree, settlement agreement, or non-judicial settlement agreement resulting from a natural resource damage claim brought by a trustee or trustees for natural resources (as defined by the National Contingency Plan at 40 CFR subpart G) under Section 311 of the Clean Water Act, Section 107 of the Comprehensive Environmental Response, Compensation and Liability Act, Section 312 of the National Marine Sanctuaries Act, Section 1002 of the Oil Pollution Act of 1990, or the Park System Resource Protection Act at 16 U.S.C. 19jj, to the extent that a Corps permit is required.

Compliance is a condition of the NWP itself. Any authorization under this NWP is automatically revoked if the permittee does not comply with the terms of this NWP or the terms of the court decision, consent decree, or judicial/non-judicial settlement agreement. This NWP does not apply to any activities occurring after the date of the decision, decree, or agreement that are not for the purpose of mitigation, restoration, or environmental benefit. Before reaching any settlement agreement, the Corps will ensure compliance with the provisions of 33 CFR part 326 and 33 CFR 330.6(d) (2) and (e). (Sections 10 and 404)

## NW-33

*Temporary Construction, Access, and Dewatering.* Temporary structures, work, and discharges, including cofferdams, necessary for construction activities or access fills or dewatering of construction sites, provided that the associated primary activity is authorized by the Corps of Engineers or the U.S. Coast Guard. This NWP also authorizes temporary

structures, work, and discharges, including cofferdams, necessary for construction activities not otherwise subject to the Corps of U.S. Coast Guard permit requirements. Appropriate measures must be taken to maintain near normal downstream flows and to minimize flooding. Fill must consist of materials, and be placed in a manner, that will not be eroded by expected high flows. The use of dredged material may be allowed if the district engineer determines that it will not cause more than minimal adverse effects on aquatic resources. Following completion of construction, temporary fill must be entirely removed to upland areas, dredged material must be returned to its original location, and the affected areas must be restored to pre-construction elevations. The affected areas must also be revegetated, as appropriate. This permit does not authorize the use of cofferdams to dewater wetlands or other aquatic areas to change their use. Structures left in place after construction is completed require a Section 10 permit if located in navigable waters of the United States, (See 33 CFR par 322.)

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity (see General Condition 27). The pre-construction notification must include a restoration plan showing how all temporary fills and structures will be removed and the area restored to pre-project conditions. (Sections 10 and 404)

## NW-34

Cranberry Production Activities. Discharges of dredged or fill material for dikes, berms, pumps, water control structures or leveling of cranberry beds associated with expansion, enhancement, or modification activities at existing cranberry production operations. The cumulative total acreage of disturbance per cranberry production operation, including but not limited to, filling, flooding, ditching, or clearing, must not exceed 10 acres of waters of the United States, including wetlands. The activity must not result in a net loss of wetland acreage. This NWP does not authorize any discharge of dredged or fill material related to other cranberry production activities such as warehouse, processing facilities, or parking areas. For the purpose of this NWP, the cumulative total of 10 acres will be measured over the period that this NWP is valid.

*Notification:* The permittee must submit a pre-construction notification to the district engineer once during the period that this NWP is valid, and the NWP will then authorize discharges of dredge or fill material at an existing operation for the permit term, provided the 10-acre limit is not exceeded. (See General Condition 27.) (Section 404)

## NW-35

Maintenance Dredging of Existing Basins. Excavation and removal of accumulated sediment for maintenance of existing marina basins, access channels to marinas or boat slips, and boat slips to previously authorized depths or controlling depths for ingress/egress, whichever is less, provided the dredged material is deposited at an upland site and proper siltation controls are used. (Section 10)

#### NW-36

**Boat Ramps.** Activities required for the construction of boat ramps, provided the activity meets all of the following criteria:

- (a) The discharge into waters of the United States does not exceed 50 cubic yards of concrete, rock, crushed stone or gravel into forms, or in the form of pre-cast concrete planks or slabs, unless the 50 cubic yard limit is waived in writing by the district engineer;
- (b) The boat ramp does not exceed 20 feet in width unless this criterion is waived in writing by the district engineer;
  - (c) The base material is crushed stone, gravel or other suitable material;
- (d) The excavation is limited to the area necessary for site preparation and all excavated material is removed to the upland; and,
- (e) No material is placed in special aquatic sites, including wetlands. The use of unsuitable material that is structurally unstable is not authorized. If dredging in navigable waters of the United States is necessary to provide access to the boat ramp, the dredging may be authorized by another NWP, a regional general permit, or an individual permit.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity if:

- (1) The discharge into waters of the United States exceeds 50 cubic yards, or
- (2) The boat ramp exceeds 20 feet in width. (See General Condition 27.) (Sections 10 and 404)

## NW-37

## *Emergency Watershed Protection and Rehabilitation.* Work done by or funded by:

- (a) The Natural Resources Conservation Service for a situation requiring immediate action under its emergency Watershed Protection Program (7 CFR par 624);
- (b) The U.S. Forest Service under its Burned-Area Emergency Rehabilitation Handbook (FSH 509.13);
- (c) The Department of the Interior for wildland fire management burned area emergency stabilization and rehabilitation (DOI Manual part 620, Ch. 3);
- (d) The Office of Surfacing Mining, or states with approved programs, for abandoned mine land reclamation activities under Title IV of the Surface Mining Control and Reclamation Act (30 CFR subchapter R), where the activity does not involve coal extraction; or
- (e) The Farm Service Agency under its Emergency Conservation Program (7 CFR part 701).

In general, the prospective permittee should wait until the district engineer issues an NWP verification before proceeding with the watershed protection and rehabilitation activity. However, in cases where there is an unacceptable hazard to life or a significant loss of property or economic hardship will occur, the emergency watershed protection and rehabilitation activity may proceed immediately and the district engineer will consider the information in the pre-construction notification any comments received as a result of agency coordination to decided whether the NWP 37 authorization should be modified, suspended, or revoked in accordance with the procedures at 33 CFR 330.5.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity (see General Condition 27). (Sections 10 and 404)

# NW-38

Cleanup of Hazards and Toxic Waste. Specific activities required to effect the containment, stabilization, or removal of hazardous or toxic waste materials that are performed, ordered, or sponsored by a government agency with established legal or regulatory authority. Court ordered remedial action plans or related settlements are also authorized by this NWP. This NWP does not authorize the establishment of new disposal sites or the expansion of existing sites use for disposal of hazardous or toxic waste.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Sections 10 and 404)

**Note:** Activities undertaken entirely on a Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) site by authority of CERCLA as approved or required by EPA, are not required to obtain permits under Section 404 of the Clean Water Act or Section 10 of the Rivers and Harbors Act.

#### NW-39

Commercial and Institutional Developments. Discharges of dredged or fill material into non-tidal waters of the United States for the construction or expansion of commercial and institutional building foundations and building pads and attendance features that are necessary for the use and maintenance of the structures. Attendant features may include, but are not limited to, roads, parking lots, garages, yards, utility lines, stormwater management facilities, and recreation facilities such as playgrounds and playing fields. Examples of commercial developments include retail stores, restaurants, business parks, and shopping centers. Examples of institutional developments include schools, fire stations, government office buildings, judicial buildings, public works buildings, libraries, hospitals, and places of worship. The construction of new golf courses, new ski areas, or oil and gas wells is not authorized by this NWP.

The discharge must not cause the loss of greater than ½-acre of non-tidal waters of the United States, including the loss of no more than 300 linear feet of stream bed, unless for intermittent and ephemeral stream beds this 300 linear foot limit is waived in writing by the district engineer. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Sections 10 and 404)

NW-40

Agricultural Activities: Discharges of dredged or fill material into non-tidal waters of the United States for agricultural activities, including the construction of building pads for farm buildings. Authorized activities include the installation, placement, or construction of drainage tiles, ditches, or levees; mechanized land clearing; land leveling; the relocation of existing serviceable drainage ditches constructed in waters of the United States; and similar activities.

This NWP also authorizes the construction of farm ponds in non-tidal waters of the United States, excluding perennial streams, provided the farm pond is used solely for agricultural purposes. This NWP does not authorize the construction of aquaculture ponds.

This NWP also authorizes discharges of dredged or fill material into non-tidal waters of the United States to relocate existing serviceable drainage ditches constructed in non-tidal streams.

The discharge must not cause the loss of greater than ½-acre of non-tidal waters of the United States. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters. This NWP does not authorize the relocation of greater than 300 linear feet of existing serviceable drainage ditches constructed in non-tidal streams, unless for drainage ditches constructed in intermittent and ephemeral streams, this 300 linear foot limit is waived in writing by the district engineer.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Section 404)

**Note:** Some discharges for agricultural activities may qualify for an emption under Section 404(f) of the Clean Water Act (see 33 CFR 323.4) This NWP authorizes the construction of farm ponds that do not qualify for the Clean Water Act Section 404(f)(1)(C) exemption because of the recapture provision at Section 404(f)(2).

NW-41

Reshaping Existing Drainage Ditches. Discharges of dredged or fill material into non-tidal waters of the United States, excluding non-tidal wetlands adjacent to tidal waters, to modify the cross-sectional configuration of currently serviceable drainage ditches constructed in waters of the United States, for the purpose of improving water quality by regarding the drainage ditch with gentler slopes, which can reduce erosion, increase growth of vegetation, and increase uptake of nutrients and other substances by vegetation. The reshaping of the ditch cannot increase drainage capacity beyond the original as-built capacity nor can it expand the area drained by the ditch as originally constructed (i.e., the capacity of the ditch must be the same as originally constructed and it cannot drain additional wetlands or other waters of the United States). Compensatory mitigation is not required because the work is designed to improve water quality.

This NWP does not authorize the relocation of drainage ditches constructed in waters of the United States; the location of the centerline of the reshaped drainage ditch must be approximately the same as the location of the centerline of the original drainage ditch. This NWP does not authorize stream channelization or stream relocation projects.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity, if more than 500 linear feet of drainage ditch will be reshaped. (See General Condition 27.) (Section 404)

NW-42 | Recreational Facilities: Discharges of dredged or fill material into non-tidal waters of the

United States for the construction or expansion of recreational facilities. Examples of recreational facilities that may be authorized by this NWP include playing fields (e.g. football fields, baseball fields), basketball courts, tennis courts, hiking trails, bike paths, golf courses, ski areas, horse paths, nature centers, and campgrounds (excluding recreational vehicle parks). This NWP also authorizes the construction of expansion of small support facilities, such as maintenance and storage buildings and stables that are directly related to the recreational activity, but it does not authorize the construction of hotels, restaurants, racetracks, stadiums, arenas, or similar facilities.

The discharge must not cause the loss of greater than ½-acre of non-tidal waters of the United States, including the loss of no more than 300 linear feet of stream bed, unless for intermittent and ephemeral stream beds this 300 linear foot limit is waived in writing by the district engineer. This NWP does not authorize discharged into non-tidal wetlands adjacent to tidal waters.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Section 404)

#### NW-43

Stormwater Management Facilities. Discharges of dredged or fill material into non-tidal waters of the United States for the construction and maintenance of stormwater management facilities, including the excavation of stormwater ponds/facilities, detention basins, and retention basins; the installation and maintenance of water control structures, outfall structures and emergency spillways; and the maintenance dredging of existing stormwater management ponds/facilities and detention and retention basins.

The discharge must not cause the loss of greater than ½-acre of non-tidal waters of the United States, including the loss of no more than 300 linear feet of stream bed, unless for intermittent and ephemeral stream beds this 300 linear foot limit is waived in writing by the district engineer. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters. This NWP does not authorize discharges of dredged or fill material for the construction of new stormwater management facilities in perennial streams.

*Notification:* For the construction of new stormwater management facilities, or the expansion of existing stormwater management facilities, the permittee must submit a preconstruction notification to the district engineer prior to commencing the activity. (See General Condition 27.) Maintenance activities do not require pre-construction notification if they are limited to restoring the original design capacities of the stormwater management facility. (Section 404)

## NW-44

*Mining Activities.* Discharges of dredged or fill material into non-tidal waters of the United States for mining activities, except coal mining activities. The discharge must not cause the loss of greater than 1/2–acre of non-tidal waters of the United States. This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) If reclamation is required by other statues, then a copy of the reclamation plan must be submitted with the preconstruction notification. (Sections 10 and 404)

#### NW-45

Repair of Uplands Damaged by Discrete Events. This NWP authorizes discharges of dredged or fill material, including dredging or excavation, into all waters of the United States for activities associated with the restoration of upland areas damaged by storms, floods, or other discrete events. This NWP authorizes bank stabilization to protect the restored uplands. The restoration of the damaged areas, including any bank stabilization, must not exceed the contours, or ordinary high water mark, that existed before the damage occurred. The district engineer retains the right to determine the extent of the pre-existing conditions and the extent of any restoration work authorized by this NWP. The work must commence, or be under contract to commence, within two years of the date of damage, unless this condition is waived

in writing by the district engineer. This NWP cannot be used to reclaim lands lost to normal erosion processes over an extended period.

Minor dredging is limited to the amount necessary to restore the damaged upland area and should not significantly alter the pre-existing bottom contours of the waterbody.

*Notification:* The permittee must submit a pre-construction notification to the district engineer (see General Condition 27) within 12-months of the date of the damage. The pre-construction notification should include documentation, such as a recent topographic survey or photographs, to justify the extent of the proposed restoration. (Sections 10 and 404)

**Note:** Uplands lost as a result of a storm, flood, or other discrete event can be replaced without a Section 404 permit, if the uplands are restored to the ordinary high water mark (in non-tidal waters) or high tide line (in tidal waters). (See also 33 CFR 328.5)

## NW-46

Discharges in Ditches. Discharges of dredged or fill material into non-tidal ditches that are:

- (1) Constructed in uplands,
- (2) Receive water from an area determined to be a water of the United States prior to the construction of the ditch,
- (3) Divert water to an area determined to be a water of the Untied States prior to the construction of the ditch, and
- (4) Are determined to be waters of the United States. The discharge must not cause the loss of greater than one acre of waters of the United States.

This NWP does not authorize discharges of dredged or fill material into ditches constructed in streams or other waters of the United States, or in streams that have been relocated in uplands. This NWP does not authorize discharges of dredged or fill material that increase the capacity of the ditch and drain those areas determined to be waters of the United States prior to construction of the ditch.

*Notification:* The permittee must submit a pre-construction notification to the district engineer prior to commencing the activity. (See General Condition 27.) (Section 404)

## NW-47

- *Pipeline Safety Program Designated Time Sensitive Inspections and Repairs.* Activities required for the inspection, repair, rehabilitation, or replacement of any currently serviceable structure or fill for pipelines that have been identified by the Pipeline and Hazardous Materials Safety Administrator's Pipeline Safety Program (PHP) within the U.S. Department of Transportation as time-sensitive (see 49 CFR parts 192 and 195) and additional maintenance activities done in conjunction with the time-sensitive inspection and repair activities. All activities must meet the following criteria:
- (a) Appropriate measures must be taken to maintain normal downstream flows and minimize flooding to the maximum extent practicable when temporary structures, work and discharges, including cofferdams, are necessary for construction activities or access fills or dewatering of construction sites;
- (b) Material resulting from trench excavation may be temporarily sidecast into waters of the United States for no more than three months, provided that the material is not placed in such a manner that it is dispersed by currents or other forces. The district engineer may extend the period of temporary side casting for no more than a total of 180 days, where appropriate. The trench cannot be constructed or backfilled in such manner as to drain waters of the United States (e.g. backfilling with the extensive gravel layers, creating a French drain effect);
- (c) Temporary fill must consist of materials, and be placed in a manner, that will not be eroded by expected high flows. Temporary fills must be removed in their entirety and the affected areas returned to pre-construction elevations. The affected areas must be revegetated, as appropriate;
  - (d) In wetlands, the top 6 to 12 inches of the trench should normally be backfilled

with topsoil from the trench so that there is no change in pre-construction contours;

- (e) To the maximum extent practicable, the restoration of open waters must be to the pre-construction course, condition, capacity, and location of the waterbody;
- (f) Any exposed slopes and stream banks must be stabilized immediately upon completion of the project;
- (g) Additional maintenance activities done in conjunction with the time-sensitive inspection or repair must not result in additional losses of waters of the United States; and
- (h) The permittee is a participant in the Pipeline Repair and Environmental Guidance System (PREGS).

Reporting: The permittee must submit a post-construction report to the PHP within seven days after completion the work. The report must be submitted electronically to PHP via PREGS. The report must contain the following information: Project sites located in waters of the United States; temporary access routes, stream dewatering sites, temporary fills and temporary structures identified on a map of the pipeline corridor; photographs of the pre- and post-construction work areas located in waters of the United States; and a list of best management practices employed for each pipeline segment shown on the map. (Section 10 and 404)

**Note:** Division engineers may modify this NWP by adding regional conditions to protect the aquatic environment, as long as those regional conditions do not require pre-construction notification or other actions that would delay time sensitive inspections and repairs. Examples of appropriate regional conditions include best management practices.

## NW-48

Existing Commercial Shellfish Aquaculture Activities: This NWP authorizes the installation of buoys, floats, racks, trays, nets, lines, tubes, containers, and other structures necessary for the continued operation of the existing commercial aquaculture activity. This NWP also authorizes discharges of dredged or fill material necessary for shellfish seeding, rearing, cultivating, transplanting, and harvesting activities. Rafts and other floating structures must be securely anchored and clearly marked.

This NWP does not authorize new operations or the expansion of the project area for an existing commercial shellfish aquaculture activity. This NWP does not authorize the cultivation of new species (i.e., species not previously cultivated in the waterbody). This NWP does not authorize attendant features such as docks, piers, boat ramps, stockpiles, staging area, or the deposition of shell material back into waters of the United States as waste.

*Reporting:* For those activities that do not require pre-construction notification, the permittee must submit a report to the district engineer that includes the following information:

- (1) The size of the project area for the commercial shellfish aquaculture activity (in acres);
  - (2) The location of the activity;
  - (3) A brief description of the culture method and harvesting method(s);
  - (4) The name(s) of the cultivated species; and
- (5) Whether canopy predator nets are being used. This is a subset of the information that would be required for pre-construction notification. This report may be provided by letter or using an optional reporting form provided by the Corps. Only one report needs to be submitted during the period this NWP is valid, as long as there are no changes to the operation that require pre-construction notification. The report must be submitted to the district engineer within 90 days of the effective date of this NWP.

*Notification:* The permittee must submit a pre-construction notification to the district engineer if:

- (1) The project area is greater than 100 acres; or
- (2) there is a any reconfiguration of the aquaculture activity, such as relocating existing operations into portions of the project area not previously used for aquaculture

activities: or

the project.

- (3) There is a change in species being cultivated; or
- (4) There is a change culture methods (e.g., from bottom culture to off-bottom culture); or
- (5) Dredge harvesting, tilling, or harrowing is conducted in areas inhabitant by submerged aquatic vegetation. (See General Condition 27.) (Sections 10 and 404)

  Note: The permittee should notify the applicable U.S. Coast Guard office regarding

NW-49

Coal Remining Activities. Discharges of dredged or fill material into non-tidal waters of the Untied States associated with the remining and reclamation of lands that were previously mined for coal, provided the activities are already authorized, or are currently being processed as part of an integrated permit processing procedure, by the Department of Interior (DOI) Office of Surface Mining (OSM), or by states with approved programs under Title IV or Title V of the Surface Mining Control and Reclamation Act of 1977. Areas previously mined include reclaimed mine sites, abandoned mine land areas, or lands under bond forfeiture contracts. The permittee must clearly demonstrate to the district engineer that the reclamation plan will result in a net increase in aquatic resources functions. As part of the project, the permittee may conduct coal mining activities in an adjacent area, provided the newly mined area is less than 40 percent of the area being remined plus any unmined area necessary for the reclamation of the remined area.

*Notification:* The permittee must submit a pre-construction notification to the district engineer and receive written authorization prior to commencing the activity. (See General Condition 27.) (Sections 10 and 404)

NWP-50 *Underground Coal Mining Activities.* Discharges of dredged or fill material into non-tidal waters of the United States associated with underground coal mining and reclamation operations provided the activities are authorized, or are currently being processed as part of an integrated permit processing procedure, by the Department of Interior (DOI), Office of Surface Mining (OSM), or by states with approved programs under Title V of the Surface Mining Control and Reclamation Act of 1977.

This NWP does not authorize discharges into non-tidal wetlands adjacent to tidal waters. This NWP does not authorize coal preparation and processing activities outside of the mine site.

*Notification:* The permittee must submit a pre-construction notification to the district engineer and receive written authorization prior to commencing the activity. (See General Condition 27.) If reclamation is required by other statutes, then a copy of the reclamation plan must be submitted with the pre-construction notification (Sections 10 and 404)

**Note:** Coal preparation and processing activities outside of the mine site may be authorized NWP 21.