## UNITED STATES DEPARTMENT OF COMMERCE WASHINGTON 25, D. C.

## National Bureau of Standards Certificate of Analyses

## Standard Sample 157A Copper-Nickel-Zinc Alloy

ANALYST	COPPER Electrolytic	ZINC ZnS-ZnO	NICKEL Weighed as nickel dimethylglyoxime	MANGANESE Photometric	IRON	LEAD Weighed as PbC2	TIN SnClKIO <sub>3</sub>	COBALT Photometric	PHOSPHORUS Photometric
1	58. 60	29.03	11.80	a 0. 175	ь 0. 174	0.034	o 0. 022	d 0.026	e 0. 008
2	58. 59	29.08	f 11.83	s. 175	<sup>h</sup> . 17	. 043	. 02		i. 011
3	58. 58	29. 11	11.84	. 171	<b>3.</b> 178	. 034	<b>≥.</b> 018	. 022	1.009
	58.62	m 29.09	{ "11.85} 11.84}	.178	{ °. 174 } □. 172 }	۹. 032	r. 021	s. 025	•. 007
	58. 62	29. 14	11.79	. 17	{ □. 17 } t. 177}	. 029	u. 026	. 019	1.009
6	58.66	29. 13	11.81	v. 179	w. 179	×. 031	у. 022	. 021	1.010
7	z 58.61	<b>2</b> 29 <b>.</b> 02	<b>11.83</b>	<b>2.17</b> 3	². 174	<b>*.</b> 036	*1.016	z. 022	.011
Average	58. 61	29. 09	11.82	0. 174	0. 174	0.034	0, 021	0. 022	0.009

\* Persulfate oxidation and potentiometric titration with sodium arsenite standardized with high-purity manganese.

sodium arsenite standardized with high-purity manganese. b SnCl<sub>2</sub>-K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub> method,

Ten-gram sample dissolved in HCl-HNO<sub>4</sub>, 5 g of NH<sub>4</sub>Cl added, and tin precipitated twice with NH<sub>4</sub>OH. Precipitate dissolved in HCl, tin reduced with test lead and titrated with 0.02 N KIO<sub>3</sub> standardized with high-purity ties.

and utrated with 0.02 N KIO3 standardized with high-purity tin.

4 Tin removed from a 10-g sample as metastannic acid, copper and lead by electrolysis, and iron with cupferron. Cobalt precipitated with  $\infty$ -nitroso  $\beta$ -naphthol and weighed as Co<sub>3</sub>O<sub>4</sub>.

Molybdenum-blue photometric method. See J. Research NBS 26, 405 (1941) RP 1386.

<sup>1</sup> Dimethylglyoxime precipitate titrated with cyanide.

8 Manganese dioxide precipitated in HNO3 solution with ClO<sub>3</sub>. Solution filtered and MnO3 titrated with Na<sub>3</sub>C<sub>2</sub>O<sub>4</sub>-

h Iron reduced with zinc and titrated with K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub>.

l Phosphomolybdate-alkalimetric method.

l SnCl<sub>2</sub>-KMnO<sub>2</sub> method.

k Tin reduced with aluminum in the presence of added antimony and titrated with KIO<sub>3</sub> standardized with highpurity tin.

l Molybdivanadophosphoric acid method.

m Copper deposited electrolytically. Electrolyte converted to chlorides and transferred to an ion exchange column of Dowex 1. See J. Research NBS, 53, 353 (1934) RP2552. After selective elution of nickel, cohalt, and iron (footnotes n, s, o) zinc eluted with HNO<sub>2</sub> (1+4) and determined as Znl<sup>2</sup>AO<sub>7</sub>.

n Nickel eluted from an ion exchange column with 9N HCl and determined by electrolysis in an ammoniacal chloride solution.

l Iron eluted from an ion exchange column with 1 N HCl and determined by the thiocyanate-photometric method.

q Lead in a 10-g sample collected on Fe+++ with NH4OH and determined polarographically in NH4Cl medium.
\* Tin in a 10-g sample collected on Fe+++ with NH4OH, distilled with HBr, and determined polarographically in HBr-NH4Cl medium.
\* Cobalt eluted from an ion exchange column with 4N HCl and determined by the nitroso-R salt-photometric method.

HCl and determined by the nitroso-R salt-photometric method.

1 K3C207 titration.

1 Tin reduced with nickel and titrated with KIO2.

2 Persulfate-arsenite method.

3 Iron precipitated twice with NH40H and titrated with Tis(SO4).

3 Tin reduced with iron and titrated with KIO2.

4 American Society for Testing Materials, Method E75-56, Chemical Analysis of Copper-Nickel-Zinc Alloys.

3 Tin separated as metastannic acid and weighed as SnO2. See ASTM Method E56-45.

## List of Analysts

- 1. R. K. Bell and E. E. Maczkowske, National Bureau of Standards, Washington, D. C.
- 2. A. B. Shapiro, H. Kramer and Co., Chicago, Ill.
- 3. John D. Kopp, Scovill Manufacturing Co., Waterbury, Conn.
- 4 Silve Kallmann, Ledoux and Co., Teaneck, N. J.
- 5. William A. Eddie and John T. Krantz, National Bearing Division, American Brake Shoe Co., St. Louis, Mo.
- 6. O. W. DeJarnett, Olin-Mathieson Chemical Corp., East Alton, Ill.
- 7. W. J. Morley and Celine M. Paul, Western Electric Co., Chicago, Ill.

The rolled metal used in the preparation of this standard was furnished by Western Electric Co., Inc.