Page 1 of 24

# United States Environmental Protection Agency Region 10 1200 Sixth Avenue, Suite 900 Seattle, Washington 98101

# Authorization to Discharge Under the National Pollutant Discharge Elimination System

In compliance with the provisions of the Clean Water Act, 33 U.S.C. §1251 *et seq.*, as amended by the Water Quality Act of 1987, P.L. 100-4, the "Act",

#### **City of Filer**

is authorized to discharge from the City of Filer Wastewater Treatment Plant facility located in Filer, Idaho, at the following location(s):

Outfall	Receiving Water	Latitude	Longitude
001	Cedar Draw Creek	42° 34′ 56" N	114° 36' 45" W

in accordance with discharge point(s), effluent limitations, monitoring requirements and other conditions set forth herein.

This permit shall become effective November 1, 2007.

This permit and the authorization to discharge shall expire at midnight October 31, 2012.

The permittee shall reapply for a permit reissuance on or before May 5, 2012, 180 days before the expiration of this permit if the permittee intends to continue operations and discharges at the facility beyond the term of this permit.

Signed this 14<sup>th</sup> day of September, 2007,

\_/s/ Jannine Jennings for

Michael F. Gearheard, Director Office of Water and Watersheds

Page 2 of 24

# **Schedule of Submissions**

The following is a summary of some of the items the permittee must complete and/or submit to EPA during the term of this permit:

Item 1. Discharge Monitoring Reports (DMR)	<b>Due Date</b> DMRs are due monthly and must be postmarked on or before the 10 <sup>th</sup> day of the month following the monitoring month.
2. Quality Assurance Plan (QAP)	The permittee must provide EPA and IDEQ with written notification that the Plan has been updated and implemented within 90 days days after the effective date of the final permit (see II.B.). The Plan must be kept on site and made available to EPA and IDEQ upon request.
3. Operation and Maintenance (O&M) Plan	The permittee must provide EPA and IDEQ with written notification that the Plan has been updated and implemented within 90 days after the effective date of the final permit (see II.A.). The Plan must be kept on site and made available to EPA and IDEQ upon request.
4. NPDES Application Renewal	The application must be submitted at least 180 days before the expiration date of the permit (see V.B.).
5. Ambient Monitoring Reports	The results from ambient monitoring must be submitted in electronic format at least 180 days before the expiration date of the permit in an excel spreadsheet(s).
6. Compliance Schedule	Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit must be submitted no later than 14 days following each schedule date (see III.J.)
7. Twenty-Four Hour Notice of Noncompliance Reporting	The permittee must report certain occurrences of noncompliance by telephone within 24 hours from the time the permittee becomes aware of the circumstances. (See III.G. and I.B.2)
8. Temperature Monitoring Reports	Temperature data must be submitted electronically to IDEQ on or before the 10 <sup>th</sup> day of the month following the monitoring month.

# Page 3 of 24

# **Table of Contents**

Sche	edule of Submissions	2
I. I	Limitations and Monitoring Requirements	5
A.	Discharge Authorization	5
В.	Effluent Limitations and Monitoring	
C.	Surface Water Monitoring	
II.	Special Conditions	9
A.	Operation and Maintenance Plan	9
В.	Quality Assurance Plan (QAP)	
C.	Sludge (Biosolids) Management Requirements	
III.	Monitoring, Recording and Reporting Requirements	10
A.	Representative Sampling (Routine and Non-Routine Discharges)	10
В.	Reporting of Monitoring Results	
В. С.	Monitoring Procedures	
D.	Additional Monitoring by Permittee	
	- The state of the	
E.	Records Contents	
F.	Retention of Records.	
G.	Twenty-four Hour Notice of Noncompliance Reporting	
H.	Other Noncompliance Reporting	
I. J.	Notice of New Introduction of Toxic Pollutants  Compliance Schedules	
	•	
IV.	Compliance Responsibilities	13
A.	Duty to Comply	13
В.	Penalties for Violations of Permit Conditions	14
C.	Need To Halt or Reduce Activity not a Defense	15
D.	Duty to Mitigate	15
E.	Proper Operation and Maintenance	16
F.	Bypass of Treatment Facilities	16
G.	Upset Conditions	17
H.	Toxic Pollutants	17
I.	Planned Changes	17
J.	Anticipated Noncompliance	18
K.	Reopener	
V.	General Provisions	18
A.	Permit Actions	18
В.	Duty to Reapply	
C.	Duty to Provide Information	
D.	·	

Permit No.: ID-002006-1 Page 4 of 24

VI.	Definitions	2
J.	State Laws	
	Transfers	
H.	Property Rights	2
G.	Inspection and Entry	
	Availability of Reports	
	Signatory Requirements	

Page 5 of 24

# I. Limitations and Monitoring Requirements

# A. Discharge Authorization

During the effective period of this permit, the permittee is authorized to discharge pollutants from the outfalls specified herein to Cedar Draw Creek, within the limits and subject to the conditions set forth herein. This permit authorizes the discharge of only those pollutants resulting from facility processes, waste streams, and operations that have been clearly identified in the permit application process.

#### **B.** Effluent Limitations and Monitoring

1. The permittee must limit and monitor discharges from outfall 001 as specified in Table 1, below. All figures represent maximum effluent limits unless otherwise indicated. The permittee must comply with the effluent limits in the tables at all times unless otherwise indicated, regardless of the frequency of monitoring or reporting required by other provisions of this permit. Discharge from outfall 001 can only occur from November 1 through March 31 of each year:

	Table 1: E	ffluent Lii	mitations a	nd Monitorin	g Require	ements	
Parameter	Effluent Limitations			Monitoring Requirements			
	Average Monthly Limit	Average Weekly Limit	Maximum Daily Limit	Instantaneous Maximum Limit	Sample Location	Sample Frequency	Sample Type
Flow, mgd					Effluent	Continuous	Record
Biochemical	30 mg/l	45 mg/l			Influent	1/week	24-hr comp
Oxygen Demand (BOD <sub>5</sub> )	70 lb/day	105 lb/day			and Effluent		
Total	30 mg/l	45 mg/l			Influent and Effluent	1/week	24-hr comp
Suspended Solids (TSS)	12 lb/day	19 lb/day					
E. Coli Bacteria <sup>1,2</sup>	126/100 ml			576/100 ml	Effluent	5/month	grab
Total Residual	0.3 mg/L		0.5 mg/L		Effluent	3/week	grab
Chlorine <sup>2</sup>	0.4 lb/day		0.6 lb/day		Elliuelli		
pН	See Part I.B	.5 for efflue	nt limitations		Effluent	3/week	grab
Total Phosphorus	17 lb/day	33 lb/day			Effluent	1/week	24-hr comp
Total Ammonia as N, mg/L					Effluent	1/month	24-hr comp
Temperature <sup>3</sup>					Influent and Effluent	Continuous	Record

<sup>1.</sup> The average monthly E. Coli bacteria counts must not exceed a geometric mean of 126/100 ml based on a minimum of five samples taken every 3-7 days within a calendar month. See Part VI for a definition of geometric mean.

<sup>2.</sup> Reporting is required within 24 hours of a maximum daily limit or instantaneous maximum limit violation. See Parts I.B.2. and III.G.

<sup>3.</sup> Samples must be recorded in one hour intervals, 24 hours a day

Page 6 of 24

2. The permittee must report within 24 hours any violation of the maximum daily or instantaneous maximum limits for the following pollutants: E. Coli and Total Residual Chlorine. Violations of all other effluent limits are to be reported at the time that discharge monitoring reports (DMR) are submitted (See III.B. and III.H.).

- 3. Compliance Schedule and Interim Limits TSS
  - a. Compliance dates: The permittee must achieve compliance with the effluent limitations for TSS and BOD established in Part I.B.1, Table 1, no later than January 1, 2011.
  - b. Beginning on the effective date of this permit and continuing to, no later than December 31, 2010 the permittee must achieve the following interim limits for TSS and BOD:

TSS:

Average Monthly Limit: 45 mg/l

105 lbs/day

Average Weekly Limit: 65 mg/l

152 lbs/day

BOD:

Average Monthly Limit: 37 mg/l

86 lbs/day

Average Weekly Limit: 56 mg/l

131 lbs/day

- c. The permittee must submit an Annual Report of Progress which outlines the progress made towards reaching the compliance date for the BOD and TSS effluent limitations. The annual Report of Progress must be submitted by November 1 of each year. The first report is due November 1, 2008 and annually thereafter, until compliance with the BOD and TSS effluent limits are achieved. See also Part III.J., "Compliance Schedules". At a minimum, the annual report must include:
  - (i) A report on progress made towards meeting the effluent limitations.
  - (ii) Further actions and milestones targeted for the upcoming year.
- 4. The permittee must not discharge any floating, suspended, or submerged matter of any kind in concentrations causing a nuisance or objectionable conditions or that may impair designated beneficial uses. This includes any petroleum products that cause a sheen or coating on the water surface. If a sheen occurs, the size and

Page 7 of 24

extent of the sheen or coating should be documented in the facility's daily log book.

- 5. The pH must not be less than 6.5 standard units (s.u.) nor greater than 9.0 standard units (s.u.).
- 6. Removal Requirements for BOD<sub>5</sub> and TSS: The monthly average effluent concentration must not exceed 15 percent of the monthly average influent concentration. Percent removal of BOD<sub>5</sub> and TSS must be reported on the DMRs. For each parameter, the monthly average percent removal must be calculated from the arithmetic mean of the influent values and the arithmetic mean of the effluent values for that month. Influent and effluent samples must be taken over approximately the same time period.
- 7. The permittee must collect effluent samples from the effluent stream after the last treatment unit prior to discharge into the receiving waters.
- 8. Minimum Levels. For all effluent monitoring, the permittee must use methods that can achieve a minimum level (ML) less than the effluent limitation. For purposes of reporting on the DMR for a single sample, if a value is less than the method detection limit (MDL), the permittee must report "less than {numeric value of the MDL}" and if a value is less than the ML, the permittee must report "less than {numeric value of the ML}."
- 9. For purposes of calculating monthly averages, zero may be assigned for values less than the MDL, and the {numeric value of the MDL} may be assigned for values between the MDL and the ML. If the average value is less than the MDL, the permittee must report "less than {numeric value of the MDL}" and if the average value is less than the ML, the permittee must report "less than {numeric value of the ML}." If a value is equal to or greater than the ML, the permittee must report and use the actual value. The resulting average value must be compared to the compliance level, the ML, in assessing compliance.

### C. Surface Water Monitoring

The permittee must conduct surface water monitoring. Surface water monitoring must start 180 days after the effective date of the permit and continue for two years, for all parameters except temperature which must be monitored for five years. Sample collection is only required November through March. The program must meet the following requirements:

1. Monitoring stations must be established in Cedar Draw Creek at the following location:

Above the influence of the facility's discharge, and

Page 8 of 24

Below the facility's discharge, at a point where the effluent and Cedar Draw Creek are completely mixed.

- 2. The permittee must seek approval of the surface water monitoring stations from IDEQ.
- 3. A failure to obtain IDEQ approval of surface water monitoring stations does not relieve the permittee of the surface water monitoring requirements of this permit.
- 4. To the extent practicable, surface water sample collection must occur on the same day as effluent sample collection.
- 5. All ambient samples must be grab samples, except temperature which must be a continuous recording.
- 6. Samples must be analyzed for the parameters in Table 2. All parameters must be monitored at the upstream station. Temperature must also be monitored at the downstream station.
- 7. The flow rate must be measured as near as practicable to the time that other ambient parameters are sampled.
- 8. An adequate, existing gauge station may be used for ambient flow data, however, the City must ensure the sampling frequency meets the requirements below, and compile and submit the data to EPA and IDEQ.

Table 2: Surface Water Monitoring Requirements			
Units	Sampling Frequency		
mgd	Monthly		
mg/L	Monthly		
mg/L	Monthly		
°C	Continuously		
standard units	Monthly		
	Units  mgd  mg/L  mg/L  °C		

- 9. Quality assurance/quality control plans for all the monitoring must be documented in the Quality Assurance Plan required under Part II.B., "Quality Assurance Plan".
- 10. Surface water monitoring results must be submitted in electronic form to EPA and IDEQ in an excel spreadsheet(s), at least 180 days before the expiration of this permit. Temperature monitoring must be submitted to IDEQ in electronic format on or before the 10<sup>th</sup> day following the monitoring month.

Page 9 of 24

# **II.** Special Conditions

# A. Operation and Maintenance Plan

The permittee must revise and update their O&M plan including the implementation of BMPs within 90 days of permit issuance. EPA has a guidance manual (*Guidance Manual for Developing Best Management Practices* EPA, 1993) that may provide some assistance in the development of BMPs. Specifically, the permittee must consider spill prevention and control, optimization of chemical use, public education aimed at controlling the introduction of household hazardous materials to the sewer system and water conservation. Additionally, the BMP operating plan must be amended whenever there is a change in the facility or in the operation of the facility which materially increases the potential for an increased discharge of pollutants. The plan shall be retained on site and made available on request to EPA and IDEQ.

# **B.** Quality Assurance Plan (QAP)

The permittee must update their quality assurance plan (QAP) for all monitoring required by this permit. The permittee must submit written notice to EPA and IDEQ that the Plan has been updated and implemented within 90 days of the effective date of this permit. Any existing QAPs may be modified for compliance with this section.

- 1. The QAP must be designed to assist in planning for the collection and analysis of effluent and receiving water samples in support of the permit and in explaining data anomalies when they occur.
- 2. Throughout all sample collection and analysis activities, the permittee must use the EPA-approved QA/QC and chain-of-custody procedures described in *Requirements for Quality Assurance Project Plans* (EPA/QA/R-5) and *Guidance for Quality Assurance Project Plans* (EPA/QA/G-5). The QAP must be prepared in the format that is specified in these documents.
- 3. At a minimum, the QAP must include the following:
  - Details on the number of samples, type of sample containers, preservation of samples, holding times, analytical methods, analytical detection and quantitation limits for each target compound, type and number of quality assurance field samples, precision and accuracy requirements, sample preparation requirements, sample shipping methods, and laboratory data delivery requirements.
  - ii. Map(s) indicating the location of each sampling point.
- iii. Qualification and training of personnel.
- iv. Name(s), address(es) and telephone number(s) of the laboratories used by or proposed to be used by the permittee.

Page 10 of 24

4. The permittee must amend the QAP whenever there is a modification in sample collection, sample analysis, or other procedure addressed by the QAP.

5. Copies of the QAP must be kept on site and made available to EPA and/or IDEQ upon request.

# C. Sludge (Biosolids) Management Requirements

The permittee must ensure that an updated biosolids permit application (Form 2S) is on file with the EPA.

# III. Monitoring, Recording and Reporting Requirements

#### A. Representative Sampling (Routine and Non-Routine Discharges)

Samples and measurements must be representative of the volume and nature of the monitored discharge. In order to ensure that the effluent limits set forth in this permit are not violated at times other than when routine samples are taken, the permittee must collect additional samples at the appropriate outfall whenever any discharge occurs that may reasonably be expected to cause or contribute to a violation that is unlikely to be detected by a routine sample. The permittee must analyze the additional samples for those parameters limited in Part I.B. of this permit that are likely to be affected by the discharge.

The permittee must collect such additional samples as soon as the spill, discharge, or bypassed effluent reaches the outfall. The samples must be analyzed in accordance with paragraph III.C ("Monitoring Procedures"). The permittee must report all additional monitoring in accordance with paragraph III.D ("Additional Monitoring by Permittee").

# **B.** Reporting of Monitoring Results

The permittee must summarize monitoring results each month on the Discharge Monitoring Report (DMR) form (EPA No. 3320-1) or equivalent. The permittee must submit reports monthly, postmarked by the 10th day of the following month. The permittee must sign and certify all DMRs, and all other reports, in accordance with the requirements of Part V.E. of this permit ("Signatory Requirements"). The permittee must submit the legible originals of these documents to the Director, Office of Compliance and Enforcement, with copies to IDEQ at the following addresses:

US EPA Region 10 Attn: ICIS Data Entry Team 1200 Sixth Avenue, Suite 900 OCE-133 Seattle, Washington 98101

Page 11 of 24

Idaho Department of Environmental Quality Twin Falls Regional Office 1363 Fillmore Street Twin Falls, ID 83301

# **C.** Monitoring Procedures

Monitoring must be conducted according to test procedures approved under 40 CFR 136, unless other test procedures have been specified in this permit or approved by EPA as an alternate test procedure under 40 CFR 136.5.

# D. Additional Monitoring by Permittee

If the permittee monitors any pollutant more frequently than required by this permit, using test procedures approved under 40 CFR 136 or as specified in this permit, the permittee must include the results of this monitoring in the calculation and reporting of the data submitted in the DMR.

Upon request by EPA, the permittee must submit results of any other sampling, regardless of the test method used.

#### E. Records Contents

Records of monitoring information must include:

- 1. the date, exact place, and time of sampling or measurements;
- 2. the name(s) of the individual(s) who performed the sampling or measurements;
- 3. the date(s) analyses were performed;
- 4. the names of the individual(s) who performed the analyses;
- 5. the analytical techniques or methods used; and
- 6. the results of such analyses.

#### F. Retention of Records

The permittee must retain records of all monitoring information, including, all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, copies of DMRs, a copy of the NPDES permit, and records of all data used to complete the application for this permit, for a period of at least five years from the date of the sample, measurement, report or application. This period may be extended by request of EPA or IDEQ at any time.

Page 12 of 24

# G. Twenty-four Hour Notice of Noncompliance Reporting

1. The permittee must report the following occurrences of noncompliance by telephone within 24 hours from the time the permittee becomes aware of the circumstances:

any noncompliance that may endanger health or the environment;

- i. any unanticipated bypass that exceeds any effluent limitation in the permit (See Part IV.F., "Bypass of Treatment Facilities");
- ii. any upset that exceeds any effluent limitation in the permit (See Part IV.G., "Upset Conditions"); or
- iii. any violation of a maximum daily discharge limitation for E. Coli or Total Residual Chlorine.
- iv. any overflow prior to the treatment works, whether or not such overflow endangers health or the environment or exceeds any effluent limitation in the permit.
- 2. The permittee must also provide a written submission within five days of the time that the permittee becomes aware of any event required to be reported under subpart 1 above. The written submission must contain:
  - i. a description of the noncompliance and its cause;
  - ii. the period of noncompliance, including exact dates and times;
- iii. the estimated time noncompliance is expected to continue if it has not been corrected; and
- iv. steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.
- v. if the noncompliance involves an overflow prior to the treatment works, an estimate of the quantity (in gallons) of untreated overflow.
- 3. The Director of the Office of Compliance and Enforcement may waive the written report on a case-by-case basis if the oral report has been received within 24 hours by the NPDES Compliance Hotline in Seattle, Washington, by telephone, (206) 553-1846.
- 4. Reports must be submitted to the addresses in Part III.B ("Reporting of Monitoring Results").

Page 13 of 24

# H. Other Noncompliance Reporting

The permittee must report all instances of noncompliance, not required to be reported within 24 hours, at the time that monitoring reports for Part III.B ("Reporting of Monitoring Results") are submitted. The reports must contain the information listed in Part III.G.2 of this permit ("Twenty-four Hour Notice of Noncompliance Reporting").

#### I. Notice of New Introduction of Toxic Pollutants

The permittee must notify the Director of the Office of Water and Watersheds and IDEQ in writing of:

- 1. Any new introduction of pollutants into the POTW from an indirect discharger which would be subject to Sections 301 or 306 of the Act if it were directly discharging those pollutants; and
- 2. Any substantial change in the volume or character of pollutants being introduced into the POTW by a source introducing pollutants into the POTW at the time of issuance of the permit.
- 3. For the purposes of this section, adequate notice must include information on:
  - i. The quality and quantity of effluent to be introduced into the POTW, and
  - ii. Any anticipated impact of the change on the quantity or quality of effluent to be discharged from the POTW.
- 4. The permittee must notify the Director of the Office of Water and Watersheds at the following address:

US EPA Region 10 Attn: NPDES Permits Unit Manager 1200 6<sup>th</sup> Avenue, Suite 900 OWW-130 Seattle, WA 98101

#### J. Compliance Schedules

Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit must be submitted no later than 14 days following each schedule date.

# IV. Compliance Responsibilities

#### A. Duty to Comply

Page 14 of 24

The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

#### **B.** Penalties for Violations of Permit Conditions

Civil and Administrative Penalties. Pursuant to 40 CFR Part 19 and the Act, any person who violates section 301, 302, 306, 307, 308, 318 or 405 of the Act, or any permit condition or limitation implementing any such sections in a permit issued under section 402, or any requirement imposed in a pretreatment program approved under sections 402(a)(3) or 402(b)(8) of the Act, is subject to a civil penalty not to exceed the maximum amounts authorized by Section 309(d) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$32,500 per day for each violation).

Administrative Penalties. Any person may be assessed an administrative penalty by the Administrator for violating section 301, 302, 306, 307, 308, 318 or 405 of this Act, or any permit condition or limitation implementing any of such sections in a permit issued under section 402 of this Act. Pursuant to 40 CFR 19 and the Act, administrative penalties for Class I violations are not to exceed the maximum amounts authorized by Section 309(g)(2)(A) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$11,000 per violation, with the maximum amount of any Class I penalty assessed not to exceed \$32,500). Pursuant to 40 CFR 19 and the Act, penalties for Class II violations are not to exceed the maximum amounts authorized by Section 309(g)(2)(B) of the Act and the Federal Civil Penalties Inflation Adjustment Act (28 U.S.C. § 2461 note) as amended by the Debt Collection Improvement Act (31 U.S.C. § 3701 note) (currently \$11,000 per day for each day during which the violation continues, with the maximum amount of any Class II penalty not to exceed \$157,500).

#### **Criminal Penalties:**

Negligent Violations. The Act provides that any person who negligently violates sections 301, 302, 306, 307, 308, 318, or 405 of the Act, or any condition or limitation implementing any of such sections in a permit issued under section 402 of the Act, or any requirement imposed in a pretreatment program approved under section 402(a)(3) or 402(b)(8) of the Act, is subject to criminal penalties of \$2,500 to \$25,000 per day of violation, or imprisonment of not more than 1 year, or both. In the case of a second or subsequent conviction for a negligent violation, a person shall be subject to criminal penalties of not more than \$50,000 per day of violation, or by imprisonment of not more than 2 years, or both.

Page 15 of 24

Knowing Violations. Any person who knowingly violates such sections, or such conditions or limitations is subject to criminal penalties of \$5,000 to \$50,000 per day of violation, or imprisonment for not more than 3 years, or both. In the case of a second or subsequent conviction for a knowing violation, a person shall be subject to criminal penalties of not more than \$100,000 per day of violation, or imprisonment of not more than 6 years, or both.

Knowing Endangerment. Any person who knowingly violates section 301, 302, 303, 306, 307, 308, 318 or 405 of the Act, or any permit condition or limitation implementing any of such sections in a permit issued under section 402 of the Act, and who knows at that time that he thereby places another person in imminent danger of death or serious bodily injury, shall, upon conviction, be subject to a fine of not more than \$250,000 or imprisonment of not more than 15 years, or both. In the case of a second or subsequent conviction for a knowing endangerment violation, a person shall be subject to a fine of not more than \$500,000 or by imprisonment of not more than 30 years, or both. An organization, as defined in section 309(c)(3)(B)(iii) of the Act, shall, upon conviction of violating the imminent danger provision, be subject to a fine of not more than \$1,000,000 and can be fined up to \$2,000,000 for second or subsequent convictions.

False Statements. The Act provides that any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000, or by imprisonment for not more than 2 years, or both. If a conviction of a person is for a violation committed after a first conviction of such person under this paragraph, punishment is a fine of not more than \$20,000 per day of violation, or by imprisonment of not more than 4 years, or both. The Act further provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or non-compliance shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than 6 months per violation, or by both.

#### C. Need To Halt or Reduce Activity not a Defense

It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with this permit.

#### **D.** Duty to Mitigate

The permittee must take all reasonable steps to minimize or prevent any discharge in violation of this permit that has a reasonable likelihood of adversely affecting human health or the environment.

Page 16 of 24

# E. Proper Operation and Maintenance

The permittee must at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

#### F. Bypass of Treatment Facilities

1. Bypass not exceeding limitations. The permittee may allow any bypass to occur that does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of paragraphs 2 and 3 of this Part.

#### 2. Notice.

- i. Anticipated bypass. If the permittee knows in advance of the need for a bypass, it must submit prior written notice, if possible at least 10 days before the date of the bypass.
- ii. Unanticipated bypass. The permittee must submit notice of an unanticipated bypass as required under Part III.G ("Twenty-four Hour Notice of Noncompliance Reporting").

#### 3. Prohibition of bypass.

- Bypass is prohibited, and the Director of the Office of Compliance and Enforcement may take enforcement action against the permittee for a bypass, unless:
  - (i) The bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
  - (ii) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass that occurred during normal periods of equipment downtime or preventive maintenance; and

Page 17 of 24

(iii) The permittee submitted notices as required under paragraph 2 of this Part.

ii. The Director of the Office of Compliance and Enforcement may approve an anticipated bypass, after considering its adverse effects, if the Director determines that it will meet the three conditions listed above in paragraph 3.a. of this Part.

# **G.** Upset Conditions

- 1. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology-based permit effluent limitations if the permittee meets the requirements of paragraph 2 of this Part. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.
- 2. Conditions necessary for a demonstration of upset. To establish the affirmative defense of upset, the permittee must demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
  - i. An upset occurred and that the permittee can identify the cause(s) of the upset;
  - ii. The permitted facility was at the time being properly operated;
- iii. The permittee submitted notice of the upset as required under Part III.G, "Twenty-four Hour Notice of Noncompliance Reporting;" and
- iv. The permittee complied with any remedial measures required under Part IV.D, "Duty to Mitigate."
- 3. Burden of proof. In any enforcement proceeding, the permittee seeking to establish the occurrence of an upset has the burden of proof.

#### H. Toxic Pollutants

The permittee must comply with effluent standards or prohibitions established under Section 307(a) of the Act for toxic pollutants within the time provided in the regulations that establish those standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.

### I. Planned Changes

The permittee must give written notice to the Director of the Office of Water and Watersheds as specified in part III.I.4. and IDEQ as soon as possible of any planned physical alterations or additions to the permitted facility whenever:

Page 18 of 24

1. The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source as determined in 40 CFR 122.29(b); or

- 2. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants that are not subject to effluent limitations in this permit.
- 3. The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application site.

# J. Anticipated Noncompliance

The permittee must give written advance notice to the Director of the Office of Compliance and Enforcement and IDEQ of any planned changes in the permitted facility or activity that may result in noncompliance with this permit.

# K. Reopener

This permit may be reopened to include any applicable standard for sewage sludge use or disposal promulgated under section 405(d) of the Act. The Director may modify or revoke and reissue the permit if the standard for sewage sludge use or disposal is more stringent than any requirements for sludge use or disposal in the permit, or controls a pollutant or practice not limited in the permit.

#### V. General Provisions

#### A. Permit Actions

This permit may be modified, revoked and reissued, or terminated for cause as specified in 40 CFR 122.62, 122.64, or 124.5. The filing of a request by the permittee for a permit modification, revocation and reissuance, termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

#### **B.** Duty to Reapply

If the permittee intends to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit. In accordance with 40 CFR 122.21(d), and unless permission for the application to be submitted at a later date has been granted by the Regional Administrator, the permittee must submit a new application at least 180 days before the expiration date of this permit.

Page 19 of 24

# C. Duty to Provide Information

The permittee must furnish to EPA and IDEQ, within the time specified in the request, any information that EPA or IDEQ may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee must also furnish to EPA or IDEQ, upon request, copies of records required to be kept by this permit.

#### **D.** Other Information

When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or that it submitted incorrect information in a permit application or any report to EPA or IDEQ, it must promptly submit the omitted facts or corrected information in writing.

#### E. Signatory Requirements

All applications, reports or information submitted to EPA and IDEQ must be signed and certified as follows.

- 1. All permit applications must be signed as follows:
  - i. For a corporation: by a responsible corporate officer.
  - ii. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively.
- iii. For a municipality, state, federal, Indian tribe, or other public agency: by either a principal executive officer or ranking elected official.
- 2. All reports required by the permit and other information requested by EPA or IDEQ must be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:
  - i. The authorization is made in writing by a person described above;
  - ii. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company; and
- iii. The written authorization is submitted to the Director of the Office of Compliance and Enforcement and IDEQ.

Page 20 of 24

3. Changes to authorization. If an authorization under Part V.E.2 is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part V.E.2. must be submitted to the Director of the Office of Compliance and Enforcement and IDEQ prior to or together with any reports, information, or applications to be signed by an authorized representative.

4. Certification. Any person signing a document under this Part must make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

# F. Availability of Reports

In accordance with 40 CFR 2, information submitted to EPA pursuant to this permit may be claimed as confidential by the permittee. In accordance with the Act, permit applications, permits and effluent data are not considered confidential. Any confidentiality claim must be asserted at the time of submission by stamping the words "confidential business information" on each page containing such information. If no claim is made at the time of submission, EPA may make the information available to the public without further notice to the permittee. If a claim is asserted, the information will be treated in accordance with the procedures in 40 CFR 2, Subpart B (Public Information) and 41 Fed. Reg. 36902 through 36924 (September 1, 1976), as amended.

#### **G.** Inspection and Entry

The permittee must allow the Director of the Office of Compliance and Enforcement, EPA Region 10; IDEQ; or an authorized representative (including an authorized contractor acting as a representative of the Administrator), upon the presentation of credentials and other documents as may be required by law, to:

- 1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
- 2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

Page 21 of 24

3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and

4. Sample or monitor at reasonable times, for the purpose of assuring permit compliance or as otherwise authorized by the Act, any substances or parameters at any location.

#### H. Property Rights

The issuance of this permit does not convey any property rights of any sort, or any exclusive privileges, nor does it authorize any injury to persons or property or invasion of other private rights, nor any infringement of federal, tribal, state or local laws or regulations.

#### I. Transfers

This permit is not transferable to any person except after written notice to the Director of the Office of Water and Watersheds as specified in part III.I.4. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under the Act. (See 40 CFR 122.61; in some cases, modification or revocation and reissuance is mandatory).

#### J. State Laws

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable state law or regulation under authority preserved by Section 510 of the Act.

#### VI. Definitions

- 1. "Act" means the Clean Water Act.
- 2. "Administrator" means the Administrator of the EPA, or an authorized representative.
- 3. "Average monthly discharge limitation" means the highest allowable average of "daily discharges" over a calendar month, calculated as the sum of all "daily discharges" measured during a calendar month divided by the number of "daily discharges" measured during that month.
- 4. "Average weekly discharge limitation" means the highest allowable average of "daily discharges" over a calendar week, calculated as the sum of all "daily

Page 22 of 24

discharges" measured during a calendar week divided by the number of "daily discharges" measured during that week.

- 5. "Best Management Practices" (BMPs) means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States. BMPs also include treatment requirements, operating procedures, and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage areas.
- 6. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility.
- 7. "Composite" see "24-hour composite".
- 8. "Daily discharge" means the discharge of a pollutant measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the "daily discharge" is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the "daily discharge" is calculated as the average measurement of the pollutant over the day.
- 9. "Director of the Office of Compliance and Enforcement" means the Director of the Office of Compliance and Enforcement, EPA Region 10, or an authorized representative.
- 10. "Director of the Office of Water and Watersheds" means the Director of the Office of Water and Watersheds, EPA Region 10, or an authorized representative.
- 11. "DMR" means discharge monitoring report.
- 12. "EPA" means the United States Environmental Protection Agency.
- 13. "Geometric Mean" means the n<sup>th</sup> root of a product of n factors, or the antilogarithm of the arithmetic mean of the logarithms of the individual sample values.
- 14. "Grab" sample is an individual sample collected over a period of time not exceeding 15 minutes.
- 15. "IDEQ" means the Idaho Department of Environmental Quality.
- 16. "Interference" is defined in 40 CFR 403.3.

Page 23 of 24

17. "Interim Minimum Level (IML)" is used when a method-specific "Minimum Level (ML)" has not been published by EPA. The IML is equal to 3.18 times the method-specified "Method Detection Limit (MDL)". The IML for non-metals is rounded to the nearest multiple of 2, 5, 10, 20, 50.

- 18. "Maximum daily discharge limitation" means the highest allowable "daily discharge."
- 19. "Method Detection Limit (MDL)" means the minimum concentration of a substance (analyte) that can be measured and reported with 99 percent confidence that the analyte concentration is greater than zero and is determined from analysis of a sample in a given matrix containing the analyte.
- 20. "Minimum Level (ML)" means the concentration at which the entire analytical system must give a recognizable signal and an acceptable calibration point. The ML is the concentration in a sample that is equivalent to the concentration of the lowest calibration standard analyzed by a specific analytical procedure, assuming that all the method-specified sample weights, volumes and processing steps have been followed.
- 21. "NPDES" means National Pollutant Discharge Elimination System, the national program for issuing, modifying, revoking and reissuing, terminating, monitoring and enforcing permits . . . under sections 307, 402, 318, and 405 of the CWA.
- 22. "Pass Through" means a Discharge which exits the POTW into waters of the United States in quantities or concentrations which, alone or in conjunction with a discharge or discharges from other sources, is a cause of a violation of any requirement of the POTW's NPDES permit (including an increase in the magnitude or duration of a violation).
- 23. "QA/QC" means quality assurance/quality control.
- 24. "Regional Administrator" means the Regional Administrator of Region 10 of the EPA, or the authorized representative of the Regional Administrator.
- 25. "Severe property damage" means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
- 26. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly

Page 24 of 24

designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.