

PROJECT facts

Sequestration

03/2006

U.S. DEPARTMENT OF ENERGY
OFFICE OF FOSSIL ENERGY
NATIONAL ENERGY TECHNOLOGY LABORATORY



GREENHOUSE GAS EMISSIONS CONTROL BY OXYGEN FIRING IN CIRCULATING FLUIDIZED BED BOILERS

Background

CONTACTS

Sean Plasynski

Sequestration Technology Manager
National Energy Technology
Laboratory
626 Cochrans Mill Road
P.O. Box 10940
Pittsburgh, PA 15236
412-386-4867
sean.plasynski@netl.doe.gov

Timothy Fout

Project Manager
National Energy Technology
Laboratory
3610 Collins Ferry Road
P.O. Box 880
Morgantown, WV 26507
304-285-1341
timothy.fout@netl.doe.gov

Nsakala ya Nsakala

ALSTOM Power, Inc.
2000 Day Hill Rd.
Windsor, CT 06095
860-285-2018
nsakala.y.nsakala@power.alstom.com

The object of oxygen-fired combustion is to burn the fuel in enriched air or pure oxygen to produce a concentrated stream of CO₂. Oxygen fired combustion presents significant challenges, but also provides a high potential for technology breakthroughs and a step-change reduction in CO₂ separation and capture costs. Barriers and issues include: 1) oxygen from cryogenic air separation is expensive, and oxygen combustion consumes several times more oxygen than gasification; 2) combustion of fuels in pure oxygen occurs at temperatures too high for existing boiler or turbine materials, while CO₂ recycle to control temperature increases the parasitic power load.

Primary Project Goal

The overall project goal is to conduct economic evaluations of the recovery of carbon dioxide using a newly constructed circulating fluidized bed (CFB) combustor while burning coal, petroleum coke, or biomass fuel with a mixture of oxygen and recycled flue gas, instead of air.

Objectives

- The Phase I objective is to determine which of the new concepts in a CFB are technically feasible and have the potential of reducing the target cost of carbon avoided.
- Petroleum coke and coal samples will be combustion tested in a 4-inch Fluidized Bed Combustion reactor to determine their gaseous (NO_x, SO₂, CO) and unburned carbon emissions and ash agglomeration/sintering potentials during combustion in oxygen-rich environments.
- The Phase II objective is to generate a refined technical and economic evaluation of the most promising concept for reducing CO₂ mitigation costs (based on recommendations from Phase I), based on data from proof-of-concept testing of the most promising concept.



PARTNERS

Alstom Power Inc.
ABB Lummus Global, Inc.
Praxair, Inc.
Parsons Energy and Chemical Group

COST

Total Project Value
\$2,730,471
DOE/Non-DOE Share
\$2,730,471 / \$546,095

ADDRESS

National Energy Technology Laboratory

1450 Queen Avenue SW
Albany, OR 97321-2198
541-967-5892

2175 University Avenue South
Suite 201
Fairbanks, AK 99709
907-452-2559

3610 Collins Ferry Road
P.O. Box 880
Morgantown, WV 26507-0880
304-285-4764

626 Cochran's Mill Road
P.O. Box 10940
Pittsburgh, PA 15236-0940
412-386-4687

One West Third Street, Suite 1400
Tulsa, OK 74103-3519
918-699-2000

CUSTOMER SERVICE

I-800-553-7681

WEBSITE

www.netl.doe.gov

Accomplishments

Phase I has been completed. The performance analysis of the base case (Air-Fired) CFB has been conducted. Key results included plant-efficiency, equipment costs, cost of electricity, and CO₂ mitigation costs. Work was completed on design/performance analyses of:

- Three advanced O₂-fired CFB concepts
- One high temperature carbonate regeneration process
- One chemical looping concept
- Two IGCC cases (one base case without CO₂ capture and one with a water-gas shift reactor to capture CO₂).


COST

Phase II pilot testing has been completed. Two test runs were performed in March and June of 2004. Experiments were conducted using coal and petcoke. Oxygen levels examined include 21% (baseline) and various levels up to a local high of 70% oxygen. The rest of the stream was CO₂ to simulate a flue gas recycle. Key results include:

- Successful operation of the 2.9MW_{th} facility with bituminous coal and petcoke with no evidence of particle agglomeration or defluidization in the furnace
- Higher than normal sulfur emissions for bituminous coal than normal for the same limestone feed rate. Due to higher furnace temperature necessary to ensure calcination of limestone.
- Lower NO_x emissions under oxygen firing. Mainly due to reduction in prompt NO_x.
- Updated performance analyses based upon testing results.

Benefits

The results from this project will provide the power industry with concrete data concerning greenhouse gas emissions control by oxygen firing in circulating fluidized bed boilers. The comparison of the several different technologies will target the most economical gas clean-up configuration.



ALSTOM's Multi-Use Test Facility (MTF)