

**NATURAL RESOURCES CONSERVATION SERVICE  
CONSERVATION PRACTICE STANDARD**

**RESIDUE AND TILLAGE MANAGEMENT  
RIDGE TILL**

(Ac.)

**CODE 346**

**DEFINITION**

Managing the amount, orientation and distribution of crop and other plant residues on the soil surface year-round, while growing crops on pre-formed ridges alternated with furrows protected by crop residue.

**PURPOSE**

- Reduce sheet and rill erosion
- Reduce wind erosion
- Reduce irrigation induced erosion
- Maintain or improve soil condition
- Reduce soil particulate emissions
- Manage snow to increase plant-available moisture
- Modify cool, wet site conditions
- Provide food and escape cover for wildlife

**CONDITIONS WHERE PRACTICE APPLIES**

This practice applies to all cropland and other land where crops are planted.

This practice includes tillage and planting methods commonly referred to as ridge till or ridge planting. It does not include no-till planting on ridges or bedding or listing operations that bury crop residues.

**CRITERIA**

**General Criteria Applicable to All Purposes**

Following crop harvest, residues shall remain on the surface until planting with no additional disturbance except for normal weathering.

Ridge height shall be maintained throughout the harvest and winter seasons by controlling equipment or livestock traffic.

After planting, residues shall be maintained in the furrows until the ridges are rebuilt by cultivation. Ridges shall be rebuilt to their original height and shape during the last row cultivation.

**Stable Outlets.** A stable outlet must exist where ridges direct runoff to areas of concentrated flow.

**Maximum Row Grade.** Row grades shall not exceed those given in the following table.

10-Year Storm Erosivity Index (EI)	Maximum Row Grade (%) <sup>1</sup>
<100	9
100 – 150	7
>150	6

<sup>1</sup> Based on existing water erosion prediction technology.

If irrigation is used with this practice, use the row grade limitation for the next higher 10-year storm EI value. Where residue cover is less than 30 percent, use the maximum row grade for the next higher 10-year storm EI value.

**Additional Criteria to Reduce Sheet and Rill Erosion**

Soil and residue removed from the top of the ridge shall be moved into the furrow between the ridges.

After planting, the top of the ridge shall be maintained at least 3 inches higher than the furrow between the ridges.

Conservation practice standards are reviewed periodically and updated if needed. To obtain the current version of this standard, contact your Natural Resources Conservation Service [State Office](#) or visit the [electronic Field Office Technical Guide](#).

**NRCS, IDAHO  
July 2006**

The ridge top shall be shaped to direct runoff to the protected furrow area.

#### **Additional Criteria to Reduce Wind Erosion**

Wind erosion calculations shall account for the effects of ridge height, spacing and orientation to the direction of erosive winds.

#### **Additional Criteria to Maintain or Improve Soil Condition**

An evaluation of the cropping system using the current, approved soil conditioning index procedure shall result in a positive trend.

Cultivation to rebuild ridges shall be done using tools that maintain residues in the surface layer.

#### **Additional Criteria to Reduce Soil Particulate Emissions**

The amount and orientation of residue needed and the amount of surface soil disturbance allowed to reduce wind erosion to the tolerable soil loss value (T) shall be determined using the current, approved wind erosion prediction technology. Calculations shall account for the effects of other practices in the conservation management system.

#### **Additional Criteria to Manage Snow to Increase Plant-available Moisture**

During the time that significant snowfall is expected to occur, the minimum distance between the bottom of the furrow and the top of the stubble shall be:

- at least 10 inches for crops with a row spacing of less than 15 inches
- at least 15 inches for crops with a row spacing of 15 inches or greater

If this minimum distance cannot be achieved, ridges shall be oriented not to exceed 45 degrees from perpendicular to the prevailing wind direction during periods of expected snowfall.

#### **Additional Criteria to Modify Cool Wet Site Conditions**

Ridge height prior to planting shall be at least 6 inches.

#### **Additional Criteria to Provide Food and Escape Cover for Wildlife**

The amount of residue and height of stubble needed to provide cover during winter months

shall be determined using an approved wildlife management plan. Stubble shall remain standing over winter.

#### **CONSIDERATIONS**

**General** - Removing of residue, such as by baling or grazing, can have negative impacts on resources. These activities should not be performed without full evaluation of impacts on soil, water, animal, plant and air resources.

Ridge till may be practiced continuously throughout some crop sequences or may be managed as part of a residue management system that includes other tillage and planting methods, such as mulch till or no till. In mixed systems, ridges must be periodically re-established. Selection of acceptable tillage methods for specific site conditions may be aided by an approved Soil Tillage Suitability Rating (STSR).

Production of adequate amounts of crop residues necessary for the proper functioning of this practice can be enhanced by selection of high-residue producing crops and crop varieties in the rotation, use of cover crops and adjustment of plant population and/or row spacing.

Since row cultivation is typically used for weed control and to reform ridges, this practice has the potential to reduce herbicide requirements.

A field border planted to permanent vegetation can assist in unobstructed turning, elimination of end rows and providing travel lanes for farming operations.

Leaving unharvested crop rows at intervals across the field can enhance the value of residue cover and food for wildlife.

#### **Maintaining or Improving Soil Condition and Reducing CO<sub>2</sub> Loss from the Soil -**

Continuous ridge planting will allow organic material to accumulate in the surface horizon. Reconstruction of ridges in the same row area year after year will maximize organic matter buildup and biological activity in the row.

CO<sub>2</sub> loss is directly related to the volume of soil disturbed, the intensity of the disturbance and the soil moisture content and soil temperature at the time the disturbance occurs.

- Shallow soil disturbance (1-3 inches) releases less CO<sub>2</sub> than deeper operations.
- When deep soil disturbance is performed, such as by subsoiling or fertilizer injection, make sure the vertical tillage slot created by these implements is closed at the surface.
- Planting with a single disk opener, no-till drill will release less CO<sub>2</sub> than planting with a wide-point hoe/chisel opener, air seeder drill.
- Soil disturbance that occurs when soil temperatures are below 50° F will release less CO<sub>2</sub> than operations done when the soil is warmer.

Soil compaction may be reduced by controlled traffic, in which wheel traffic from all operations is limited to the area between designated rows or traffic areas.

#### **Providing Food and Escape Cover for**

**Wildlife** - Avoid disturbing standing stubble or heavy residue during the nesting season for ground-nesting species.

Forgoing fall shredding or tillage operations will maximize the amount of wildlife food and cover during critical winter months.

Leaving rows of unharvested crop standing at intervals across the field or adjacent to permanent cover will enhance the value of residues for wildlife food and cover. Leaving unharvested crop rows for two growing seasons will further enhance the value of these areas for wildlife.

#### **PLANS AND SPECIFICATIONS**

Specifications for establishment and operation of this practice shall be prepared for each field or treatment unit according to the Criteria, Considerations and Operation and Maintenance described in this standard. Specifications shall be recorded using approved specification sheets, job sheets, narrative statements in the conservation plan or other acceptable documentation.

#### **OPERATION AND MAINTENANCE**

No operation and maintenance requirements, national in scope, have been identified for this practice.

#### **REFERENCES**

- Bolton, Ryan. 2003. Impact of the surface residue layer on decomposition, soil water properties and nitrogen dynamics. M.S. thesis. Univ. of Saskatchewan, Saskatoon, Saskatchewan, CA.
- Renard, K.G., G.R. Foster, G.A. Weesies, D.K. McCool and D.C. Yoder, coordinators. 1997. Predicting soil erosion by water: A guide to conservation planning with the Revised Universal Soil Loss Equation (RUSLE). U.S. Department of Agriculture, Agriculture Handbook. No. 703.
- Shaffer, M.J. and W.E. Larson (ed.). 1987. Tillage and surface-residue sensitive potential evaporation submodel. *In* NTRM, a soil-crop simulation model for nitrogen, tillage and crop residue management. USDA Conserv. Res. Rep. 34-1. USDA-ARS.
- Skidmore, E.L. and N.P. Woodruff. 1968. Wind erosion forces in the United States and their use in predicting soil loss. U.S. Department of Agriculture. Agriculture Handbook, No. 346.
- U.S.D.A. Natural Resources Conservation Service. 2002. National Agronomy Manual. 190-V. 3<sup>rd</sup> ed.

Conservation practice standards are reviewed periodically and updated if needed. To obtain the current version of this standard, contact your Natural Resources Conservation Service [State Office](#) or visit the [electronic Field Office Technical Guide](#).

**NRCS, IDAHO**  
**July 2006**