

sc - Buried Cable

Cables listed below comply 7 CFR 1755.390 or 1755.890.

Manufacturer Name	PE-39	PE-89	Accepted Cables	Suffixes
General Cable	X	X(6)	PE-__39-AL	A(1)
	X	X(6)	PE-__39-CU5	C(1)
	X	X(6)	PE-__39-CBS	Y(1)
	X	X(6)	PE-__39-CAC	X(1)
	X	X(6)	__(3)T1	H(1)
	X	X(6)	__(3)T1C	H1C(2)
Nacional De Conductores Eléctricos (Conduxmex)(5)		X		
	X	X(6)	AM__(12)C	A(1)
	X	X(6)	AM__(12)Q	Y(1)
	X	X(6)	AM__(12)D	X(1)
Superior/Essex	X		SEALPIC ^R -F	A(1)
		X(7)	SEALPIC ^R -F__(11)	A(1)
	X		CUPIC ^R -F	C(1)
		X(7)	CUPIC ^R -F__(11)	C(1)
	X		GOPIC ^R -F	Y(1)
			CUPIC ^R -F10	
		X(7)	GOPIC ^R -F__(11)	Y(1)
			CUPIC ^R -F__(11)10	
	X		CASPIC ^R -F	X(1)
		X(7)	CASPIC ^R -F__(11)	X(1)
	X	X(7)	__(3)T1	H(1)
			__(3)T1	
	X	X(7)	__(3)T1C	H1C(2)
__(3)T1C				
X	X(7)	__(4)P	P(1)	
		__(4)P		

Suffixes

- Coated Aluminum Shield-----A
- 5 Mil Copper Shield-----C
- Gopher-Resistant Shield Containing Copper-----Y
- Gopher-Resistant Shield/Armor Design -----X
- Screened Cable for T1 Carrier-----H
- Screened Cable for T1C Carrier-----H1C
- Pre-connectorized Cable 100 pairs and greater-----P

See notes on page 1.1.2.

1.1.2
012-27-2005
sc

Notes:

- (1) Available in 19 through 26 AWG conductor sizes.
- (2) Available in 19 through 24 AWG conductor sizes.
- (3) Replace blank with manufacturer's catalog designation shown in the listing for suffixes A through X.
- (4) Replace blank with manufacturer's catalog designation shown in the listing for suffixes A through H1C.
- (5) Not accepted for 19 AWG conductor sizes.
- (6) Accepted for only foam/skin.
- (7) Accepted for foam and foam/skin.
- (10) Replace the blank with the letters AR, CR, JR, or WR to specify shield type.
- (11) Replace blank with either the letter F or the letters SF to specify conductor insulation type.
- (12) Replace blank with either the letter A, M, or T to specify conductor AWG size.