1-06 1135

## NATIONAL TRANSPORTATION SAFETY BOARD WASHINGTON, D.C.

ISSUED: March 13, 1980

Forwarded to: Honorable Langhorne M. Bond Administrator Federal Aviation Administration Washington, D.C. 20591

SAFETY RECOMMENDATION(S)

A-80-19

On November 18, 1979, at 0447 m.s.t., a Transamerica Airline, L-188, N-859U, with three crewmembers and 27,000 pounds of cargo aboard, departed Hill Air Force Base, Utah. While climbing from 12,000 to 13,000 feet, the crew advised Salt Lake Center that it had lost all electrical power, and requested an immediate descent to VFR conditions with vectors to avoid high terrain. During the descent, the aircraft attained a high airspeed and rate of descent, and broke up in flight. Although the Safety Board's analysis has not yet been completed, the evidence developed in the investigation indicates that certain precautionary action should be initiated on an expedited basis.

Federal Aviation Regulations (14 CFR 121.305(j)) require that all turbojet aircraft be equipped with three gyroscopic bank-and-pitch indicators, the third of which is to be powered independently of the normal electrical generating system; this requirement, however, does not apply to large turboprop aircraft operating under 14 CFR 121 regulations. The Safety Board believes that had N-859U had a third attitude-indicating instrument aboard, the crew probably could have avoided the high airspeed and descent rates which contributed to the airplane breakup.

The Safety Board supported the 1969 proposed rulemaking to require the indicating instrument in all turbine engine powered transport category aircraft, including large turboprop aircraft. However, turboprop aircraft were not included in the final rule NPRM 69-26, which instituted the requirement for large turbojet aircraft.

2881

AAR-80-11

Accordingly, the Safety Board recommends that the Federal Aviation Administration:

Amend 14 CFR 121.305(j) to extend its application to all large turboprop aircraft to require an additional attitude-indicating instrument, for bank and pitch, operating from a source of power independent of the normal electrical generating system as is now required on all large turbojet aircraft. (Class II, Priority Action) (A-80-19)

KING, Chairman, DRIVER, Vice Chairman, McADAMS, GOLDMAN, and BURSLEY, Members, concurred in this recommendation.

lames & James B. King Chairman

