

RCN 218-070-07-20

**DEMONSTRATION OF INNOVATIVE APPLICATIONS
OF TECHNOLOGY FOR THE CT-121 FGD PROCESS**

Plant Yates

**Environmental Monitoring Program Report:
Fourth Quarter and Annual 1995
(Final)**

**DOE DE-FC22-90PC89650
SCS C-90-00284**

Prepared for:

**Southern Company Services, Inc.
P.O. Box 2625
600 North 18th Street
Birmingham, Alabama 35291-1195**

Prepared by:

**Radian International LLC
8501 North Mopac Boulevard
P.O. Box 201088
Austin, Texas 78720-1088**

Cleared by DOE Patent Counsel.

Legal Notice

This report was prepared by Radian International LLC for Southern Company Services, Inc. pursuant to a cooperative agreement partially funded by the U.S. Department of Energy and neither Southern Company Services, Inc., nor any of its subcontractors, nor the U.S. Department of Energy, nor any person acting on behalf of either:

1. Makes any warranty or representation, express or implied with respect to the accuracy, completeness, or usefulness of the information contained in this report or that the process disclosed in this report may not infringe privately-owned rights; or
2. Assumes any liabilities with respect to the use of or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Department of Energy. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Department of Energy.

**Demonstration of Innovative Applications
of Technology for the CT-121 FGD Process**

Plant Yates

**Environmental Monitoring Program Report:
Fourth Quarter and Annual 1995**

This progress report summarizes activities associated with the environmental monitoring program (EMP) during the calendar year of 1995 for the U.S. Department of Energy's Innovative Clean Coal Technology project entitled "Demonstration of Innovative Applications of Technology for the CT-121 FGD Process." This demonstration project was conducted at Georgia Power Company's Plant Yates Unit 1, located near Newnan, Georgia, until January 1995, when operational responsibility was permanently transferred to Georgia Power Company from Southern Company Services, Inc., manager of the demonstration project.

No further operational testing is planned, and monitoring under the EMP will be limited to groundwater monitoring.

Post-operational-phase groundwater monitoring began during the first quarter of 1995 and continued throughout the year. A report containing the results of groundwater monitoring conducted during the third quarter of 1995 is attached.

Attachment

**Groundwater Monitoring Report
for the Third Quarter of 1995**

Table of Contents

1.0	Introduction	1
1.1	Project Summary	1
1.2	Purpose and Scope of Groundwater Monitoring	2
1.3	Report Contents	5
2.0	Sampling and Analytical Methods	5
2.1	Sampling Methods	5
2.2	Analytical Procedures	6
3.0	Summary of Results	6
4.0	Summary of QA/QC Activities	13
	Appendix A: Historical Monitoring Data for Selected Parameters	A-1
	Appendix B: QA/QC Results	B-1

List of Figures

1	Location of Groundwater Monitoring Wells	4
2	Historical Data for Representative Species from Well GWA-1 (Upgradient)	14
3	Historical Data for Representative Species from Well GWC-2 (Downgradient)	15
4	Historical Data for Representative Species from Well GWC-4 (Downgradient)	16

List of Tables

1	EMP Groundwater Monitoring Parameters	3
2	Summary of Groundwater Samples Collected at Plant Yates on September 11-12, 1995	7
3	Sample Containers, Preservation Methods, and Maximum Holding Times	8
4	Analytical Methods	9
5	Results of Groundwater Monitoring Conducted September 11-12, 1995 (Third Quarter 1995)	10
6	Results for Duplicate Samples—Third Quarter 1995	18

1.0 Introduction

This report summarizes the results of groundwater monitoring performed during the third calendar quarter of 1995 as part of the environmental monitoring program (EMP) for the U.S. Department of Energy's Innovative Clean Coal Technology project entitled "Demonstration of Innovative Applications of Technology for the CT-121 FGD Process." This demonstration project is being conducted at Georgia Power Company's Plant Yates Unit 1, located near Newnan, Georgia.

1.1 Project Summary

The purpose of this ICCT project is to demonstrate the use of the Chiyoda Thoroughbred-121 flue gas desulfurization process as a means of reducing SO₂ and particulate emissions from pulverized-coal utility boilers that use medium-sulfur coal. This project is also designed to demonstrate the lower cost and higher reliability of the CT-121 process compared to conventional wet limestone FGD processes.

The demonstration project at Plant Yates consists of four distinct environmental test periods:

- ▶ Period 0: Site Preparation, Construction, and Startup of the Demonstration Project (including background groundwater monitoring [29 months]);
- ▶ Period 1: Baseline Testing at Low Particulate Loading—ESP In Service (12 months);
- ▶ Period 2: Testing at High Particulate Loading—ESP Detuned or Out of Service (12 months); and
- ▶ Period 3: Post Demonstration Groundwater Testing and Gypsum Byproduct Evaluation.

Period 2 ended in December 1994. Groundwater monitoring was initiated in Period 0 and will continue through 24 months of Period 3.

1.2 Purpose and Scope of Groundwater Monitoring

The CT-121 process produces gypsum, which is being disposed of in an on-site stacking area where the solids are concentrated as they are allowed to settle, dewater, and dry. The gypsum and gypsum/fly ash stacking area is lined with a synthetic liner to minimize the potential for adverse impacts on the groundwater. Requirements for the liner, leachate collection system, and groundwater monitoring are specified in the permit issued by the Georgia Department of Natural Resources (DNR). One requirement is the regular monitoring of groundwater before, during, and for two years after completion of the demonstration program. The purpose of this monitoring is to demonstrate that the gypsum stacking area can be operated in an environmentally benign and acceptable manner.

In 1990, five groundwater monitoring wells were installed in the vicinity of the proposed gypsum stacking area. These wells were used to monitor baseline groundwater quality prior to construction of the stacking area. Monitoring was conducted every two months from September 1990 through July 1991. Table 1 is a summary of the parameters that were monitored during this period. The results of this monitoring activity were summarized in the report "Environmental Monitoring Program Report of Preconstruction Monitoring: 1990-1991 Background Water Quality."

Following the preconstruction monitoring period, and as a DNR permit requirement, two additional monitoring wells were installed in 1992. The locations of all seven monitoring wells are shown in Figure 1. Because of a delay in the commencement of Period 1 testing, an additional round of preoperational groundwater monitoring was conducted on September 3-4 and October 14, 1992. The results of this monitoring effort were presented in the report "Interim Data Report of Preoperational Groundwater Monitoring: September 3-4 and October 14, 1992."

Operational-phase groundwater monitoring, performed on a quarterly basis, was initiated in the fourth quarter of 1992. Monitoring was conducted for the suite of parameters shown previously in Table 1. Samples were analyzed each quarter for all parameters shown except for radionuclides, which are monitored semiannually.

Beginning in the second quarter of 1994, monitoring is also being performed quarterly for total organic halides (TOX) and annually for volatile organic compounds (VOCs). These

Table 1. EMP Groundwater Monitoring Parameters

pH	Conductivity	Temperature
Eh	Alkalinity	Total Dissolved Solids
Bromide	Chloride	Total Organic Carbon
Fluoride	Nitrate-Nitrite	Sulfate
Trace Elements (Dissolved)		
Silver	Aluminum	Arsenic
Boron	Barium	Beryllium
Bismuth	Calcium	Cadmium
Cobalt	Copper	Chromium
Mercury	Iron	Potassium
Lithium	Magnesium	Manganese
Molybdenum	Sodium	Nickel
Phosphorus	Lead	Sulfur
Antimony	Selenium	Silicon
Tin	Strontium	Tellurium
Titanium	Thallium	Uranium
Vanadium	Tungsten	Zinc
Other		
Radionuclides		




Figure 1. Location of Groundwater Monitoring Wells

parameters have been added to comply with requirements of the permit issued by the Environmental Protection Division of the Georgia DNR.

The post-demonstration groundwater monitoring period began in the first quarter of 1995 and will be conducted over a period of two years for the same parameters and at the same frequency as during the operational phase.

1.3 Report Contents

This report includes the results of quarterly post-demonstration groundwater monitoring for the third calendar quarter of 1995. The groundwater monitoring wells were sampled on September 11-12, 1995.

Section 2 is a brief summary of the groundwater sampling and analytical methods used to conduct the monitoring. The results of the monitoring are presented in Section 3. Results of quality assurance/quality control (QA/QC) activities associated with sample analyses are summarized in Section 4. Tables of historical trends for selected parameters and the results for field and laboratory duplicates are given in the appendices.

2.0 Sampling and Analytical Methods

This section describes the methods used to obtain and analyze groundwater samples. These methods were specified in Radian's "Test Plan for Groundwater Monitoring Around the Plant Yates Gypsum Stacking Area," August 30, 1990, as amended.

2.1 Sampling Methods

The QED Well Wizard dedicated sampling system was used to purge the monitoring wells and collect samples. The Well Wizard system utilizes a dedicated Teflon® bladder pump and portable air compressor to extract groundwater samples.

To ensure the collection of a representative sample, standing water was removed from each well by purging a minimum of three wetted casing volumes. Conductivity, pH, redox potential, and temperature were monitored and recorded on field sampling forms during purging. Samples were collected after these indicator parameters stabilized and (1) after at least three wetted casing volumes of water were removed or (2) immediately following recovery if a well was purged dry.

Samples were obtained from the upgradient well (GWA-1) and five of the six downgradient wells (GWC-1, GWC-2, GWC-3, GWC-4, and GWC-5). As has been the case during all previous rounds of monitoring, well GWC-6 could not be sampled since it was unproductive and contained no water. Table 2 summarizes the groundwater samples collected during this monitoring period.

To preserve the integrity of the groundwater samples before analyses, proper sample containment, preservation, holding time requirements, shipment, and chain-of-custody procedures were followed. Sample bottles, preservation methods, and maximum holding times are summarized in Table 3.

2.2 Analytical Procedures

The analytical methods used in this program are listed in Table 4. There were no deviations from these methods.

3.0 Summary of Results

The results of the third-quarter 1995 groundwater monitoring are presented in Table 5. The concentrations of all of the monitored dissolved constituents in the groundwater near the gypsum stacking area continue to be low.

**Table 2. Summary of Groundwater Samples Collected
at Plant Yates on September 11-12, 1995**

Well ID	Sample ID	Analyses
GWA-1	GWA-1-19-1	Anions, TOC, TOX, and Metals ^a
GWC-1	GWC-1-19-1	Anions, TOC, TOX, Metals, and Radionuclides
GWC-2	GWC-2-19-1	Anions, TOC, TOX, Metals, and Radionuclides
GWC-3	GWC-3-19-1	Anions, TOC, TOX, Metals, and Radionuclides
GWC-4	GWC-4-19-1	Anions, TOC, TOX, Metals, and Radionuclides
	GWC-4-19-2	Anions, TOC, TOX, Metals, and Radionuclides
GWC-5	GWC-5-19-1	Anions, TOC, TOX, Metals, and Radionuclides
GWC-6	None	Well dry; no samples collected

^a Insufficient volume was produced by this well for radionuclide analysis.

Table 3. Sample Containers, Preservation Methods, and Maximum Holding Times

Bottle Label	Containers*	Parameter	Preservation Method	Maximum Holding Time (days)
Total Organic Carbon	500-mL Amber Glass	Total Organic Carbon	H ₂ SO ₄ pH<2	28
Anions/TDS	1-L Plastic	Bromide	4 °C	28
		Chloride	4 °C	28
		Fluoride	4 °C	28
		Nitrate-Nitrite	4 °C	28
		Sulfate	4 °C	28
		Total Dissolved Solids	4 °C	7
TOX	250-mL Amber Glass, no headspace	Total Organic Halogens	H ₂ SO ₄ pH<2	28
VOCs	(2) 40-mL VOA Vials	Volatile Organics	HCl pH<2	14
Metals	1-L Plastic	Trace Metals	Filtered On Site Ultrex II HNO ₃ pH<2	180
Radioactivity	(3) 1-L Plastic	Radium 226, Radium 228, Gross Alpha, Gross Beta, Gross Gamma	Filtered On Site Ultrex II HNO ₃ pH<2	180

* Sample containers supplied by either I-Chem or Eagle Picher.

Table 4. Analytical Methods

Parameter	Technique	Reference
pH	Potentiometry	EPA 150.1
Conductivity	Specific Conductance	EPA 120.1
Temperature	Temperature Probe	EPA 170.1
Eh	Electrometry	ASTM D1498
Alkalinity	Titrimetric or Colorimetric	EPA 310.1 or 310.2
Bromide	Ion Chromatography	EPA 300
Chloride	Ion Chromatography	EPA 300
Total Organic Carbon	Combustion/IR	EPA 415.1
TOX	Carbon Adsorption/Combustion/ Electrolytic Titration	SW-846 Method 9020A
VOCs	GC/MS	SW-846 Method 8260
Fluoride	SIE	EPA 340.2
Nitrate/Nitrite	Colorimetry	EPA 353.1
Sulfate	Ion Chromatography	EPA 300
Total Dissolved Solids	Filtration/Evaporation/Gravimetry	EPA 160.2
Mercury	On-site Filtration/Cold Vapor AA	EPA 245.1
Trace Elements	On-site Filtration/AA and ICP-AES	EPA 200.7, 7421 (Cr), 7060 (As), 7421 (Pb), 7041 (Sb), 7740 (Se), and 7841 (Tl)
Radium 226 and 228	Proportional Counter	ASTM D2460
Gross Alpha	Proportional Counter	ASTM D1943
Gross Beta	Proportional Counter	ASTM D1890
Gross Gamma	Gamma Ray Spectrometer	ASTM D2459

Legend:

- AA = Atomic absorption spectrophotometry;
- SIE = Specific ion electrode;
- ICP-AES = Inductively coupled plasma-atomic emission spectrometry;
- IR = Infrared detection; and
- GC/MS = Gas chromatography/mass spectroscopy

References:

- EPA = "Methods for Chemical Analysis of Water and Wastes," EPA-600/4-79-020, revised March 1983.
- ASTM = American Society for Testing and Materials, *Annual Book of ASTM Standards*.
- SW-846 = "Test Methods for Evaluating Solid Waste," SW-846, 3rd Ed., November 1986.

Table 5. Results of Groundwater Monitoring Conducted September 11-12, 1995 (Third Quarter 1995)

Parameter	GWA-1-19-1	GWC-1-19-1	GWC-2-19-1	GWC-3-19-1	GWC-4-19-1	GWC-5-19-1
pH	6.38	6.00	5.41	5.02	4.79	5.20
Conductivity ($\mu\text{S}/\text{cm}$)	165	79	67.5	45	180	60
Temperature ($^{\circ}\text{C}$)	20.2	18.0	18.8	18.2	18.7	18.4
Eh (mV)	231	127	141	156	219	148
Alkalinity (mg/L CaCO_3)	23	31	13.5	9.0	4.5	11.0
Total Dissolved Solids (mg/L)	114	58	54	37	123	64
Bromide (mg/L)	<0.0181	<0.0181	<0.0181	<0.0181	<0.0181	<0.0181
Chloride (mg/L)	2.27	2.77	3.83	3.64	37.5	2.70
Total Organic Carbon (mg/L)	<0.117	<0.117	0.571 ^c	<0.117	1.86	<0.117
Fluoride (mg/L)	0.0904 ^b	0.0582 ^b	0.0402 ^b	0.0370 ^b	0.0325 ^b	0.0304 ^b
Nitrate-Nitrite (mg/L as N)	0.0999	0.287	0.888	0.298	1.74	0.0298
Sulfate (mg/L)	24.4	1.06	3.90	0.595	3.03	6.80
Radium-226 and -228 (pCi/L)	NA	0.310 \pm 1.33 -0.490 \pm 1.68	0.120 \pm 0.770 -0.680 \pm 1.67	0.230 \pm 0.890 -0.230 \pm 1.39	0.190 \pm 0.840 -0.430 \pm 1.59	-0.530 \pm 0.892 -0.980 \pm 1.70
Gross Alpha (pCi/L)	NA	0.71 \pm 0.25	<0.44	<0.37	<0.67	0.53 \pm 0.20
Gross Beta (pCi/L)	NA	<1.4	<1.4	<1.3	<1.6	1.47 \pm 0.49
Gross Gamma (pCi/L)						
Ac-228	NA	18.3 \pm 8.35	14.7 \pm 9.34	7.36 \pm 7.36	16.1 \pm 7.71	5.14 \pm 9.33
Bi-214	NA	5.06 \pm 13.2	-6.50 \pm 17.0	12.2 \pm 13.7	-1.93 \pm 13.5	-3.19 \pm 17.1
K-40	NA	10.9 \pm 94.6	-90.4 \pm 108	-128 \pm 85.3	-67.3 \pm 84.5	0.000 \pm 108
Pb-214	NA	4.31 \pm 12.1	-8.63 \pm 14.8	26.8 \pm 4.96	9.62 \pm 4.23	-7.13 \pm 14.8
Silver (mg/L)	<0.00519	<0.00519	<0.00519	<0.00519	<0.00519	<0.00519
Aluminum (mg/L)	<0.0523	<0.0523	<0.0523	0.0716 ^c	<0.0523	<0.0523
Arsenic (mg/L)	<0.00102	<0.00102 ^b	<0.00102 ^b	<0.00102 ^b	<0.00102 ^b	<0.00102 ^b

Table 5 (continued)

Parameter	GWA-1-19-1	GWC-1-19-1	GWC-2-19-1	GWC-3-19-1	GWC-4-19-1	GWC-5-19-1
Boron (mg/L)	<0.0176	<0.0176	<0.0176	<0.0176	0.234	<0.0176
Barium (mg/L)	0.0289	0.0111	0.00888	0.00933	0.0262	0.00799
Beryllium (mg/L)	<0.00051	<0.00051	<0.00051	<0.00051	<0.00051	<0.00051
Bismuth (mg/L)	<0.00504	<0.00504	<0.00504	<0.00504	<0.00504	<0.00504
Calcium (mg/L)	8.47	5.12	2.16	0.389	3.03	1.48
Cadmium (mg/L)	<0.00386	<0.00386	<0.00386	<0.00386	<0.00386	<0.00386
Cobalt (mg/L)	0.0101 ^{b,c}	0.0101 ^{b,c}	0.00757 ^{b,c}	0.00756 ^{b,c}	0.0126 ^{b,c}	0.0108 ^{b,c}
Copper (mg/L)	<0.00916	<0.00916	<0.00916	<0.00916	<0.00916	<0.00916
Chromium (mg/L)	0.0180 ^c	<0.00524	<0.00524	<0.00524	0.0113 ^c	0.0108 ^c
Mercury (mg/L)	<0.000028	<0.000028	<0.000028	<0.000028	<0.000028	<0.000028
Iron (mg/L)	<0.00452 ^b	0.0410 ^b	0.0336 ^b	0.0772 ^b	0.0217 ^b	0.0681 ^b
Potassium (mg/L)	1.65 ^c	<0.822	<0.822	<0.822	<0.822	<0.822
Lithium (mg/L)	<0.00543	<0.00543	<0.00543	<0.00543	<0.00543	<0.00543
Magnesium (mg/L)	6.30	3.80	1.88	1.21	10.0	1.78
Manganese (mg/L)	<0.00155	<0.00155	<0.00155	0.00296 ^{b,c}	0.124 ^b	0.00884 ^b
Molybdenum (mg/L)	<0.00739	<0.00739	<0.00739	<0.00739	<0.00739	<0.00739
Sodium (mg/L)	4.53	4.28	6.94	4.83	8.42	6.12
Nickel (mg/L)	<0.0141	<0.0141	0.0190 ^c	<0.0141	<0.0141	<0.0141
Phosphorus (mg/L)	<0.109	<0.109	<0.109	<0.109	0.462	<0.109
Lead (mg/L)	<0.00120	<0.00120	<0.00120	<0.00120	<0.00120	<0.00120
Sulfur (mg/L)	8.57	<0.175	1.03	<0.175	0.826	2.48
Antimony (mg/L)	0.00167 ^{b,c}	0.00196 ^{b,c}	0.00183 ^{b,c}	0.00151 ^{b,c}	0.00194 ^{b,c}	0.00156 ^{b,c}
Selenium (mg/L)	<0.00124	<0.00124	<0.00124	<0.00124	<0.00124	<0.00124
Silicon (mg/L)	17.6	12.3	13.5	9.94	10.4	11.5

Table 5 (continued)

Parameter	GWA-1-19-1	GWC-1-19-1	GWC-2-19-1	GWC-3-19-1	GWC-4-19-1	GWC-5-19-1
Tin (mg/L)	<0.0145	<0.0145	<0.0145	<0.0145	<0.0145	<0.0145
Strontium (mg/L)	0.0242	0.0171	0.0128	0.00617	0.0290	0.0147
Tellurium (mg/L)	<0.00449	<0.00449	<0.00449	<0.00449	<0.00449	<0.00449
Titanium (mg/L)	<0.00159	0.00455 ^c	0.00264 ^c	0.00892	<0.00159	<0.00159
Thallium (mg/L)	<0.00119	<0.00119	<0.00119	<0.00119	<0.00119	<0.00119
Uranium (mg/L)	<0.199	<0.199	<0.199	<0.199	<0.199	<0.199
Vanadium (mg/L)	<0.00454	<0.00454	<0.00454	<0.00454	<0.00454	<0.00454
Tungsten (mg/L)	0.0524 ^c	<0.0408	<0.0408	<0.0408	<0.0408	<0.0408
Zinc (mg/L)	<0.00402	<0.00402	<0.00402	<0.00402	<0.00402	<0.00402
TOX (µg/L)	42.3 ^c	14.6 ^c	12.2 ^c	17.9 ^c	25.0 ^c	20.6 ^c

^a Well was dry; no samples collected.

^b Detected in the method blank.

^c Less than five times the detection limit; results are expected to be less accurate as concentrations approach the detection limit.

NA = Not analyzed; insufficient sample was obtained.


To help determine whether the material in the gypsum stacking area is having an impact on groundwater quality, the monitoring data for a selected number of representative species from all of the monitoring rounds conducted to date were tabulated and examined. The representative species selected are those present in appreciable concentrations in the gypsum slurry, including the major cations and anions (i.e., calcium, magnesium, chloride, and sulfate), as well as several other indicator parameters such as pH, TDS, conductivity, and alkalinity. The complete set of historical data for these species is provided in Appendix A. Examples of concentration-versus-time plots for several species are provided in Figures 2 through 4. Data are presented for the upgradient well, GWA-1, and two downgradient wells, GWC-2 and GWC-4. The locations of these wells were shown previously in Figure 1. Samples were not obtained this quarter from downgradient well GWC-6.

In wells GWA-1 and GWC-2, the measured concentrations for all monitored parameters are generally close to the historically observed concentrations of these species. In well GWC-4, the concentrations of calcium, magnesium, chloride, and sulfate all declined slightly relative to last quarter. The calcium, magnesium, and chloride concentrations in this well have been higher than baseline levels since the fourth quarter of 1993. These higher levels may be due, at least in part, to a leak from the gypsum pond that occurred on July 24, 1993, in the vicinity of well GWC-4. Although the contaminant levels in the groundwater at this location continue to be higher than they were prior to the gypsum pond leak, they are still quite low. For example, the latest chloride concentration is only equivalent to 15% of the maximum concentration recommended in the National Secondary Drinking Water Standards (i.e., 37.5 mg/L versus 250 mg/L).


4.0 Summary of QA/QC Activities

A number of QA/QC activities are being performed, as specified in the project's EMP, to assure that the data obtained meet project objectives. These include the following:


- ▶ Groundwater samples were split for independent analysis by a laboratory selected by SCS.
- ▶ Established sampling and analytical methods were specified and used. All samples were analyzed within the specified holding times, as outlined in Section 2. There were no deviations from the specified methods during this quarter's monitoring effort.




(a) Calcium



(b) Magnesium




(c) Chloride




(d) Sulfate


Figure 2. Historical Data for Representative Species from Well GWA-1 (Upgradient)




(a) Calcium



(b) Magnesium




(c) Chloride




(d) Sulfate


Figure 3. Historical Data for Representative Species from Well GWC-2 (Downgradient)




(a) Calcium



(b) Magnesium



(c) Chloride



(d) Sulfate

Figure 4. Historical Data for Representative Species from Well GWC-4 (Downgradient)

- ▶ Chain-of-custody procedures established in the test plan for this project were observed.
- ▶ In the laboratory, method blanks, control samples, and matrix spikes were analyzed in conjunction with the sample analyses, following recognized good laboratory practice. Specified recovery limits (typically 80 to 120%) were met for all analytes in the laboratory control samples.
- ▶ Duplicate samples were obtained in the field and analyzed for all parameters. Replicate analyses were performed for a smaller number of parameters.

The results of the analysis of field and laboratory duplicates are summarized in Table 6 for those parameters measured above the detection limit. Complete results are provided in Appendix B. Differences in the duplicate analyses results were small for most species (i.e., less than 10%). Differences larger than 10% between sample duplicates were obtained for nitrate-nitrite, total organic halides (TOX), barium, cobalt, chromium, mercury, iron, sulfur, and antimony; for many of these species, the measured concentrations were less than five times the detection limit, where more data scatter can be expected. The results of the duplicate analyses were all within specified quality limits.

Table 6. Results for Duplicate Samples—Third Quarter 1995

Parameter	Units	Sample GWC-4-19-1	Field Duplicate GWC-4-19-2	% Diff. ^a	Duplicate Analysis GWC-4-19-2	% RPD ^b	Spec. Limit
Total Dissolved Solids	mg/L	123	125	1.6		NC	15
Chloride	mg/L	37.5	37.9	1.1	37.1	2.1	20
Fluoride	mg/L	0.0325 ^c	0.0314 ^c	-3.4	0.0317 ^c	1.0	20
Sulfate	mg/L	3.03	3.19	5.3	3.18	0.3	20
Nitrate-Nitrite as N	mg/L	1.74	1.52	-12.6	1.48	2.7	20
Total Organic Halides	mg/L	25 ^d	29.8 ^d	19.2			20
Boron	mg/L	0.234	0.225	-3.8			
Barium	mg/L	0.0262	0.0293	11.8			
Calcium	mg/L	3.03	3.20	5.6			
Cobalt	mg/L	0.0126 ^c	0.0227 ^c	80.2			
Chromium	mg/L	0.0113 ^d	0.00834 ^d	-26.2			
Mercury	mg/L	0.00016	0.000070 ^d	-56.3			
Iron	mg/L	0.0217 ^c	0.0769 ^c	254.4			
Magnesium	mg/L	10.0	10.5	5.0			
Manganese	mg/L	0.124 ^c	0.127 ^c	2.4			
Sodium	mg/L	8.42	8.65	2.7			
Phosphorus	mg/L	0.462	0.461	-0.2			
Sulfur	mg/L	0.826 ^d	0.620 ^d	-24.9			
Antimony	mg/L	0.00194 ^{c,d}	0.00266 ^{c,d}	37.1			
Silicon	mg/L	10.4	10.6	1.9			
Strontium	mg/L	0.0290	0.0299	3.1			

^a % Difference = (GWC-4-19-2 - GWC-4-19-1)/GWC-4-19-1 x 100%

^b RPD = Relative Percent Difference, defined as follows:

$$RPD = \frac{(\text{Larger Value} - \text{Smaller Value}) \times 100\%}{(\text{Larger Value} + \text{Smaller Value})/2}$$

^c Detected in the method blank

^d Value is less than five times the detection limit; results are expected to be less accurate as concentrations approach the detection limit.

Appendix A

Historical Monitoring Data for Selected Parameters

Table A-1. Historical Monitoring Data for Selected Parameters

Parameter	Baseline Monitoring										
	Round 1 6 Sep 90	Round 2 2 Nov 90	Round 3 8-9 Jan 91	Round 4 11 Mar 91	Round 5 8 May 91	Round 6 1-2 Jul 91	Round 7 3-4 Sep 92	Round 8 29-30 Dec 92	Round 9 30-31 Mar 93	Round 10 21 Jun 93	Round 11 23-24 Sep 93
Well: GWA-1 (Formerly CW-1)											
pH	5.86	6.27	5.6	6.7	6.05	5.94	6.4	5.7	6.82	6.1	5.9
Conductivity	98	114	112	121	104	85	116	101	128	100	110
Alkalinity	15.6	22.3	25.8	27.1	25	16.4	35.4	22.7	28	27	24.8
TDS	94	87	86	84	90	77	99	110	110	116	99
Chloride	7.3	7.4	5.9	4.6	3.8	8.2	1.9	2.1	2.1	2.1	1.9
Sulfate	4.5	8.5	8.5	11	17	3.7	17	26	30	20	28
Calcium	6.2	7.6	7.7	7	7.5	5.3	7.9	8.1	4.1	8.0	8.3
Magnesium	3.4	4.9	4.8	4.6	5.1	3.5	5.6	6.0	2.9	5.8	5.9
Sodium	4.2	4.8	4.9	4.3	4.4	3.8	4.1	4.2	4.0	4.4	4.3
Silicon	9.8	11	14	16	17	9.6	15	17	11	18	17
Parameter	Round 12 5 Jan 94	Round 13 22-23 Mar 94	Round 14 21-22 Jun 94	Round 15 31 Aug 94	Round 16 20-21 Dec 94	Round 17 28-29 Mar 95	Round 18 13-14 Jun 95	Round 19 11-12 Sep 95			
Well: GWA-1 (Formerly CW-1) (continued)											
pH	NS	NS	NS	NS	NS	NS	6.31	6.38			
Conductivity	NS	NS	NS	NS	NS	NS	116	165			
Alkalinity	NS	NS	NS	NS	NS	NS	28.6	23			
TDS	NS	NS	NS	NS	NS	NS	108	114			
Chloride	NS	NS	NS	NS	NS	NS	2.10	2.27			
Sulfate	NS	NS	NS	NS	NS	NS	18.3	24.4			
Calcium	NS	NS	NS	NS	NS	NS	6.98	8.47			
Magnesium	NS	NS	NS	NS	NS	NS	5.47	6.30			
Sodium	NS	NS	NS	NS	NS	NS	4.29	4.53			
Silicon	NS	NS	NS	NS	NS	NS	16.6	17.6			

Table A-1 (continued)

Parameter	Baseline Monitoring										
	Round 1 6 Sep 90	Round 2 2 Nov 90	Round 3 8-9 Jan 91	Round 4 11 Mar 91	Round 5 8 May 91	Round 6 1-2 Jul 91	Round 7 3-4 Sep 92	Round 8 29-30 Dec 92	Round 9 30-31 Mar 93	Round 10 21 Jun 93	Round 11 23-24 Sep 93
Well: GWC-1 (Formerly CW-2)											
pH	6.09	5.79	5.62	5.93	6.04	5.96	6.1	4.5	5.83	6.0	6.0
Conductivity	81	70	72	63	63	66	78	57	67	57	61
Alkalinity	21.7	22.9	24.4	22.1	20.5	25.8	27.8	23.3	22.5	24.1	27.3
TDS	81	51	59	52	48	64	64	68	43	74	70
Chloride	3.5	2.8	3.1	3.4	2.8	2.5	2.5	2.6	2.6	2.6	2.5
Sulfate	7.6	5	2.8	<0.05	1.2	1.5	3.2	3.3	2.2	<2.5	2.6
Calcium	3.9	3.6	3.8	3.2	3.4	3.6	4.3	4.0	8.8	4.1	4.1
Magnesium	2.3	2.5	2.8	2.2	2.4	2.5	3.2	3.0	6.2	2.9	3.0
Sodium	5.9	5.2	4.3	4.1	4.2	4.1	4.0	4.0	4.2	4.0	3.8
Silicon	9	9	9.2	11	11	11	11	12	16	12	12
Well: GWC-1 (Formerly CW-2) (continued)											
Parameter	Round 12 5 Jan 94	Round 13 22-23 Mar 94	Round 14 21-22 Jun 94	Round 15 31 Aug 94	Round 16 20-21 Dec 94	Round 17 28-29 Mar 95	Round 18 13-14 Jun 95	Round 19 11-12 Sep 95			
pH	6.1	5.89	5.91	6.09	6.09	6.05	5.70	6.00			
Conductivity	74	61	60	68	76	77	66	79			
Alkalinity	29.9	25	30.1	25	22	29.1	31.0	31			
TDS	22	66	56	64	46	63	72	58			
Chloride	3.5	2.43	2.77	2.71	2.68	2.64	2.76	2.77			
Sulfate	3.3	1.75	1.77	1.64	1.19	1.23	1.10	1.06			
Calcium	5.1	4.72	4.65	5.00	4.50	5.30	5.12	5.12			
Magnesium	3.7	3.14	3.39	3.70	3.33	3.65	3.83	3.80			
Sodium	4.3	4.12	4.16	4.32	4.10	4.21	4.15	4.28			
Silicon	12.7	11.9	11.9	11.8	10.9	10.9	11.8	12.3			

Table A-1 (continued)

Parameter	Baseline Monitoring										
	Round 1 6 Sep 90	Round 2 2 Nov 90	Round 3 8-9 Jan 91	Round 4 11 Mar 91	Round 5 8 May 91	Round 6 1-2 Jul 91	Round 7 3-4 Sep 92	Round 8 29-30 Dec 92	Round 9 30-31 Mar 93	Round 10 21 Jun 93	Round 11 23-24 Sep 93
Well: GWC-2 (Formerly CW-3)											
pH	5.64	5.6	5.04	5.5	4.97	5.65	5.5	4.6	5.29	5.4	5.6
Conductivity	76	69	64	66	33	71	66	56	67	56	49
Alkalinity	23.5	19.3	15.2	16.9	12.2	17.5	18.2	17.3	12.5	14.1	15.9
TDS	76	50	55	55	63	65	79	71	68	77	60
Chloride	4.3	5.2	6.9	6.2	5	5.3	3.0	3.4	4.0	4.5	3.5
Sulfate	6.4	5.5	6.3	5.9	5.8	6.3	6.5	7.6	7.9	7.5	7.7
Calcium	4.4	2.8	2.3	2	2	1.7	1.4	1.6	1.7	1.6	1.9
Magnesium	1.6	1.5	1.6	1.7	1.8	1.9	1.9	2.1	2.1	1.9	2.0
Sodium	7.3	7.4	6.9	7	7.5	7.6	7.5	7.4	7.5	6.7	6.8
Silicon	10	10	9.3	12	11	11	11	13	12.0	11	13
Parameter	Round 12 5 Jan 94	Round 13 22-23 Mar 94	Round 14 21-22 Jun 94	Round 15 31 Aug 94	Round 16 20-21 Dec 94	Round 17 28-29 Mar 95	Round 18 13-14 Jun 95	Round 19 11-12 Sep 95			
Well: GWC-2 (Formerly CW-3) (continued)											
pH	5.75	5.5	5.72	5.63	5.34	5.53	5.39	5.41			
Conductivity	53	57	59	60	66	65	65	67.5			
Alkalinity	15.7	14	16.2	7.0	6.9	13.3	14.5	13.5			
TDS	27	76	58	60	65	63	64	54			
Chloride	3.8	3.7	3.79	3.92	4.00	3.81	3.97	3.83			
Sulfate	5.78	5.97	5.95	6.73	5.78	4.98	4.33	3.90			
Calcium	2.0	2.19	2.05	2.11	1.89	2.23	2.08	2.16			
Magnesium	1.8	1.92	1.93	2.03	1.87	1.88	1.92	1.88			
Sodium	7.0	7.15	7.09	7.17	6.96	6.79	6.85	6.94			
Silicon	12.9	13.3	13.0	12.9	12.2	12.2	13.4	13.5			

Table A-1 (continued)

Baseline Monitoring											
Parameter	Round 1	Round 2	Round 3	Round 4	Round 5	Round 6	Round 7	Round 8	Round 9	Round 10	Round 11
	6 Sep 90	2 Nov 90	8-9 Jan 91	11 Mar 91	8 May 91	1-2 Jul 91	3-4 Sep 92	29-30 Dec 92	30-31 Mar 93	21 Jun 93	23-24 Sep 93
Well: GWC-3 (Formerly CW-4)											
pH	5.4	5.15	4.8	4.73	6.19	5.08	5.25	3.8	5.23	5.2	5.3
Conductivity	40	35	30	34	32	35	32	27	33	27	27
Alkalinity	11.5	15.2	9.9	11	7	11.1	10.0	8.9	7.0	8.5	9.1
TDS	50	35	31	34	39	41	28	37	44	52	21
Chloride	3	2.8	3.2	3.4	3.1	3.1	2.0	2.3	2.7	2.9	2.8
Sulfate	2.6	2.1	<0.05	<0.05	0.9	1.5	1.7	2.6	1.6	<2.5	<2.5
Calcium	1	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Magnesium	1	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
Sodium	4.4	4.5	4.3	4.1	4.6	4.3	4.1	4.0	4.1	3.9	3.8
Silicon	8	7.8	3.9	8.5	8.6	8.3	8.3	9.3	9.0	8.7	9.2
Well: GWC-3 (Formerly CW-4)											
Parameter	Round 12	Round 13	Round 14	Round 15	Round 16	Round 17	Round 18	Round 19			
	5 Jan 94	22-23 Mar 94	21-22 Jun 94	31 Aug 94	20-21 Dec 94	28-29 Mar 95	13-14 Jun 95	11-12 Sep 95			
pH	5.5	5.18	5.43	5.41	5.06	5.10	5.10	5.02			
Conductivity	22	28	29	30	36	36	37	45			
Alkalinity	9.3	7.5	8.5	7.7	4.8	8.6	8.5	9.0			
TDS	<8.7	42	36	39	30	44	52	37			
Chloride	2.8	2.77	2.76	2.91	3.02	3.15	3.13	3.64			
Sulfate	<0.06	1.38	1.52	<0.0471	1.01	<0.0471	0.968	0.595			
Calcium	<1.0	0.392	0.321	0.328	0.335	0.441	0.314	0.389			
Magnesium	<1.0	0.962	0.935	1.00	1.02	1.10	1.08	1.21			
Sodium	4.1	4.35	4.14	4.17	4.34	4.39	4.47	4.83			
Silicon	9.7	10.1	9.16	9.15	8.94	8.97	8.90	9.94			

Table A-1 (continued)

Parameter	Baseline Monitoring										
	Round 1 6 Sep 90	Round 2 2 Nov 90	Round 3 8-9 Jan 91	Round 4 11 Mar 91	Round 5 8 May 91	Round 6 1-2 Jul 91	Round 7 3-4 Sep 92	Round 8 29-30 Dec 92	Round 9 30-31 Mar 93	Round 10 21 Jun 93	Round 11 23-24 Sep 93
Well: GWC-4 (Formerly CW-5)											
pH	5.34	4.97	4.8	4.6	5.03	5.4	5.05	3.9	5.04	5.2	5.2
Conductivity	62	62	66	72	54	70	72	58	64	52	54
Alkalinity	12.5	15.3	13.1	15.1	8.6	14.2	11.5	8.0	6.0	6.9	7.0
TDS	61	52	60	51	58	64	61	65	63	55	44
Chloride	5	4.2	5	5.6	4.5	5.2	3.1	3.4	3.6	3.6	3.8
Sulfate	2.2	4.6	8	6.8	7.1	5.8	5.3	5.5	5.0	5.9	4.9
Calcium	1.3	<1.0	<1.0	1.3	1.6	1.2	<1.0	<1.0	1.0	<1.0	<1.0
Magnesium	2.5	2.5	3.1	3.8	3.9	3.7	3.3	3.2	3.2	2.7	2.9
Sodium	5.4	5.8	5.3	5.1	5	5.2	4.8	4.9	4.7	4.4	4.4
Silicon	9.9	9.1	4.7	9.7	9.2	10	8.6	9.5	8.7	8.3	9.3
Parameter	Round 12 5 Jan 94	Round 13 22-23 Mar 94	Round 14 21-22 Jun 94	Round 15 31 Aug 94	Round 16 20-21 Dec 94	Round 17 28-29 Mar 95	Round 18 13-14 Jun 95	Round 19 11-12 Sep 95			
Well: GWC-4 (Formerly CW-5) (continued)											
pH	5.2	4.98	5.2	5.10	4.92	5.10	4.98	4.79			
Conductivity	63	72	81	108	188	163	148	180			
Alkalinity	9.2	5.0	10.3	5.0	3.8	9.0	4.6	4.5			
TDS	20	64	75	93	110	113	132	123			
Chloride	6.7	11.3	13.5	20.8	39.7	34.1	39.1	37.5			
Sulfate	4.4	4.64	4.50	4.83	4.34	4.18	3.91	3.03			
Calcium	1.3	1.81	1.62	2.73	4.04	3.21	3.89	3.03			
Magnesium	3.7	5.05	4.98	7.32	11.0	10.2	12.5	10.0			
Sodium	5.0	5.33	4.87	5.80	7.86	7.63	8.61	8.42			
Silicon	9.8	9.91	9.18	9.91	10.1	9.36	10.0	10.4			

Table A-1 (continued)

Parameter	Baseline Monitoring										
	Round 1 6 Sep 90	Round 2 2 Nov 90	Round 3 8-9 Jan 91	Round 4 11 Mar 91	Round 5 8 May 91	Round 6 1-2 Jul 91	Round 7 3-4 Sep 92	Round 8 29-30 Dec 92	Round 9 30-31 Mar 93	Round 10 21 Jun 93	Round 11 23-24 Sep 93
Well: GWC-5											
pH							5.6	4.4	6.13	5.4	5.6
Conductivity							61	60	54	41	40
Alkalinity							14.8	13.5	12.5	10.2	11.5
TDS							91	86	67	56	50
Chloride							1.8	2.6	2.7	2.9	2.5
Sulfate							8.8	10	7.4	6.7	5.5
Calcium							2.1	2.7	2.2	1.6	1.4
Magnesium							1.9	2.3	1.8	1.5	1.4
Sodium							6.0	6.2	5.7	5.5	5.2
Silicon							12	14	13	12	12
Well: GWC-5 (continued)											
Parameter	Round 12 5 Jan 94	Round 13 22-23 Mar 94	Round 14 21-22 Jun 94	Round 15 31 Aug 94	Round 16 20-21 Dec 94	Round 17 28-29 Mar 95	Round 18 13-14 Jun 95	Round 19 11-12 Sep 95			
pH	7.0	5.38	5.42	5.53	5.57	5.52	5.60	5.20			
Conductivity	39	43	45	43	47	50	52	60			
Alkalinity	10.8	8.6	10.8	13.0	11.2	9.5	8.5	11.0			
TDS	29	53	61	61	45	50	64	64			
Chloride	2.6	2.34	2.48	2.67	2.70	2.54	2.62	2.70			
Sulfate	5.3	6.56	7.65	6.68	5.75	6.45	6.64	6.80			
Calcium	1.3	1.65	1.38	1.26	1.20	1.51	1.31	1.48			
Magnesium	1.3	1.6	1.55	1.46	1.32	1.59	1.73	1.78			
Sodium	5.5	5.74	5.77	5.38	5.43	5.34	5.54	6.12			
Silicon	11.4	11.8	11.3	10.5	10.3	10.3	11.1	11.5			

Appendix B
QA/QC Results

Table B-1. Results for Duplicate Samples—Third Quarter 1995

Parameter	Units	Sample GWC-4-19-1	Field Duplicate GWC-4-19-2	% Diff. ^a	Duplicate Analysis GWC-4-19-2	% RPD ^b	Spec. Limit
Total Dissolved Solids	mg/L	123	125	1.6		NC	15
Bromide	mg/L	<0.0181	<0.0181	NC	<0.0181	NC	20
Chloride	mg/L	37.5	37.9	1.1	37.1	2.1	20
Fluoride	mg/L	0.0325 ^c	0.0314 ^c	-3.4	0.0317 ^c	1.0	20
Sulfate	mg/L	3.03	3.19	5.3	3.18	0.3	20
Total Organic Carbon	mg/L	1.86	<0.117	NC	<0.117	NC	20
Nitrate-Nitrite as N	mg/L	1.74	1.52	-12.6	1.48	2.7	20
Total Organic Halides	mg/L	25 ^d	29.8 ^d	19.2			20
Radium-226	pCi/L	0.190 ± 0.840	0.130 ± 0.810	NC			
Radium-228	pCi/L	-0.430 ± 1.59	-0.400 ± 1.57	NC			
Gross alpha	pCi/L	<0.67	<0.67	NC			
Gross beta	pCi/L	<1.6	<1.6	NC			
Ac-228	pCi/L	16.1 ± 7.71	8.61 ± 8.15	NC			
Bi-214	pCi/L	-1.93 ± 13.5	9.44 ± 13.2	NC			
K-40	pCi/L	-67.3 ± 84.5	30.9 ± 95.0	NC			
Pb-214	pCi/L	9.62 ± 4.23	2.90 ± 12.2	NC			
Silver	mg/L	<0.00519	<0.00519	NC			
Aluminum	mg/L	<0.0523	0.0632 ^d	NC			
Arsenic	mg/L	<0.00102 ^c	<0.00102 ^c	NC			
Boron	mg/L	0.234	0.225	-3.8			
Barium	mg/L	0.0262	0.0293	11.8			
Beryllium	mg/L	<0.000510	0.00059 ^d	NC			
Bismuth	mg/L	<0.00504	<0.00504	NC			
Calcium	mg/L	3.03	3.20	5.6			
Cadmium	mg/L	<0.00386	<0.00386	NC			
Cobalt	mg/L	0.0126 ^c	0.0227 ^c	80.2			
Copper	mg/L	<0.00916	<0.00916	NC			
Chromium	mg/L	0.0113 ^d	0.00834 ^d	-26.2			
Mercury	mg/L	0.00016	0.000070 ^d	-56.3			
Iron	mg/L	0.0217 ^c	0.0769 ^c	254.4			
Potassium	mg/L	<0.822	<0.822	NC			
Lithium	mg/L	<0.00543	<0.00543	NC			
Magnesium	mg/L	10.0	10.5	5.0			
Manganese	mg/L	0.124 ^c	0.127 ^c	2.4			
Molybdenum	mg/L	<0.00739	<0.00739	NC			
Sodium	mg/L	8.42	8.65	2.7			
Nickel	mg/L	<0.0141	<0.0141	NC			
Phosphorus	mg/L	0.462	0.461	-0.2			
Lead	mg/L	<0.00120	<0.00120	NC			