

**Table 61. Year Round Gasoline Specifications by Petroleum Administration for Defense Districts (PADD)**

PADD	Reid Vapor Pressure (Max PSI)	Oxygen Weight Percent (Min) (Max)		Aromatics Volume Percent (Max)	Benzene Volume Percent (Max)	Initial Sulfur PPM (Max)	Olefin Volume Percent (Max)	Percent Evaporated at 200°	Percent Evaluated at 300°
<b>Conventional</b>									
PADD I	9.6	—	—	26.0	1.1	338.4	11.6	47.1	82.0
PADD II	10.2	—	—	26.1	1.1	338.4	11.6	47.1	81.9
PADD III	9.9	—	—	26.1	1.1	338.4	11.6	47.1	81.9
PADD IV	10.8	—	—	26.1	1.1	338.4	11.6	47.1	81.9
PADD V	9.2	—	—	26.7	1.1	338.4	11.6	45.7	81.4
<b>Reformulated</b>									
PADD I	8.5	2.0	2.1	20.7	0.6	135.0	11.9	50.2	84.6
PADD II	9.5	2.0	2.1	18.5	0.8	135.0	7.1	50.8	85.6
PADD III	8.6	2.0	2.1	19.8	0.6	135.0	11.2	51.6	83.9
PADD V									
Nonattainment	7.9	2.0	2.1	22.0	0.70	25.0	6.0	49.0	85.0
CARB (attainment)	7.9	—	1.2	22.0	0.70	25.0	6.0	49.0	85.0

Max = Maximum.

Min = Minimum.

PADD = Petroleum Administration for Defense District.

PPM = Parts per million by weight.

PSI = Pounds per Square Inch.

Source: Energy Information Administration, Office of Integrated Analysis and Forecasting. Derived using U.S. EPA's Complex Model, and updated with U.S. EPA's 2002 gasoline projection survey (<http://www.epa.gov/otag/regs/fuels/rfg/properf/rfgper.htm>).