

Agency : MINE SAFETY AND HEALTH ADMINISTRATION  
Title : Low- and Medium-Voltage Diesel-Powered Electrical Generators  
Subject Category : Coal mine safety and health: Underground mines-- Low- and medium-voltage diesel-powered generators; use as alternative means of powering electrical equipment  
Docket ID :  
CFR Citation : 30 CFR 75  
Published : June 25, 2004  
Comments Due : August 24, 2004  
Phase : PROPOSED RULES

---

Your comment has been sent. To verify that this agency has received your comment, please contact the agency directly. If you wish to retain a copy of your comment, print out a copy of this document for you

Please note your REGULATIONS.GOV number.

Regulations.gov #: EREG - 1 Submitted Jul 19,2004

Author : Mr. Ernal Shaw

Organization : Bowie Resources LLC

Attached Files :

Comment : 75.901(b)(10) requires that all trailing cables extending from the generator comply 75.907.

This would require a low voltage permissible pump to use a shielded trailing cable. These pumps are not approved with a packing gland that would accommodate a large enough cable OD to use a shielded cable. This regulation needs to be re-written so that 75.907 applies to medium voltage trailing cables from the generator and not to low voltage. A permissible pump supplied power by a generator should use a cable that it was approved with. The proposed regulation would require field changes or SNAPS for a pump to be in permissible condition when powered by a generator.

---