

# New Locks



**Cheryl P. George**  
**Structural Engineer**  
**Canal Capacity Division**  
**Autoridad del Canal de Panamá**

**March 8, 2007**



# Agenda

- **Project Location**
- **Configuration**
- **Conceptual Design**
- **Significant Quantities**
- **Lock Animation**

# Project Location

Atlantic Lock



The image shows a topographic map of a river basin, likely the Colorado River. The map is overlaid with a grid. Two yellow callout boxes with black text and black outlines are present. The first box, labeled 'Atlantic Lock', has a pointer pointing to a location on the northern part of the river. The second box, labeled 'Pacific Lock', has a pointer pointing to a location on the southern part of the river. The terrain is color-coded by elevation, with green for lower elevations and brown for higher elevations. The river is shown in blue, flowing from the upper right towards the lower left.

Pacific Lock

# The Challenge

- ◆ Post Panamax Ship Transit between the Atlantic and the Pacific Oceans
- ◆ Maximize throughput (tonnage)
- ◆ Minimize water consumption
- ◆ Minimize saltwater intrusion
- ◆ Minimize maintenance
- ◆ Minimize outages

# Lock Configuration Conceptual Design

- ◆ 3 Lift Locks
- ◆ 3 Water Saving Basins per Lift
  - ◆ (60% water saving)
- ◆ Approach Walls at the Entrances
- ◆ Side port Filling and Emptying
- ◆ Rolling Gates
- ◆ Vessel Positioning with Tugs

# Lock Dimensions (minimum requirements)

- ◆ Lock Width – 55m
- ◆ Length between inner gates – 427m
- ◆ Length between outer gates – 458m
- ◆ Minimum depth over sill – 18.3m
- ◆ Minimum freeboard – 1.52m

# Pacific




# Atlantic







# Pacific Lock - Conceptual Design




# Atlantic Lock – Conceptual Design



# Pacific – Conceptual Design




# Atlantic – Conceptual Design






# Filling/Emptying Conceptual Design


CORTE TRANSVERSAL DE UNA CÁMARA




# Lock Walls Conceptual Design



















# Gate Lockhead















































































# Water Saving Basins





# Water Saving Basins




**Water saving basins used in Germany help reduce water usage**

























# Gates and Valves

# Gates

Berendrecht Lock  
Antwerp, Belgium



# Gate in Recess

Berendrecht Lock  
Antwerp, Belgium





# Gate Installation



Berendrecht Lock  
Antwerp, Belgium

# Gate Installation




Berendrecht Lock  
Antwerp, Belgium

# Gate Installation


Berendrecht Lock  
Antwerp, Belgium




# Gate model (Conceptual Design)



# Rolling gate supports Conceptual Design



# Gate Operation



# Valves

## (Conceptual Design)



# Valves

Valve Stem



Valve Body





# Valves

Embedments in Concrete




# **Electrical System (each lock site)**

- **Primary Distribution System**
  - **Two 12,000 volt, 60Hz loops**
  - **Each loop fed by independent feeders from nearby substation and can supply the total electrical requirement**
- **Back up generator can supply total electrical requirement**

# Electrical Requirements

- **Electricity supplied by less than 600volt, 60Hz systems connected to the distribution loops for:**
  - **Lighting**
  - **Operating equipment for gates and valves**
  - **Miscellaneous: A/C for buildings, Sump pumps, air compressors, fire fighting equipment**

# Lighting Conceptual Design



# **Buildings – each lock**

## **Conceptual Design**

- **Main Control Building**
- **Emergency Generator Buildings**
- **Transformer Rooms**
- **Gates Technical Buildings**
- **Culvert Technical Buildings**
- **WSB Technical Buildings**
- **Maintenance Buildings**
- **Storage Buildings**

# **Appurtenances – each lock Conceptual Design**

- **Fire protection system**
- **Waste water treatment plant**
- **Elevators to underground crossings**
- **Bollards**
- **Fenders**
- **Station markers, telephones,  
loudspeakers**
- **Security fence and controlled access  
points**
- **Roads and parking lots**



# Quantities

# Approximate Quantities Civil Work Conceptual Design

(thousands)

Material	Pacific	Atlantic	Total
Excavation (m3)	12,000	18,000	30,000
Reinforced Concrete (m3)	1,750	1,680	3,430
RCC (m3)	260	330	590
Reinforcing bars (ton)	130	130	260
Cement (ton)	540	520	1,060
*Processed Material (m3)	7,800	5,600	13,400

\*Processed material includes fill and aggregate



# Approximate Quantities Electromechanical Conceptual Design

Equipment	Quantity (per lock)	Atlantic (ton)	Pacific (ton)	Total (ton)
Valves	52	3,300	3,800	7,100
Bulkheads	24	2,800	3,000	5,800
Gates	8	20,000	21,000	41,000
Total		26,100	27,800	53,900

# Conceptual Design



ACP


AMERICAN COUNCIL ON PORTS



Thank You !



# Filling/Emptying Concept Design



# Studies

- ◆ 1939 Design
- ◆ 1993 Study (Panama-Japan-USA)
- ◆ 1998 Start of Present Studies
  - ◆ Water Supply
  - ◆ Vessel Positioning
  - ◆ Alignment
  - ◆ Alternatives for moving ships
  - ◆ Saltwater intrusion
  - ◆ Lock Concepts