

CURRENT INDUSTRIAL REPORTS SERIES

2008

MA335J — INSULATED WIRE AND CABLE (SHIPMENTS)

DEFINITIONS AND SPECIAL INSTRUCTIONS

1. Scope of survey

This survey covers establishments manufacturing and fabricating insulated wire and cable and/or apparatus wire and cordage with a copper/copper clad or aluminum/aluminum clad core. This survey also includes optical fiber cable.

2. Figures to be reported

We prefer that a separate report be filed for each establishment. However, if you wish, you may combine two or more establishments in a single report. If you do file a combined report, you should report transfers in between the various plants as interplant transfers in sections I–VIII. Such shipments should also be included, as provided below, in those data which represent "total shipments, including interplant transfers."

If you manufacture apparatus wire and cordage, you should report:

- If you buy wire and insulate it and/or
- If you buy wire already insulated,

You should report all shipments (including both domestic and export) of insulated or covered wire and cable for transmitting electrical energy, signals, or communication. Exclude bare and tinned wire and cable and ACSR.

Report interplant transfers for those shipments "shipped" for use by your own company, an affiliate, subsidiary, or parent company. The interplant transfer figure should also be included with "total shipments including interplant transfers."

Transfers to sales branch location should be excluded from interplant transfers but should be included in shipments to other companies.

Exclude resales — products bought and sold without further manufacture.

The value of the products shipped should be based on the net selling value, f.o.b. plant, after discounts and returns and allowances. Freight charges and excise taxes should be excluded.

Be sure to sum all of the items designated under the indicated product groups that you have reported. This total should agree with your shipments for that section. If your shipments are greater than the individual items you have reported, you may have omitted an item(s). If this is the case, please insert those items omitted. If, however, your shipments are less than the individual item reported, you may have double counted one or more items.

Item

code

Product group

2298	Total electronic wire and cable
2598	Total telephone and telegraph wire and cable
3298	Total power wire and cable
4198	Total control and signal wire and cable
4298	Total building wire and cable
5298	Total apparatus wire and cordage
5398	Total other insulated wire and cable
6199	Total magnet wire
8199	Total optical fiber cable
9103	Total optical fiber for data and nondata transmissions

3. Columnar structure of report

When posting your figures to the report, please be sure to report the information in the correct columns. These are:

SECTIONS I–VIII — INSULATED WIRE AND CABLE, OTHER THAN MAGNET WIRE AND OPTICAL FIBER CABLE

Column 1 — Copper content (excluding insulation) in thousands of pounds for total shipments, including interplant transfers

Column 2 — Aluminum content (excluding insulation) in thousands of pounds

For sections I, II, V, and VII, report quantity of aluminum content for:

- Item code 2298 — Total electronic wire and cable
 - Item code 2598 — Total telephone and telegraph wire and cable
 - Item code 4198 — Total control and signal wire and cable
 - Item code 5298 — Total apparatus wire and cordage
- Metal content of "copper clad aluminum" should be reported in the aluminum column.

Column 3 — Value in thousands of dollars for total shipments, including interplant transfer. Example: \$1,000,000, report as \$1,000.

Column 4 — Value in thousands of dollars for interplant transfers, excluding shipments to sales branches (Total only) Example: \$1,000,000, report as \$1,000.

SECTION IX — MAGNET WIRE (Item codes 6106–6199)

You should report products with thermal ratings falling between those listed in the report under the next lower rating, except that products with a thermal rating of less than 105 C should be included with 105 C products.

CURRENT INDUSTRIAL REPORTS SERIES

MA335J

DEFINITIONS AND SPECIAL INSTRUCTIONS — Continued

3. Columnar structure of report — Continued

SECTION IX - MAGNET WIRE (Item codes 6106-6199) — Continued

The U.S. Government specification for magnet wire, MW 1000, should be used as the guide for determining the thermal classification of magnet wire.

Column 1 — Quantity of copper wire in thousand pounds gross weight (including insulation) for total shipments including interplant transfers

Column 2 — Value of copper wire (including insulation) in thousands of dollars for total shipments including interplant transfers. Example: \$1,000,000, report as \$1,000.

Column 3 — Quantity of aluminum wire in thousand pounds gross weight (including insulation) for total shipments including interplant transfers

Column 4 — Value of aluminum wire (including insulation) in thousands of dollars for total shipments including interplant transfers. Example: \$1,000,000, report as \$1,000.

Column 5 — Quantity of copper wire in thousand pounds gross weight for interplant transfers, excluding shipments to sales branches

Column 6 — Quantity of aluminum wire in thousand pounds gross weight for interplant transfers, excluding shipments to sales branches

SECTION X — OPTICAL FIBER CABLE (Item codes 8101-8199)

This section provides for the collection of insulated optical fiber cable.

Column 1 — Quantity (Report thousands of Cable Conductor Kilometers (CCKM)).

Column 2 — Value (Report in thousands of dollars the value of optical fiber cable, including insulation). Example: \$1,000,000, report as \$1,000.

SECTION XI — OPTICAL FIBER (Item codes 9101-9103)

This section provides for the collection of optical fiber.

Column 2 — Value (Report in thousands of dollars the value of optical fiber). Example: \$1,000,000, report as \$1,000.

4. Definitions

INSULATED WIRE — A rod of drawn metal filament covered with insulation.

INSULATED CABLE — A number of conductors twisted or grouped together.

Dual rated products should be classified according to their higher ratings.

Multi-insulated cables should be classified according to their primary insulation, i.e., the layer of material designed to do the electrical insulating, usually the first layer of material applied over the conductor.

GROSS WEIGHT — Include insulating materials but exclude packaging materials.

INSULATION — A non-conductive material usually surrounding or separating two or more conductive materials.

THERMOPLASTIC — Insulation that will soften and distort from its formed shape by heating above a critical temperature peculiar to the material.

THERMOSETTING — Insulation that will not resoften or distort from its formed shape by heating until a destructive temperature is reached.

ARMOR — The outer layer of a cable applied for mechanical protection, usually consisting of a layer or layers of a metallic tape, braid, or several wires.

CROSS-LINKED — Intermolecular bonds produced between long chain molecules in a material to increase molecular size by chemical or electron bombardment, resulting in a change in physical properties in the material usually improved properties.

ELASTOMER — Any elastic rubber-like substance, such as natural or synthetic rubber; when stretched to twice its length will resume approximately the original shape.

JACKET — A covering put around an insulated conductor for the purpose of protection and/or resistance.

INSULATED WIRE AND CABLE — All insulated wire and cable for transmitting electrical energy, signals, or communications. Exclude bare and tinned wire and cable and ACSR.

ELECTRONIC WIRE AND CABLE — All single and multi-conductor wire and cable used for transmission, reception, or reproduction of electrical frequencies (16 gauge and smaller). Excludes telephone cable. See Apparatus Wire and Cordage for larger gauges.

SEMI-RIGID — A cable containing a flexible inner core and a relatively inflexible sheathing.

CURRENT INDUSTRIAL REPORTS SERIES

MA335J

DEFINITIONS AND SPECIAL INSTRUCTIONS — Continued

4. Definitions — Continued

COAXIAL CABLE — Cable consisting of two or more cylindrical conductors with a common axis. The two conductors are separated by a dielectric for use as high frequency transmission lines and communication systems.

HOO-K-UP WIRE, SINGLE CONDUCTOR — Single conductor wire (16 AWG and smaller) used for internal equipment wiring.

RIBBON CABLE — A cable consisting of two or more conductors laid parallel in one plane and held in place by the insulation or some other means.

MULTI-CONDUCTOR CABLE — More than one conductor within a single cable complex.

SHIELDED CABLE — Constructed so that substantially every point on the insulation is at ground potential or some pre-determined potential with respect to ground.

TELEPHONE WIRE AND CABLE — All wires and cables used in the telephone industry to transmit, receive, and monitor communications signals. Excludes coaxial and other electronic wire and cable.

DROP WIRE — Service drop from pole to subscribers house: parallel, twisted or dumbbell style.

BRIDLE WIRE — For connection of open wire and terminals or protectors and as apparatus leads.

TELEPHONE CORD SETS — Cut lengths of wire with terminals or connectors for use in telephone hand or head set applications and telephone line cords.

POWER CABLE (2kv or less) — Single and multi-conductor cable rated 2kv or less, sizes 14AWG and larger, insulated with thermosetting or thermoplastic insulation, and with or without a metallic armor overall.

Include:

- Airport lighting cable
- Bus drop cable
- Cathodic protection cable
- Network cable
- Oil tray cable
- Overhead line wire
- Pole and bracket cable
- Power tray cable
- Service drop and secondary cable (8AWG or larger)
- Submarine power cable (8AWG or larger)
- Submersible pump or water well cable (8AWG or larger)
- Weatherproof cable

Exclude:

- Insulated single conductor with UL label
- Secondary underground distribution cables

Single conductor multiplexed or paralleled reported as 0–2kv BX and AC wire

POWER CABLE (2.1–15kv) — Single and multiconductor cable rated 2.1–1.5kv, in sizes 8AWG and larger, insulated with dielectric insulation, either thermosetting or thermoplastic, shielded or unshielded, jacketed or unjacketed and armored or unarmored.

Include

- Aerial spacer cables
- Airport lighting cable
- Oil well cable — armored and unarmored
- Pole and bracket cable
- Power cable
- Street lighting cable
- Submarine power cable

Exclude

- Portable power cables
- UD cables
- Mine power feeder cable

POWER CABLE (over 15kv) — Single and multi-conductor cable rated 15.1kv and over, in sizes 2AWG and larger, insulated with dielectric insulation, thermosetting, shielded or unshielded, jacketed or unjacketed and armored or unarmored.

Include

- Power cable
- Submarine power cable

Exclude

- Portable power cables
- UD cables
- Mine power feeder cable

POWER CABLE, UNDERGROUND CABLE (US) 0–2KV (UL listed, single conductor cable) — Single, multiplex, or paralleled solid dielectric insulated cable with or without concentric neutral (either thermosetting or thermoplastic insulation) rated 0–2kv and specifically used for residential and/or commercial underground services and/or feeders. Exclude single conductor UL labeled USE.

POWER CABLE, UNDERGROUND CABLE (US) OVER 2KV — Single, multiplex, or paralleled solid dielectric insulated cable with or without concentric neutral (either thermosetting or thermoplastic insulation) rated over 2kv and designated for use as a primary distribution cable in underground locations.

CONTROL AND SIGNAL WIRE AND CABLE — Any solid dielectric insulated (thermosetting or thermoplastic), jacketed or unjacketed cable, multi-conductor, rated 2500V or less, sized 22AWG through 9AWG, utilized to operate control valves and relays, or to implement or record an event (but

CURRENT INDUSTRIAL REPORTS SERIES

MA335J

DEFINITIONS AND SPECIAL INSTRUCTIONS — Continued

4. Definitions — Continued

CONTROL AND SIGNAL WIRE AND CABLE—Continued

does not supply the energy being controlled in the event); also utilized to actuate, power and control railroad signaling, warning or crossing protective devices; or utilized to actuate or control fire alarm circuits.

Include

- Signal cable — less than 16AWG or less than 2kv
- Control cable — 9AWG and smaller, 2kv or less than 300V
- Fire alarm cable
- Submarine control cable
- Instrumentation cable
- Railroad signal cable
- Traffic control and signal cable

PORTABLE CROSS LINKED JACKETED CABLE

Include

- Shielded and non-shielded
- Round types: SO, W, G, PG, PCG, SH, AND SH-A, B, C, D, and GGC
- Types SO, SJO, AND SJO shielded and unshielded
- Twin or triple types W and G
- Locomotive Gathering reel
- Battery
- Concentric
- Elevator Control
- Grounding cable
- High tension
- Trolley bus
- Magnet Crane
- Motor Lead
- Power Jumper
- Railway Utility
- Sand Cutter
- Train Jumper

PORTABLE NON-CROSS LINKED JACKETED CABLE —

All portable cable not bearing UL flexible cord or appliance wiring material label. Include thermoplastic mining machine cable; thermoplastic and thermoset mine power feeder. Exclude welding cable.

BUILDING WIRE — All wire and cable (601 volts or less) used within structures for light and power for permanent installation. Includes service entrance cable.

APPARATUS WIRE AND CABLE — Insulated wire and cable used in connecting electrical apparatus to a power source, and appliance wiring material (22 AWG and heavier including motor lead and transformer lead wire). See electronic wire and cable for appliance wiring material finer than 22 AWG.

CORD SETS — Portable cords, fitted with any type of wiring device at one or both ends.

CORD — A small, flexible, multiple-conductor cable.

APPLIANCE WIRING MATERIAL — Insulated wire and cable intended for internal wiring of appliances and equipment.

FLEXIBLE CORDAGE (Flexible cord, portable cord, or appliance cord) — Cordage of two or more conductors, normally used for electrical and electronic appliances, tools, and business machines.

OTHER APPARATUS WIRE AND CORDAGE (Including machine tool wire) — Other types such as battery cable: non-transportation uses, defroster wire, and electric furnace cable.

OTHER WIRE AND CABLE — Includes bulk automotive battery and ignition wire, elevator hatch and traveling cable, weatherproof cable, and air-frame, shipboard, and ground support cable.

BULK AUTOMOTIVE PRIMARY WIRE — Used for low voltage lighting and control circuits, including wiring for automotive harnesses.

BULK BATTERY CABLE — Used for positive and negative cables, switch to starter cables.

BULK IGNITION WIRE — High tension (5mm or 7mm) shielded or unshielded for internal combustion engines.

BATTERY CABLE SETS — Cut lengths of wire with ends prepared for connection between automotive battery and starter, battery and battery, battery and ground or switch to starter.

MAGNET WIRE, including insulated magnet strip conductor — all insulated wire of the type generally used in the winding of coils, including Litz wire and including insulated magnet sheet, strip, and foil. The thermal classification for bondable wires should be determined by the underlying insulation. Also, the combination (film-fabric) product should be classified based on the insulation on the top side.

LITZ WIRE — Litz wire refers to multistrand construction of small gauge film insulated wire that is precision twisted. This construction minimizes the power loss related to the "skin effect" of current at radio frequencies.

OPTICAL FIBER — Optical Fiber used for data purposes — A long thin strand of transparent glass, plastic or other materials usually consisting of a fiber optical core and a fiber optical cladding capable of conducting light along its axial length by internal reflection, used in the transmission of voice, video, and/or data information.

ALL GLASS OPTICAL FIBER (single mode) — An optical fiber consisting of a glass core and glass cladding that supports the propagation of only one mode, or ray, of light at a time.

CURRENT INDUSTRIAL REPORTS SERIES

DEFINITIONS AND SPECIAL INSTRUCTIONS

MA335J

4. Definitions — Continued

OPTICAL FIBER — Continued

ALL GLASS FIBER (multimode) — An optical fiber consisting of a glass core and a glass cladding that supports the propagation of more than one mode, or ray, of light at a time.

PLASTIC CLAD GLASS FIBER — An optical fiber with a glass core and a plastic optical cladding.

ALL PLASTIC OPTICAL FIBER — An optical fiber consisting of a plastic optical core and a plastic optical cladding.

NONCOHERENT BUNDLE — A collection of optical fibers arranged randomly for the purpose of transmitting light but not images.

COHERENT BUNDLE — A collection of optical fibers arranged non-randomly to permit the transmission of images, excluding faceplates and sensors.

FACEPLATE — A fused coherent bundle used for the transmission of images over a short distance, excluding sensors.

SENSORS — Optical fibers used in apparatus designed to detect or sense environmental effects such as pressure, temperature, magnetic, electric fields, rotation, etc.

4. Abbreviations

C	Centigrade
AWG	American wire gauge
UD	Underground distribution
URD	Underground residential distribution
UL	Underwriters laboratory
USE	Underground service entrance cable, 75 c wet location
KV	Kilovolt (1000 volts)
R	Rubber insulated
RH	Rubber insulated, heat resistant cable, 75 c dry location
RHH	Rubber insulated, heat resistant cable, 90 c dry locations
RHW	Rubber insulated, heat and moisture resistant, 75 c dry and wet locations
XHHW	Cross-linked polyethylene insulated, 90 c dry location, 75 c wet location
THHN	Thermoplastic insulated, high heat resistant, nylon jacketed cable, 90 c dry location.
THWN	Thermoplastic insulated, heat and moisture resistant, nylon jacket cable, 75 c dry and wet location
TW	Thermoplastic insulated, moisture resistant cable, 60 c wet or dry location

THW	Thermoplastic insulated, heat and moisture resistant cable, 75 c dry and wet location
SER	Round service entrance cable (rubber)
SEU	Service entrance cable (unarmored)
SEA	Service entrance cable (armored)
NM	Designation for nonmetallic sheathed cable, building wire
NMC	Nonmetallic sheathed cable, corrosion resistant, 60 c wet or dry location
UF	Underground feeder cable, thermoplastic insulated, 60 c wet or dry location
AC	Alternating current
MI	Mineral insulated 85 c dry and wet location, 250 c special application
PIC	Thermoplastic insulated
PULP	Paper and pulp insulated

4. Comparability

If you report in the Annual Survey of Manufactures (Form MA-10000), the sum of values for item codes shown in column (a) should correspond to dollar values reported under product codes indicated in column (b) below.

Current Industrial Report (Form MA335J)	Annual Survey of Manufactures (Form MA-10000)
Item codes (a)	Product class (b)
2213 through 2272	335929A
2503 through 2513	335929B
3201 through 3279	3359291
4111 through 4119	335929F
4242 through 4265	335929D
5221 through 5247	3314224
5310 through 5331	335929F
8101 through 8120	3359210
9101 through 9102	327215B231

¹ For these item codes sum of columns 2 and 4

CURRENT INDUSTRIAL REPORTS SERIES

REFERENCE LIST

FORM MA335J		
INSULATED WIRE AND CABLE (SHIPMENTS)		
Product code	Item code	Item description
Section I — ELECTRONIC WIRE AND CABLE, INCLUDING PRODUCTS FABRICATED FROM WIRE AND CABLE (Exclude fiber optics)		
335929A100pt	2213	Electronic coaxial cable, armored or nonarmored, flexible: 135 C and over
335929A100pt	2221	Under 135 C
Hook-up wire, (single conductor, shielded and nonshielded):		
335929A100pt	2245	135 C and over temperature rating
335929A100pt	2250	Under 135 C temperature rating, 16 AWG and smaller
Multiconductor electronic wire and cable (shielded and unshielded):		
335929A100pt	2253	Flat and ribbon cable
Other multiconductor electronic wire and cable:		
Shielded:		
335929A100pt	2255	135 C and over temperature rating
335929A100pt	2260	Under 135 C temperature rating
Nonshielded:		
335929A100pt	2265	135 C and over temperature rating
335929A100pt	2270	Under 135 C temperature rating
335929A100pt	2272	Other electronic wire and cable, including products fabricated from wire and cable (excluding fiber optics)
335929A100	2298	Total electronic wire and cable (Sum of item codes 2213–2272)
Section II — TELEPHONE AND TELEGRAPH WIRE AND CABLE, INCLUDING PRODUCTS FABRICATED FROM WIRE AND CABLE (Exclude fiber optics)		
335929B100pt	2503	Station wire and cable
335929B100pt	2509	Inside wiring cable
335929B100pt	2513	Other telephone and telegraph wire and cable, including products fabricated from wire and cable (excluding fiber optics)
335929B100	2598	Total telephone and telegraph wire and cable (Sum of item codes 2503–2513)
Section III — POWER WIRE AND CABLE, INCLUDING PORTABLE (Exclude fiber optics)		
3359291800pt	3201	Paper insulated cable (all types, all voltages)
Plastic and rubber insulated:		
2 KV or less:		
3359291800pt	3203	Portable welding cable
3359291800pt	3219	Underground distribution cable (UD, URD), all insulations (jacketed and unjacketed, excluding single conductor UL labeled USE)

pt = part

CURRENT INDUSTRIAL REPORTS SERIES

REFERENCE LIST — Continued

FORM MA335J		
Product code	Item code	Item description
Section III — POWER WIRE AND CABLE (Exclude fiber optics) — Continued		
3359291800pt	3231	2KV or less— Continued: Thermoplastic insulated power cable (exclude underground)
3359291800pt	3233	Thermoset, insulated power cable (exclude underground): Armored, rubber and cross linked
3359291800pt	3235	Unarmored, rubber (exclude single conductor UL labeled USE)
3359291800pt	3245	Unarmored, cross linked
3359291800pt	3249	Weatherproof cable
3359291800pt	3257	Service drop cable, thermoset and thermoplastic insulated
Over 2KV:		
3359291800pt	3263	Underground distribution cable (UD, URD), all insulations (jacketed and unjacketed)
Thermoset, insulated power cable (exclude underground):		
2KV to 15KV:		
3359291800pt	3267	Armored, rubber and cross linked
3359291800pt	3271	Unarmored, rubber (exclude single conductor UL labeled USE)
3359291800pt	3273	Unarmored, cross linked
3359291800pt	3275	Over 15.1 KV, rubber and cross linked
3359291800pt	3279	Other power wire and cable
3359291800	3298	Total power wire and cable (Sum of item codes 3201–3279)
Section V — CONTROL AND SIGNAL WIRE AND CABLE (Exclude fiber optics)		
335929F100pt	4111	Signal wire and cable
Control wire and cable (exclude elevator cable):		
335929F100pt	4115	Thermoset insulated
335929F100pt	4119	Thermoplastic insulated
XXX	4198	Total control and signal wire and cable (Sum of item codes 4111–4119)
Section VI — BUILDING WIRE AND CABLE (Exclude fiber optics)		
Building wire and cable:		
Thermoset insulated:		
335929D100pt	4242	Cross linked polyethylene (XHHW)
335929D100pt	4244	Cross linked polyethylene (XLP, USE)
Thermoplastic insulated:		
335929D100pt	4246	Flame-retardant nylon (THHN, THWN)
335929D100pt	4248	Moisture and heat resistant (TW, THW)
335929D100pt	4254	Service entrance cable (SER, SEU, ASE)
Non-metallic branch-circuit and underground feeder:		
335929D100pt	4256	Type NM-B
335929D100pt	4258	Type UF and NMC (corrosion resistant)
335929D100pt	4265	Other building wire and cable, including metallic armored cable (AC and MC type)
335929D100	4298	Total building wire and cable (Sum of item codes 4242–4265)

pt = part

CURRENT INDUSTRIAL REPORTS SERIES

REFERENCE LIST — Continued

FORM MA335J		
Product code	Item code	Item description
Section VII — APPARATUS WIRE AND CORDAGE INCLUDING PRODUCTS FABRICATED FROM WIRE AND CABLE (Exclude fiber optics)		
Flexible cordage:		
3314224218	5221	Thermostat insulated
3314224218	5223	Thermoplastic (include thermoplastic elastomers)
3314224218	5225	Extension cord sets
3314224218	5227	Fixed power supply cords
3314224218	5231	Detachable power supply cords
3314224218	5233	Retractable power supply cords
Apparatus wire:		
3314224218	5235	Appliance fixture wire
3314224218	5240	Appliance wiring material 14 gauge and larger (include motor lead and transformer lead wire), thermoset and thermoplastic insulated
3314224218	5243	Submersible pump cable
3314224218	5247	Other apparatus wire and cordage (include machine tool wire)
XXX	5298	Total apparatus wire and cordage (Sum of item codes 5221–5247)
Section VIII — OTHER INSULATED WIRE AND CABLE INCLUDING PRODUCTS FABRICATED FROM WIRE AND CABLE (Exclude fiber optics) (Exclude appliance wire and cord and flexible cord sets, ignition harness sets, cable sets, etc.)		
Automotive:		
335929F100	5310	Bulk automotive primary wire
335929F100	5312	Bulk battery cable
335929F100	5315	Bulk ignition wire
335929F100	5318	Other automotive wire and cable
Airframe, shipboard, and ground support cable (exclude coaxial cable and ignition cable):		
335929F100	5324	Airframe and missile (including ground support cable)
335929F100	5328	Shipboard cable
335929F100	5331	Other insulated or covered wire and cable, not elsewhere classified
XXX	5398	Total other insulated or covered wire and cable (Sum of item codes 5310–5331)
Section IX — MAGNET WIRE (Include insulated magnet sheet, strip, and foil but exclude fiber optics)		
Film coated (Report products with thermal rating between classes in the next lower class):		
Class 105 and below:		
6106		7 AWG and larger round (include all square and rectangular)
6108		8–21 AWG
6113		22–33 AWG and finer
Class 130–155:		
6119		8–21 AWG
6121		22–32 AWG
6125		33 AWG and finer

CURRENT INDUSTRIAL REPORTS SERIES

REFERENCE LIST – Continued

FORM MA335J		
Product code	Item code	Item description
		Section IX – MAGNET WIRE (Include insulated magnet sheet, strip, and foil but exclude fiber optics) – Continued Film coated (Report products with thermal rating between classes in the next lower class) – Continued: Class 180 and above: 7 AWG and larger round (include all square and rectangular) 8–21 AWG 22–32 AWG 33 AWG and finer Other film coated Nonfilm coated: Class 130 and below: Fibrous Tape Class 155 and above: Fibrous Tape 6188 Other non-film coated
XXX	6199	Total magnet wire (Sum of item codes 6106–6188)
		Section X – FIBER OPTICAL CABLE Communication applications: Single-mode stepped-index: 8101 Dispersion shifted 8102 Dispersion unshifted 8104 Multimode index 8120 Other applications
XXX	8199	Total fiber optical cable (Sum of item codes 8101–8120)
		Section XI – OPTICAL CABLE 9101 Optical glass fiber used for data purposes 9102 Optical glass fiber used for nondata purposes 9103 Total optical fiber for data and nondata transmission (sum of item codes 9101 and 9102)
9999998900	9973	SELECTED NONMANUFACTURING REVENUES OF THIS ESTABLISHMENT Resales – Sales of products bought and sold without further manufacture, processing, or assembly.

3/4/09

pt = part